

FCC LISTED, REGISTRATION  
 NUMBER: 720267

Informe de ensayo nº:  
 Test report No:

IC LISTED REGISTRATION  
 NUMBER IC 4621A-1

**NIE: 46887RRF.001**

### Test report

USA FCC Part 15.247, 15.209

CANADA RSS-247, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz,  
 and 5725 - 5850 MHz.

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and Licence-  
 Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

<b>Identificación del objeto ensayado.....:</b> Identification of item tested	MITSUBISHI BLUETOOTH HANDS FREE MODULE
<b>Marca .....</b> Trademark	Visteon Corporation
<b>Modelo y/o referencia tipo .....</b> Model and /or type reference	MDGMY10
<b>Other identification of the product .....</b>	FCC ID: NT8MDGMY10 IC: 3043A- MDGMY10
<b>Final HW version .....</b>	16
<b>Final SW version .....</b>	16.76.000
<b>Características .....</b> Features	Bluetooth
<b>Fabricante .....</b> Manufacturer	VISTEON CORPORATION One Village Center Drive Van Buren Township, Zip code: 48111-5711 MICHIGAN USA
<b>Método de ensayo solicitado, norma.....:</b> Test method requested, standard	USA FCC Part 15.247 10-1-14 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. - Emission limitations radiated (Transmitter) USA FCC Part 15.209 10-1-14 Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 1 (May 2015). CANADA RSS-Gen Issue 4 (November 2014). FCC part 15.247 and Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum System DA 00-705 Released March 30, 2000. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
<b>Resultado.....:</b> Summary	IN COMPLIANCE
<b>Aprobado por (nombre / cargo y firma) .....</b> Approved by (name / position & signature)	A. Llamas RF Lab. Manager

<b>Fecha de realización .....</b>	<b>2015-09-09</b>
Date of issue	
<b>Formato de informe No.....</b>	<b>FDT08_17</b>
Report template No	

# Index

Competences and guarantees.....	4
General conditions.....	4
Uncertainty .....	4
Usage of samples.....	4
Test sample description .....	5
Identification of the client .....	5
Testing period.....	5
Environmental conditions.....	5
Remarks and comments.....	6
Testing verdicts .....	7
Appendix A – Test result “Bluetooth EDR” .....	8

## Competences and guarantees

AT4 wireless is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

AT4 wireless is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621A-1.

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

## General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

## Uncertainty

Uncertainty (factor  $k=2$ ) was calculated according to the AT4 wireless internal document PODT000.

## Usage of samples

Samples undergoing test have been selected by: **the client**

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
46887/002	Bluetooth Hands Free module with integral antenna	MDGMY10	---	2015-07-29

1. Sample S/01 has undergone the following test(s):  
All radiated tests indicated in appendix A.

## Test sample description

The test sample consists of a Bluetooth hands free module.

## Identification of the client

VISTEON CORPORATION

One Village Center Drive

Van Buren Township, Zip code: 48111-5711 MICHIGAN USA

## Testing period

The performed test started on 2015-08-11 and finished on 2015-08-12.

The tests have been performed at AT4 wireless.

## Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 20 % Max. = 75 %
<b>Shielding effectiveness</b>	> 100 dB
<b>Electric insulation</b>	> 10 kΩ
<b>Reference resistance to earth</b>	< 1 Ω

In the semianechoic chamber, the following limits were not exceeded during the test.

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 20 % Max. = 75 %
<b>Air pressure</b>	Min. = 860 mbar Max. = 1060 mbar
<b>Shielding effectiveness</b>	> 100 dB
<b>Electric insulation</b>	> 10 kΩ
<b>Reference resistance to earth</b>	< 1 Ω
<b>Normal site attenuation (NSA)</b>	< ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz)
<b>Field homogeneity</b>	More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).

## Remarks and comments

1: Used instrumentation:

### Radiated Measurements

		Last Cal. date	Cal. due date
1.	Semianechoic Absorber Lined Chamber ETS FACT3 200STP	N.A.	N.A.
2.	BiconicalLog antenna ETS LINDGREN 3142E	2014/03	2017/03
3.	Multi Device Controller EMCO 2090	N.A.	N.A.
4.	Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D	2013/11	2016/11
5.	Double-ridge Guide Horn antenna 14-40 GHz SCHWARZBECK BBHA 9170	2014/03	2017/03
6.	EMI Test Receiver R&S ESU 40	2014/02	2016/02
7.	Spectrum analyser Rohde & Schwarz FSW50	2013/10	2015/10
8.	RF pre-amplifier 10 MHz-6 GHz SCHWARZBECK BBV9743	2015/03	2016/03
9.	RF pre-amplifier 1-18 GHz Bonn Elektronik BLMA 0118-3A	2015/05	2016/05
10.	RF pre-amplifier BONN BLMA 1840-1M 18-40 GHz.	2014/02	2016/02
11.	Bluetooth Signalling unit ANRITSU MT8852B	N.A.	N.A.

2: Test not requested.

## Testing verdicts

<b>Not applicable</b> .....	N/A
<b>Pass</b> .....	P
<b>Fail</b> .....	F
<b>Not measured</b> .....	N/M

FCC PART 15 PARAGRAPH / RSS-247		VERDICT			
		NA	P	F	NM <sup>2</sup>
FCC 15.247 Subclause (a) (1) / RSS-247 Clause 5.1 (2)	20 dB Bandwidth and Carrier frequency separation				NM <sup>2</sup>
FCC 15.247 Subclause (a)(1)(iii) / RSS-247 Clause 5.1 (4)	Number of hopping channels				NM <sup>2</sup>
FCC 15.247 Subclause (a)(1)(iii) / RSS-247 Clause 5.1 (4)	Time of occupancy (Dwell Time)				NM <sup>2</sup>
FCC 15.247 Subclause (b) / RSS-247, Clause 5.4 (2)	Maximum peak output power and antenna gain				NM <sup>2</sup>
FCC 15.247 Subclause (d) / RSS-247 Clause 5.5	Emission limitations conducted (Transmitter)				NM <sup>2</sup>
FCC 15.247 Subclause (d) / RSS-247 Clause 5.5	Emission limitations radiated (Transmitter)		P		

2: See remarks and comments.

## Appendix A – Test result “Bluetooth EDR”



## INDEX

TEST CONDITIONS .....	10
FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations radiated (Transmitter) .....	11

## TEST CONDITIONS

Power supply (V):

$V_{\text{nominal}} = 12 \text{ Vdc}$

Type of power supply = DC voltage from external power source.

Type of antenna = Integral antenna

Declared Gain for antenna (maximum) = 1 dBi

### TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

### RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

An additional horn antenna is used to control the equipment under test with the Bluetooth signalling unit (Bluetooth test set).

**FCC Section 15.247 Subclause (d) / RSS-247 Clause 5.5. Emission limitations radiated (Transmitter)**

SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

Frequency Range (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	300
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 25000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

**Frequency range 30 MHz-1000 MHz.**

Note: The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

**Spurious levels operating (radiated) closest to limit.**

Spurious frequency (MHz)	Polarization	Detector	Emission Level (dBµV/m)	Measurement Uncertainty (dB)
400.055	H	Quasi-peak	32.78	±4.12
406.069	H	Quasi-peak	30.53	±4.12
444.384	H	Quasi-peak	28.90	±4.12
533.333	H	Quasi-peak	26.98	±4.12
666.708	H	Quasi-peak	33.63	±4.12
800.083	H	Quasi-peak	27.49	±4.12
933.361	H	Quasi-peak	36.68	±4.12

**Frequency range 1 GHz-25 GHz**

**Modulation: GFSK**

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dBµV/m)	Measurement Uncertainty (dB)
4.80375	V	Peak	47.55	± 4.0
	V	Average	42.30	± 4.0
9.60750	V	Peak	46.03	± 4.0
	V	Average	39.07	± 4.0

2. CHANNEL: MIDDLE (2441 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.88225	V	Peak	45.00	$\pm 4.0$
	V	Average	42.81	$\pm 4.0$

3. CHANNEL: HIGHEST (2480 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.95975	V	Peak	46.75	$\pm 4.0$
	V	Average	44.65	$\pm 4.0$

Verdict: PASS

**Modulation:  $\Pi/4$ -DQPSK**

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.80375	V	Peak	40.20	$\pm 4.0$
	V	Average	33.57	$\pm 4.0$

2. CHANNEL: MIDDLE (2441 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.88175	V	Peak	41.50	$\pm 4.0$
	V	Average	34.64	$\pm 4.0$

3. CHANNEL: HIGHEST (2480 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.96025	V	Peak	41.11	$\pm 4.0$
	V	Average	34.25	$\pm 4.0$

Verdict: PASS

**Modulation: 8-DPSK**

1. CHANNEL: LOWEST (2402 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.80425	V	Peak	41.65	$\pm 4.0$
	V	Average	34.00	$\pm 4.0$

2. CHANNEL: MIDDLE (2441 MHz).


Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.88225	V	Peak	40.83	$\pm 4.0$
	V	Average	34.48	$\pm 4.0$

3. CHANNEL: HIGHEST (2480 MHz).

Spurious frequency (GHz)	Polarization	Detector	Emission Level (dB $\mu$ V/m)	Measurement Uncertainty (dB)
4.95975	V	Peak	40.19	$\pm 4.0$
	V	Average	34.20	$\pm 4.0$

Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels and all modulation modes).



### FREQUENCY RANGE 1 GHz to 3 GHz.


Modulation: GFSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot is the carrier frequency.


Modulation:  $\pi/4$ -DQPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot is the carrier frequency.


Modulation: 8-DPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Highest (2480 MHz).




Note: The peak shown in the plot is the carrier frequency.


**FREQUENCY RANGE 3 GHz to 18 GHz.**

Modulation: GFSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).




Modulation: Π/4-DQPSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).






Modulation: 8-DPSK


CHANNEL: Lowest (2402 MHz).




CHANNEL: Middle (2441 MHz).



CHANNEL: Highest (2480 MHz).



### FREQUENCY RANGE 18 GHz to 26 GHz.




(This plot is valid for all three channels and all modulation modes).


**FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)**

CHANNEL: Lowest


Modulation: GFSK



Modulation: Π/4-DQPSK




Modulation: 8-DPSK




CHANNEL: Middle


Modulation: GFSK



Modulation:  $\Pi/4$ -DQPSK




Modulation: 8-DPSK




CHANNEL: Highest


Modulation: GFSK



Modulation: Π/4-DQPSK



Modulation: 8-DPSK







**FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)**

CHANNEL: Lowest


Modulation: GFSK



Modulation: Π/4-DQPSK




Modulation: 8-DPSK




CHANNEL: Middle


Modulation: GFSK



### Modulation: $\Pi/4$ -DQPSK




### Modulation: 8-DPSK




CHANNEL: Highest

Modulation: GFSK



Modulation: Π/4-DQPSK



Modulation: 8-DPSK

