

2WMMR

February 20, 2013

RF Exposure calculation

Based on FCC 1.1307 & 2.1091, FCC OET Bulletin 65

1. Categorically Exclusion from exposure Evaluation:

According to FCC regulation, RF exposure evaluation is Categorically Excluded if transmitter's operation frequency is less than 1.5GHz and ERP is less than 1.5W.

- 2. Absolute maximum specification of 2WMMR transmitter
 - Operational frequency band **450MHz to 479MHz**
 - The 2WMMR transmitter is measured for **MAX RF Power4W**
 - Absolute Maximum transmission time(duration) for any 2WMMR transmitters does not exceed 26 s
 - Transmission period-absolute maximum is **30 transmission perhour**
 - ALL 2WMMR transmitters utilize 4GFSK modulation
- 3. Average RF Power Calculation

FCC regulation on permissible RF exposure are not based on the peak envelope power, but on average power (P_ave) over a 30-minute time period for uncontrolled environments.

As mentioned in (2), during any 30 minutes 2WMMR can transmit 15 times. Duration is 26 second.

With maximum RF radiation equal to 4W, the average RF Power over 30 minutes is:

P_ave(worst case) at 30 minute=4×15×26/30×60=870mW

4. Maximum radiated Power Density prediction (S):

The predict power density (**S**) at distance **R=20cm** from transmitter with **P_ave**=870mW, next formula is used:

S=P_ave/($4 \times \pi \times R^2$)

For the worst case prediction of power density at or near a transmitter surface let's use:

S=P_ave/(4×π×R²)=870mW/(4×3.14×20cm×20cm)=0.173mW/cm²

This is the worst case of the near field power density of 2WMMR transmitter.

5. Maximum Permissible Exposure (MPE) from 2WMMR

As FCC require, the maximum permissible exposure for general public in "uncontrolled situation" at 20cm is:

${\sf MPE=frequency[MHz]/1500=460MHz/1500=0.307mW/cm^2}$

Compare results in (4) and (5),

${\tt S=0.173mW/cm^2 < MPE=0.307mW/cm^2}$

We see that 2WMMR fully complies with RF safety at a distance 20cm.

Dr. Slava Snitkovsky

Telematics-Wireless