

TNET

April 23, 2013

## RF Exposure calculation

Based on FCC 1.1307 & 2.1091, FCC OET Bulletin 65

### 1. Categorically Exclusion from exposure Evaluation:

According to FCC regulation, RF exposure evaluation is Categorically Excluded if transmitter's operation frequency is less than 1.5GHz and ERP is less than 1.5W.

### 2. Absolute maximum specification of TNET210 transmitter

- Operational frequency band **902MHz to 928MHz**
- The TNET transmitter is measured for **MAX RF Power 0.5W**
- Absolute **Maximum transmission time(duration)** for any TNET transmitters does not exceed **30ms**
- Transmission period-absolute maximum is **1 transmission per 1.5s**
- ALL TNET transmitters utilize 2GFSK modulation

### 3. Average RF Power Calculation

FCC regulation on permissible RF exposure are not based on the peak envelope power, but on average power ( $P_{ave}$ ) over a 30-minute time period for uncontrolled environments.

As mentioned in (2), during any 30 minutes TNET can transmit 2700 times. Duration is 30ms.

With maximum RF radiation equal to 0.5W, the average RF Power over 30 minutes is:

$$P_{ave}(\text{worst case}) \text{ at } 30 \text{ minute} = 0.5 \times 0.03 \times 2700 / 30 \times 60 = 0.0225W$$

### 4. Maximum radiated Power Density prediction (S):

The predict power density (S) at distance **R=20cm** from transmitter with  $P_{ave}=0.0225W$ , next formula is used:

$$S = P_{\text{ave}} / (4 \times \pi \times R^2)$$

For the worst case prediction of power density at or near a transmitter surface let's use:

$$S = P_{\text{ave}} / (4 \times \pi \times R^2) = 0.0225 \text{ mW} / (4 \times 3.14 \times 20 \text{ cm} \times 20 \text{ cm}) = 0.0045 \text{ mW/cm}^2$$

This is the worst case of the near field power density of TNET transmitter.

#### 5. Maximum Permissible Exposure (MPE) from TNET

As FCC require, the maximum permissible exposure for general public in "uncontrolled situation" at 20cm is:

$$\text{MPE} = \text{frequency [MHz]} / 1500 = 902 \text{ MHz} / 1500 = 0.6 \text{ mW/cm}^2$$

Compare results in (4) and (5),

$$S = 0.0045 \text{ mW/cm}^2 < \text{MPE} = 0.6 \text{ mW/cm}^2$$

We see that TNET fully complies with RF safety at a distance 20cm.

Dr. Slava Snitkovsky

Telematics-Wireless