

Draft

User Manual

TMW-40D

TMW-40D

FCC ID: NTAXMETER3

Manufacturer: Tadiran-Telematics Ltd.

This device complies with Part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and**
- (2) this device must accept any interference received, including interference that may cause undesired operation.**

Note:

The digital portion of the transceiver has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.

Draft

Installation

Following information will be included in the User Manual

- The user and the installer should be aware that changes and modifications not expressly approved by Tadiran Telematics could void the user's authority to operate the equipment.
- This equipment shall be installed by professional personnel. The equipment shall be installed at the bottom of the water meter pit as described in the following picture:



The unit is installed as shown in the center of the bottom of the pit.

Draft

- There are 3 types of the pits: metal, concrete and plastic. The covers of the pits are made of metal, concrete or plastic and may or may not include small rectangular lid at the center of the cover. The lids can be either metal or plastic. Possible configurations of the pits and its covers are shown on the following pictures:



Metal Pit



Concrete Pit w. concrete cover and metal lid



Plastic Pit w. plastic cover and metal lid



Plastic Pit w. plastic cover and plastic lid



Plastic Pit w. concrete cover and metal lid



Plastic Pit w. plastic cover and no lid

Draft

Special instructions for installation in the concrete or plastic pits.

When installing the equipment in the pit made of plastic or concrete, regardless of the type of the cover, a special adhesive sticker shall be attached to the meter as described in the drawings (see attached picture).

The sticker is copper foil sticker (e.g. type 3M 1181, PPI 9115 or compatible), intended for permanent adhesion. Stickers used for the product are produced with special adhesive and are designed to withstand the installation conditions during the lifetime of the product.

Only stickers, supplied as a part of the installation kit of the meter, shall be used. Use of stickers unauthorized by the manufacturer is prohibited.

