

FCC Part 74 Subpart H

EMI TEST REPORT

of

E.U.T. : Wireless Handheld Microphone
FCC ID. : NTMEJ-501TM
Model No. : EJ-501TM
Serial Model : EJ-501TG; EJ-501TS
Working Frequency : 640~664 MHz

for

APPLICANT : E-J Electronics Co., Ltd.
ADDRESS : 4F., No.11, Ln. 125, Sec. 1, Guoguang Rd., Dali
Dist., Taichung City 412, Taiwan (R.O.C.)

Test Performed by

ELECTRONICS TESTING CENTER (ETC) , TAIWAN
NO. 34, LIN 5, DINGFU TSUEN, LINKOU SHIANG
TAIPEI COUNTY, TAIWAN, 24442, R.O.C.
TEL : (02)26023052 FAX : (02)26010910
[http:// www.etc.org.tw](http://www.etc.org.tw) ; e-mail:emc@etc.org.tw

Report Number : 10-12-RBF-097-01

TEST REPORT CERTIFICATION

Applicant : E-J Electronics Co., Ltd.
4F., No.11, Ln. 125, Sec. 1, Guoguang Rd., Dali Dist., Taichung City
412, Taiwan (R.O.C.)

Manufacturer : E-J Electronics Co., Ltd.
4F., No.11, Ln. 125, Sec. 1, Guoguang Rd., Dali Dist., Taichung City
412, Taiwan (R.O.C.)

Description of EUT :

a) Type of EUT : Wireless Handheld Microphone

b) Trade Name : OKAYO

c) Model No. : EJ-501TM

d) Serial Model : EJ-501TG; EJ-501TS

e) FCC ID : NTMEJ-501TM


f) Working Frequency : 640~664 MHz


g) Power Supply : 1.2V(Ni-MH) x 2 AA type rechargeable batteries /
1.5V x 2 AA Alkaline disposable


Regulation Applied: FCC Rules and Regulations Part 74 Subpart H (2009)

I HEREBY CERTIFY THAT; The data shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Issued Date : Jan. 24, 2011

Test Engineer : 
(Vincent Chang, Engineer)

Check By : 
(Charles Wang, Supervisor)

Approve & Authorized : 
Will Yauo, Manager
EMC Dept. II of ELECTRONICS
TESTING CENTER, TAIWAN

<i>Table of Contents</i>	<i>Page</i>
1. GENERAL INFORMATION	1
1.1 PRODUCT DESCRIPTION.....	1
1.2 TEST METHODOLOGY.....	1
1.3 TEST FACILITY	1
2. REQUIREMENTS OF PROVISIONS.....	2
2.1 DEFINITION.....	2
2.2 FREQUENCIES AVAILABLE.....	2
2.3 REQUIREMENTS FOR RADIO EQUIPMENT ON CERTIFICATION	2
2.4 LABELING REQUIREMENT.....	3
3. OUTPUT POWER MEASUREMENT	4
3.1 PROVISION APPLICABLE	4
3.2 MEASUREMENT PROCEDURE.....	4
3.3 TEST DATA.....	6
3.4 RESULT CALCULATION.....	7
3.5 TEST EQUIPMENT	7
4. MODULATION CHARACTERISTICS.....	8
4.1 PROVISIONS APPLICABLE.....	8
4.2 MEASUREMENT METHOD.....	8
4.3 MEASUREMENT INSTRUMENT	9
4.4 MEASUREMENT RESULT.....	9
5. OCCUPIED BANDWIDTH OF EMISSION.....	11
5.1 PROVISIONS APPLICABLE.....	11
5.2 MEASUREMENT METHOD.....	11
5.3 OCCUPIED BANDWIDTH TEST EQUIPMENT	11
5.4 BANDWIDTH MEASURED	12
5.4.1 <i>Input Level Derived</i>	12
5.4.2 <i>Occupied Bandwidth Plotted</i>	13
6. FIELD STRENGTH OF EMISSION	17
6.1 PROVISIONS APPLICABLE.....	17
6.2 MEASUREMENT PROCEDURE.....	17
6.3 MEASURING INSTRUMENT.....	18
6.4 MEASURING DATA	19
6.4.1 <i>Emission Test Data</i>	19
6.4.2 <i>Emission mask plots</i>	22
6.5 OTHER EMISSION.....	25
6.6 RADIATED MEASUREMENT PHOTOS.....	26
7. FREQUENCY STABILITY MEASUREMENT	27
7.1 PROVISIONS APPLICABLE.....	27
7.2 MEASUREMENT PROCEDURE.....	27
7.3 MEASUREMENT INSTRUMENT	28
7.4 MEASUREMENT DATA.....	29
8 CONDUCTED EMISSION MEASUREMENT	32
8.1 STANDARD APPLICABLE.....	32

1. GENERAL INFORMATION

1.1 Product Description

a) Type of EUT	: Wireless Handheld Microphone
b) Trade Name	: OKAYO
c) Model No.	: EJ-501TM
d) Serial Model	: EJ-501TG; EJ-501TS
e) Model difference declared by the manufacturer	: Serial model EJ-501TG is the same with EJ-501TM and the only difference is the channel setting. EJ-501TS is the same with EJ-501TM and the only difference is the microphone head.
f) FCC ID	: NTMEJ-501TM
g) Working Frequency	: 640~664 MHz
h) Power Supply	: 1.2V(Ni-MH) x 2 AA type rechargeable batteries / 1.5V x 2 AA Alkaline disposable
i) Emission Designator	: 112KF3E $2M+2DK=2x(6kHz)+2x(50kHz)x1=112kHz$

1.2 Test Methodology

Both conducted and radiated testing were performed according to the procedures in chapter 13 of ANSI C63.4 (2003). Test also follow "TIA/ELA 603-Land Mobile FM or PM Communications Equipment Measurement and Performance Standards" and section 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, and 2.1055 of Part 2 of CFR 47.

1.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at NO.34, LIN 5, DINGFU TSUEN, LINKOU SHIANG TAIPEI COUNTY, TAIWAN, 24442, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Aug. 05, 2008.

2. REQUIREMENTS OF PROVISIONS

2.1 Definition

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Frequencies Available

According to sec. 74.802 of Part 74, the following frequencies are available for low power auxiliary station :

Frequencies (MHz)	
26.100-26.480	455.000-456.000
54.000-72.000	470.000-488.000
76.000-88.000	488.000-494.000
161.625-161.775	494.000-608.000
174.000-216.000	614.000-806.000
450.000-451.000	944.000-952.000

2.3 Requirements for Radio Equipment on Certification

(1) RF Output Power

For transmitters, the power output shall be measured at the RF output terminals.

(2) Modulation Characteristics

For Voice Modulated Communication Equipment, a curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted.

(3) Occupied Bandwidth

For radiotelephone transmitter, other than single sideband or independent sideband transmitter, when modulated by a 2.5kHz tone at an input level 16 dB greater than that necessary to produce 50 percent modulation.

(4) Spurious Emissions at Antenna Terminals

The radio frequency voltage or power generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminal when properly loaded with a suitable artificial antenna.

(5) Field Strength of Spurious Emissions

Measurements shall be made to detect spurious emission that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal condition of installation and operation.

(6) Frequencies Tolerance

- a) The frequency stability shall be measured with variation of ambient temperature.
- b) The frequency stability shall be measured with variation of primary supply voltage.

2.4 Labeling Requirement

Each equipment for which a type acceptance application is filed on or after May 1,1981, shall bear an identification plate or label pursuant to § 2.925 (Identification of equipment) and §2.926 (FCC identifier) .

3. OUTPUT POWER MEASUREMENT


3.1 Provision Applicable

According to §74.861(e)(1)(ii), the output power shall not exceed 250 milliwatts.

3.2 Measurement Procedure


1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively, adjusting the input voltage to produce the maximum power.
2. Adjust the analyzer for each frequency measured in chapter 6 on a 1 MHz frequency span and 1MHz resolution bandwidth.
3. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° , and record the highest value indicated on spectrum analyzer as reference value.
4. Repeat step 3 until all frequencies need to be measured were complete.
5. Repeat step 4 with search antenna in vertical polarized orientations.
6. Replace the EUT with a tuned dipole antenna (horn antenna for above 1 GHz) relative to each frequency in horizontally polarized orientation and as the same polarized orientation with search antenna. Connect the tuned dipole antenna to a standard signal generator (SG) via a low loss cable. Power on the SG and tune the right frequency in measuring as well as set SG at a appreciated output level. Rise and lower the search antenna to get the highest value on spectrum analyzer, and then hold this position. Adjust the SG output to get a identical value derived from step 3 on spectrum analyzer. Record this value for result calculated.
7. Repeat step 6 until all frequencies need to be measured were complete.
8. Repeat step 7 with both dipole antenna (horn antenna for above 1 GHz) and search antenna in vertical polarized orientations.

Figure 1 : Frequencies measured below 1 GHz configuration



Note: For substitution method, replace the EUT with a tuned dipole antenna relative to each frequency and connect to a standard signal generator (SG) via a low loss cable.

Figure 2 : Frequencies measured above 1 GHz configuration



Note: For substitution method, replace the EUT with a horn antenna and connect to a standard signal generator (SG) via a low loss cable.

3.3 Test Data

Band 640 – 664 MHz

Operated mode : TX

Test Date : Dec. 16, 2010

Temperature : 18 °C

Humidity : 70 %

Frequency (MHz)	Meter Reading (dB μ V/m)	SG Reading (dBm)	Cable Loss (dB)	Antenna Gain	Result (dBm)	Output Power (mW)	Limit (mW)
640.1	78.6	6.6	2.4	----	5.2	3.311	250

Frequency (MHz)	Meter Reading (dB μ V/m)	SG Reading (dBm)	Cable Loss (dB)	Antenna Gain	Result (dBm)	Output Power (mW)	Limit (mW)
652.1	78.5	7.0	2.4	----	4.6	2.884	250

Frequency (MHz)	Meter Reading (dB μ V/m)	SG Reading (dBm)	Cable Loss (dB)	Antenna Gain	Result (dBm)	Output Power (mW)	Limit (mW)
663.9	78.7	8.1	2.3	----	5.8	3.801	250

Note: For measured frequency below 1GHz, a tuned dipole antenna is used.

3.4 Result Calculation

Result calculation is as following :

Result = SG Reading + Cable Loss + Antenna Gain Corrected

Antenna Gain Corrected : is used for antenna other than dipole to convert radiated power to ERP.

$$\text{mW} = \log^{-1} \left[\frac{\text{Result(dBm)}}{10} \right]$$

3.5 Test Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2010/02/03	2011/02/02
Dipole Antenna	Schwarzbeck	897;898	2009/09/03	2011/09/02
Log-periodic Antenna	EMCO	3146	2010/10/11	2011/10/10
Amplifier	HP	8447D	2010/05/10	2011/05/09
Signal generator	HP	8656B	2010/12/09	2011/12/08

4. MODULATION CHARACTERISTICS

4.1 Provisions Applicable

According to § 2.1047 (a), for Voice Modulated Communication Equipment, the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be measured.

4.2 Measurement Method


A) Modulation Limit

1. Position the EUT as shown in figure 3, adjust the audio input frequency to 100 Hz and the input level from 0V to maximum permitted input voltage with recording each carrier frequency deviation responding to respective input level.
2. Repeat step 1 with changing the input frequency for 200, 500, 1000, 3000, and 5000 Hz in sequence.

B) Frequency response of all circuits

1. Position the EUT as shown in figure 3.
2. Vary the modulating frequency from 100 Hz to 15000 Hz with constant input voltage (derived from 5.4(a) of this test report), and observe the change in output.

Figure 3 : Modulation characteristic measurement configuration




4.3 Measurement Instrument

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Communications Service Monitor	AEROFLEX	2945B	2010/12/10	2011/12/09
Spectrum Analyzer	Rohde & Schwarz	FSP40	2010/09/17	2011/09/16


4.4 Measurement Result

RF Frequency : 640MHz


A). Frequency response



B). Modulation Limit



C). Frequency response of all circuits



5. OCCUPIED BANDWIDTH OF EMISSION

5.1 Provisions Applicable


According to §2.1049 (c)(1), For radiotelephone transmitter, other than single sideband or indenpent sideband transmitter, when modulated by a 2.5kHz tone at an input level 16 dB greater than that necessary to produce 50 percent modulation.

According to §74.861(e)(5), the frequency emission bandwidth shall not exceed 200 kHz.

5.2 Measurement Method

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in figure 4, and Install new batteries in the EUT. Turn on the EUT ant set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Apply a 2.5 kHz modulation signal to EUT and measure the frequencies of the modulated signal from the EUT where it is the specified number of dB below the reference level set in step 2. This is the occupied bandwidth specified.

Figure 4 : Occupied bandwidth measurement configuration



5.3 Occupied Bandwidth Test Equipment


Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Communications Service Monitor	AEROFLEX	2945B	2010/12/10	2011/12/09
Spectrum Analyzer	Rohde & Schwarz	FSP40	2010/09/17	2011/09/16

5.4 Bandwidth Measured

5.4.1 Input Level Derived

RF Frequency : 640MHz


Input Audio Frequency : 2.5 kHz, Sine Wave





The Level input to produce 50% modulation is 40 mV, therefore the magnitude 16 dB greater than it is 252.4 mV.

5.4.2 Occupied Bandwidth Plotted

RF Frequency (MHz)	26 dB Bandwidth (kHz)
640.100	112.000
652.100	110.500
663.900	114.000







6. FIELD STRENGTH OF EMISSION

6.1 Provisions Applicable

According to §2.1053, measurements shall be made to detect spurious emission that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal condition of installation and operation. Information submitted shall include the relative radiated power of spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from a halfwave dipole antenna.

According to §74.861(e)(6), the mean power of emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (i) on any frequency removed from the operating frequency by more than 50 percent up to and including 100 percent of the authorized bandwidth: at least 25 dB.
- (ii) on any frequency removed from the operating frequency by more than 100 percent up to and including 250 percent of the authorized bandwidth: at least 35 dB.
- (iii) on any frequency removed from the operating frequency by more than 250 percent of the authorized bandwidth shall be attenuated below the unmodulated carrier by at least 43 plus 10 Log(output power in watts) dB.

6.2 Measurement Procedure

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively, adjusting the input voltage to produce the maximum power as measured in chapter 3.
2. Adjust the analyzer for each frequency measured in chapter 6 on a 1 MHz frequency span and 1MHz resolution bandwidth.
3. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° , and record the highest value indicated on spectrum analyzer as reference value.
4. Repeat step 3 until all frequencies need to be measured were complete.
5. Repeat step 4 with search antenna in vertical polarized orientations.
6. Replace the EUT with a tuned dipole antenna (horn antenna for above 1 GHz) relative to each frequency in horizontally polarized orientation and as the same polarized orientation with search antenna. Connect the tuned dipole antenna to a standard signal generator (SG) via a low loss cable. Power on the SG and tune the right frequency in measuring as well as set SG at a appreciated output level. Rise and lower the search antenna to get the highest value on spectrum analyzer, and then hold this position. Adjust the SG output to get a identical value derived from step 3 on spectrum analyzer. Record this value for result calculated.

7. Repeat step 6 until all frequencies need to be measured were complete.
8. Repeat step 7 with both dipole antenna (horn antenna for above 1 GHz) and search antenna in vertical polarized orientations.

6.3 Measuring Instrument

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2010/09/17	2011/09/16
Double Ridged Antenna	EMCO	3115	2010/05/11	2011/05/10
Double Ridged Antenna	EMCO	3115	2010/08/10	2011/08/09
Log-periodic Antenna	EMCO	3146	2010/10/11	2011/10/10
Biconical Antenna	EMCO	3110	2010/10/11	2011/10/10
Dipole Antenna	Schwarzbeck	897;898	2009/09/03	2011/09/02
Amplifier	HP	8449B	2009/12/16	2010/12/15
Amplifier	HP	8447D	2010/05/10	2011/05/09
Signal generator	HP	8656B	2010/12/09	2011/12/08

Measuring instrument setup in frequency band measured is as following :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz

6.4 Measuring Data

6.4.1. Emission Test Data

a. Tx Frequency: 640.1MHz

Operated mode : TX

Test Date : Dec. 13, 2010

Temperature : 18 °C

Humidity : 70 %

Unmodulated carrier output power is 5.6 dBm , or 3.630 mW (ERP).

The limit of spurious or harmonics is calculated as following :

$$5.6-[43+10\log(\text{carrier output power in W})], \text{ or } -13\text{dBm}$$

Frequency (MHz)	Meter Reading (dBuV)		SG Reading (dBm)		Antenna Gain	Antenna Gain Corr'	Cable Loss (dB)	Result (dBm)		Limit (dBm)	Margin (dB)
	H	V	H	V				H	V		
1280.200	---	---	---	---	6.4	-2.0	1.30	---	---	-13.0	---
1920.300	---	---	---	---	9.3	-2.0	1.75	---	---	-13.0	---
2560.400	---	---	---	---	9.2	-2.0	1.75	---	---	-13.0	---
3200.500	---	---	---	---	9.7	-2.0	1.75	---	---	-13.0	---
3840.600	---	---	---	---	9.6	-2.0	2.10	---	---	-13.0	---
4480.700	---	---	---	---	10.6	-2.0	2.10	---	---	-13.0	---
5120.800	---	---	---	---	10.9	-2.0	2.10	---	---	-13.0	---
5760.900	---	---	---	---	10.9	-2.0	2.60	---	---	-13.0	---
6401.000	---	---	---	---	12.1	-2.0	2.60	---	---	-13.0	---

Note :

1. Remark “---“ means that the emission level is too weak to be detected.
2. For measured frequency below 1GHz, a tuned dipole antenna is used.
3. Result calculation is as following :

$$\text{Result} = \text{SG Reading} + \text{Cable Loss} + \text{Antenna Gain} + \text{Antenna Gain Corrected}$$
 Antenna Gain Corrected : is used for antenna other than dipole to convert radiated power to ERP.
4. Spurious or harmonics above 1 GHz is too low to be detected or attenuated more than 60 dB from limit value.

b. Tx Frequency: 652.1MH

Operated mode : TX

Test Date : Dec. 13, 2010

Temperature : 18 °C

Humidity : 70 %

Unmodulated carrier output power is 5.0 dBm , or 3.162 mW (ERP).

The limit of spurious or harmonics is calculated as following :

$$5.0-[43+10\log(\text{carrier output power in W})], \text{ or } -13\text{dBm}$$

Frequency (MHz)	Meter Reading (dBuV)		SG Reading (dBm)		Antenna Gain	Antenna Gain Corr'	Cable Loss (dB)	Result (dBm)		Limit (dBm)	Margin (dB)
	H	V	H	V				H	V		
1304.200	---	---	---	---	6.4	-2.0	1.30	---	---	-13.0	---
1956.300	---	---	---	---	9.3	-2.0	1.75	---	---	-13.0	---
2608.400	---	---	---	---	9.2	-2.0	1.75	---	---	-13.0	---
3260.500	---	---	---	---	9.7	-2.0	1.75	---	---	-13.0	---
3912.600	---	---	---	---	9.6	-2.0	2.10	---	---	-13.0	---
4564.700	---	---	---	---	10.6	-2.0	2.10	---	---	-13.0	---
5216.800	---	---	---	---	10.9	-2.0	2.10	---	---	-13.0	---
5868.900	---	---	---	---	10.9	-2.0	2.60	---	---	-13.0	---
6521.000	---	---	---	---	12.1	-2.0	2.60	---	---	-13.0	---

Note :

1. Remark “---“ means that the emission level is too weak to be detected.
2. For measured frequency below 1GHz, a tuned dipole antenna is used.
3. Result calculation is as following :

$$\text{Result} = \text{SG Reading} + \text{Cable Loss} + \text{Antenna Gain} + \text{Antenna Gain Corrected}$$

Antenna Gain Corrected : is used for antenna other than dipole to convert radiated power to ERP.

4. Spurious or harmonics above 1 GHz is too low to be detected or attenuated more than 60 dB from limit value.

c. Tx Frequency: 663.9MHz

Operated mode : TX
Temperature : 18 °C

Test Date : Dec. 13, 2010
Humidity : 70 %

Unmodulated carrier output power is 6.2 dBm , or 4.168 mW (ERP).

The limit of spurious or harmonics is calculated as following :

$$6.2-[43+10\log(\text{carrier output power in W})], \text{ or } -13\text{dBm}$$

Frequency (MHz)	Meter Reading (dBuV)		SG Reading (dBm)		Antenna Gain	Antenna Gain Corr'	Cable Loss (dB)	Result (dBm)		Limit (dBm)	Margin (dB)
	H	V	H	V				H	V		
1327.800	---	---	---	---	6.4	-2.0	1.30	---	---	-13.0	---
1991.700	---	---	---	---	9.3	-2.0	1.75	---	---	-13.0	---
2655.600	---	---	---	---	9.2	-2.0	1.75	---	---	-13.0	---
3319.500	---	---	---	---	9.7	-2.0	1.75	---	---	-13.0	---
3983.400	---	---	---	---	9.6	-2.0	2.10	---	---	-13.0	---
4647.300	---	---	---	---	10.6	-2.0	2.10	---	---	-13.0	---
5311.200	---	---	---	---	10.9	-2.0	2.10	---	---	-13.0	---
5975.100	---	---	---	---	10.9	-2.0	2.60	---	---	-13.0	---
6639.000	---	---	---	---	12.1	-2.0	2.60	---	---	-13.0	---

Note :


1. Remark “---“ means that the emission level is too weak to be detected.
2. For measured frequency below 1GHz, a tuned dipole antenna is used.
3. Result calculation is as following :


$$\text{Result} = \text{SG Reading} + \text{Cable Loss} + \text{Antenna Gain} + \text{Antenna Gain Corrected}$$

Antenna Gain Corrected : is used for antenna other than dipole to convert radiated power to ERP.

4. Spurious or harmonics above 1 GHz is too low to be detected or attenuated more than 60 dB from limit value.


6.4.2 Emission mask plots







Ref 10 dBm Att 40 dB *RBW 10 kHz Marker 1 [T1]
VBW 30 kHz 0.09 dBm
SWT 20 ms 663.948000000 MHz



6.5 Other Emission

a) Emission frequencies below 1 GHz

Test Date : Dec. 13, 2010

Temperature : 18 °C

Humidity : 70 %

Frequency (MHz)	Ant-Pol H/V	Meter Reading (dBuV)	Corrected Factor (dB)	Result @3m (dBuV/m)	Limit @3m (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
34.24	V	13.5	14.0	27.5	40.0	-12.5	188	1.0
133.21	V	14.6	13.7	28.3	43.5	-15.2	194	1.0
158.39	V	14.8	14.6	29.4	43.5	-14.1	180	1.0
179.81	H	15.0	16.2	31.2	43.5	-12.3	78	1.5
188.92	H	14.6	17.5	32.1	43.5	-11.4	92	1.5
229.11	H	13.7	19.1	32.8	46.0	-13.2	79	1.5

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The expanded uncertainty of the radiated emission tests is 3.53 dB.

b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 25 GHz were too low to be measured with a pre-amplifier of 35 dB.

6.6 Radiated Measurement Photos



7. FREQUENCY STABILITY MEASUREMENT

7.1 Provisions Applicable

According to §2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to $+50^{\circ}\text{C}$ centigrade, and according to §2.1055 (d)(2), the frequency stability shall be measured with variation of primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

According to §74.861(e)(4), the frequency tolerance of the transmitter shall be 0.005 percent.

7.2 Measurement Procedure

A) Frequency stability versus environmental temperature

1. Setup the configuration per figure 5 for frequencies measured at ambient temperature if it is within 15°C to 25°C . Otherwise, an environmental chamber set for a temperature of 20°C shall be used.
2. Turn on EUT and set SA center frequency to the right frequency needs to be measured. Then set SA RBW to 30 kHz, VBW to 100kHz and frequency span to 500 kHz. Record this frequency to be a reference.
3. Set the temperature of chamber to 50°C . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10°C decreased per stage until the lowest temperature -30°C is measured, record all measurement frequencies.


B) Frequency stability versus input voltage

1. Setup the configuration per figure 7 for frequencies measured at ambient temperature if it is within 15°C to 25°C . Otherwise, an environmental chamber set for a temperature of 20°C shall be used. Install new batteries in the EUT.

2. Set SA center frequency to the right frequency needs to be measured. Then set SA RBW to 30 kHz, VBW to 100kHz and frequency span to 500 kHz. Record this frequency to be a reference.

3. For non hand carried, battery operated device, supply the EUT primary voltage with 85 and 115 percent of the nominal value and record the frequency.

Figure 5 : Frequency stability measurement configuration



7.3 Measurement Instrument

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2010/09/17	2011/09/16
Temperature Chamber	MALLIER	MCT-2X-M	2010/12/03	2011/12/02

7.4 Measurement Data**A. Tx Frequency 604.1MHz****A1. Frequency stability versus enviroment tempture**

Reference Frequency :640.1 MHz		Limit : 0.005%					
Enviroment Tempature (°C)	Power Supplied (Vdc)	Frequency measured with time elapsed					
		2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
50	3.0Vdc (New Batt.)	640.0905	-0.00148	640.0991	-0.00014	640.1004	0.00006
40		640.0772	-0.00356	640.1137	0.00214	640.1007	0.00010
30		640.0909	-0.00142	640.0878	-0.00190	640.1221	0.00346
20		640.1088	0.00138	640.1225	0.00351	640.0987	-0.00021
10		640.0922	-0.00122	640.1225	0.00351	640.1147	0.00230
0		640.0958	-0.00066	640.0972	-0.00044	640.0939	-0.00096
-10		640.0892	-0.00169	640.0858	-0.00222	640.1217	0.00339
-20		640.0897	-0.00160	640.1138	0.00215	640.1213	0.00333
-30		640.1056	0.00087	640.1056	0.00087	640.1129	0.00201

A2. Frequency stability versus supplied voltage (85% - 115%)

Reference Frequency : 640.1 MHz		Limit : 0.005%					
Enviroment Tempature (°C)	Power Supplied (Vac)	Frequency measured with time elapsed					
		2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
25	2.55	640.0897	-0.00162	640.0967	-0.00051	640.0918	-0.00128
25	2.55	640.0764	-0.00369	640.0915	-0.00133	640.0762	-0.00372

B. Tx Frequency 652.1MHz**B1. Frequency stability versus environment temperature**

Reference Frequency : 652.1 MHz		Limit : 0.005%					
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency measured with time elapsed					
		2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
50	3.0Vdc (New Batt.)	652.1224	0.00343	652.1124	0.00191	652.0946	-0.00083
40		652.1027	0.00042	652.1040	0.00062	652.1064	0.00098
30		652.1046	0.00071	652.1221	0.00339	652.1043	0.00066
20		652.1017	0.00026	652.1194	0.00297	652.0936	-0.00098
10		652.1245	0.00376	652.0973	-0.00042	652.0945	-0.00085
0		652.1172	0.00263	652.1174	0.00267	652.1222	0.00340
-10		652.1012	0.00018	652.0952	-0.00073	652.0896	-0.00160
-20		652.0958	-0.00064	652.0784	-0.00331	652.0929	-0.00109
-30		652.1009	0.00015	652.1122	0.00186	652.1016	0.00025

B2. Frequency stability versus supplied voltage (85% - 115%)

Reference Frequency : 652.1 MHz		Limit : 0.005%					
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency measured with time elapsed					
		2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
25	2.55	652.1161	0.00246	652.0871	-0.00198	652.0823	-0.00271
25	2.55	652.0965	-0.00054	652.1195	0.00298	652.0959	-0.00063

C. Tx Frequency 663.9MHz**C1. Frequency stability versus environment temperature**

Reference Frequency : 663.9 MHz		Limit : 0.005%					
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency measured with time elapsed					
		2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
50	3.0Vdc (New Batt.)	663.9238	0.00359	663.8908	-0.00139	663.9201	0.00303
40		663.9186	0.00281	663.9003	0.00004	663.8778	-0.00334
30		663.8988	-0.00018	663.8865	-0.00203	663.8771	-0.00345
20		663.9103	0.00155	663.9092	0.00138	663.8999	-0.00001
10		663.9173	0.00261	663.9170	0.00255	663.8806	-0.00292
0		663.9030	0.00046	663.8920	-0.00120	663.8935	-0.00098
-10		663.8951	-0.00074	663.8815	-0.00278	663.9199	0.00299
-20		663.8923	-0.00116	663.8840	-0.00241	663.8793	-0.00311
-30		663.8846	-0.00233	663.9248	0.00374	663.8984	-0.00024

C2. Frequency stability versus supplied voltage (85% - 115%)

Reference Frequency : 663.9 MHz		Limit : 0.005%					
Environment Temperature (°C)	Power Supplied (Vdc)	Frequency measured with time elapsed					
		2 minute		5 minute		10 minute	
		(MHz)	(%)	(MHz)	(%)	(MHz)	(%)
25	2.55	663.9167	0.00252	663.8852	-0.00223	663.9082	0.00123
25	2.55	663.9231	0.00348	663.9133	0.00201	663.8853	-0.00222

8 CONDUCTED EMISSION MEASUREMENT

8.1 Standard Applicable

This EUT is excused from investigation of conducted emission, for it is powered by DC battery only. According to §15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.