



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	<b>Unex Technology Corporation</b>
Applicant Address	11F-3, No.100, Sec. 1, Jiafeng 11th Rd., Zhubei City, Hsinchu County 302, Taiwan
FCC ID	<b>NUK-DNMAH92</b>
Manufacturer's company	<b>Unex Technology Corporation</b>
Manufacturer Address	11F-3, No.100, Sec. 1, Jiafeng 11th Rd., Zhubei City, Hsinchu County 302, Taiwan

Product Name	WLAN 802.11a/b/g/n Mini-PCI module
Brand Name	Unex
Model Name	DNMA-H92
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5350MHz / 5470 ~ 5725MHz
Received Date	Nov. 20, 2009
Final Test Date	Dec. 07, 2009
Submission Type	Original Equipment



### Statement

**Test result included is for the 802.11n and 802.11a (5150 ~ 5350MHz / 5470 ~ 5725MHz) of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart E**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Testing Laboratory  
1190

## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	5
3.3. Table for Filed Antenna .....	5
3.4. Table for Carrier Frequencies .....	6
3.5. Table for Test Modes.....	7
3.6. Table for Testing Locations.....	8
3.7. Table for Supporting Units .....	8
3.8. Table for Parameters of Test Software Setting .....	9
3.9. Test Configurations .....	10
<b>4. TEST RESULT .....</b>	<b>13</b>
4.1. AC Power Line Conducted Emissions Measurement.....	13
4.2. 99% Occupied Bandwidth Measurement .....	17
4.3. Maximum Conducted Output Power Measurement.....	33
4.4. Power Spectral Density Measurement .....	65
4.5. Peak Excursion Measurement.....	81
4.6. Radiated Emissions Measurement .....	97
4.7. Band Edge Emissions Measurement .....	153
4.8. Frequency Stability Measurement .....	163
4.9. Antenna Requirements .....	165
<b>5. LIST OF MEASURING EQUIPMENTS.....</b>	<b>166</b>
<b>6. TEST LOCATION .....</b>	<b>167</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>168</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT .....</b>	<b>A1 ~ A5</b>
<b>APPENDIX B. TEST PHOTOS.....</b>	<b>B1 ~ B6</b>
<b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE .....</b>	<b>C1 ~ C3</b>





## 1. CERTIFICATE OF COMPLIANCE

Product Name : WLAN 802.11a/b/g/n Mini-PCI module  
Brand Name : Unex  
Model Name : DNMA-H92  
Applicant : Unex Technology Corporation  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 20, 2009 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

*Jordan Hsiao 2010.10.7*

Jordan Hsiao

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.30 dB
4.2	15.407(a)	99% Occupied Bandwidth Measurement	Complies	-
4.3	15.407(a)	Maximum Conducted Output Power	Complies	0.04 dB
4.4	15.407(a)	Power Spectral Density	Complies	7.80 dB
4.5	15.407(a)	Peak Excursion	Complies	6.41 dB
4.6	15.407(b)	Radiated Emissions	Complies	0.03 dB
4.7	15.407(b)	Band Edge Emissions	Complies	0.03 dB
4.8	15.407(g)	Frequency Stability	Complies	-
4.9	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.5dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
Peak Excursion	±0.5dB	Confidence levels of 95%
26dB Spectrum Bandwidth / Frequency Stability	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	5150 ~ 5350MHz / 5470 ~ 5725MHz
Channel Number	16 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 18.56 MHz ; MCS0 (40MHz): 36.64 MHz
Conducted Output Power	Band 1: MCS0 (20MHz): 16.03 dBm ; MCS0 (40MHz): 16.91 dBm Band 2: MCS0 (20MHz): 23.93 dBm ; MCS0 (40MHz): 23.83 dBm Band 3: MCS0 (20MHz): 23.87 dBm ; MCS0 (40MHz): 23.90 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

##### IEEE 802.11a

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	OFDM for IEEE 802.11a
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5150 ~ 5350MHz / 5470 ~ 5725MHz
Channel Number	16
Channel Band Width (99%)	Band 1: 16.96 MHz ; Band 2: 17.12 MHz ; Band 3: 17.12 MHz
Conducted Output Power	Band 1: 16.96 dBm ; Band 2: 23.94 dBm ; Band 3: 23.87 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**Antenna & Band width**

Antenna	Single (TX)		Two (TX)	
	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11a	X	X	V	X
IEEE 802.11n	X	X	V	V

**IEEE 802.11n spec**

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
					20MHz	40MHz	20MHz	40MHz	800nsGI		400nsGI	
									20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

### 3.2. Accessories

N/A


### 3.3. Table for Filed Antenna

<For 5GHz Band>:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
A (J4)	LCU	F1B-204406-52	Dipole Antenna	Reversed-SMA	2.50	TX/RX
B (J5)	LCU	F1B-204406-52	Dipole Antenna	Reversed-SMA	2.50	TX/RX

Note: The EUT has two Antennas.

Both Antenna A and B can be used as transmitting/receiving antenna.





### 3.4. Table for Carrier Frequencies

#### Frequency Allocation for 802.11a

There are two bandwidth systems for 802.11n.

For both 20MHz bandwidth systems, use Channel 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 132, 136, 140.

For both 40MHz bandwidth systems, use Channel 38, 46, 54, 62, 102, 110, 134.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
5250~5350 MHz Band 2	52	5260 MHz	60	5300 MHz
	54	5270 MHz	62	5310 MHz
	56	5280 MHz	64	5320 MHz
5470~5725 MHz Band 3	100	5500 MHz	116	5580 MHz
	102	5510MHz	132	5660 MHz
	104	5520 MHz	134	5670 MHz
	108	5540 MHz	136	5680 MHz
	110	5550 MHz	140	5700 MHz
	112	5560 MHz	-	-

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Antenna
AC Power Conducted Emission	Normal Link		Auto	-	A+B
Max. Conducted Output Power	MCS0/20MHz	Band 1~2	13Mbps	36/40/48/52/60/64	A / B / A+B
		Band 3	13Mbps	100/116/140	A / B / A+B
	MCS0/40MHz	Band 1~2	27Mbps	38/46/54/62	A / B / A+B
		Band 3	27Mbps	102/110/134	A / B / A+B
	11a/BPSK	Band 1~2	13Mbps	36/40/48/52/60/64	A / B / A+B
		Band 3	13Mbps	100/116/140	A / B / A+B
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement Power Spectral Density Peak Excursion	MCS0/20MHz	Band 1~2	13Mbps	36/40/48/52/60/64	A+B
		Band 3	13Mbps	100/116/140	A+B
	MCS0/40MHz	Band 1~2	27Mbps	38/46/54/62	A+B
		Band 3	27Mbps	102/110/134	A+B
	11a/BPSK	Band 1~2	13Mbps	36/40/48/52/60/64	A+B
		Band 3	13Mbps	100/116/140	A+B
Radiated Emission Below 1GHz	Normal Link		Auto	-	A+B
Radiated Emission Above 1GHz	MCS0/20MHz	Band 1~2	13Mbps	36/40/48/52/60/64	A+B
		Band 3	13Mbps	100/116/140	A+B
	MCS0/40MHz	Band 1~2	27Mbps	38/46/54/62	A+B
		Band 3	27Mbps	102/110/134	A+B
	11a/BPSK	Band 1~2	13Mbps	36/40/48/52/60/64	A+B
		Band 3	13Mbps	100/116/140	A+B
Band Edge Emission	MCS0/20MHz	Band 1~2	13Mbps	36/40/60/64	A+B
		Band 3	13Mbps	100/140	A+B
	MCS0/40MHz	Band 1~2	27Mbps	38/46/54/62	A+B
		Band 3	27Mbps	102/110/134	A+B
	11a/BPSK	Band 1~2	13Mbps	36/40/60/64	A+B
		Band 3	13Mbps	100/140	A+B
Frequency Stability	Un-modulation		-	60	N/A

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	879474	IC 4086	-
CO04-HY	Conduction	Hwa Ya	879474	IC 4086	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	E2K24GBRL
Mouse	iCooky	AMS0706W	DoC
Wireless AP	Planex	GW-AP54SGX	N/A
Modem	ACEEX	DM1414	IFAXDM1414
Printer	EPSON	LQ-300+	DoC
POWER SUPPLY	GW	GPC-6030D	DoC

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	ART Revision 0.9 BUILD #7								
Frequency	5180 MHz	5200 MHz	5240 MHz	5260 MHz	5300 MHz	5320 MHz	5500 MHz	5580 MHz	5700 MHz
IEEE 802.11n MCS0 20MHz	6	6.5	6.5	10.5	11.5	11.5	13	11.5	11.5

#### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	ART Revision 0.9 BUILD #7						
Frequency	5190 MHz	5230 MHz	5270 MHz	5310 MHz	5510 MHz	5550 MHz	5670 MHz
IEEE 802.11n MCS0 40MHz	6	6	11.5	10	9.5	11	11.5

#### Power Parameters of IEEE 802.11a

Test Software Version	ART Revision 0.9 BUILD #7								
Frequency	5180 MHz	5200 MHz	5240 MHz	5260 MHz	5300 MHz	5320 MHz	5500 MHz	5580 MHz	5700 MHz
IEEE 802.11a	6.5	7	6.5	11	12	11.5	11	11.5	11.5



During the test, the following programs under WIN XP were executed:

Executed "ART Revision 0.9 BUILD #7" to control the EUT continuously transmit RF signal.


### 3.9. Test Configurations

#### 3.9.1. Radiation Emissions Test Configuration


Test Configuration: 9kHz~1GHz



Test Configuration: above 1GHz



### 3.9.2. AC Power Line Conduction Emissions Test Configuration



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.



#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	54%
Test Engineer	Rex Chiu	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	2.237	20.96	-25.04	46.00	20.70	0.06	0.20	AVERAGE
2	2.237	35.93	-20.07	56.00	35.67	0.06	0.20	QP
3	2.461	24.33	-21.67	46.00	24.06	0.07	0.20	AVERAGE
4	2.461	38.45	-17.55	56.00	38.18	0.07	0.20	QP
5	2.678	23.18	-22.82	46.00	22.91	0.07	0.20	AVERAGE
6	2.678	36.67	-19.33	56.00	36.40	0.07	0.20	QP
7	3.031	30.30	-15.70	46.00	30.01	0.08	0.21	AVERAGE
8	3.031	37.14	-18.86	56.00	36.85	0.08	0.21	QP
9	3.293	29.24	-16.76	46.00	28.89	0.09	0.26	AVERAGE
10	3.293	37.45	-18.55	56.00	37.10	0.09	0.26	QP
11	5.787	36.11	-13.89	50.00	35.61	0.20	0.30	AVERAGE
12	5.787	42.38	-17.62	60.00	41.88	0.20	0.30	QP

Temperature	23°C	Humidity	54%
Test Engineer	Rex Chiu	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	2.474	24.79	-21.21	46.00	24.48	0.11	0.20	AVERAGE
2	2.474	36.83	-19.17	56.00	36.52	0.11	0.20	QP
3	3.025	30.99	-15.01	46.00	30.66	0.12	0.21	AVERAGE
4	3.025	38.69	-17.31	56.00	38.36	0.12	0.21	QP
5	3.140	27.86	-18.14	46.00	27.50	0.12	0.23	AVERAGE
6	3.140	38.71	-17.29	56.00	38.35	0.12	0.23	QP
7	3.417	27.59	-18.41	46.00	27.18	0.13	0.28	AVERAGE
8	3.417	36.23	-19.77	56.00	35.82	0.13	0.28	QP
9	3.603	37.37	-18.63	56.00	36.94	0.13	0.30	QP
10	3.603	29.88	-16.12	46.00	29.45	0.13	0.30	AVERAGE
11	5.795	43.84	-16.16	60.00	43.30	0.24	0.30	QP
12	5.795	37.70	-12.30	50.00	37.16	0.24	0.30	AVERAGE

Note:

$$\text{Level} = \text{Read Level} + \text{LISN Factor} + \text{Cable Loss}$$

## 4.2. 99% Occupied Bandwidth Measurement

### 4.2.1. Limit

No restriction limits. But resolution bandwidth within band edge measurement is 1% of the 99% occupied bandwidth.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RB	300 kHz
VB	1000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 300 kHz and the video bandwidth of 1000 kHz were used.
3. Measured the spectrum width with power higher than 26dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of 99% Occupied Bandwidth

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	23.04	16.96
40	5200 MHz	23.36	16.96
48	5240 MHz	23.20	16.96
52	5260 MHz	24.00	16.96
60	5300 MHz	23.68	16.96
64	5320 MHz	22.88	16.96
100	5500 MHz	23.52	17.12
116	5580 MHz	25.60	18.56
140	5700 MHz	24.16	17.12

##### Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	46.40	36.48
46	5230 MHz	47.52	36.64
54	5270 MHz	47.36	36.48
62	5310 MHz	47.52	36.64
102	5510MHz	46.08	36.64
110	5550 MHz	46.72	36.64
134	5670 MHz	46.72	36.48

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a Ant. A + Ant. B**


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	23.36	16.96
40	5200 MHz	23.36	16.96
48	5240 MHz	23.20	16.96
52	5260 MHz	23.20	17.12
60	5300 MHz	23.68	16.96
64	5320 MHz	23.20	16.96
100	5500 MHz	23.68	17.12
116	5580 MHz	22.72	17.12
140	5700 MHz	23.68	16.96

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5180 MHz**




Date: 25.NOV.2009 14:54:02

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5200 MHz**




Date: 25.NOV.2009 14:55:12

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5240 MHz



Date: 25.NOV.2009 14:56:07


26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5260 MHz



Date: 25.NOV.2009 14:57:11




26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5300 MHz




Date: 25.NOV.2009 14:58:08

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5320 MHz




Date: 25.NOV.2009 14:58:58

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5500 MHz**




Date: 25.NOV.2009 14:59:59

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5580 MHz**




Date: 25.NOV.2009 15:02:43

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5700 MHz




Date: 25.NOV.2009 15:01:19

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5190 MHz




Date: 25.NOV.2009 15:36:34

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5230 MHz




Date: 25.NOV.2009 15:37:57

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5270 MHz




Date: 25.NOV.2009 15:39:13

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5310 MHz**




Date: 25.NOV.2009 15:41:59

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5510MHz**




Date: 25.NOV.2009 15:43:26

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5550 MHz**




Date: 25.NOV.2009 15:44:46

**26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5670 MHz**




Date: 25.NOV.2009 15:45:53

**26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5180 MHz**




Date: 25.NOV.2009 15:26:56

**26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5200 MHz**




Date: 25.NOV.2009 15:25:57

### 26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5240 MHz



Date: 25.NOV.2009 15:25:06


### 26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5260 MHz



Date: 25.NOV.2009 15:24:01




### 26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5300 MHz




Date: 25.NOV.2009 15:22:45

### 26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5320 MHz




Date: 25.NOV.2009 15:21:47

### 26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5500 MHz




Date: 25.NOV.2009 15:20:46

### 26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5580 MHz



Date: 25.NOV.2009 15:15:21

26 dB Bandwidth Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5700 MHz



Date: 25.NOV.2009 15:18:31

### 4.3. Maximum Conducted Output Power Measurement

#### 4.3.1. Limit

For the band 5.15~5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW (17dBm) or  $4 \text{ dBm} + 10\log B$ , where B is the 26 dB emissions bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power and power density from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.470-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW (24dBm) or  $11 \text{ dBm} + 10\log B$ . If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power and power density from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.825 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 1 W (30dBm) or  $17 \text{ dBm} + 10\log B$ . If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power and power density from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain up to 23 dBi without any corresponding reduction in the transmitter peak output power and peak power spectral density. For fixed, point-to-point U-NII transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in peak transmitter power and peak power spectral density for each 1 dB of antenna gain in excess of 23 dBi would be required.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	PEAK
Trace	MAX HOLD
Sweep Time	Auto

#### 4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Maximum Conducted Output Power

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	12.68	17.00	Complies
40	5200 MHz	12.59	17.00	Complies
48	5240 MHz	12.80	17.00	Complies
52	5260 MHz	20.53	24.00	Complies
60	5300 MHz	20.90	24.00	Complies
64	5320 MHz	20.91	24.00	Complies
100	5500 MHz	20.03	24.00	Complies
116	5580 MHz	20.12	24.00	Complies
140	5700 MHz	20.77	24.00	Complies

##### Configuration IEEE 802.11n MCS0 20MHz Ant. B

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	13.06	17.00	Complies
40	5200 MHz	13.32	17.00	Complies
48	5240 MHz	13.23	17.00	Complies
52	5260 MHz	20.57	24.00	Complies
60	5300 MHz	20.94	24.00	Complies
64	5320 MHz	20.87	24.00	Complies
100	5500 MHz	21.56	24.00	Complies
116	5580 MHz	20.69	24.00	Complies
140	5700 MHz	20.55	24.00	Complies

**Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B**

<b>Channel</b>	<b>Frequency</b>	<b>Conducted Power (dBm)</b>	<b>Max. Limit (dBm)</b>	<b>Result</b>
36	5180 MHz	15.88	17.00	<b>Complies</b>
40	5200 MHz	15.98	17.00	<b>Complies</b>
48	5240 MHz	16.03	17.00	<b>Complies</b>
52	5260 MHz	23.56	24.00	<b>Complies</b>
60	5300 MHz	23.93	24.00	<b>Complies</b>
64	5320 MHz	23.90	24.00	<b>Complies</b>
100	5500 MHz	23.87	24.00	<b>Complies</b>
116	5580 MHz	23.42	24.00	<b>Complies</b>
140	5700 MHz	23.67	24.00	<b>Complies</b>

**Configuration IEEE 802.11n MCS0 40MHz Ant. A**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	13.37	17.00	Complies
46	5230 MHz	13.45	17.00	Complies
54	5270 MHz	20.74	24.00	Complies
62	5310 MHz	19.46	24.00	Complies
102	5510MHz	19.49	24.00	Complies
110	5550 MHz	20.65	24.00	Complies
134	5670 MHz	20.89	24.00	Complies

**Configuration IEEE 802.11n MCS0 40MHz Ant. B**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	14.38	17.00	Complies
46	5230 MHz	14.31	17.00	Complies
54	5270 MHz	20.89	24.00	Complies
62	5310 MHz	19.66	24.00	Complies
102	5510MHz	20.13	24.00	Complies
110	5550 MHz	21.05	24.00	Complies
134	5670 MHz	20.88	24.00	Complies

**Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	16.91	17.00	Complies
46	5230 MHz	16.91	17.00	Complies
54	5270 MHz	23.83	24.00	Complies
62	5310 MHz	22.57	24.00	Complies
102	5510MHz	22.83	24.00	Complies
110	5550 MHz	23.86	24.00	Complies
134	5670 MHz	23.90	24.00	Complies



<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a Ant. A**

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	13.06	17.00	<b>Complies</b>
40	5200 MHz	13.49	17.00	<b>Complies</b>
48	5240 MHz	12.66	17.00	<b>Complies</b>
52	5260 MHz	20.20	24.00	<b>Complies</b>
60	5300 MHz	20.62	24.00	<b>Complies</b>
64	5320 MHz	20.32	24.00	<b>Complies</b>
100	5500 MHz	19.85	24.00	<b>Complies</b>
116	5580 MHz	20.84	24.00	<b>Complies</b>
140	5700 MHz	20.50	24.00	<b>Complies</b>

**Configuration IEEE 802.11a Ant. B**


Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	14.46	17.00	<b>Complies</b>
40	5200 MHz	14.37	17.00	<b>Complies</b>
48	5240 MHz	13.55	17.00	<b>Complies</b>
52	5260 MHz	20.85	24.00	<b>Complies</b>
60	5300 MHz	21.21	24.00	<b>Complies</b>
64	5320 MHz	20.71	24.00	<b>Complies</b>
100	5500 MHz	21.48	24.00	<b>Complies</b>
116	5580 MHz	20.88	24.00	<b>Complies</b>
140	5700 MHz	21.06	24.00	<b>Complies</b>

**Configuration IEEE 802.11a Ant. A + Ant. B**

<b>Channel</b>	<b>Frequency</b>	<b>Conducted Power (dBm)</b>	<b>Max. Limit (dBm)</b>	<b>Result</b>
36	5180 MHz	16.83	17.00	<b>Complies</b>
40	5200 MHz	16.96	17.00	<b>Complies</b>
48	5240 MHz	16.14	17.00	<b>Complies</b>
52	5260 MHz	23.55	24.00	<b>Complies</b>
60	5300 MHz	23.94	24.00	<b>Complies</b>
64	5320 MHz	23.53	24.00	<b>Complies</b>
100	5500 MHz	23.75	24.00	<b>Complies</b>
116	5580 MHz	23.87	24.00	<b>Complies</b>
140	5700 MHz	23.80	24.00	<b>Complies</b>




**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A / 5240 MHz**



Date: 25.NOV.2009 16:31:26


**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A / 5260 MHz**



Date: 25.NOV.2009 16:33:20




**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A / 5500 MHz**




Date: 25.NOV.2009 11:33:09

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A / 5580 MHz**




Date: 25.NOV.2009 11:24:54

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A / 5700 MHz**



Date: 25.NOV.2009 11:21:41

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. B / 5180 MHz**



Date: 25.NOV.2009 16:25:16











**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. B / 5580 MHz**



Date: 25.NOV.2009 11:23:42

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. B / 5700 MHz**




Date: 25.NOV.2009 11:22:52






**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A / 5510MHz**




Date: 25.NOV.2009 16:15:58

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A / 5550 MHz**




Date: 25.NOV.2009 16:17:46

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A / 5670 MHz**



Date: 25.NOV.2009 16:20:57

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. B / 5190 MHz**



Date: 25.NOV.2009 16:03:37













### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5240 MHz




Date: 25.NOV.2009 10:35:25

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5260 MHz




Date: 25.NOV.2009 10:36:14

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5300 MHz




Date: 25.NOV.2009 10:38:27

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5320 MHz




Date: 25.NOV.2009 10:39:25

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5500 MHz




Date: 25.NOV.2009 10:43:00

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5580 MHz




Date: 25.NOV.2009 10:46:30

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. A / 5700 MHz




Date: 25.NOV.2009 10:47:21

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5180 MHz




Date: 25.NOV.2009 10:27:42

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5200 MHz



Date: 25.NOV.2009 10:28:48


### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5240 MHz



Date: 25.NOV.2009 10:33:35




**Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5260 MHz**




Date: 25.NOV.2009 10:36:59

**Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5300 MHz**




Date: 25.NOV.2009 10:37:49

**Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5320 MHz**




Date: 25.NOV.2009 10:40:15

**Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5500 MHz**




Date: 25.NOV.2009 10:43:40

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5580 MHz



Date: 25.NOV.2009 10:45:04

### Conducted Output Power Plot on Configuration IEEE 802.11a Ant. B / 5700 MHz



Date: 25.NOV.2009 10:48:37

## 4.4. Power Spectral Density Measurement

### 4.4.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.15~5.25 GHz	4
5.25-5.35 GHz	11
5470-5725	11

### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 1000kHz and VBW to 3000kHz. Set Detector to Peak, Trace to Max Hold. Mark the frequency with maximum peak power as the center of the display of the spectrum.
3. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

### 4.4.4. Test Setup Layout



### 4.4.5. Test Deviation

There is no deviation with the original standard.

#### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of Power Spectral Density

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	-4.46	4.00	Complies
40	5200 MHz	-4.65	4.00	Complies
48	5240 MHz	-5.23	4.00	Complies
52	5260 MHz	2.22	11.00	Complies
60	5300 MHz	3.20	11.00	Complies
64	5320 MHz	3.04	11.00	Complies
100	5500 MHz	2.63	11.00	Complies
116	5580 MHz	1.34	11.00	Complies
140	5700 MHz	0.77	11.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
38	5190 MHz	-8.37	4.00	Complies
46	5230 MHz	-8.28	4.00	Complies
54	5270 MHz	-0.60	11.00	Complies
62	5310 MHz	-2.01	11.00	Complies
102	5510MHz	-2.93	11.00	Complies
110	5550 MHz	-2.12	11.00	Complies
134	5670 MHz	-1.45	11.00	Complies

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a Ant. A + Ant. B**


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
36	5180 MHz	-5.30	4.00	<b>Complies</b>
40	5200 MHz	-4.42	4.00	<b>Complies</b>
48	5240 MHz	-6.16	4.00	<b>Complies</b>
52	5260 MHz	2.24	11.00	<b>Complies</b>
60	5300 MHz	3.02	11.00	<b>Complies</b>
64	5320 MHz	2.98	11.00	<b>Complies</b>
100	5500 MHz	1.98	11.00	<b>Complies</b>
116	5580 MHz	1.43	11.00	<b>Complies</b>
140	5700 MHz	0.54	11.00	<b>Complies</b>

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5180 MHz**




Date: 25.NOV.2009 14:54:08

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5200 MHz**




Date: 25.NOV.2009 14:55:19

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5240 MHz**



Date: 25.NOV.2009 14:56:14


**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5260 MHz**



Date: 25.NOV.2009 14:57:18




**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5300 MHz**




Date: 25.NOV.2009 14:58:15

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5320 MHz**




Date: 25.NOV.2009 14:59:05

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5500 MHz**




Date: 25.NOV.2009 15:00:07

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5580 MHz**




Date: 25.NOV.2009 15:02:50

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5700 MHz**




Date: 25.NOV.2009 15:01:26

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5190 MHz**




Date: 25.NOV.2009 15:36:41

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5230 MHz**




Date: 25.NOV.2009 15:38:04

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5270 MHz**




Date: 25.NOV.2009 15:39:20

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5310 MHz**




Date: 25.NOV.2009 15:42:05

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5510MHz**




Date: 25.NOV.2009 15:43:33

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5550 MHz




Date: 25.NOV.2009 15:44:53

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5670 MHz




Date: 25.NOV.2009 15:46:00

**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5180 MHz**




Date: 25.NOV.2009 15:27:03

**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5200 MHz**




Date: 25.NOV.2009 15:26:04

**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5240 MHz**



Date: 25.NOV.2009 15:25:12


**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5260 MHz**



Date: 25.NOV.2009 15:24:07




**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5300 MHz**




Date: 25.NOV.2009 15:22:51

**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5320 MHz**




Date: 25.NOV.2009 15:21:54

**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5500 MHz**




Date: 25.NOV.2009 15:20:53

**Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5580 MHz**



Date: 25.NOV.2009 15:15:29

### Power Density Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5700 MHz



Date: 25.NOV.2009 15:18:38

## 4.5. Peak Excursion Measurement

### 4.5.1. Limit

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emissions bandwidth whichever is less.

### 4.5.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz (Peak Trace) / 1000 kHz (Average Trace)
VB	3000 kHz (Peak Trace) / 300 kHz (Average Trace)
Detector	Peak (Peak Trace) / Sample (Average Trace)
Trace	Max Hold
Sweep Time	60s

### 4.5.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set the spectrum analyzer span to view the entire emissions bandwidth. The largest difference between the following two traces (Peak Trace and Average Trace) must be  $\leq 13$  dB for all frequencies across the emissions bandwidth. Submit a plot.
3. Peak Trace: Set RBW = 1 MHz, VBW  $\geq 3$  MHz with peak detector and max-hold settings.
4. Average Trace: Method #3—video averaging with max hold--and sum power across the band. Set span to encompass the entire emissions bandwidth (EBW) of the signal. Set sweep trigger to "free run". Set RBW = 1 MHz. Set VBW  $\geq 1/T$  (IEEE 802.11n VBW = 300kHz  $\geq 1/4\mu\text{s}$ ). Use sample detector mode if bin width (i.e., span/number of points in spectrum)  $< 0.5$  RBW. Otherwise use peak detector mode. Set max hold. Allow max hold to run for 60 seconds.
5. Measuring multiple antennas, the connector is required to link with Power Meter through a combiner.

### 4.5.4. Test Setup Layout



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Test Result of Peak Excursion

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B

Channel	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
36	5180 MHz	4.43	13	Complies
40	5200 MHz	5.02	13	Complies
48	5240 MHz	4.52	13	Complies
52	5260 MHz	5.40	13	Complies
60	5300 MHz	5.30	13	Complies
64	5320 MHz	4.94	13	Complies
100	5500 MHz	4.74	13	Complies
116	5580 MHz	5.15	13	Complies
140	5700 MHz	4.97	13	Complies

##### Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B


Channel	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
38	5190 MHz	4.93	13	Complies
46	5230 MHz	5.49	13	Complies
54	5270 MHz	5.60	13	Complies
62	5310 MHz	5.74	13	Complies
102	5510MHz	5.15	13	Complies
110	5550 MHz	5.05	13	Complies
134	5670 MHz	6.59	13	Complies

<b>Temperature</b>	23°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Beck Wu	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a Ant. A + Ant. B**


<b>Channel</b>	<b>Frequency</b>	<b>Peak Excursion (dB)</b>	<b>Max. Limit (dB)</b>	<b>Result</b>
36	5180 MHz	5.12	13	<b>Complies</b>
40	5200 MHz	4.04	13	<b>Complies</b>
48	5240 MHz	5.59	13	<b>Complies</b>
52	5260 MHz	4.69	13	<b>Complies</b>
60	5300 MHz	5.37	13	<b>Complies</b>
64	5320 MHz	4.87	13	<b>Complies</b>
100	5500 MHz	5.17	13	<b>Complies</b>
116	5580 MHz	5.64	13	<b>Complies</b>
140	5700 MHz	5.00	13	<b>Complies</b>

Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5180 MHz




Date: 25.NOV.2009 14:54:29

Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5200 MHz




Date: 25.NOV.2009 14:55:39

Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5240 MHz



Date: 25.NOV.2009 14:56:35


Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5260 MHz



Date: 25.NOV.2009 14:57:39




**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5300 MHz**




Date: 25.NOV.2009 14:58:36

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5320 MHz**




Date: 25.NOV.2009 14:59:26

Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5500 MHz




Date: 25.NOV.2009 15:00:29

Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5580 MHz




Date: 25.NOV.2009 15:03:12

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 20MHz Ant. A + Ant. B / 5700 MHz**




Date: 25.NOV.2009 15:01:48

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5190 MHz**




Date: 25.NOV.2009 15:37:02

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5230 MHz**




Date: 25.NOV.2009 15:38:24

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5270 MHz**




Date: 25.NOV.2009 15:39:41

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5310 MHz**




Date: 25.NOV.2009 15:42:26

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5510MHz**




Date: 25.NOV.2009 15:43:54

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5550 MHz**




Date: 25.NOV.2009 15:45:14

**Peak Excursion Plot on Configuration IEEE 802.11n MCS0 40MHz Ant. A + Ant. B / 5670 MHz**




Date: 25.NOV.2009 15:46:21

**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5180 MHz**




Date: 25.NOV.2009 15:27:24

**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5200 MHz**




Date: 25.NOV.2009 15:26:25

**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5240 MHz**



Date: 25.NOV.2009 15:25:33


**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5260 MHz**



Date: 25.NOV.2009 15:24:28




**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5300 MHz**




Date: 25.NOV.2009 15:23:12

**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5320 MHz**




Date: 25.NOV.2009 15:22:15

**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5500 MHz**




Date: 25.NOV.2009 15:21:15

**Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5580 MHz**



Date: 25.NOV.2009 15:15:51

Peak Excursion Plot on Configuration IEEE 802.11a Ant. A + Ant. B / 5700 MHz



Date: 25.NOV.2009 15:19:00