

**FCC PART 15 SUBPART B & SUBPART C SECTION 15.249,
RSS 210, & RSS GEN
TEST REPORT**

for

**ZWAVE PLUS SERIES SMARTCODE LOCKS
Models: Smartcode 910, Smartcode 912, Smartcode 914, & Smartcode 916**

Prepared for

SPECTRUM BRANDS
19701 DAVINCI
LAKE FOREST, CA 92610

Prepared by: _____

MATT HARRISON

Reviewed by: _____

JOEY MADLANGBAYAN

COMPATIBLE ELECTRONICS INC.
20621 PASCAL WAY
LAKE FOREST, CALIFORNIA 92630
(949) 587-0400

DATE: SEPTEMBER 15, 2016

	REPORT BODY	APPENDICES					TOTAL
		A	B	C	D	E	
PAGES	17	2	2	2	11	36	70

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

TABLE OF CONTENTS

Section / Title	PAGE
GENERAL REPORT SUMMARY	4
SUMMARY OF TEST RESULTS	5
1. PURPOSE	6
2. ADMINISTRATIVE DATA	7
2.1 Location of Testing	7
2.2 Traceability Statement	7
2.3 Cognizant Personnel	7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	7
3. APPLICABLE DOCUMENTS	8
4. DESCRIPTION OF TEST CONFIGURATION	9
4.1 Description of Test Configuration	9
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT	11
5.1 EUT and Accessory List	11
5.2 EMI Test Equipment	12
6. TEST SITE DESCRIPTION	13
6.1 Test Facility Description	13
6.2 EUT Mounting, Bonding and Grounding	13
6.3 Facility Environmental Characteristics	13
6.4 Measurement Uncertainty	13
7. CHARACTERISTICS OF THE TRANSMITTER	14
7.1 Channel Number and Frequencies	14
7.2 Antenna	14
8. TEST PROCEDURES	15
8.1 RF Emissions	15
9. TEST PROCEDURE DEVIATIONS	17
10. CONCLUSIONS	17



LIST OF APPENDICES

APPENDIX	TITLE
A	Laboratory Accreditations and Recognitions
B	Modifications to the EUT
C	Additional Models Covered Under This Report
D	Diagrams, Charts, and Photos <ul style="list-style-type: none">• Test Setup Diagrams• Antenna and Amplifier Gain Factors• Radiated Emissions Photos
E	Radiated Emissions Data Sheets

LIST OF FIGURES

FIGURE	TITLE
1	Plot Map and Layout of Test Site Below 1GHz
2	Plot Map and Layout of Test Site Above 1GHz



GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full with the written permission of Compatible Electronics.

This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST, or any agency of the federal government.

Device Tested: Zwave Plus Series Smartcode Locks
Models: Smartcode 910, 912, 914, & 916
S/N: None

Product Description: The EUTs are Zwave Plus Series Smartcode Locks operating via Zwave technology.

Modifications: The EUTs were not modified in order to comply with specifications.

Manufacturer: Spectrum Brands
19701 DaVinci
Lake Forest, CA 92610

Test Date: January 12-14, 2016

Test Specifications Covered by Accreditation:



EMI requirements

CFR Title 47, Part 15 Subpart B Sections 15.107, 15.109, Subpart C Sections 15.205, 15.207, 15.209, and 15.249

RSS 210 & RSS GEN

Test Procedure: ANSI C63.4 & C63.10



SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 150 kHz - 30 MHz.	The EUT is battery powered; therefore this test was not performed.
2	Radiated RF Emissions & Harmonics, 9 kHz – 25,000 MHz.	Complies with the limits of CFR Title 47 Part 15 Subpart B Section 15.109 & Subpart C Sections 15.205, 15.209, & 15.249, RSS 210 & RSS GEN
3	Fundamental Field Strength	Complies with the limits of CFR Title 47 Part 15 Subpart C Section 15.249 & RSS 210
4	Emissions Radiated Outside of the Fundamental Frequency Band	Complies with the limits of CFR Title 47 Part 15 Subpart B Section 15.109 & Subpart C Sections 15.205, 15.209, & 15.249, RSS 210 & RSS GEN
5	Occupied Bandwidth	Complies with the limits of RSS 210 & RSS GEN



1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Zwave Plus Series Smartcode Locks Models: Smartcode 910, 912, 914, & 916. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4 & C63.10. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT (equipment under test) hereafter, are within the specification limits defined by the Code of Federal Regulations Title 47, Part 15 Subpart B sections 15.109, & Part 15 Subpart C sections 15.205, 15.209, 15.249, RSS GEN, & RSS 210.



2. ADMINISTRATIVE DATA

2.1 Location of Testing

The tests described herein were performed at the test facility of Compatible Electronics, 20621 Pascal Way Lake Forest, California 92630.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Spectrum Brands

Thuan Nguyen Senior Electronics Engineer

Compatible Electronics, Inc.

Torey Oliver Test Engineer

Matt Harrison Lab Manager

2.4 Date Test Sample was Received

The test sample was received on January 12th, 2016.

2.5 Disposition of the Test Sample

The test sample remains at Compatible Electronics, Inc. as of the date of this test report.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
NVLAP	National Voluntary Laboratory Accreditation Program
CFR	Code of Federal Regulations
PCB	Printed Circuit Board
TX	Transmit
RX	Receive



3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 2014	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10: 2013	American National Standard for Testing Unlicensed Wireless Devices
RSS GEN	General Requirements for Compliance of Radio Apparatus
RSS 210	Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment



4. DESCRIPTION OF TEST CONFIGURATION


4.1 Description of Test Configuration

The Zwave Plus Series Smartcode Locks Models: Smartcode 910, 912, 914, & 916 (EUT) were setup individually in a tabletop configuration. The EUTs were checked all 3 axis. The worst case was found to be the X-Axis. The EUTs were continuously transmitting a data stream during transmitter tests and continuously receiving during receive tests.

The tests were performed using new batteries.

It was determined that the emissions were at their highest level when the EUTs were transmitting in the configuration described above for Radiated Emissions. The final radiated data was taken in the above configuration. Please see Appendix E for the test data.

4.1.1 Photograph Test Configuration (X-Axis)



4.1.2 Cable Construction and Termination

There were no interconnecting cables.

4.1.3 Axis Determination



5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT

5.1 EUT and Accessory List

#	EQUIPMENT TYPE	MANUFACTURER	MODEL	SERIAL NUMBER
1	ZWAVE PLUS SERIES SMARTCODE LOCKS (EUT)	SPECTRUM BRANDS	SMARTCODE 910	NONE
2	ZWAVE PLUS SERIES SMARTCODE LOCKS (EUT)	SPECTRUM BRANDS	SMARTCODE 912	NONE
3	ZWAVE PLUS SERIES SMARTCODE LOCKS (EUT)	SPECTRUM BRANDS	SMARTCODE 914	NONE
4	ZWAVE PLUS SERIES SMARTCODE LOCKS (EUT)	SPECTRUM BRANDS	SMARTCODE 916	NONE
5	BATTERIES (4)	RAYOVAC	AA	NONE

5.1.1 Software Used to Exercise the Transmitter:

Version: v4.04, Date: 09/12/2016,

Storage Location: Spectrum Brands, Inc.

Released Notes, Docs & Firmware\Firmware Releases for QA\Z-Wave Daughter Card\Cobra



5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. DUE DATE
Computer	Compatible Electronics	NONE	NONE	N/A	N/A
EMI Receiver	Rohde & Schwarz	ESIB40	100219	09/03/2015	09/03/2016
EMI Receiver	Agilent	N9038A	MY51100115	12/29/2015	12/29/2016
Antenna, Loop	Com Power	AL-130	121049	12/06/2013	12/06/2016
Antenna, CombiLog	Com Power	AC-220	25857	05/21/2014	05/21/2016
Antenna, Horn 1-18GHz	Com Power	AH-118	071250	07/01/2014	07/01/2016
Antenna, Horn 18-26GHz	Com-Power	AH-826	081033	07/06/2014	07/06/2016
Pre-Amp, 1-18GHz	Com Power	PAM-118A	551034	8/25/2015	8/25/2016
Pre-Amp, 18-40GHz	Com-Power	PA-840	181289	6/16/2015	6/16/2016
High Pass Filter	AMTI Microwave Circuits	H3G020G4	481230	8/26/2015	8/26/2016
Mast, Antenna Positioner	Sunol Science Corporation	TWR 95-4	020808-3	N/A	N/A
Antenna Mast	Sunol Science Corporation	TWR 95-4	020808-3	N/A	N/A
Turntable	Sunol Science Corporation	FM 2001	N/A	N/A	N/A
Mast and Turntable Controller	Sunol Science Corporation	SC104V	020808-1	N/A	N/A



6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to section 2.1 and the figures in Appendix D of this report for test location.

6.2 EUT Mounting, Bonding and Grounding

The EUTs were mounted on a 1.0 by 1.5 by 0.8-meter-high non-conductive table, which was placed on the ground plane.

For above 1GHz testing the EUTs were placed 1.5 meters above high, above the ground plane.

The EUTs were not grounded.

6.3 Facility Environmental Characteristics

When applicable refer to the data sheets in Appendix E for the relative humidity, air temperature, and barometric pressure.

6.4 Measurement Uncertainty

“Compatible Electronics’ U_{lab} value is less than U_{cispr} , thus based on this – compliance is deemed to occur if no measured disturbance exceeds the disturbance limit.

$$u_c(y) = \sqrt{\sum_i c_i^2 u^2(x_i)}$$

Measurement		U_{cispr}	$U_{lab} = 2 u_c(y)$
Conducted disturbance (mains port)	(150 kHz – 30 MHz)	3,6 dB	2.88
Radiated disturbance (electric field strength on an open area test site or alternative test site)	(30 MHz – 1 000 MHz)	5,2 dB	3.53



7. CHARACTERISTICS OF THE TRANSMITTER

7.1 Channel Number and Frequencies

There are a total of 2 channels. The low channel is at 908.4 MHz and the high channel is at 916.0 MHz. The EUT uses FSK & GFSK modulation.

7.2 Antenna

The antenna is a PCB trace located on the PCB.



8. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

8.1 RF Emissions


8.1.1 *Conducted Emissions Test*

Test Results: The EUT is battery powered; therefore this test was not performed.

The EMI receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. The LISN output was measured using the EMI receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT received its power through the LISN, which was bonded to the ground plane. The EUTs were set up with the minimum distances from any conductive surfaces as specified in ANSI 63.4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The different configurations were investigated to find the worst case as well the worst case channel. The final data was collected under program control by the computer software. The final qualification data is located in Appendix E.



8.1.2 Radiated Emissions (Spurious and Harmonics) Test

The EMI receiver was used as a measuring meter. The receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the receiver records the highest measured reading over all the sweeps. Amplifiers were used to increase the sensitivity of the instrument. There was one Microwave Preamplifier used for frequencies above 1 GHz.

For spurious emissions the quasi-peak detector was used for frequencies below 1GHz and the average detector was used for frequencies above 1 GHz.

For the harmonic and fundamental emissions a linear average was used. For the non-intentional emissions above 1GHz a linear average was used.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE (MHz)	TRANSDUCER	EFFECTIVE MEASUREMENT BANDWIDTH
.009 to .150	Active Loop Antenna	200 Hz
.150 to 30	Active Loop Antenna	9 kHz
30 to 1000	Combilog Antenna	100 kHz (120 kHz for QP Measurements)
1000 to 25000	Horn Antenna	1 MHz

The TDK FAC-3 shielded test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4 & ANSI C63.10. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUTs were rotated 360 degrees and the antenna height was varied from 1 to 4 meters in both vertical and horizontal polarizations (for E field radiated field strength).

Test Results:

The EUT complies with the limits of CFR Title 47 Part 15 Subpart B section 15.109, & Part 15 Subpart C sections 15.205, 15.209, 15.249, RSS GEN, & RSS 210. The six highest emissions are listed in table 1.



8.1.3 *Fundamental Field Strength*

The Peak Transmit Radiated Field Strength was measured at a 3-meter test distance. The EMI Receiver was used to obtain the final test data. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15 Subpart C, Section 15.249 & RSS 210.

8.1.4 *Emissions Radiated Outside of the Fundamental Frequency Band*

The Band Edge measurement was measured using the EMI Receiver at a 3-meter test distance to obtain the final test data. The lower and upper channels were tuned during the low and high band edge tests. The final qualification data sheets are located in Appendix E.

Test Results:

The EUT complies with Part 15 Subpart C, Section 15.205, 15.249, RSS GEN, & RSS 210.

9. **TEST PROCEDURE DEVIATIONS**

The test procedures were not deviated from throughout all tests.

10. **CONCLUSIONS**

The Zwave Plus Series Smartcode Locks Model: Smartcode 910, 912, 914, & 916 meets all of the relevant specification requirements defined in the Code of Federal Regulations Title 47, Part 15 Subpart B section 15.109, & Subpart C sections 15.205, 15.209, 15.249, RSS GEN, & RSS 210.



APPENDIX A



***LABORATORY ACCREDITATIONS AND
RECOGNITIONS***



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

LABORATORY ACCREDITATIONS AND RECOGNITIONS



For US, Canada, Australia/New Zealand, Japan, Taiwan, Korea, and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025.

For the most up-to-date version of our scopes and certificates please visit

<http://celectronics.com/quality/scope/>

Quote from ISO-ILAC-IAF Communiqué on 17025:

"A laboratory's fulfilment of the requirements of ISO/IEC 17025:2005 means the laboratory meets both the technical competence requirements and management system requirements that are necessary for it to consistently deliver technically valid test results and calibrations. The management system requirements in ISO/IEC 17025:2005 (Section 4) are written in language relevant to laboratory operations and meet the principles of ISO 9001:2008 Quality Management Systems — Requirements."

IC OAT's Test Site Registration Number: 2154C-1



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



APPENDIX B

MODIFICATIONS TO THE EUT



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400



MODIFICATIONS TO THE EUT

There were no modifications were made during testing.



APPENDIX C

***ADDITIONAL MODELS COVERED
UNDER THIS REPORT***



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

ADDITIONAL MODELS COVERED UNDER THIS REPORT


USED FOR THE PRIMARY TEST

ZWAVE PLUS SERIES SMARTCODE LOCKS
Model: Smartcode 910, 912, 914, & 916
S/N: NONE

No additional models were tested.



APPENDIX D



DIAGRAMS, CHARTS, AND PHOTOS



FIGURE 1: PLOT MAP AND LAYOUT OF TEST SITE BELOW 1GHZ





FIGURE 2: PLOT MAP AND LAYOUT OF TEST SITE ABOVE 1GHZ



COM-POWER AL-130**LOOP ANTENNA**

S/N: 121049

CALIBRATION DUE: DECEMBER 6, 2016

FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)	FREQUENCY (MHz)	MAGNETIC (dB/m)	ELECTRIC (dB/m)
0.009	-34.64	16.86	0.8	-36.32	15.18
0.01	-34.78	16.72	0.9	-36.22	15.28
0.02	-35.91	15.59	1.0	-36.22	15.28
0.03	-35.48	16.02	2.0	-35.91	15.59
0.04	-35.82	15.68	3.0	-35.91	15.59
0.05	-36.49	15.01	4.0	-36.01	15.49
0.06	-36.30	15.20	5.0	-35.80	15.70
0.07	-36.43	15.07	6.0	-36.00	15.50
0.08	-36.30	15.20	7.0	-35.90	15.60
0.09	-36.39	15.11	8.0	-35.70	15.80
0.1	-36.41	15.09	9.0	-35.70	15.80
0.2	-36.61	14.89	10.0	-35.60	15.90
0.3	-36.63	14.87	15.0	-36.52	14.98
0.4	-36.52	14.99	20.0	-35.75	15.75
0.5	-36.63	14.87	25.0	-37.78	13.72
0.6	-36.62	14.88	30.0	-38.62	12.88
0.7	-36.53	14.97			



COM-POWER AC-220**LAB R - COMBILOG ANTENNA**

S/N: 25857

CALIBRATION DUE: MAY 21, 2016

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
30	22.5	160	13.3
35	22.5	180	15.0
40	23.0	200	14.6
45	21.5	250	16.5
50	21.3	300	18.1
60	18.2	400	19.4
70	13.2	500	21.4
80	11.6	600	21.6
90	11.9	700	23.7
100	12.6	800	26.0
120	15.1	900	26.6
140	13.6	1000	28.5



COM-POWER AH-118**HORN ANTENNA**

S/N: 071250

CALIBRATION DUE: JULY 1, 2016

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
1000	30.1	9500	44.2
1500	29.2	10000	43.4
2000	31.6	10500	44.6
2500	35.5	11000	45.1
3000	33.7	11500	45.7
3500	36.0	12000	46.2
4000	35.4	12500	45.4
4500	35.5	13000	44.8
5000	40.1	13500	46.7
5500	37.8	14000	47.8
6000	39.0	14500	46.4
6500	39.9	15000	47.2
7000	40.4	15500	45.5
7500	44.4	16000	45.0
8000	44.1	16500	44.5
8500	43.1	17000	47.0
9000	43.0	17500	47.8
		18000	44.2



COM-POWER PAM-118A**1-18GHz - PREAMPLIFIER**

S/N: 551034

CALIBRATION DUE: AUGUST 25, 2016

FREQUENCY (MHz)	FACTOR (dB)	FREQUENCY (MHz)	FACTOR (dB)
500	36.77	5500	39.82
1000	38.63	6000	38.74
1100	38.72	6500	39.60
1200	38.97	7000	35.52
1300	38.59	7500	36.61
1400	39.18	8000	36.92
1500	38.71	8500	37.13
1600	39.28	9000	36.50
1700	39.25	9500	38.92
1800	39.06	10000	38.74
1900	40.34	11000	35.23
2000	40.07	12000	35.64
2500	39.69	13000	36.73
3000	40.94	14000	36.48
3500	40.41	15000	37.57
4000	40.44	16000	38.10
4500	41.20	17000	37.34
5000	39.35	18000	36.80






FRONT VIEW

**SPECTRUM BRANDS
ZWAVE PLUS SERIES SMARTCODE LOCKS
Model: Smartcode 910, 912, 914, & 916
FCC SUBPART B & C - RADIATED EMISSIONS < 1GHz**

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**






REAR VIEW

**SPECTRUM BRANDS
ZWAVE PLUS SERIES SMARTCODE LOCKS
Model: Smartcode 910, 912, 914, & 916
FCC SUBPART B & C - RADIATED EMISSIONS < 1GHz**

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**






FRONT VIEW

**SPECTRUM BRANDS
ZWAVE PLUS SERIES SMARTCODE LOCKS
Model: Smartcode 910, 912, 914, & 916
FCC SUBPART B & C - RADIATED EMISSIONS > 1GHz**

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**





REAR VIEW

**SPECTRUM BRANDS
ZWAVE PLUS SERIES SMARTCODE LOCKS
Model: Smartcode 910, 912, 914, & 916
FCC SUBPART B & C - RADIATED EMISSIONS > 1GHz**

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



APPENDIX E

RADIATED EMISSIONS DATA SHEETS



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600


Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

Title: FCC 15.209
 File: Radiated Pre-Scan 30-1000Mhz.set
 Operator: Torey Oliver
 EUT Type: Electronic Lock / 914ZW-C
 EUT Condition: The EUT is constantly transmitting 908.40 MHz.
 Comments: Temp: 71f
 Hum: 39%
 Battery Powered

1/13/2016 8:03:04 AM
 Sequence: Preliminary Scan

Compatible Electronics, Inc. FAC-3 (Lab R)



There were no radiated emissions other than harmonics found below 30 MHz or above 1GHz. This is the worst case spurious emissions from all locks, channels, and modes.



Brea Division
 114 Olinda Drive
 Brea, CA 92823
 (714) 579-0500

Agoura Division
 2337 Troutdale Drive
 Agoura, CA 91301
 (818) 597-0600

Silverado Division
 19121 El Toro Road
 Silverado, CA 92676
 (949) 589-0700

Lake Forest Division
 20621 Pascal Way
 Lake Forest, CA 92630
 (949) 587-0400

Title: FCC 15.209
File: Radiated Final 30-1000Mhz.set
Operator: Torey Oliver
EUT Type: Electronic Lock / 914ZW-C
EUT Condition: The EUT is constantly transmitting 908.40 MHz.
Comments: Temp: 71f
Hum: 39%
Battery Powered

1/13/2016 8:24:21 AM
Sequence: Final Measurements

Compatible Electronics, Inc. FAC-3 (Lab R)


Freq (MHz)	(QP) Margin (dB)	(QP) EMI (dB μ V/m)	(PEAK) EMI (dB μ V/m)	Limit (dB μ V/m)	Pol	Ttbl Agl (deg)	Twr Ht (cm)	Transducer (dB)	Cable (dB)
40.20	-18.94	21.06	26.43	40.00	H	74.75	400.29	22.94	1.27
45.80	-20.91	19.09	24.78	40.00	V	0.00	287.82	21.47	0.58
48.00	-9.64	30.36	32.67	40.00	H	16.00	316.05	21.38	0.32
48.00	-9.20	30.80	33.00	40.00	V	201.00	142.56	21.38	0.32
51.50	-21.71	18.29	23.27	40.00	H	349.75	185.85	20.81	0.24
57.10	-22.93	17.07	22.18	40.00	H	4.50	139.22	19.01	0.76

*There were no radiated emissions other than harmonics found below 30 MHz or above 1GHz.
This is the worst case spurious emissions from all locks, channels, and modes.*



FUNDAMENTAL & HARMONICS

DATA SHEETS



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

FUNDAMENTAL FIELD STRENGTH Smartcode 910

FCC 15.249 RSS210Company: Spectrum Brands
EUT: Zwave Plus Series Smartcode Locks
Model: Smartcode 910Date: 1/12/2016
Lab: R
Tested By: Torey Oliver**Compatible Electronics, Inc. FAC-3**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table	Tower	Comments
908.40	88.62	H	93.97	-5.35	Peak	70	1.50	
908.40	92.94	V	93.97	-1.03	Peak	360	1.12	
916.00	87.73	H	93.97	-6.24	Peak	237	1.47	
916.00	90.03	V	93.97	-3.94	Peak	160	1.00	

Test distance
3 meter

FUNDAMENTAL FIELD STRENGTH Smartcode 912

FCC 15.249 RSS210Company: Spectrum Brands
EUT: Zwave Plus Series Smartcode Locks
Model: Smartcode 912Date: 1/13/2016
Lab: R
Tested By: Torey Oliver**Compatible Electronics, Inc. FAC-3**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table	Tower	Comments
908.40	82.33	H	93.97	-11.64	Peak	360	1.42	908.40
908.40	82.78	V	93.97	-11.19	Peak	186	1.13	908.40
916.00	78.97	H	93.97	-15.00	Peak	360	1.46	916.00
916.00	78.78	V	93.97	-15.19	Peak	360	1.09	916.00

Test distance
3 meter

FUNDAMENTAL FIELD STRENGTH Smartcode 914

FCC 15.249 RSS210Company: Spectrum Brands
EUT: Zwave Plus Series Smartcode Locks
Model: Smartcode 914Date: 1/13/2016
Lab: R
Tested By: Torey Oliver**Compatible Electronics, Inc. FAC-3**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table	Tower	Comments
908.40	88.63	H	93.97	-5.34	Peak	150	1.50	
908.40	90.04	V	93.97	-3.93	Peak	0	1.07	
916.00	81.70	H	93.97	-12.27	Peak	129	1.39	
916.00	87.55	V	93.97	-6.42	Peak	360	1.09	

Test distance
3 meter

FUNDAMENTAL FIELD STRENGTH Smartcode 916

FCC 15.249 RSS210Company: Spectrum Brands
EUT: Zwave Plus Series Smartcode Locks
Model: Smartcode 916Date: 1/13/2016
Lab: R
Tested By: Torey Oliver**Compatible Electronics, Inc. FAC-3**

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table	Tower	Comments
908.40	82.80	H	93.97	-11.17	Peak	281	1.34	
908.40	86.7	V	93.97	-7.27	Peak	360	1.00	
916.00	79.74	H	93.97	-14.23	Peak	135	1.49	
916.00	86.58	V	93.97	-7.39	Peak	11	1.58	

Test distance
3 meter

HARMONICS LOW CHANNEL HORIZONTAL, SMARTCODE 910

FCC 15.249, RSS 210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 910

 Date: 1/12/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8	42.76	H	73.98	-31.22	Peak	2.47	160	
1816.8	35.78	H	53.98	-18.20	Avg	2.47	160	
2725.2		H	73.98		Peak			No Emissions Found
2725.2		H	53.98		Avg			No Emissions Found
3633.6		H	73.98		Peak			No Emissions Found
3633.6		H	53.98		Avg			No Emissions Found
4542.0	49.84	H	73.98	-24.14	Peak	1.44	355	
4542.0	45.50	H	53.98	-8.48	Avg	1.44	355	
5450.4		H	73.98		Peak			No Emissions Found
5450.4		H	53.98		Avg			No Emissions Found
6358.8	53.01	H	73.98	-20.97	Peak	1.83	346	
6358.8	44.63	H	53.98	-9.35	Avg	1.83	346	
7267.2		H	73.98		Peak			No Emissions Found
7267.2		H	53.98		Avg			No Emissions Found
8175.6	54.35	H	73.98	-19.63	Peak	1.05	360	
8175.6	41.93	H	53.98	-12.05	Avg	1.05	360	
9084.0	53.98	H	73.98	-20.00	Peak	1.76	326	
9084.0	41.05	H	53.98	-12.93	Avg	1.76	326	

 Test distance
 3 meter


HARMONICS LOW CHANNEL VERTICAL, SMARTCODE 910

FCC 15.249, RSS 210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 910

 Date: 1/12/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8	42.89	V	73.98	-31.09	Peak	1.05	319	
1816.8	37.03	V	53.98	-16.95	Avg	1.05	319	
2725.2		V	73.98		Peak			No Emissions Found
2725.2		V	53.98		Avg			No Emissions Found
3633.6		V	73.98		Peak			No Emissions Found
3633.6		V	53.98		Avg			No Emissions Found
4542.0	50.13	V	73.98	-23.85	Peak	1.76	22	
4542.0	46.18	V	53.98	-7.80	Avg	1.76	22	
5450.4		V	73.98		Peak			No Emissions Found
5450.4		V	53.98		Avg			No Emissions Found
6358.8	52.60	V	73.98	-21.38	Peak	2.77	334	
6358.8	43.81	V	53.98	-10.17	Avg	2.77	334	
7267.2		V	73.98		Peak			No Emissions Found
7267.2		V	53.98		Avg			No Emissions Found
8175.6	54.74	V	73.98	-19.24	Peak	1.55	0	
8175.6	41.85	V	53.98	-12.13	Avg	1.55	0	
9084.0	54.11	V	73.98	-19.87	Peak	1.59	29	
9084.0	41.02	V	53.98	-12.96	Avg	1.59	29	

 Test distance
 3 meter


HARMONICS HIGH CHANNEL HORIZONTAL, SMARTCODE 910

FCC 15.249, RSS 210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 910

Date: 1/12/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0	37.29	H	73.98	-36.69	Peak	3.38	155	
1832.0	24.57	H	53.98	-29.41	Avg	3.38	155	
2748.0		H	73.98		Peak			No emissions found
2748.0		H	53.98		Avg			No emissions found
3664.0		H	73.98		Peak			No emissions found
3664.0		H	53.98		Avg			No emissions found
4580.0	51.95	H	73.98	-22.03	Peak	1.76	175	
4580.0	47.54	H	53.98	-6.44	Avg	1.76	175	
5496.0		H	73.98		Peak			No Emissions Found
5496.0		H	53.98		Avg			No Emissions Found
6412.0		H	73.98		Peak			No Emissions Found
6412.0		H	53.98		Avg			No Emissions Found
7328.0		H	73.98		Peak			No Emissions Found
7328.0		H	53.98		Avg			No Emissions Found
8244.0	55.12	H	73.98	-18.86	Peak	1.20	192	
8244.0	42.26	H	53.98	-11.72	Avg	1.20	192	
9160.0	54.16	H	73.98	-19.82	Peak	1.70	141	
9160.0	41.23	H	53.98	-12.75	Avg	1.70	141	

Test distance
 3 meter



HARMONICS HIGH CHANNEL VERTICAL, SMARTCODE 910

FCC 15.249, RSS 210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 910

 Date: 1/12/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0	41.51	V	73.98	-32.47	Peak	2.20	155	
1832.0	32.02	V	53.98	-21.96	Avg	2.20	155	
2748.0		V	73.98		Peak			No Emissions Found
2748.0		V	53.98		Avg			No Emissions Found
3664.0		V	73.98		Peak			No Emissions Found
3664.0		V	53.98		Avg			No Emissions Found
4580.0	50.33	V	73.98	-23.65	Peak	3.00	219	
4580.0	45.28	V	53.98	-8.70	Avg	3.00	219	
5496.0		V	73.98		Peak			No Emissions Found
5496.0		V	53.98		Avg			No Emissions Found
6412.0		V	73.98		Peak			No Emissions Found
6412.0		V	53.98		Avg			No Emissions Found
7328.0		V	73.98		Peak			No Emissions Found
7328.0		V	53.98		Avg			No Emissions Found
8244.0	54.60	V	73.98	-19.38	Peak	1.45	188	
8244.0	42.19	V	53.98	-11.79	Avg	1.45	188	
9160.0	53.77	V	73.98	-20.21	Peak	2.64	360	
9160.0	41.13	V	53.98	-12.85	Avg	2.64	360	

 Test distance
 3 meter


HARMONICS LOW CHANNEL HORIZONTAL, SMARTCODE 912

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 912

Date: 1/14/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8		H	73.98		Peak			No Emissions Found
1816.8		H	53.98		Avg			No Emissions Found
2725.2		H	73.98		Peak			No Emissions Found
2725.2		H	53.98		Avg			No Emissions Found
3633.6		H	73.98		Peak			No Emissions Found
3633.6		H	53.98		Avg			No Emissions Found
4542.0	48.86	H	73.98	-25.12	Peak	1.13	354	
4542.0	43.79	H	53.98	-10.19	Avg	1.13	354	
5450.4		H	73.98		Peak			No Emissions Found
5450.4		H	53.98		Avg			No Emissions Found
6358.8	53.36	H	73.98	-20.62	Peak	1.94	60	
6358.8	45.72	H	53.98	-8.26	Avg	1.94	60	
7267.2		H	73.98		Peak			No Emissions Found
7267.2		H	53.98		Avg			No Emissions Found
8175.6	54.23	H	73.98	-19.75	Peak	1.08	319	
8175.6	41.77	H	53.98	-12.21	Avg	1.08	319	
9084.0		H	73.98		Peak			No Emissions Found
9084.0		H	53.98		Avg			No Emissions Found

Test distance
 3 meter



HARMONICS LOW CHANNEL VERTICAL, SMARTCODE 912

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 912

Date: 1/14/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8		V	73.98		Peak			No Emissions Found
1816.8		V	53.98		Avg			No Emissions Found
2725.2		V	73.98		Peak			No Emissions Found
2725.2		V	53.98		Avg			No Emissions Found
3633.6		V	73.98		Peak			No Emissions Found
3633.6		V	53.98		Avg			No Emissions Found
4542.0	46.00	V	73.98	-27.98	Peak	1.37	0	
4542.0	38.43	V	53.98	-15.55	Avg	1.37	0	
5450.4		V	73.98		Peak			No Emissions Found
5450.4		V	53.98		Avg			No Emissions Found
6358.8	49.04	V	73.98	-24.94	Peak	1.94	1	
6358.8	36.26	V	53.98	-17.72	Avg	1.94	1	
7267.2		V	73.98		Peak			No Emissions Found
7267.2		V	53.98		Avg			No Emissions Found
8175.6	54.87	V	73.98	-19.11	Peak	1.62	0	
8175.6	41.78	V	53.98	-12.20	Avg	1.62	0	
9084.0		V	73.98		Peak			No Emissions Found
9084.0		V	53.98		Avg			No Emissions Found

Test distance
3 meter



HARMONICS HIGH CHANNEL HORIZONTAL, SMARTCODE 912

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 912

Date: 1/15/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0		H	73.98		Peak			No emissions found
1832.0		H	53.98		Avg			No emissions found
2748.0	42.70	H	73.98	-31.28	Peak	1.05	115	
2748.0	32.82	H	53.98	-21.16	Avg	1.05	115	
3664.0	45.57	H	73.98	-28.41	Peak	1.80	195	
3664.0	35.38	H	53.98	-18.60	Avg	1.80	195	
4580.0	48.22	H	73.98	-25.76	Peak	1.50	183	
4580.0	30.79	H	53.98	-23.19	Avg	1.50	183	
5496.0		H	73.98		Peak			No Emissions Found
5496.0		H	53.98		Avg			No Emissions Found
6412.0	49.69	H	73.98	-24.29	Peak	2.03	232	
6412.0	35.78	H	53.98	-18.20	Avg	2.03	232	
7328.0	53.79	H	73.98	-20.19	Peak	3.99	189	
7328.0	41.39	H	53.98	-12.59	Avg	3.99	189	
8244.0	54.73	H	73.98	-19.25	Peak	2.52	126	
8244.0	42.11	H	53.98	-11.87	Avg	2.52	126	
9160.0		H	73.98		Peak			No Emissions Found
9160.0		H	53.98		Avg			No Emissions Found

Test distance
 3 meter



HARMONICS HIGH CHANNEL VERTICAL, SMARTCODE 912

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 912

Date: 1/15/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0		V	73.98		Peak			No Emissions Found
1832.0		V	53.98		Avg			No Emissions Found
2748.0	43.97	V	73.98	-30.01	Peak	2.02	175	
2748.0	35.55	V	53.98	-18.43	Avg	2.02	175	
3664.0	45.34	V	73.98	-28.64	Peak	1.82	167	
3664.0	34.47	V	53.98	-19.51	Avg	1.82	167	
4580.0	45.39	V	73.98	-28.59	Peak	1.84	360	
4580.0	30.93	V	53.98	-23.05	Avg	1.84	360	
5496.0		V	73.98		Peak			No Emissions Found
5496.0		V	53.98		Avg			No Emissions Found
6412.0	48.17	V	73.98	-25.81	Peak	2.76	74	
6412.0	35.44	V	53.98	-18.54	Avg	2.76	74	
7328.0	53.92	V	73.98	-20.06	Peak	1.61	205	
7328.0	41.32	V	53.98	-12.66	Avg	1.61	205	
8244.0	54.48	V	73.98	-19.50	Peak	4.00	247	
8244.0	42.04	V	53.98	-11.94	Avg	4.00	247	
9160.0	53.38	V	73.98	-20.60	Peak	3.50	146	
9160.0	41.07	V	53.98	-12.91	Avg	3.50	146	

Test distance
 3 meter



HARMONICS LOW CHANNEL HORIZONTAL, SMARTCODE 914

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 914

Date: 1/14/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8	51.23	H	73.98	-22.75	Peak	2.01	177	
1816.8	49.32	H	53.98	-4.66	Avg	2.01	177	
2725.2	41.08	H	73.98	-32.90	Peak	2.20	160	
2725.2	28.34	H	53.98	-25.64	Avg	2.20	160	
3633.6		H	73.98		Peak			No Emissions Found
3633.6		H	53.98		Avg			No Emissions Found
4542.0	49.64	H	73.98	-24.34	Peak	1.32	138	
4542.0	45.19	H	53.98	-8.79	Avg	1.32	138	
5450.4		H	73.98		Peak			No Emissions Found
5450.4		H	53.98		Avg			No Emissions Found
6358.8	55.31	H	73.98	-18.67	Peak	1.92	182	
6358.8	49.46	H	53.98	-4.52	Avg	1.92	182	
7267.2		H	73.98		Peak			No Emissions Found
7267.2		H	53.98		Avg			No Emissions Found
8175.6	55.00	H	73.98	-18.98	Peak	1.18	137	
8175.6	41.80	H	53.98	-12.18	Avg	1.18	137	
9084.0	54.37	H	73.98	-19.61	Peak	2.15	141	
9084.0	40.96	H	53.98	-13.02	Avg	2.15	141	

Test distance
3 meter



HARMONICS LOW CHANNEL VERTICAL, SMARTCODE 914

FCC 15.249, RSS210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 914

 Date: 1/14/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8	43.62	V	73.98	-30.36	Peak	2.48	33	
1816.8	38.41	V	53.98	-15.57	Avg	2.48	33	
2725.2	46.25	V	73.98	-27.73	Peak	2.29	198	
2725.2	39.88	V	53.98	-14.10	Avg	2.29	198	
3633.6		V	73.98		Peak			No Emissions Found
3633.6		V	53.98		Avg			No Emissions Found
4542.0	51.60	V	73.98	-22.38	Peak	1.78	163	
4542.0	47.80	V	53.98	-6.18	Avg	1.78	163	
5450.4		V	73.98		Peak			No Emissions Found
5450.4		V	53.98		Avg			No Emissions Found
6358.8	50.65	V	73.98	-23.33	Peak	2.38	360	
6358.8	39.36	V	53.98	-14.62	Avg	2.38	360	
7267.2		V	73.98		Peak			No Emissions Found
7267.2		V	53.98		Avg			No Emissions Found
8175.6	54.35	V	73.98	-19.63	Peak	1.25	214	
8175.6	41.80	V	53.98	-12.18	Avg	1.25	214	
9084.0	53.34	V	73.98	-20.64	Peak	1.18	195	
9084.0	40.93	V	53.98	-13.05	Avg	1.18	195	

 Test distance
 3 meter


HARMONICS HIGH CHANNEL HORIZONTAL, SMARTCODE 914

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 914

Date: 1/15/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0	48.91	H	73.98	-25.07	Peak	1.93	164	
1832.0	46.29	H	53.98	-7.69	Avg	1.93	164	
2748.0	45.63	H	73.98	-28.35	Peak	2.34	181	
2748.0	39.91	H	53.98	-14.07	Avg	2.34	181	
3664.0		H	73.98		Peak			No emissions found
3664.0		H	53.98		Avg			No emissions found
4580.0	52.75	H	73.98	-21.23	Peak	1.41	165	
4580.0	48.74	H	53.98	-5.24	Avg	1.41	165	
5496.0		H	73.98		Peak			No Emissions Found
5496.0		H	53.98		Avg			No Emissions Found
6412.0	53.99	H	73.98	-19.99	Peak	1.82	178	
6412.0	46.87	H	53.98	-7.11	Avg	1.82	178	
7328.0	54.05	H	73.98	-19.93	Peak	2.15	159	
7328.0	41.37	H	53.98	-12.61	Avg	2.15	159	
8244.0	55.12	H	73.98	-18.86	Peak	2.72	0	
8244.0	42.11	H	53.98	-11.87	Avg	2.72	0	
9160.0	54.41	H	73.98	-19.57	Peak	2.16	145	
9160.0	41.13	H	53.98	-12.85	Avg	2.16	145	

Test distance
 3 meter



HARMONICS HIGH CHANNEL VERTICAL, SMARTCODE 914

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 914

Date: 1/15/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0	42.45	V	73.98	-31.53	Peak	2.41	186	
1832.0	36.78	V	53.98	-17.20	Avg	2.41	186	
2748.0	44.66	V	73.98	-29.32	Peak	1.94	193	
2748.0	37.51	V	53.98	-16.47	Avg	1.94	193	
3664.0		V	73.98		Peak			No Emissions Found
3664.0		V	53.98		Avg			No Emissions Found
4580.0	53.43	V	73.98	-20.55	Peak	1.80	165	
4580.0	49.57	V	53.98	-4.41	Avg	1.80	165	
5496.0		V	73.98		Peak			No Emissions Found
5496.0		V	53.98		Avg			No Emissions Found
6412.0	53.04	V	73.98	-20.94	Peak	1.97	207	
6412.0	52.94	V	53.98	-1.04	Avg	1.97	207	
7328.0	54.30	V	73.98	-19.68	Peak	1.48	0	
7328.0	41.32	V	53.98	-12.66	Avg	1.48	0	
8244.0	54.73	V	73.98	-19.25	Peak	1.25	140	
8244.0	42.02	V	53.98	-11.96	Avg	1.25	140	
9160.0	54.55	V	73.98	-19.43	Peak	1.36	209	
9160.0	41.06	V	53.98	-12.92	Avg	1.36	209	

Test distance
3 meter



HARMONICS LOW CHANNEL HORIZONTAL, SMARTCODE 916

FCC 15.249, RSS210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 916

 Date: 1/14/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8	44.39	H	73.98	-29.59	Peak	1.48	119	
1816.8	27.04	H	53.98	-26.94	Avg	1.49	119	
2725.2	46.61	H	73.98	-27.37	Peak	1.75	171	
2725.2	29.75	H	53.98	-24.23	Avg	1.75	171	
3633.6		H	73.98		Peak			No Emissions Found
3633.6		H	53.98		Avg			No Emissions Found
4542.0	50.05	H	73.98	-23.93	Peak	1.40	155	
4542.0	30.86	H	53.98	-23.12	Avg	1.40	155	
5450.4		H	73.98		Peak			No Emissions Found
5450.4		H	53.98		Avg			No Emissions Found
6358.8	49.16	H	73.98	-24.82	Peak	3.68	0	
6358.8	36.36	H	53.98	-17.62	Avg	3.68	0	
7267.2	54.01	H	73.98	-19.97	Peak	2.87	285	
7267.2	40.99	H	53.98	-12.99	Avg	2.87	285	
8175.6	54.87	H	73.98	-19.11	Peak	3.56	87	
8175.6	41.92	H	53.98	-12.06	Avg	3.56	87	
9084.0	53.34	H	73.98	-20.64	Peak	2.77	342	
9084.0	41.04	H	53.98	-12.94	Avg	2.77	342	

 Test distance
 3 meter


HARMONICS LOW CHANNEL VERTICAL, SMARTCODE 916

FCC 15.249, RSS210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 916

 Date: 1/14/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1816.8	37.72	V	73.98	-36.26	Peak	2.63	212	
1816.8	24.56	V	53.98	-29.42	Avg	2.63	212	
2725.2	40.79	V	73.98	-33.19	Peak	1.46	189	
2725.2	28.32	V	53.98	-25.66	Avg	1.46	189	
3633.6		V	73.98		Peak			No Emissions Found
3633.6		V	53.98		Avg			No Emissions Found
4542.0	50.05	V	73.98	-23.93	Peak	1.83	163	
4542.0	31.12	V	53.98	-22.86	Avg	1.83	163	
5450.4		V	73.98		Peak			No Emissions Found
5450.4		V	53.98		Avg			No Emissions Found
6358.8	48.78	V	73.98	-25.20	Peak	2.78	180	
6358.8	36.45	V	53.98	-17.53	Avg	2.78	180	
7267.2	53.48	V	73.98	-20.50	Peak	1.51	42	
7267.2	40.97	V	53.98	-13.01	Avg	1.51	42	
8175.6	54.23	V	73.98	-19.75	Peak	2.66	98	
8175.6	41.89	V	53.98	-12.09	Avg	2.66	98	
9084.0	53.72	V	73.98	-20.26	Peak	3.87	83	
9084.0	41.04	V	53.98	-12.94	Avg	3.87	83	

 Test distance
 3 meter


HARMONICS HIGH CHANNEL HORIZONTAL, SMARTCODE 916

FCC 15.249, RSS210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 916

 Date: 1/15/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0	45.60	H	73.98	-28.38	Peak	2.25	232	
1832.0	41.41	H	53.98	-12.57	Avg	2.25	232	
2748.0	40.92	H	73.98	-33.06	Peak	1.90	172	
2748.0	27.88	H	53.98	-26.10	Avg	1.90	172	
3664.0		H	73.98		Peak			No emissions found
3664.0		H	53.98		Avg			No emissions found
4580.0	50.20	H	73.98	-23.78	Peak	1.59	160	
4580.0	31.15	H	53.98	-22.83	Avg	1.59	160	
5496.0		H	73.98		Peak			No Emissions Found
5496.0		H	53.98		Avg			No Emissions Found
6412.0	53.64	H	73.98	-20.34	Peak	1.83	191	
6412.0	36.13	H	53.98	-17.85	Avg	1.83	191	
7328.0	54.16	H	73.98	-19.82	Peak	2.51	188	
7328.0	41.31	H	53.98	-12.67	Avg	2.51	188	
8244.0	54.61	H	73.98	-19.37	Peak	2.16	235	
8244.0	42.06	H	53.98	-11.92	Avg	2.16	235	
9160.0	53.90	H	73.98	-20.08	Peak	2.92	228	
9160.0	41.09	H	53.98	-12.89	Avg	2.92	228	

 Test distance
 3 meter


HARMONICS HIGH CHANNEL VERTICAL, SMARTCODE 916

FCC 15.249, RSS210

Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 916

Date: 1/15/2016
 Lab: R
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
1832.0	42.45	V	73.98	-31.53	Peak	2.46	35	
1832.0	36.01	V	53.98	-17.97	Avg	2.46	35	
2748.0	41.78	V	73.98	-32.20	Peak	1.67	172	
2748.0	28.07	V	53.98	-25.91	Avg	1.67	172	
3664.0		V	73.98		Peak			No Emissions Found
3664.0		V	53.98		Avg			No Emissions Found
4580.0	51.31	V	73.98	-22.67	Peak	1.70	177	
4580.0	31.92	V	53.98	-22.06	Avg	1.70	177	
5496.0		V	73.98		Peak			No Emissions Found
5496.0		V	53.98		Avg			No Emissions Found
6412.0	47.92	V	73.98	-26.06	Peak	2.48	182	
6412.0	35.43	V	53.98	-18.55	Avg	2.48	182	
7328.0	53.41	V	73.98	-20.57	Peak	1.98	360	
7328.0	41.28	V	53.98	-12.70	Avg	1.98	360	
8244.0	54.73	V	73.98	-19.25	Peak	2.08	257	
8244.0	42.00	V	53.98	-11.98	Avg	2.08	257	
9160.0	53.64	V	73.98	-20.34	Peak	1.18	11	
9160.0	41.05	V	53.98	-12.93	Avg	1.18	11	

Test distance
 3 meter





***EMISSIONS RADIATED OUTSIDE OF THE FUNDAMENTAL
FREQUENCY BAND***

DATA SHEETS



Brea Division
114 Olinda Drive
Brea, CA 92823
(714) 579-0500

Agoura Division
2337 Troutdale Drive
Agoura, CA 91301
(818) 597-0600

Silverado Division
19121 El Toro Road
Silverado, CA 92676
(949) 589-0700

Lake Forest Division
20621 Pascal Way
Lake Forest, CA 92630
(949) 587-0400

BAND EDGES, LOW CHANNEL, SMARTCODE 910

FCC 15.249, RSS210


Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 910

Date: 1/12/2016
 Lab: R
 Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	Pol	Limit (dBµV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
900.49	33.86	H	46.00	-12.14	Peak	1.50	70	No Marker Delta
900.49	--	H	--	--	QP	--	--	Method Used
933.19	35.28	H	46.00	-10.72	Peak	1.50	70	No Marker Delta
933.19	--	H	--	--	QP	--	--	Method Used
901.29	35.48	V	46.00	-10.52	Peak	1.12	360	No Marker Delta
901.29	--	V	--	--	QP	--	--	Method Used
929.83	35.64	V	46.00	-10.36	Peak	1.12	360	No Marker Delta
929.83	--	V	--	--	QP	--	--	Method Used

Test distance
3 meter



Comment A: Band Edge 908.40 Horizontal
 Date: 12.JAN.2016 16:05:19

Comment A: Band Edge 908.40 MHz Vertical
 Date: 12.JAN.2016 14:11:31



BAND EDGES, HIGH CHANNEL, SMARTCODE 910

FCC 15.249, RSS210


Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 910

Date: 1/12/2016
 Lab: R
 Test ENG: Torey Oliver


Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	Pol	Limit (dBµV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
897.68	33.74	H	46.00	-12.26	Peak	1.47	237	No Marker Delta
897.68	--	H	--	--	QP	--	--	Method Used
934.72	35.06	H	46.00	-10.94	Peak	1.47	237	No Marker Delta
934.72	--	H	--	--	QP	--	--	Method Used
896.00	41.87	V	46.00	-4.13	Peak	1	160	No Marker Delta
896.00	--	V	--	--	QP	--	--	Method Used
928.06	42.79	V	46.00	-3.21	Peak	1	160	No Marker Delta
928.06	--	V	--	--	QP	--	--	Method Used

Test distance
 3 meter



Comment A: Band Edge Horizontal
 Date: 12.JAN.2016 08:14:38



Comment A: Band Edge Vertical
 Date: 12.JAN.2016 08:11:29



BAND EDGES, LOW CHANNEL, SMARTCODE 912

FCC 15.249, RSS210


Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 912

Date: 1/13/2016
 Lab: R
 Test ENG: Torey Oliver


Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	Pol	Limit (dBµV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
898.97	34.36	H	46.00	-11.64	Peak	1.42	360	No Marker Delta
898.97	--	H	--	--	QP	--	--	Method Used
932.15	35.18	H	46.00	-10.82	Peak	1.42	360	No Marker Delta
932.15	--	H	--	--	QP	--	--	Method Used
901.29	34.80	V	46.00	-11.20	Peak	1.13	186	No Marker Delta
901.29	--	V	--	--	QP	--	--	Method Used
929.59	35.43	V	46.00	-10.57	Peak	1.13	186	No Marker Delta
929.59	--	V	--	--	QP	--	--	Method Used

Test distance
3 meter



Comment A: Band Edge 908 MHz Horizontal
 Date: 13.JAN.2016 10:14:30



Comment A: Band Edge 908 MHz Vertical
 Date: 13.JAN.2016 10:11:33



BAND EDGES, HIGH CHANNEL, SMARTCODE 912



FCC 15.249, RSS210

 Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 912

 Date: 1/13/2016
 Lab: R
 Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dB μ V/m)	Pol	Limit (dB μ V)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
899.51	34.02	H	46.00	-11.98	Peak	1.46	360	No Marker Delta
899.51	--	H	--	--	QP	--	--	Method Used
930.07	35.54	H	46.00	-10.46	Peak	1.46	360	No Marker Delta
930.07	--	H	--	--	QP	--	--	Method Used
900.17	33.97	V	46.00	-12.03	Peak	1.08	360	No Marker Delta
900.17	--	V	--	--	QP	--	--	Method Used
931.83	34.99	V	46.00	-11.01	Peak	1.08	360	No Marker Delta
931.83	--	V	--	--	QP	--	--	Method Used

 Test distance
 3 meter

 Comment A: Band Edge 916 MHz Horizontal
 Date: 13.JAN.2016 16:19:35

 Comment A: Band Edge 916 MHz Vertical
 Date: 13.JAN.2016 16:14:48


BAND EDGES, LOW CHANNEL, SMARTCODE 914

FCC 15.249, RSS210


Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 914

Date: 1/13/2016
 Lab: R
 Test ENG: Torey Oliver


Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	PoI	Limit (dBµV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
901.13	34.64	H	46.00	-11.36	Peak	1.50	150	No Marker Delta
901.13	--	H	--	--	QP	--	--	Method Used
934.16	35.58	H	46.00	-10.42	Peak	1.50	150	No Marker Delta
934.16	--	H	--	--	QP	--	--	Method Used
900.09	34.37	V	46.00	-11.63	Peak	1.07	0	No Marker Delta
900.09	--	V	--	--	QP	--	--	Method Used
933.76	34.76	V	46.00	-11.24	Peak	1.07	0	No Marker Delta
933.76	--	V	--	--	QP	--	--	Method Used

Test distance
 3 meter



Comment A: Band Edge 908 MHz Horizontal
 Date: 13.JAN.2016 08:09:58



Comment A: Band Edge 908 MHz Vertical
 Date: 13.JAN.2016 08:08:38



BAND EDGES, HIGH CHANNEL, SMARTCODE 914

FCC 15.249, RSS210



Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 914

Date: 1/13/2016
 Lab: R
 Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	Pol	Limit (dBµV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
901.13	34.64	H	46.00	-11.36	Peak	1.50	150	No Marker Delta
901.13	--	H	--	--	QP	--	--	Method Used
934.16	35.58	H	46.00	-10.42	Peak	1.50	150	No Marker Delta
934.16	--	H	--	--	QP	--	--	Method Used
900.09	34.37	V	46.00	-11.63	Peak	1.07	0	No Marker Delta
900.09	--	V	--	--	QP	--	--	Method Used
933.76	34.76	V	46.00	-11.24	Peak	1.07	0	No Marker Delta
933.76	--	V	--	--	QP	--	--	Method Used

Test distance
3 meter



BAND EDGES, LOW CHANNEL, SMARTCODE 916

FCC 15.249, RSS210


Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 916

Date: 1/13/2016
 Lab: R
 Test ENG: Torey Oliver


Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	Pol	Limit (dBµV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
898.81	35.08	H	46.00	-10.92	Peak	1.34	281	No Marker Delta
898.81	--	H	--	--	QP	--	--	Method Used
930.39	35.68	H	46.00	-10.32	Peak	1.34	281	No Marker Delta
930.39	--	H	--	--	QP	--	--	Method Used
901.29	36.45	V	46.00	-9.55	Peak	1.00	360	No Marker Delta
901.29	--	V	--	--	QP	--	--	Method Used
931.43	34.85	V	46.00	-11.15	Peak	1.00	360	No Marker Delta
931.43	--	V	--	--	QP	--	--	Method Used

Test distance
 3 meter



Comment A: Band Edge 908 MHz Horizontal
 Date: 13.JAN.2016 10:42:18



Comment A: Band Edge 908 MHz Vertical
 Date: 13.JAN.2016 10:48:35



BAND EDGES, HIGH CHANNEL, SMARTCODE 916

FCC 15.249, RSS210


Company: Kwikset
 EUT: Zwave Plus Series Smartcode Lock
 Model: Smartcode 916

Date: 1/13/2016
 Lab: R
 Test ENG: Torey Oliver


Compatible Electronics, Inc. FAC-3 (Lab R)

Freq. (MHz)	Level (dBµV/m)	Pol	Limit (dBµV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
896.88	33.89	H	46.00	-12.11	Peak	1.46	135	No Marker Delta
896.88	--	H	--	--	QP	--	--	Method Used
930.47	35.22	H	46.00	-10.78	Peak	1.46	135	No Marker Delta
930.47	--	H	--	--	QP	--	--	Method Used
896.88	34.66	V	46.00	-11.34	Peak	1.58	11	No Marker Delta
896.88	--	V	--	--	QP	--	--	Method Used
935.04	35.09	V	46.00	-10.91	Peak	1.58	11	No Marker Delta
935.04	--	V	--	--	QP	--	--	Method Used

Test distance
3 meter




Comment A: Band Edge 916MHz Horizontal
 Date: 13.JAN.2016 14:08:29



Comment A: Band Edge 916MHz Vertical
 Date: 13.JAN.2016 14:05:34



99% OCCUPIED BANDWIDTH



DATA SHEETS







RSS GEN

Company: Spectrum Brands Date: 1/12/2016
 EUT: Zwave Plus Series Smartcode Locks Lab: R
 Model: Smartcode 910 Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)

99% Occupied Bandwidth

Freq. (MHz)	Measured BW (kHz)	Peak / QP / Avg	Comments
908.40	97.70	Peak	
916.00	132.77	Peak	







RSS GEN

Company: Spectrum Brands Date: 1/12/2016
 EUT: Zwave Plus Series Smartcode Locks Lab: R
 Model: Smartcode 912 Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)
99% Occupied Bandwidth

Freq. (MHz)	Measured BW (kHz)	Peak / QP / Avg	Comments
908.40	102.71	Peak	
916.00	117.74	Peak	




RSS GEN

Company: Spectrum Brands Date: 1/12/2016
 EUT: Zwave Plus Series Smartcode Locks Lab: R
 Model: Smartcode 914 Test ENG: Torey Oliver


Compatible Electronics, Inc. FAC-3 (Lab R)

99% Occupied Bandwidth


Freq. (MHz)	Measured BW (kHz)	Peak / QP / Avg	Comments
908.40	107.72	Peak	
916.00	122.75	Peak	




Comment A: IC Bandwidth
 Date: 13.JAN.2016 08:30:42



Comment A: IC Bandwidth
 Date: 13.JAN.2016 08:31:46



Comment A: IC Bandwidth 916 MHz
 Date: 13.JAN.2016 16:21:57



Comment A: IC Bandwidth 916 MHz
 Date: 13.JAN.2016 16:26:23

RSS GEN

Company: Spectrum Brands Date: 1/12/2016
 EUT: Zwave Plus Series Smartcode Locks Lab: R
 Model: Smartcode 916 Test ENG: Torey Oliver

Compatible Electronics, Inc. FAC-3 (Lab R)

99% Occupied Bandwidth

Freq. (MHz)	Measured BW (kHz)	Peak / QP / Avg	Comments
908.40	107.71	Peak	
916.00	132.77	Peak	

