

**FCC PART 15 SUBPART B & SUBPART C SECTION 15.249,  
RSS 210, & RSS GEN  
TEST REPORT**

*for*

**HOMEKIT ENABLED RESIDENTIAL DOOR LOCK  
Model: SmartCode 919**

Prepared for

SPECTRUM BRANDS  
19701 DaVinci  
LAKE FOREST, CA 92610



Prepared by: \_\_\_\_\_

MATT HARRISON



Reviewed by: \_\_\_\_\_

TOREY OLIVER

COMPATIBLE ELECTRONICS INC.  
20621 PASCAL WAY  
LAKE FOREST, CALIFORNIA 92630  
(949) 587-0400

DATE: MARCH 28<sup>th</sup>, 2016

	REPORT BODY	APPENDICES					TOTAL
		A	B	C	D	E	
PAGES	18	2	2	2	11	20	55

This report shall not be reproduced except in full, without the written approval of Compatible Electronics.



**TABLE OF CONTENTS**

<b>Section / Title</b>	<b>PAGE</b>
<b>GENERAL REPORT SUMMARY</b>	<b>4</b>
<b>SUMMARY OF TEST RESULTS</b>	<b>5</b>
<b>1. PURPOSE</b>	<b>6</b>
<b>2. ADMINISTRATIVE DATA</b>	<b>7</b>
2.1 Location of Testing	7
2.2 Traceability Statement	7
2.3 Cognizant Personnel	7
2.4 Date Test Sample was Received	7
2.5 Disposition of the Test Sample	7
2.6 Abbreviations and Acronyms	7
<b>3. APPLICABLE DOCUMENTS</b>	<b>8</b>
<b>4. DESCRIPTION OF TEST CONFIGURATION</b>	<b>9</b>
4.1 Description of Test Configuration	9
4.1.1 Photograph Test Configuration (X-Axis)	9
4.1.2 Cable Construction and Termination	10
<b>5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT</b>	<b>11</b>
5.1 EUT and Accessory List	11
5.2 EMI Test Equipment	12
<b>6. TEST SITE DESCRIPTION</b>	<b>13</b>
6.1 Test Facility Description	13
6.2 EUT Mounting, Bonding and Grounding	13
6.3 Facility Environmental Characteristics	13
<b>7. CHARACTERISTICS OF THE TRANSMITTER</b>	<b>14</b>
7.1 Channel Number and Frequencies	14
7.2 Antenna	14
<b>8. TEST PROCEDURES</b>	<b>15</b>
8.1 RF Emissions	15
8.1.1 Conducted Emissions Test	15
8.1.2 Radiated Emissions (Spurious and Harmonics) Test	16
8.1.3 Fundamental Field Strength	17
8.1.4 Emissions Radiated Outside of the Fundamental Frequency Band	17
<b>9. TEST PROCEDURE DEVIATIONS</b>	<b>18</b>
<b>10. CONCLUSIONS</b>	<b>18</b>



**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>
A	Laboratory Accreditations and Recognitions
B	Modifications to the EUT
C	Additional Models Covered Under This Report
D	Diagrams, Charts, and Photos <ul style="list-style-type: none"><li>• Test Setup Diagrams</li><li>• Antenna and Amplifier Factors</li><li>• Radiated Emissions Photos</li></ul>
E	Radiated Emissions Data Sheets

**LIST OF FIGURES**

<b>FIGURE</b>	<b>TITLE</b>
1	Plot Map And Layout of Test Site Below 1GHz
2	Plot Map And Layout of Test Site Above 1GHz



## GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Compatible Electronics Inc., which is an independent testing and consulting firm. The test report is based on testing performed by Compatible Electronics personnel according to the measurement procedures described in the test specifications given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full with the written permission of Compatible Electronics.

This report must not be used to claim product certification, approval or endorsement by NVLAP, NIST, or any agency of the federal government.

Device Tested: HomeKit Enabled Residential Door Lock  
Model: SmartCode 919  
S/N: None

Product Description: The EUT is a HomeKit Enabled Residential Door Lock operating via Bluetooth 4.0 Low Energy technology.

Modifications: The EUT was not modified in order to comply with specifications.

Manufacturer: Spectrum Brands  
19701 DaVinci  
Lake Forest, CA 92610

Test Date: April 8 and 11, 2016

Test Specifications: EMI requirements  
CFR Title 47, Part 15 Subpart B Sections 15.107, 15.109, Subpart C Sections 15.205, 15.207, 15.209, and 15.249

RSS 210 & RSS GEN

Test Procedure: ANSI C63.4 & C63.10



## SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	RESULTS
1	Conducted RF Emissions, 150 kHz - 30 MHz.	The EUT is battery powered; therefore this test was not performed.
2	Radiated RF Emissions & Harmonics, 9 kHz – 25,000 MHz.	Complies with the limits of CFR Title 47 Part 15 Subpart B Section 15.109 & Subpart C Sections 15.205, 15.209, & 15.249, RSS 210 & RSS GEN
3	Fundamental Field Strength	Complies with the limits of CFR Title 47 Part 15 Subpart C Section 15.249 & RSS 210
4	Emissions Radiated Outside of the Fundamental Frequency Band	Complies with the limits of CFR Title 47 Part 15 Subpart B Section 15.109 & Subpart C Sections 15.205, 15.209, & 15.249, RSS 210 & RSS GEN
5	Occupied Bandwidth	Complies with the limits of RSS 210 & RSS GEN

**TABLE 1:  
SIX HIGHEST RADIATED EMISSIONS READINGS**

	Reading Type (PK / QP / AV)	Polarization (Vert / Horz)	Frequency (MHz)	Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Delta (dB)	Test Distance
1	AV	H	7440	48.37	53.98	-5.61	3-Meter
2	AV	V	7440	45.72	53.98	-8.26	3-Meter
3	AV	H	7278	45.56	53.98	-8.42	3-Meter
4	AV	H	7206	43.10	53.98	-10.88	3-Meter
5	AV	V	7278	42.08	53.98	-11.90	3-Meter
6	AV	V	7206	38.67	53.98	-15.31	3-Meter



**1. PURPOSE**

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the HomeKit Enabled Residential Door Lock Model: SmartCode 919. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4 & C63.10. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT (equipment under test) hereafter, are within the specification limits defined by the Code of Federal Regulations Title 47, Part 15 Subpart B sections 15.109, & Part 15 Subpart C sections 15.205, 15.209, 15.249, RSS GEN, & RSS 210.



## 2. ADMINISTRATIVE DATA

### 2.1 Location of Testing

The tests described herein were performed at the test facility of Compatible Electronics, 20621 Pascal Way Lake Forest, California 92630.

### 2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The calibration is traceable to the National Institute of Standards and Technology (NIST).

### 2.3 Cognizant Personnel

Spectrum Brands

Thuan Nguyen Senior Electronics Engineer

Compatible Electronics, Inc.

Torey Oliver Test Technician

Matt Harrison Lab Manager

### 2.4 Date Test Sample was Received

The test sample was received on April 8<sup>th</sup>, 2016.

### 2.5 Disposition of the Test Sample

The test sample remains at Compatible Electronics, Inc. as of the date of this test report.

### 2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
NVLAP	National Voluntary Laboratory Accreditation Program
CFR	Code of Federal Regulations
PCB	Printed Circuit Board
TX	Transmit
RX	Receive



### 3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this Test Report.

SPEC	TITLE
CFR Title 47, Part 15	FCC Rules – Radio frequency devices (including digital devices)
ANSI C63.4 2014	Methods of measurement of radio-noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10: 2013	American National Standard for Testing Unlicensed Wireless Devices
RSS GEN	General Requirements for Compliance of Radio Apparatus
RSS 210	Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment





#### 4. DESCRIPTION OF TEST CONFIGURATION

##### 4.1 Description of Test Configuration

The HomeKit Enabled Residential Door Lock Model: SmartCode 919 (EUT) was setup in a tabletop configuration. The EUT was checked all 3 axis. The worst case was found to be the X-Axis. The EUT was continuously transmitting a data stream during testing.

The tests were performed using new batteries.

It was determined that the emissions were at their highest level when the EUT was transmitting in the configuration described above for Radiated Emissions. The final radiated data was taken in the above configuration. Please see Appendix E for the test data.

##### 4.1.1 Photograph Test Configuration (X-Axis)



#### 4.1.2 Cable Construction and Termination

There were no interconnecting cables.



**5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT****5.1 EUT and Accessory List**

#	EQUIPMENT TYPE	MANU-FACTURER	MODEL	SERIAL NUMBER
1	HOMEKIT ENABLED RESIDENTIAL DOOR LOCK (EUT)	SPECTRUM BRANDS	SMARTCODE 919	NONE
2	BATTERIES (4)	RAYOVAC	AA	NONE



## 5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. DUE DATE
Computer	Compatible Electronics	NONE	NONE	N/A	N/A
EMI Receiver	Rohde & Schwarz	ESIB40	100219	09/03/2015	09/03/2016
EMI Receiver	Agilent	N9038A	MY51100115	12/29/2015	12/29/2016
Antenna, Loop	Com Power	AL-130	121049	12/06/2013	12/06/2016
Antenna, CombiLog	Com Power	AC-220	25857	05/21/2014	05/21/2016
Antenna, Horn 1-18GHz	Com Power	AH-118	071250	07/01/2014	07/01/2016
Antenna, Horn 18-26GHz	Com-Power	AH-826	081033	07/06/2014	07/06/2016
Pre-Amp, 1-18GHz	Com Power	PAM-118A	551034	8/25/2015	8/25/2016
Pre-Amp, 18-40GHz	Com-Power	PA-840	181289	6/16/2015	6/16/2016
High Pass Filter	AMTI Microwave Circuits	H3G020G4	481230	8/26/2015	8/26/2016
Mast, Antenna Positioner	Sunol Science Corporation	TWR 95-4	020808-3	N/A	N/A
Antenna Mast	Sunol Science Corporation	TWR 95-4	020808-3	N/A	N/A
Turntable	Sunol Science Corporation	FM 2001	N/A	N/A	N/A
Mast and Turntable Controller	Sunol Science Corporation	SC104V	020808-1	N/A	N/A



## 6. TEST SITE DESCRIPTION

### 6.1 Test Facility Description

Please refer to section 2.1 and the figures in Appendix D of this report for test location.

### 6.2 EUT Mounting, Bonding and Grounding


The EUT was mounted on a 1.0 by 1.5 by 0.8 meter high non-conductive table, which was placed on the ground plane.

For above 1GHz testing the EUT was placed 1.5 meters above high, above the ground plane.

The EUT was not grounded.

### 6.3 Facility Environmental Characteristics

When applicable refer to the data sheets in Appendix E for the relative humidity, air temperature, and barometric pressure.



## 7. CHARACTERISTICS OF THE TRANSMITTER

### 7.1 Channel Number and Frequencies

There are a total of 40 channels. The low channel is at 2402.0 MHz and the high channel is at 2480.0 MHz. There is approximately 2 MHz separation between channels and the EUT uses GFSK modulation.

### 7.2 Antenna

The Antenna is a Chip Antenna located on the transmitter PCB.



## 8. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests. Test results are also included in this section.

### 8.1 RF Emissions


#### 8.1.1 Conducted Emissions Test

*Test Results: The EUT is battery powered; therefore this test was not performed.*

The EMI receiver was used as a measuring meter. A quasi-peak and/or average reading was taken only where indicated in the data sheets. The LISN output was measured using the EMI receiver. The output of the second LISN was terminated by a 50-ohm termination. The effective measurement bandwidth used for this test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding, and grounding of the EUT. The EUT received its power through the LISN, which was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI 63.4. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The conducted emissions from the EUT were maximized for operating mode as well as cable placement. The different configurations were investigated to find the worst case as well the worst case channel. The final data was collected under program control by the computer software. The final qualification data is located in Appendix E.



### 8.1.2 Radiated Emissions (Spurious and Harmonics) Test

The EMI receiver was used as a measuring meter. The receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the receiver records the highest measured reading over all the sweeps. Amplifiers were used to increase the sensitivity of the instrument. There was one Microwave Preamplifier used for frequencies above 1 GHz.

For spurious emissions the quasi-peak detector was used for frequencies below 1GHz and the average detector was used for frequencies above 1 GHz.

For the harmonic and fundamental emissions a duty cycle average was used. For the non-intentional emissions a linear average was used.

The measurement bandwidths and transducers used for the radiated emissions test were:

FREQUENCY RANGE (MHz)	TRANSDUCER	EFFECTIVE MEASUREMENT BANDWIDTH
.009 to .150	Active Loop Antenna	200 Hz
.150 to 30	Active Loop Antenna	9 kHz
30 to 1000	Combilog Antenna	100 kHz (120 kHz for QP Measurements)
1000 to 25000	Horn Antenna	1 MHz

The TDK FAC-3 shielded test chamber of Compatible Electronics, Inc. was used for radiated emissions testing. This test site is in full compliance with ANSI C63.4 & ANSI C63.10. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. At each reading, the EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters in both vertical and horizontal polarizations (for E field radiated field strength).

#### Test Results:

The EUT complies with the limits of CFR Title 47 Part 15 Subpart B section 15.109, & Part 15 Subpart C sections 15.205, 15.209, 15.249, RSS GEN, & RSS 210. The six highest emissions are listed in table 1.





### 8.1.3 Fundamental Field Strength

The Peak Transmit Radiated Field Strength was measured at a 3-meter test distance. The EMI Receiver was used to obtain the final test data. The final qualification data sheets are located in Appendix E.

Where

$$\delta(\text{dB}) = 20 \log \left[ \frac{\sum (nt_1 + mt_2 + \dots + \xi t_x)}{T} \right]$$

$n$  is the number of pulses of duration  $t_1$

$m$  is the number of pulses of duration  $t_2$

$\xi$  is the number of pulses of duration  $t_x$

$T$  is the period of the pulse train or 100 ms if the pulse train length is greater than 100 ms

Duty Cycle Correction Factor = -20.00dB

Pulse Type 1 =  $10 * 292.1844 \text{ uS} = 2921.844 \text{ uS}$

Pulse Type 2 =  $5 * 194.7896 \text{ uS} = 973.948 \text{ uS}$

Total On Time =  $2921.844 \text{ mS} + 973.948 \text{ mS} = 3895.792 \text{ uS} = 3.895792 \text{ mS}$

$3.895792 \text{ mS} / 100 \text{ mS} = 0.03895792 \text{ mS}$

$20 \log (0.03895792) = -28.188 \text{ dB}$  correction factor

**Max Duty Cycle Correction Factor = -20.00dB**

#### Test Results:

The EUT complies with Part 15 Subpart C, Section 15.249.

### 8.1.4 Emissions Radiated Outside of the Fundamental Frequency Band

The Band Edge measurement was measured using the EMI Receiver at a 3-meter test distance to obtain the final test data. The lower and upper channels were tuned during the low and high band edge tests. The final qualification data sheets are located in Appendix E.

#### Test Results:

The EUT complies with Part 15 Subpart C, Section 15.205, 15.249, RSS GEN, & RSS 210.



**9. TEST PROCEDURE DEVIATIONS**

The test procedures were not deviated from throughout all tests.

**10. CONCLUSIONS**

The HomeKit Enabled Residential Door Lock Model: SmartCode 919 meets all of the relevant specification requirements defined in the Code of Federal Regulations Title 47, Part 15 Subpart B section 15.109, & Subpart C sections 15.205, 15.209, 15.249, RSS GEN, & RSS 210.



**APPENDIX A**

***LABORATORY ACCREDITATIONS AND  
RECOGNITIONS***



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

## LABORATORY ACCREDITATIONS AND RECOGNITIONS

NVLAP LAB CODES 200063-0,  
200528-0, 200527-0

For US, Canada, Australia/New Zealand, Taiwan and the European Union, Compatible Electronics is currently accredited by NVLAP to ISO/IEC 17025 an ISO 9002 equivalent. Please follow the link to the NIST site for each of our facilities NVLAP certificate and scope of accreditation.

### NVLAP listing links

Agoura Division - <http://ts.nist.gov/Standards/scopes/2000630.htm>Brea Division - <http://ts.nist.gov/Standards/scopes/2005280.htm>Silverado/Lake Forest Division - <http://ts.nist.gov/Standards/scopes/2005270.htm>

### ANSI listing

[CETCB](#)<https://www.ansica.org/wwwversion2/outside/ALLdirectoryDetails.asp?menuID=1&prgID=3&orgID=123&status=4>

Compatible Electronics has been nominated as a Conformity Assessment Body (CAB) for EMC under the US/EU Mutual Recognition Agreement (MRA).



Compatible Electronics has been nominated as a Conformity Assessment Body (CAB) for Taiwan/BSMI under the US/APEC (Asia-Pacific Economic Cooperation) Mutual Recognition Agreement (MRA).

We are also certified/listed for IT products by the following country/agency:



### VCCI Listing, from VCCI site

[Enter "Compatible" in search form](http://www.vcci.or.jp/vcci_e/activity/registration/setsubi.html) [http://www.vcci.or.jp/vcci\\_e/activity/registration/setsubi.html](http://www.vcci.or.jp/vcci_e/activity/registration/setsubi.html)

### FCC Listing, from FCC OET site

[FCC test lab search](https://fjallfoss.fcc.gov/oetcf/eas/reports/TestFirmSearch.cfm) <https://fjallfoss.fcc.gov/oetcf/eas/reports/TestFirmSearch.cfm>

Compatible Electronics IC listing can be found at:

<http://www.ic.gc.ca/eic/site/ic1.nsf/eng/home>

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400



**APPENDIX B**

***MODIFICATIONS TO THE EUT***



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400



---

## MODIFICATIONS TO THE EUT

There were no modifications were made during testing.



**APPENDIX C**

***ADDITIONAL MODELS COVERED  
UNDER THIS REPORT***



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

## ADDITIONAL MODELS COVERED UNDER THIS REPORT

USED FOR THE PRIMARY TEST

HOMEKIT ENABLED RESIDENTIAL DOOR LOCK  
Model: SmartCode 919  
S/N: NONE

No additional models were tested.






**APPENDIX D**


***DIAGRAMS, CHARTS, AND PHOTOS***



# FIGURE 1: PLOT MAP AND LAYOUT OF TEST SITE BELOW 1GHZ



## FIGURE 2: PLOT MAP AND LAYOUT OF TEST SITE ABOVE 1GHZ



**COM-POWER AL-130****LOOP ANTENNA****S/N: 121049****CALIBRATION DUE: DECEMBER 6, 2016**

<b>FREQUENCY (MHz)</b>	<b>MAGNETIC (dB/m)</b>	<b>ELECTRIC (dB/m)</b>	<b>FREQUENCY (MHz)</b>	<b>MAGNETIC (dB/m)</b>	<b>ELECTRIC (dB/m)</b>
<b>0.009</b>	-34.64	16.86	<b>0.8</b>	-36.32	15.18
<b>0.01</b>	-34.78	16.72	<b>0.9</b>	-36.22	15.28
<b>0.02</b>	-35.91	15.59	<b>1.0</b>	-36.22	15.28
<b>0.03</b>	-35.48	16.02	<b>2.0</b>	-35.91	15.59
<b>0.04</b>	-35.82	15.68	<b>3.0</b>	-35.91	15.59
<b>0.05</b>	-36.49	15.01	<b>4.0</b>	-36.01	15.49
<b>0.06</b>	-36.30	15.20	<b>5.0</b>	-35.80	15.70
<b>0.07</b>	-36.43	15.07	<b>6.0</b>	-36.00	15.50
<b>0.08</b>	-36.30	15.20	<b>7.0</b>	-35.90	15.60
<b>0.09</b>	-36.39	15.11	<b>8.0</b>	-35.70	15.80
<b>0.1</b>	-36.41	15.09	<b>9.0</b>	-35.70	15.80
<b>0.2</b>	-36.61	14.89	<b>10.0</b>	-35.60	15.90
<b>0.3</b>	-36.63	14.87	<b>15.0</b>	-36.52	14.98
<b>0.4</b>	-36.52	14.99	<b>20.0</b>	-35.75	15.75
<b>0.5</b>	-36.63	14.87	<b>25.0</b>	-37.78	13.72
<b>0.6</b>	-36.62	14.88	<b>30.0</b>	-38.62	12.88
<b>0.7</b>	-36.53	14.97			



**COM-POWER AC-220****LAB R - COMBILOG ANTENNA****S/N: 25857****CALIBRATION DUE: MAY 21, 2016**

<b>FREQUENCY (MHz)</b>	<b>FACTOR (dB)</b>	<b>FREQUENCY (MHz)</b>	<b>FACTOR (dB)</b>
<b>30</b>	22.5	<b>160</b>	13.3
<b>35</b>	22.5	<b>180</b>	15.0
<b>40</b>	23.0	<b>200</b>	14.6
<b>45</b>	21.5	<b>250</b>	16.5
<b>50</b>	21.3	<b>300</b>	18.1
<b>60</b>	18.2	<b>400</b>	19.4
<b>70</b>	13.2	<b>500</b>	21.4
<b>80</b>	11.6	<b>600</b>	21.6
<b>90</b>	11.9	<b>700</b>	23.7
<b>100</b>	12.6	<b>800</b>	26.0
<b>120</b>	15.1	<b>900</b>	26.6
<b>140</b>	13.6	<b>1000</b>	28.5



**COM-POWER AH-118****HORN ANTENNA**

S/N: 071250

**CALIBRATION DUE: JULY 1, 2016**

<b>FREQUENCY (MHz)</b>	<b>FACTOR (dB)</b>	<b>FREQUENCY (MHz)</b>	<b>FACTOR (dB)</b>
1000	30.1	9500	44.2
1500	29.2	10000	43.4
2000	31.6	10500	44.6
2500	35.5	11000	45.1
3000	33.7	11500	45.7
3500	36.0	12000	46.2
4000	35.4	12500	45.4
4500	35.5	13000	44.8
5000	40.1	13500	46.7
5500	37.8	14000	47.8
6000	39.0	14500	46.4
6500	39.9	15000	47.2
7000	40.4	15500	45.5
7500	44.4	16000	45.0
8000	44.1	16500	44.5
8500	43.1	17000	47.0
9000	43.0	17500	47.8
		18000	44.2



**COM-POWER PAM-118A****1-18GHz - PREAMPLIFIER**

S/N: 551034

CALIBRATION DUE: AUGUST 25, 2016

<b>FREQUENCY (MHz)</b>	<b>FACTOR (dB)</b>	<b>FREQUENCY (MHz)</b>	<b>FACTOR (dB)</b>
500	36.77	5500	39.82
1000	38.63	6000	38.74
1100	38.72	6500	39.60
1200	38.97	7000	35.52
1300	38.59	7500	36.61
1400	39.18	8000	36.92
1500	38.71	8500	37.13
1600	39.28	9000	36.50
1700	39.25	9500	38.92
1800	39.06	10000	38.74
1900	40.34	11000	35.23
2000	40.07	12000	35.64
2500	39.69	13000	36.73
3000	40.94	14000	36.48
3500	40.41	15000	37.57
4000	40.44	16000	38.10
4500	41.20	17000	37.34
5000	39.35	18000	36.80





**FRONT VIEW**

SPECTRUM BRANDS  
HOMEKIT ENABLED RESIDENTIAL DOOR LOCK  
Model: SmartCode 919  
FCC SUBPART B & C - RADIATED EMISSIONS < 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**







**REAR VIEW**

SPECTRUM BRANDS  
HOMEKIT ENABLED RESIDENTIAL DOOR LOCK  
Model: SmartCode 919  
FCC SUBPART B & C - RADIATED EMISSIONS < 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**





**FRONT VIEW**

SPECTRUM BRANDS  
HOMEKIT ENABLED RESIDENTIAL DOOR LOCK  
Model: SmartCode 919  
FCC SUBPART B & C - RADIATED EMISSIONS > 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**





**REAR VIEW**

SPECTRUM BRANDS  
HOMEKIT ENABLED RESIDENTIAL DOOR LOCK  
Model: SmartCode 919  
FCC SUBPART B & C - RADIATED EMISSIONS > 1GHz

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION  
FOR MAXIMUM EMISSIONS**



**APPENDIX E**

***RADIATED EMISSIONS DATA SHEETS***



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600


**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

Title: FCC 15.209  
File: Radiated Pre-Scan 30-1000Mhz.set  
Operator: Torey Oliver  
EUT Type: Homekit Electronic Lock / SmartCode 919  
EUT Condition: The EUT is constantly transmitting 2480 MHz.  
Comments:  
Temp: 72f  
Hum: 38%  
Battery Powered

4/11/2016 9:52:29 AM  
Sequence: Preliminary Scan

Compatible Electronics, Inc. FAC-3 (Lab R)



**There were no radiated emissions other than harmonics found below 30 MHz or above 1GHz.  
This is the worst case channel and mode for spurious emissions.**



**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

Title: FCC 15.209  
 File: Radiated Final 30-1000Mhz.set  
 Operator: Torey Oliver  
 EUT Type: Homekit Electronic Lock / SmartCode 919  
 EUT Condition: The EUT is constantly transmitting 2480 MHz.  
 Comments:  
 Temp: 72f  
 Hum: 38%  
 Battery Powered

4/11/2016 10:14:22 AM  
 Sequence: Final Measurements


**Compatible Electronics, Inc. FAC-3 (Lab R)**

Freq (MHz)	(QP) Margin (dB)	(QP) EMI (dB $\mu$ V/m)	(PEAK) EMI (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Pol	Ttbl Agl (deg)	Twr Ht (cm)	Transducer (dB)	Cable (dB)
32.00	-20.82	19.18	25.48	40.00	H	10.25	241.82	22.50	0.52
32.80	-20.66	19.34	24.96	40.00	H	156.00	228.74	22.50	0.53
38.10	-20.08	19.92	26.18	40.00	V	307.50	227.19	22.82	0.58
38.90	-20.01	19.99	25.94	40.00	V	84.50	221.82	22.89	0.59
41.00	-20.15	19.85	25.23	40.00	V	245.25	208.62	22.66	0.61
41.40	-20.21	19.79	25.00	40.00	H	146.50	210.00	22.59	0.61

*There were no radiated emissions other than harmonics found below 30 MHz or above 1GHz.  
 This is the worst case channel and mode.*



***DUTY CYCLE  
DATA SHEETS***



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500


**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

## DUTY CYCLE


Pulse Train On Time (ms)	# of Pulses in Train	Total on Time (ms)	period (ms)	Duty Cycle	Correction (db)	Applied Correction (db)
0.192282565	5	3.895792	100	0.0390	-28.188	-20.00




Comment A: 100ms Duty Cycle  
Date: 8.APR.2016 09:35:52



# DUTY CYCLE



Comment A: Pulse Type 1  
Date: 8.APR.2016 09:53:23




Comment A: Pulse Type 2  
Date: 8.APR.2016 09:53:55



## *FUNDAMENTAL & HARMONICS*

### *DATA SHEETS*



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

## FUNDAMENTAL FIELD STRENGTH

### FCC 15.249 & RSS 210

Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

Date: 4/11/2016  
 Lab: R  
 Tested By: Torey Oliver

### Compatible Electronics, Inc. FAC-3

Freq. (MHz)	Level (dBuV/m)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Table	Tower	Comments
2402.00	85.62	H	113.97	-28.35	Peak	1.57	360	X-Axis
2402.00	65.62	H	93.97	-28.35	Avg	1.57	360	X-Axis
2402.00	82.41	V	113.97	-31.56	Peak	1.66	25	X-Axis
2402.00	62.41	V	93.97	-31.56	Avg	1.66	25	X-Axis
2426.00	86.55	H	113.97	-27.42	Peak	1.53	360	X-Axis
2426.00	66.55	H	93.97	-27.42	Avg	1.53	360	X-Axis
2426.00	84.19	V	113.97	-29.78	Peak	1.10	24	X-Axis
2426.00	64.19	V	93.97	-29.78	Avg	1.10	24	X-Axis
2480.00	83.47	H	113.97	-30.50	Peak	1.63	360	X-Axis
2480.00	63.47	H	93.97	-30.50	Avg	1.63	360	X-Axis
2480.00	79.55	V	113.97	-34.42	Peak	2.10	28	X-Axis
2480.00	59.55	V	93.97	-34.42	Avg	2.10	28	X-Axis

Test distance  
 3 meter



## HARMONICS LOW CHANNEL HORIZONTAL

**FCC 15.249 & RSS 210**

Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

Date: 4/8/2016  
 Lab: R  
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	PoI (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4804.0	50.64	H	73.98	-23.34	Peak	1.07	177	
4804.0	30.64	H	53.98	-23.34	Avg	1.07	177	
7206.0	63.10	H	73.98	-10.88	Peak	1.06	148	
7206.0	43.10	H	53.98	-10.88	Avg	1.06	148	
9608.0		H	73.98		Peak			No Emissions Found
9608.0		H	53.98		Avg			No Emissions Found
12010.0		H	73.98		Peak			No Emissions Found
12010.0		H	53.98		Avg			No Emissions Found
14412.0		H	73.98		Peak			No Emissions Found
14412.0		H	53.98		Avg			No Emissions Found
16814.0		H	73.98		Peak			No Emissions Found
16814.0		H	53.98		Avg			No Emissions Found
19216.0		H	73.98		Peak			No Emissions Found
19216.0		H	53.98		Avg			No Emissions Found
21618.0		H	73.98		Peak			No Emissions Found
21618.0		H	53.98		Avg			No Emissions Found
24020.0		H	73.98		Peak			No Emissions Found
24020.0		H	53.98		Avg			No Emissions Found

Test distance  
 3 meter



## HARMONICS LOW CHANNEL VERTICAL, ANTENNA 1

**FCC 15.249 & RSS 210**

Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

Date: 4/8/2016  
 Lab: R  
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Poi (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4804.0	45.67	V	73.98	-28.31	Peak	3.74	92	
4804.0	25.67	V	53.98	-28.31	Avg	3.74	92	
7206.0	58.67	V	73.98	-15.31	Peak	2.16	193	
7206.0	38.67	V	53.98	-15.31	Avg	2.16	193	
9608.0		V	73.98		Peak			No Emissions Found
9608.0		V	53.98		Avg			No Emissions Found
12010.0		V	73.98		Peak			No Emissions Found
12010.0		V	53.98		Avg			No Emissions Found
14412.0		V	73.98		Peak			No Emissions Found
14412.0		V	53.98		Avg			No Emissions Found
16814.0		V	73.98		Peak			No Emissions Found
16814.0		V	53.98		Avg			No Emissions Found
19216.0		V	73.98		Peak			No Emissions Found
19216.0		V	53.98		Avg			No Emissions Found
21618.0		V	73.98		Peak			No Emissions Found
21618.0		V	53.98		Avg			No Emissions Found
24020.0		V	73.98		Peak			No Emissions Found
24020.0		V	53.98		Avg			No Emissions Found

Test distance  
 3 meter



## HARMONICS MID CHANNEL HORIZONTAL

**FCC 15.249 & RSS 210**

Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

Date: 4/8/2016  
 Lab: R  
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	PoI (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4852.0	52.09	H	73.98	-21.89	Peak	1.20	26	
4852.0	32.09	H	53.98	-21.89	Avg	1.20	26	
7278.0	65.56	H	73.98	-8.42	Peak	1.01	329	
7278.0	45.56	H	53.98	-8.42	Avg	1.01	329	
9704.0		H	73.98		Peak			No Emissions Found
9704.0		H	53.98		Avg			No Emissions Found
12130.0		H	73.98		Peak			No Emissions Found
12130.0		H	53.98		Avg			No Emissions Found
14556.0		H	73.98		Peak			No Emissions Found
14556.0		H	53.98		Avg			No Emissions Found
16982.0		H	73.98		Peak			No Emissions Found
16982.0		H	53.98		Avg			No Emissions Found
19408.0		H	73.98		Peak			No Emissions Found
19408.0		H	53.98		Avg			No Emissions Found
21834.0		H	73.98		Peak			No Emissions Found
21834.0		H	53.98		Avg			No Emissions Found
24260.0		H	73.98		Peak			No Emissions Found
24260.0		H	53.98		Avg			No Emissions Found

Test distance  
 3 meter



## HARMONICS MID CHANNEL VERTICAL

**FCC 15.249 & RSS 210**

Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

Date: 4/8/2016  
 Lab: R  
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	PoI (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4852.0	50.19	V	73.98	-23.79	Peak	2.42	30	
4852.0	30.19	V	53.98	-23.79	Avg	2.42	30	
7278.0	62.08	V	73.98	-11.90	Peak	2.17	349	
7278.0	42.08	V	53.98	-11.90	Avg	2.17	349	
9704.0		V	73.98		Peak			No Emissions Found
9704.0		V	53.98		Avg			No Emissions Found
12130.0		V	73.98		Peak			No Emissions Found
12130.0		V	53.98		Avg			No Emissions Found
14556.0		V	73.98		Peak			No Emissions Found
14556.0		V	53.98		Avg			No Emissions Found
16982.0		V	73.98		Peak			No Emissions Found
16982.0		V	53.98		Avg			No Emissions Found
19408.0		V	73.98		Peak			No Emissions Found
19408.0		V	53.98		Avg			No Emissions Found
21834.0		V	73.98		Peak			No Emissions Found
21834.0		V	53.98		Avg			No Emissions Found
24260.0		V	73.98		Peak			No Emissions Found
24260.0		V	53.98		Avg			No Emissions Found

Test distance  
 3 meter



## HARMONICS HIGH CHANNEL HORIZONTAL

**FCC 15.249 & RSS 210**

Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

Date: 4/8/2016  
 Lab: R  
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	PoI (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4960.0		H	73.98		Peak			No Emissions Found
4960.0		H	53.98		Avg			No Emissions Found
7440.0	68.37	H	73.98	-5.61	Peak	1.26	321	
7440.0	48.37	H	53.98	-5.61	Avg	1.26	321	
9920.0		H	73.98		Peak			No Emissions Found
9920.0		H	53.98		Avg			No Emissions Found
12400.0		H	73.98		Peak			No Emissions Found
12400.0		H	53.98		Avg			No Emissions Found
14880.0		H	73.98		Peak			No Emissions Found
14880.0		H	53.98		Avg			No Emissions Found
17360.0		H	73.98		Peak			No Emissions Found
17360.0		H	53.98		Avg			No Emissions Found
19840.0		H	73.98		Peak			No Emissions Found
19840.0		H	53.98		Avg			No Emissions Found
22320.0		H	73.98		Peak			No Emissions Found
22320.0		H	53.98		Avg			No Emissions Found
24800.0		H	73.98		Peak			No Emissions Found
24800.0		H	53.98		Avg			No Emissions Found

Test distance  
 3 meter





## HARMONICS HIGH CHANNEL VERTICAL

**FCC 15.249 & RSS 210**

Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

Date: 4/8/2016  
 Lab: R  
 Tested By: Torey Oliver

Freq. (MHz)	Level (dBuV)	Pol (v/h)	Limit	Margin	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
4960.0		V	73.98		Peak			No Emissions Found
4960.0		V	53.98		Avg			No Emissions Found
7440.0	65.72	V	73.98	-8.26	Peak	2.02	23	
7440.0	45.72	V	53.98	-8.26	Avg	2.02	23	
9920.0		V	73.98		Peak			No Emissions Found
9920.0		V	53.98		Avg			No Emissions Found
12400.0		V	73.98		Peak			No Emissions Found
12400.0		V	53.98		Avg			No Emissions Found
14880.0		V	73.98		Peak			No Emissions Found
14880.0		V	53.98		Avg			No Emissions Found
17360.0		V	73.98		Peak			No Emissions Found
17360.0		V	53.98		Avg			No Emissions Found
19840.0		V	73.98		Peak			No Emissions Found
19840.0		V	53.98		Avg			No Emissions Found
22320.0		V	73.98		Peak			No Emissions Found
22320.0		V	53.98		Avg			No Emissions Found
24800.0		V	73.98		Peak			No Emissions Found
24800.0		V	53.98		Avg			No Emissions Found

Test distance  
 3 meter



***EMISSIONS RADIATED OUTSIDE OF THE FUNDAMENTAL  
FREQUENCY BAND***

***DATA SHEETS***



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

# BAND EDGES HORIZONTAL

**FCC 15.249 & RSS 210**

Company: Spectrum Brands

Date: 4/11/2016

EUT: Homekit Enabled Residential Door Lock

Lab: R

Model: SmartCode 919

Test ENG: Torey Oliver



Duty Cycle Correction Factor = -20

**Compatible Electronics, Inc. FAC-3 ( Lab R )**

Freq. (MHz)	Level (dBμV/m)	Pol	Limit (dBμV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
2400.00	57.52	H	73.98	-16.46	Peak	1.57	360	No Marker Delta
2400.00	37.52	H	53.98	-16.46	AVG	1.57	360	Method Used
2487.83	52.09	H	73.98	-21.89	Peak	1.63	360	No Marker Delta
2487.83	32.09	H	53.98	-21.89	AVG	1.63	360	Method Used

Test distance

3 meter


 Comment A: Lower Band Edge Horizontal  
 Date: 11.APR.2016 07:36:44

 Comment A: Upper Band Edge Horizontal  
 Date: 11.APR.2016 08:46:50


# BAND EDGES VERTICAL



**FCC 15.249 & RSS 210**

 Company: Spectrum Brands  
 EUT: Homekit Enabled Residential Door Lock  
 Model: SmartCode 919  
 Duty Cycle Correction Factor = -20

 Date: 4/11/2016  
 Lab: R  
 Test ENG: Torey Oliver

**Compatible Electronics, Inc. FAC-3 ( Lab R )**

Freq. (MHz)	Level (dBμV/m)	Pol	Limit (dBμV)	Margin (dB)	Peak / QP / Avg	Ant. Height (m)	Table Angle (deg)	Comments
2400.00	55.29	V	73.98	-18.69	Peak	1.66	25	No Marker Delta
2400.00	35.29	V	53.98	-18.69	AVG	1.66	25	Method Used
2485.51	52.13	V	73.98	-21.85	Peak	2.10	28	No Marker Delta
2485.51	32.13	V	53.98	-21.85	AVG	2.10	28	Method Used

 Test distance  
 3 meter

 Comment A: Lower Band Edge Vertical  
 Date: 11.APR.2016 07:42:50

 Comment A: Upper Band Edge Vertical  
 Date: 11.APR.2016 08:53:07


***OCCUPIED BANDWIDTH***

***DATA SHEETS***



---

**Brea Division**  
114 Olinda Drive  
Brea, CA 92823  
(714) 579-0500

**Agoura Division**  
2337 Troutdale Drive  
Agoura, CA 91301  
(818) 597-0600

**Silverado Division**  
19121 El Toro Road  
Silverado, CA 92676  
(949) 589-0700

**Lake Forest Division**  
20621 Pascal Way  
Lake Forest, CA 92630  
(949) 587-0400

**RSS GEN**

Company:	Spectrum Brands	Date:	4/11/2016
EUT:	HomeKit Enabled Residential Door Lock	Lab:	R
Model:	SmartCode 919	Test ENG:	Torey Oliver

**Compatible Electronics, Inc. FAC-3 ( Lab R )**

## Occupied Bandwidth

Freq. (MHz)	Measured BW (kHz)	Peak / QP / Avg	Comments
2412	1812.10	Peak	
2426	1757.60	Peak	
2462	1823.60	Peak	

