



FCC CFR47 PART 15 DIGITAL DEVICE

TEST REPORT

FOR

USB HUB

MODEL: UT-T71T

FCC ID: NUOUSBT71T

REPORT NUMBER: 98E7435


ISSUE DATE: MAY 5, 1999

Prepared for

UNIXSTAR TECHNOLOGY, INC.
3F, NO. 3, LANE 538, CHUNG CHENG RD.
HSIN TIEN, TAIPEI, TAIWAN, R. O. C.

Prepared by

COMPLIANCE ENGINEERING SERVICES, INC.
No. 199, CHUNG SHENG ROAD
HSIN TIEN CITY, TAIPEI, TAIWAN R.O.C.
TEL: (02) 2217-0894
FAX: (02) 2217-1254



FCC, VCCI, CISPR, CE
UL, CSA, TÜV, VDE

U.S.A. : P.O.BOX 612650, SAN JOSE, CA 95161-2650
TAIPEI : P.O.BOX 17-82, HSIN TIEN, TAIWAN, R.O.C.

TABLE OF CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE.....	1
2. PRODUCT DESCRIPTION.....	2
3. TESTED SYSTEM DETAILS.....	2
4. TEST FACILITY.....	3
5. ACCREDITATION AND LISTING.....	3
6. MEASUREMENT INSTRUMENTATION.....	3
7. MEASURING INSTRUMENT CALIBRATION.....	3
8. UNITS OF MEASUREMENT.....	4
9. ANTENNAS.....	4
10. CLASSIFICATION OF DIGITAL DEVICE.....	5
11. RADIATED EMISSION LIMITS.....	5
12. CONDUCTED EMISSION LIMITS.....	6
13. CONDUCTED EMISSION TEST PROCEDURE.....	6
14. RADIATED EMISSION TEST PROCEDURE.....	7
15. AMBIENT CONDITIONS.....	7
16. SYSTEM TEST CONFIGURATION.....	8
17. EQUIPMENT MODIFICATIONS.....	8
18. EUT SETUP PHOTOS.....	9
19. TEST EQUIPMENT LIST.....	11
20. CORRECTION FACTOR.....	12
21. TEST RESULT SUMMARY.....	13
APPENDICES	15
EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION	
CONFIGURATION BLOCK DIAGRAM	
CONDUCTED EMISSION PLOT	
RADIATED EMISSION DATA	
EUT PHOTOGRAPHS	

1. VERIFICATION OF COMPLIANCE



COMPANY NAME: UNIXSTAR TECHNOLOGY, INC.
3F, NO. 3, LANE 538, CHUNG CHENG RD.
HSIN TIEN, TAIPEI, TAIWAN, R. O. C.

CONTACT PERSON: BOBSON CHENG / ENGINEERING MANAGER

TELEPHONE NO: (02) 2218-2100

MODEL NO/NAME: UT-T71T

SERIAL NO: N/A

DATE TESTED: MAY 3, 1999 ~ MAY 5, 1999

TYPE OF EQUIPMENT:	INFORMATION TECHNOLOGY EQUIPMENT (ITE)
MEASUREMENT DISTANCE:	() 3 METER <input checked="" type="checkbox"/> 10 METER
TECHNICAL LIMIT:	CLASS B
FCC RULES:	PART 15
MEASUREMENT PROCEDURE	ANSI C63.4:92 / EN55022
EQUIPMENT AUTHORIZATION PROCEDURE	CERTIFICATION
MODIFICATION MADE ON EUT	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
DEVIATIONS FROM MEASUREMENT PROCEDURE	<input type="checkbox"/> YES (refer to section 21 for comments) <input checked="" type="checkbox"/> NO
RADIATED EMISSION TEST RESULT	-3.14 dB @ 168.028 MHz/VERTICAL
CONDUCTED EMISSION TEST RESULT	-10.10 dB @ 0.505 MHz/L1

The above equipment was tested by Compliance Engineering Services, Inc. for compliance with the requirements set forth in the FCC CFR 47, PART 15. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By

Acknowledged By

MIKE C.I. KUO / VICE PRESIDENT
COMPLIANCE ENGINEERING SERVICES

BOBSON CHENG / ENGINEERING MANAGER
UNIXSTAR TECHNOLOGY, INC.

2. PRODUCT DESCRIPTION

CHASSIS TYPE	PLASTIC
LIST OF EACH OSC. OR XTAL. FREQ. (FREQ.>=1 MHz)	Y1=48 MHz
CHIPSET BRAND AND PART NO.	CKHV, TUSB2070
NUMBER OF PCB LAYERS	4 LAYERS
BOARD REVISION NO.	REV:4.2
POWER REQUIREMENTS	INPUT:AC 120V, 60Hz OUTPUT:DC 6V, 4A
AC/DC ADAPTOR/MODEL	UNIXTAR, MKD-64000UK
NO. OF EXTERNAL I/O CONNECTORS	8

3. TESTED SYSTEM DETAILS

The Model names for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Host Computer

Device Type	Manufacturer	Model Number	Serial Number	FCC ID / DoC
NOTEBOOK COMPUTER	INVENTEC	P5023BAA	J92P33P1036	DOC

External Peripheral Devices

Device Type	Manufacturer	Model Number	Serial No.	FCC ID / DoC
KEYBOARD	CHERRY	MY3000 USB 4A	KB-14	DOC
USB HUB (EUT)	UNIXTAR	UT-T71T	N/A	NUOUSBT71T
MODEM	DISCOVERY	2496CF	MD-04	I972496AF
PRINTER	MATSUSHITA	KX-P1080i	PRN-01	ACJ5Z6KX-P1080I

4. TEST FACILITY

The open area test sites and conducted measurement facilities used to collect the radiated data are located at No. 199, Chung Sheng Road, Hsin Tien City, Taipei, Taiwan R.O.C. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5. ACCREDITATION AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code:200064-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT(1300F2))

6. MEASUREMENT INSTRUMENTATION

Radiated emissions were measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, ridged waveguide, liner horn. EMI receivers were used for line conducted readings, spectrum analyzers with pre-selectors and quasi-peak detectors were used to perform radiated measurements. Receiving equipment (i.e., receiver, analyzer, quasi-peak adapter, pre-selector) and LISNs conform to CISPR specification for "Radio Interference Measuring Apparatus and Measurement Methods," Publication 16.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

7. MEASURING INSTRUMENT CALIBRATION

The measuring equipment which was utilized in performing the tests documented herein has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment which is traceable to recognized national standards.

8. UNITS OF MEASUREMENT

Measurements of radiated interference are reported in terms of dB(uV/m) at a specified distance. The indicated readings on the spectrum analyzer were converted to dB(uV/m) by use of appropriate conversion factors. Measurements of conducted interference are reported in terms of dB(uV).

The field strength is calculated by adding the Antenna Factor and Cable Factors, then by subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

Assume a receiver reading of 52.5 dBuV is obtained. The Antenna Factor of 7.4dB/m and a Cable Factor of 1.1dB is added. The Amplifier Gain of 29 dB is subtracted, giving a field strength of 32 dBuV/m. The 32 dBuV/m value was mathematically converted to its corresponding level in uV/m.

$$FS = 52.5 + 7.4 + 1.1 - 29 = 32 \text{ dBuV/m}$$

$$\text{Level in uV/m} = \text{Common Antilogarithm} [(32 \text{ dBuV/m})/20] = 39.8 \text{ uV/m}$$

9. ANTENNAS

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 10 meters from the leading edge of the turn table.

10. CLASSIFICATION OF DIGITAL DEVICE

Class A includes digital devices that are marketed for use in commercial, industrial or business environments, excluding devices which are marketed for use by the general public or are intended to be used in the home.

Class B includes digital devices that are marketed for use in residential environments, notwithstanding use in commercial, business and industrial environments.

Note: The responsible party may also qualify a device intended to be marketed in a commercial, business or industrial environment as Class B device, and in fact is encouraged to do so provided the device complies with the technical specifications for a Class B digital device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B digital device, regardless of its intended use.

11. RADIATED EMISSION LIMITS

FCC PART 15 CLASS B

MEASURING DISTANCE OF 3 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

FCC CLASS B ALTERNATIVE DISTANCE (CISPR 22:1993)

MEASURING DISTANCE OF 10 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	30	29.5
88-216	45	33.0
216-960	60	35.6
960-1000	150	43.5
ABOVE 1000	150	43.5

Note: Limits extrapolated 20dB/decade

FCC PART 15 CLASS A

MEASURING DISTANCE OF 10 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	90	39.1
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

12. CONDUCTED EMISSION LIMITS

CLASS B

FREQUENCY RANGE	FIELD STRENGTH (Microvolts)	FIELD STRENGTH (dBuV)
450kHz-30MHz	250	48

CLASS A

FREQUENCY RANGE	FIELD STRENGTH (Microvolts)	FIELD STRENGTH (dBuV)
450kHz-1.705MHz	1000	60
1.705MHz - 30MHz	3000	69.54

13. CONDUCTED EMISSION TEST PROCEDURE

The EUT is located so that the distance between the boundary of the EUT and the closest surface to the LISN is 0.8m.

EUT test configuration is according to Section 7 of ANSI C63.4/1992.

Conducted disturbance shall be measured between the phase lead and the ground, and between the neutral lead and the ground. The frequency 0.450 - 30 MHz shall be investigated.

Set the EMI receiver to PEAK detector setting and sweep continuously over the frequency range to be investigated. Set resolution bandwidth to 9kHz minimum. Connect EMI receiver input cable to LINE 1 RF measurement connection on the LISN. Connect a 50ohm terminator to the unused RF connection on the LISN. For each mode of EUT operation, maximize emissions readings by manipulating cable and wire positions. Record the configuration for each EUT power cord which produces emissions closest to the limit. Repeat the same procedure for LINE 2 of each EUT power cord.

14. RADIATED EMISSION TEST PROCEDURE

The EUT and all other support equipment are placed on a wooden table 80 cm above the ground screen. Antenna to EUT distance is either 3 meters or 10 meters (Class B or Class A). During the test, the table is rotated 360 degrees to maximize emissions, and the antenna is positioned from 1 to 4 meters above the ground screen to further maximize emissions. The antenna is polarized in both vertical and horizontal positions.

EUT test configuration is according to Section 8 of ANSI C63.4/1992.

Monitor the frequency range of interest at a fixed antenna height and EUT azimuth. Frequency span should be small enough to easily differentiate between broadcast stations and intermittent ambients. Rotate EUT 360 degrees to maximize emissions received from EUT. If emission increases by more than 1 dB, or if another emission appears that is greater by 1 dB, return to azimuth where maximum occurred and perform additional cable manipulation to further maximize received emission.

Move antenna up and down to further maximize suspected highest amplitude signal. If emission increased by 1 dB or more, or if another emission appears that is greater by 1dB or more, return to antenna height where maximum signal was observed and manipulate cables to produce highest emissions, noting frequency and amplitude.

15. AMBIENT CONDITIONS

The ambient conditions at the time of final tests were as follows:

	Radiated Emission	Conducted Emission
Temperature	23C J	23C J
Humidity	85%	85%

16. SYSTEM TEST CONFIGURATION

The equipment under test was configured and operated in a manner which tended to maximize its emission characteristics in a typical application. Power and signal distribution, ground, interconnecting cabling and physical placement of equipment simulated the typical application and usage insofar as practicable.


SOFTWARE USED DURING THE TESTS	
Operating System	WINDOWS 98
File Name	EMITEST.EXE
Program Sequence	1. WINDOWS 98 BOOTS SYSTEM. 2. RUN MS-DOS MODE. 3. RUN EMITEST.EXE TO ACTIVATE ALL PERIPHERALS AND DISPLAY "H" PATTERN ON MONITOR SCREEN.

17. EQUIPMENT MODIFICATIONS



To achieve compliance to CLASS B levels, the following change(s) were made during compliance testing:

NOT APPLICABLE

18. EUT SETUP PHOTOS



Radiated Emission Setup Photos (Worst Emission Position)



Conducted Emission Setup Photos (Worst Emission Position)

19. TEST EQUIPMENT LIST

Equipment	Manuf.	Model No.	Serial No.	Site	Cal Date	Due Date
EMI TEST DISPLAY	ROHDE & SCHWARZ	DSAI-D 804.8932.52	827832/001	D	10/98	10/99
EMI TEST RF UNIT	ROHDE & SCHWARZ	ESBI-RF/1005.4300.52	827832/003	D	10/98	10/99
AMPLIFIER	TEST EQUIPMENT	PA-102	43685	D	9/98	9/99
ANTENNA	CHASE	CBL 6111A	1547	D	12/98	12/99
LISN	EMCO	3825/2	1842	D	1/99	1/00
LISN(EUT)	EMCO	3825/2	1435	D	1/99	1/00
CABLE	TALLEY	HELIX FSJ4-50B	D0301	D	9/98	9/99
CABLE	TIME MICROWAVE	LMR-400-2	D1001	D	9/98	9/99
SPECTRUM ANALYZER	H.P.	8568B	2928A04814	E	2/99	2/00
SPECTRUM DISPLAY	H.P.	85662A	2848A18276	E	2/99	2/00
QUASI-PEAK DETECTOR	H.P.	85650A	2811A01439	E	2/99	2/00
AMPLIFIER	H.P.	8447D B	1644A02328	E	4/98	4/99
ANTENNA	EMC TEST SYSTEMS	3142	1310	E	8/98	2/00
TEST RECEIVER	ROHDE & SCHWARZ	ESHS20	840455/006	E	2/99	2/00
LISN	SOLAR	8012-50-R-24-BNC	8305114	E	7/98	7/99
LISN(EUT)	FISCHER	FCC-LISN-50/250 -25-2	107	E	4/98	4/99
CABLE	TIME MICROWAVE	LMR-400-2	E1001	E	4/98	4/99
CABLE	TALLEY	HELIX FSJ4-50B	E0301	E	4/98	4/99

20. CORRECTION FACTOR

OATS NO. D

FREQ (MHZ)	ANTENNA 3 METER			ANTENNA 10 METER			SITE D
	HORI.	VERT.	CABLE LOSS (dB)	HORI.	VERT.	CABLE LOSS (dB)	AMP GAIN (dB)
30	20.05	18.37	0.41	17.80	16.30	0.64	21.45
35	17.24	16.40	0.46	16.00	15.05	0.61	21.68
40	14.52	12.68	0.56	13.27	12.58	0.73	21.70
45	11.90	10.73	0.59	10.59	10.08	0.71	21.73
50	9.72	8.44	0.58	8.56	8.24	0.76	21.75
60	6.61	5.60	0.71	6.02	5.06	0.99	21.67
70	6.30	6.38	0.78	6.34	5.87	0.96	21.70
80	7.90	7.89	0.81	7.45	7.91	0.97	21.73
90	9.35	10.17	0.81	8.61	9.20	1.07	21.72
100	11.15	11.51	0.92	10.12	10.05	1.20	21.70
120	12.31	12.86	1.09	11.75	12.13	1.27	21.59
125	12.46	13.09	1.07	11.87	11.82	1.30	21.65
140	12.25	13.11	1.19	11.97	12.03	1.42	21.57
150	11.65	12.50	1.17	11.34	11.27	1.45	21.49
160	11.08	11.56	1.30	10.44	10.77	1.60	21.48
175	9.99	10.51	1.32	9.65	9.62	1.62	21.42
180	9.72	10.00	1.27	9.21	9.58	1.47	21.42
200	10.75	10.26	1.42	8.98	10.06	1.67	21.35
250	12.90	12.75	1.57	12.21	12.46	1.93	21.25
300	14.04	13.70	1.88	13.33	13.59	2.27	21.20
400	16.87	16.33	2.11	16.24	16.20	2.69	21.10
500	18.05	18.36	2.33	17.97	17.81	2.79	21.12
600	20.06	20.03	2.54	19.64	19.52	3.12	20.79
700	21.24	21.61	2.77	20.61	20.87	3.46	20.56
800	22.52	22.59	2.92	21.98	21.89	3.45	20.53
900	23.50	23.58	3.32	22.76	22.98	3.98	20.23
1000	24.71	25.04	3.40	24.37	24.30	4.19	19.67
1100	25.33	25.46	3.83	24.62	24.94	4.24	20.28
1200	26.89	26.32	3.98	25.32	25.45	4.98	20.06
1300	29.05	28.56	3.86	27.78	28.07	4.82	20.38
1400	27.35	27.51	4.70	26.53	26.99	5.21	19.44
1500	29.70	30.09	5.28	27.94	28.16	5.82	19.39
1600	28.07	27.82	5.03	27.71	27.98	5.64	19.67
1700	31.93	31.40	5.24	29.00	29.42	5.41	20.25
1800	31.56	31.91	4.57	30.06	30.42	5.99	19.70
1900	32.49	32.73	5.18	31.85	30.72	6.53	20.33
2000	31.12	30.32	6.12	30.97	30.46	4.90	19.87

21. TEST RESULT SUMMARY

Preliminary Radiated Emission Tests were performed at the 10 meter open area test site. CCS test procedure no:CCSUE2001B and the procedure listed in ANSI C63.4 /1992 section 8.3.1.1. were used. The following preliminary tests were conducted to determine the worst mode of operation and configuration.

Preliminary Radiated Emission Test				
Frequency Range Investigated		30 MHz TO 1000 MHz		
Mode of operation	Date	Data Report No.	Worst Mode	
NORMAL MODE	05/03/99	7435D#(1, 2)	<input checked="" type="checkbox"/>	

Final Radiated Emission Test was conducted by operating the worst mode as indicated above.

OATS No: D / 10 M	Data Report No. 7435D#(1, 2)		Date 05/03/99		Tested By: ERIC LIN							
Six Highest Radiated Emission Readings												
Frequency Range Investigated				30 MHz TO 1000 MHz								
Freq (MHz)	Meter Reading (dBuV)	C.F. (dB/m)	Corrected Reading (dBuV)	Limits (dBuV)	Margin (dB)	Reading Type P/Q/A	Pol. H/V					
42.989	29.34	-3.67	25.67	30.00	-4.33	P	V					
48.000	31.33	-5.84	25.49	30.00	-4.51	P	V					
120.028	26.75	-2.68	24.07	30.00	-5.93	P	H					
119.972	27.23	-2.32	24.91	30.00	-5.09	P	V					
143.967	29.10	-2.47	26.63	30.00	-3.37	P	V					
168.028	30.56	-3.70	26.86	30.00	-3.14	P	V					

C.F. (Correction Factor) = Antenna Factor+Cable Loss+6dB Attenuator
-Amplifier Gain

Corrected Reading = Metering Reading + C.F.

Margin=Corrected Reading - Limits

P=Peak Reading H=Horizontal Polarization/Antenna

Q=Quasi-peak V=Vertical Polarization/Antenna

A=Average Reading

Comments: **N/A**

APPENDICES

EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION

CONFIGURATION BLOCK DIAGRAM

CONDUCTED EMISSION PLOT

RADIATED EMISSION DATA

EUT PHOTOGRAPHS

External I/O Cable Construction Description

CABLE NO: 1, 2~4	Number of I/O ports of this type: 7
I/O Port: USB KB , LOOP CABLE	Connector Type: USB
Capture Type: Snap-in	Type of Cable used: Shielded
Cable Connector Type: Molded	Cable Length: 1.8M
Bundled During Tests: No, Yes	Data Traffic Generated: Yes
Remarks: N/A	

CABLE NO: 5	Number of I/O ports of this type: 1
I/O Port: USB CABLE	Connector Type: USB
Capture Type: Snap-in	Type of Cable used: Shielded
Cable Connector Type: Molded	Cable Length: 1.8M
Bundled During Tests: Yes	Data Traffic Generated: Yes
Remarks: Ferrite bead loaded at both ends.	

CABLE NO: 6	Number of I/O ports of this type: 1
I/O Port: PARALLEL	Connector Type: DB25
Capture Type: Screw-in	Type of Cable used: Shielded
Cable Connector Type: Molded	Cable Length: 1.5M
Bundled During Tests: Yes	Data Traffic Generated: Yes
Remarks: N/A	

CABLE NO: 7	Number of I/O ports of this type: 1
I/O Port: RS232 Modem	Connector Type: DB9
Capture Type: Screw-in	Type of Cable used: Shielded
Cable Connector Type: Metal	Cable Length: 1.0M
Bundled During Tests: No	Data Traffic Generated: Yes
Remarks: N/A	

CABLE NO: 8~9	Number of I/O ports of this type: 2
I/O Port: AC ADAPTOR	Connector Type: AC Inlet
Capture Type: Snap-in	Type of Cable used: Un-Shielded
Cable Connector Type: Molded	Cable Length: 3.0M, 3.9M
Bundled During Tests: No (Radiation), Yes (Line Conduction)	Data Traffic Generated: No
Remarks: NO.8: A Ferrite bead on the cable of PC end.NO.9:N/A	

CABLE NO: 10~11	Number of I/O ports of this type: 2
I/O Port: Power Cord	Connector Type: AC Inlet
Capture Type: Snap-in	Type of Cable used: Un-Shielded
Cable Connector Type: Molded	Cable Length: 1.8M
Bundled During Tests: No (Radiation), Yes (Line Conduction)	Data Traffic Generated: No
Remarks: N/A	

Configuration Block Diagram

