



# RF EXPOSURE REPORT

**REPORT NO.:** SA951003L04

**MODEL NO.:** CS8088

**SERIES MODELS NO.:** CS8089

**APPLICANT:** In-Tech Electronics Ltd.

**ADDRESS:** 207-210, 2F., Century Centre, 44-46 Hung To Road,  
Kwun Tong, Kowloon, Hong Kong

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** No. 47, 14<sup>th</sup> Ling, Chia Pau Tsuen, Lin Kou Hsiang  
244, Taipei Hsien, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



## 5 Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.585
High	2.480	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)
Conducted Power	3.95
EIRP Power	3.95

**\*Note:** The antenna is PCB antenna with 0dBi gain

Threshold for no SAR evaluation is 24.585mW

Transmitter power is 2.483mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold