



RF EXPOSURE REPORT

REPORT NO.: SA951201L04

MODEL NO.: CS8112

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: In- Tech Electronics Ltd.

ADDRESS: 207-210, 2F., Century Centre, 44-46 Hung To Road,
Kwun Tong, Kowloon, Hong Kong

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang
244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



Conclusion

No evaluation required if power is below this threshold:

F (GHz)		mW
Low	2.402	24.580
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	2.73	1.875
EIRP Power	2.73	1.875

***NOTE:** The antenna is Chip antenna with 0dBi gain

Threshold for no SAR evaluation is 24.580mW.

Transmitter power is 1.875mW.

Conclusion: No SAR evaluation required since Transmitter Power is below FCC threshold.