



RF EXPOSURE REPORT

REPORT NO.: SA960125L04

MODEL NO.: CS8122

SERIES MODEL NO.: CS8123

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: In-Tech Electronics Ltd.

ADDRESS: Unit A, 13/F, Wing Tai Centre, 12 Hing Yip
Street, Kwun Tong, Kowloon, Hong Kong.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



CONCLUSION

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	3.61	2.296
EIRP Power	3.61	2.296

***Note:** The antenna is PCB micro strip antenna with 0dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 2.296mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold