



# RF EXPOSURE REPORT

**REPORT NO.:** SA960409L06A

**MODEL NO.:** CS8124, CS8125

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** In-Tech Electronics Ltd.

**ADDRESS:** Unit A, 13/F, Wing Tai Centre, 12 Hing Yip Street,  
Kwun Tong, Kowloon, Hong Kong

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	-0.39	0.914
EIRP Power	-0.39	0.914

**\*Note:** The antenna is PCB antenna with 0dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 0.914mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold