



RF EXPOSURE REPORT

REPORT NO.: SA971021L11

MODEL NO.: CS8136, CS8139

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: In-Tech Electronics Ltd.

ADDRESS: Unit A, 13/F, Wing Tai Centre, 12 Hing Yip Street ,
Kwun Tong, Kowloon , Hong Kong.

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,
Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.580
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	6.72	4.699
EIRP Power	6.72	4.699

***Note:** The antenna is PCB micro strip antenna with 0dBi gain

Threshold for no SAR evaluation is 24.580mW

Transmitter power is 4.699mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold