

RF EXPOSURE **EVALUATION REPORT**

APPLICANT dormakaba EAD GmbH

PRODUCT NAME data collection terminal

MODEL NAME 9600-K6 MRD

TRADE NAME Terminal 96 00

BRAND NAME dormakaba

FCC ID NVI-KT9600K6L

47CFR 2.1091

KDB 447498 D01 General RF Exposure STANDARD(S)

Guidance v06

ISSUE DATE 2017-10-30

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

TEST REPORT DECLARATION	3
1. TECHNICAL INFORMATION	<u>3</u>
1.1. IDENTIFICATION OF APPLICANT	4
1.2. IDENTIFICATION OF MANUFACTURER ·····	4
1.3. EQUIPMENT UNDER TEST (EUT) ·····	4
1.3.1. PHOTOGRAPHS OF THE EUT	
1.3.2. IDENTIFICATION OF ALL USED EUT·····	٠6
1.4. APPLIED REFERENCE DOCUMENTS ·····	6
2. DEVICE CATEGORY AND RF EXPOSURE LIMIT	7
3 RF EXPOSURE EVALUATION	8
ANNEX C GENERAL INFORMATION	9

Change History				
Issue	Date	Reason for change		
1.0	2017-10-30	First edition		



TEST REPORT DECLARATION

Applicant	dormakaba EAD GmbH
Applicant Address	Albertistr. 3, 78056 Villingen-Schwenningen, Germany
Manufacturer	In-Tech Electronics Ltd
Manufacturer Address	Unit A,13/F, Wing Tai Centre,12 Hing Yip Street, Kwun Tong Kowloon, Hong Kong
Product Name	data collection terminal
Model Name	9600-K6 MRD
Brand Name	dormakaba
HW Version	02
SW Version	V5
Test Standards	47CFR 2.1091; KDB 447498 D01 General RF Exposure Guidance v06
Issue Date	2017-10-30
SAR Evaluation	Not Required

Tested by	by :		eng hunes
redica by			Peng Fuwei (Test engineer)

Approved by Peng Huarui (Supervisor)



1. TECHNICAL INFORMATION

Note: the following data is based on the information by the applicant.

1.1. Identification of Applicant

Company Name:	dormakaba EAD GmbH
Address:	Albertistr. 3, 78056 Villingen-Schwenningen, Germany

1.2. Identification of Manufacturer

Company Name:	In-Tech Electronics Ltd		
Address:	Unit A,13/F, Wing Tai Centre,12 Hing Yip Street, Kwun Tong Kowloon,		
	Hong Kong		

1.3. Equipment Under Test (EUT)

Model Name:	9600-K6 MRD
Trade Name:	Terminal 96 00
Brand Name:	dormakaba
Hardware Version:	02
Software Version:	V5
Frequency Bands:	13.56MHz
Antenna type:	PCB Antenna





1.3.1. Photographs of the EUT

1. EUT front view



2. EUT rear view





1.3.2. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	02	V5

1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1091	Radiofrequency Radiation Exposure Evaluation: mobile
		devices
2	KDB 447498 D01v06	General RF Exposure Guidance



2. DEVICE CATEGORY AND RF EXPOSURE LIMIT

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m) Population/Uncontro	Power density (mW/cm²)	Averaging time (minutes)
· ·	•	•	•	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz



^{* =} Plane-wave equivalent power density



RF EXPOSURE EVALUATION 3

Standalone transmission MPE evaluation

Frequency	Max Emission (dBµA/m)	Magnetic field strength (A/m)	Limit of Magnetic field strength (A/m)
13.56MHz	-34.8	1.82×10 ⁻⁸	0.162



ANNEX C GENERAL INFORMATION

1. Identification of the Responsible Testing Laboratory

Shenzhen Morlab Communications Technology Co., Ltd.
Morlab Laboratory
FL.3, Building A, FeiYang Science Park, No.8 LongChang
Road, Block 67, BaoAn District, ShenZhen, GuangDong
Province, P. R. China
Mr. Su Feng
+86 755 36698555
+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

**** END OF REPORT ****

