

REPORT OF MEASUREMENTS

FOR

CELLULAR SPECIALTIES, INC.

BI-DIRECTIONAL AMPLIFIER

MODEL: 565smr

FCC ID: NVRBA56X-01

CERTIFICATION APPLICATION

Applicant/Manufacturer: **Cellular Specialties
670 North Commercial Street
Manchester, NH 03101**

Equipment under Test (EUT): **The EUT is a Bidirectional Amplifier used to amplify cellular signals in the smr band.**

Model: **565smr**

FCC ID Number: **FCC ID: NVRBA56X-01**

Applicable Test Standard: **FCC Parts 2 & 90**

Device Classification: **Mobile**

EUT Frequency Range: **Uplink: 806MHz TO 821MHz
Downlink: 851MHz TO 866MHz**

EUT Gain: **Uplink: 63.07dB
Downlink: 63.07dB**

Measured Power Output at maximum input, single channel **Uplink: +2.366 Watts
Downlink: +1.879 Watts**

Power Output Rating Based on Intermodulation Data (For Certification Grant): **Uplink: +29dBm=794mW
Downlink: +27.48dBm=560mW**

Modulation Types: **TDMA**

RF Exposure + Antenna Installation: **See Attached Installation/Users Manual and MPE Evaluation**

Power Ratings Per Channel: **See Power Per Channel Test Data**

Measurements Required by FCC: **See Report Section 1 (Summary of Test Program) and the following Test Report Data Attachments:**

- RF Power Output**
- Intermodulation Characteristics**
- Occupied Bandwidth**
- Spurious Emissions at Antenna Terminals**
- Effective Radiated Power of Spurious Radiation**
- Frequency Stability**

SECTION 1
SUMMARY OF TEST PROGRAM

POWER OUTPUT

Measurement Procedure:

The uplink and downlink of the test sample were alternately connected through external attenuators to a spectrum analyzer. Each link had an unmodulated signal sent to the input. The level of the input signal was adjusted to achieve maximum output power of the amplifier.

Testing was performed at 1 frequency within each passband (uplink and downlink). The levels of the input signals and maximized output power levels were recorded and are shown below.

UPLINK (Power Input @ 1dB Compression):

Frequency (MHz)	Input (dBm)	Output (dBm)
813.5	-29.33	33.74

DOWNLINK (Power Input @ 1dB Compression):

Frequency (MHz)	Input (dBm)	Output (dBm)
858.5	-30.33	32.74

For complete test data, see electronic Test Report Attachment, **RF Power Output Data**.

INTERMODULATION CHARACTERISTICS

Measurement Procedure:

Three CW signals were injected, in turn, to the uplink and downlink via a three way power combiner. Two signals were close together and at the low end of the passband, one signal was close to the high end of the passband. The output of each signal generator was adjusted so that the three output fundamental frequencies were equal in magnitude. At the specified input power levels all intermodulation products were at -13dBm or below. The requested power rating of the device for the certification grant is derived by summing the levels of the three input signals for each the uplink and downlink.

For complete test data, including actual X/Y plots of intermodulation signals, see electronic Test Report Attachment, **Intermodulation Characteristics Data**.

OCCUPIED BANDWIDTH

Measurement Procedure:

The test sample does not have any frequency generating circuits therefore measurements were made to compare the input signal to the output signal. The signal generator output was connected to the spectrum analyzer. A TDMA modulation signal was then applied to the carrier.

Waveforms were then noted on an X-Y plot. Next, the signal generator was connected to the EUT and the output of the EUT was connected to the spectrum analyzer. The output waveform after amplification was then compared to the emission mask requirement for TDMA signals (46dB down at plus and minus one channel spacing, 30kHz). Testing was performed at one frequency within each passband (uplink and downlink).

For complete test data, see electronic Test Report Attachment, **Occupied Bandwidth Data**.

An explanation of the data is as follows: There are two signals superimposed on each plot, one signal is the waveform before modulation, the other is the modulated carrier. In each case the center of the grid shows a narrowband signal projecting out from the center of the modulation envelope. This signal is actually the stored unmodulated signal.

ANTENNA CONDUCTED EMISSIONS

Measurement Procedure:

The signal generator output was connected in turn to the uplink and downlink input ports of the EUT. The input power level was at the level which was ascertained during the Power Output test. A spectrum analyzer was connected to the output of the EUT. The input test frequencies used were one frequency within each passband (uplink and downlink). The level of any spurious emission was recorded. Testing was performed in the frequency range of 30MHz to 8.66GHz. The spurious emissions limit is -13dBm as specified in FCC Part 90.

For complete test data, including harmonic and spurious emissions measured at antenna terminal, see electronic Test Report Attachment, **Antenna Conducted Data**.

EFFECTIVE RADIATED POWER OF SPURIOUS RADIATION

Measurement Procedure:

The test sample was placed on a 80cm high wooden test stand which was located 3 meters from the test antenna on an FCC listed test site. A signal generator was connected to the input of the amplifier. The signal generator output was set to provide the input power level necessary to achieve maximum output power of the amplifier at 1 frequency within each passband (uplink and downlink). The effective radiated power of each out of band spurious emission was measured using the substitution method specified in TIA/EIA-603. The frequency range of the test was 30MHz – 8.66GHz. The limit for out of band spurious emissions is -13dBm as specified in Part 90.

For complete test data, see electronic Test Report Attachment, **Radiated Emissions Data**.

FREQUENCY STABILITY MEASUREMENTS

Measurement Procedure (Frequency vs. Voltage & Temperature):

The test sample does not have any frequency determining circuits however testing was performed at frequency versus input voltage and temperature. The test sample was placed in a temperature chamber and connected to a signal generator. The RF output of the signal generator was set to a frequency within each passband (uplink and downlink) of the test sample, and the output of the test sample was connected to a spectrum analyzer. The AC input voltage to the test sample was varied plus and minus 15% in 5% increments while the temperature was varied from -30 degrees c to +50 degrees c in 10 degree increments. The output frequency from the test sample was measured and compared to the input frequency.

For complete test data, see electronic Test Report Attachment, **Frequency Stability Data**.

SECTION 2

EQUIPMENT LIST

Frequency Stability

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4995	Signal Generator	Marconi Instru.	10 kHz - 1 GHz	2022	11/5/02	11/5/03
4997	Digital Thermometer	Omega	N/A		11/21/01	12/21/02
5013	Variac	Powerstat	0 - 140 VAC	116B	5/30/02	5/30/03
520N	Digital Multimeter	Wavetek	N/A	25XT	11/26/02	5/26/03
557	Temperature Chamber	Associated Env.	-73 C - +177 C	SK 3105	6/11/02	6/11/03

Intermodulation Characteristics

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
3130	20 dB Attenuator	Narda	DC - 18 GHz	768-20	1/25/02	1/25/03
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4935	6.0 dB Attenuator	JFW Inc.	DC - 2 GHz	50FH-006-50N	1/25/02	1/25/03
4995	Signal Generator	Marconi Instru.	10 kHz - 1 GHz	2022	11/5/02	11/5/03
5001	Sweep Oscillator	Hewlett Packard	.01 - 20.4 GHz	8350B	2/25/02	2/25/03
5001	Oscillator Plug-In	Hewlett Packard	.01 - 20 GHz	83592A	2/25/02	2/25/03
530A	AM/FM Signal Generator	Marconi Instru.	10 kHz - 1.2 GHz	2023	7/10/02	7/10/03

Occupied Bandwidth

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
3130	20 dB Attenuator	Narda	DC - 18 GHz	768-20	1/25/02	1/25/03
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4935A	6.0 dB Attenuator	JFW Inc.	DC - 2 GHz	50FH-006-50N	1/25/02	1/25/03
	Signal Generator	Hewlett Packard	250kHz - 2 GHz	E4431B	12/27/01	12/27/02

EQUIPMENT LIST

RF Power Output

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
4898	Power Amplifier	Eaton Corporation	100 MHz - 512 MHz	2052B	11/7/02	11/7/03
4935	6.0 dB Attenuator	JFW Inc.	DC - 2 GHz	50FH-006-50N	1/25/02	1/25/03
4962	Attenuator	Narda	DC - 18 GHz	757C-20dB	11/6/02	11/6/03
530A	AM/FM Signal Generator	Marconi Instru.	10 kHz - 1.2 GHz	2023	7/10/02	7/10/03

Spurious Emissions (ERP)

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
3258	Double Ridge Guide	EMCO	1 - 18 GHz	3115	5/6/02	5/6/03
4029	Test Site Attenuation	Retlif	3 / 10 Meters	RNH	11/27/02	11/27/03
4202	Biconilog	EMCO	26 MHz - 2 GHz	3142	7/25/02	7/25/03
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4921	Graphics Plotter	Hewlett Packard	N/A	7550A	9/20/02	9/20/03

Antenna Conducted Spurious Emissions

EN	Type	Manufacturer	Description	Model No.	Cal Date	Due Date
4895	Spectrum Analyzer	Hewlett Packard	9kHz - 22GHz	8593EM	2/13/02	2/13/03
4935	6.0 dB Attenuator	JFW Inc.	DC - 2 GHz	50FH-006-50N	1/25/02	1/25/03
4962	Attenuator	Narda	DC - 18 GHz	757C-20dB	11/6/02	11/6/03
530A	AM/FM Signal Generator	Marconi Instru.	10 kHz - 1.2 GHz	2023	7/10/02	7/10/03