

**Evaluation of the CSI Model CSI-DSP85-25X-AW BDA
For
Compliance with FCC Guidelines
For Human Exposure to Radio Frequency
Electromagnetic Fields**

18 October 2010

General

The CSI Model CSI-DSP85-25X-AW Bi-directional amplifier is considered to be a dual-band “mobile” device operating in both the Cellular Service authorized under part 27. As such, the equipment is required to be evaluated for RF exposure if operated below 1.5 GHz with an effective radiated power (ERP) of 1.5 watts or more or if operated above 1.5 GHz with an effective radiated power (ERP) of 3.0 watts or more, as defined in 2.1091 of FCC rules.

Downlink

For the downlink portion of the Model CSI-DSP85-25X-AW BDA, the maximum rated output power is +30.0dbm (1000 mW) in the AWS band (>1.5 GHz). As stated in the Model CSI-DSP85-25X-AW Manual, the maximum authorized indoor antenna gain is 3 dBi, corresponding to a typical Multi-Band Omni-Directional antenna. The Table below shows the results of the calculated ERP, neglecting cable losses.

Frequency	Power Out	Ant Gain	EIRP	ERP	Limit
2110-2155 MHz	30.0 dBm	3 dBi	33.0 dBm	1,216 mW	3.0 W

In the above case the ERP is well below the allowable limits excluding the downlink from routine evaluation.

The Cautions in the Model CSI-DSP85-25X-AW manual clearly define the antenna selection and installation criteria in order to maintain a minimum 20-centimeter separation.

Uplink

For the downlink portion of the Model CSI-DSP85-25X-AW BDA, the maximum rated output power is +30.0dbm (1000 mW) in the AWS Band (>1.5 GHz). As stated in the Model CSI-DSP85-25X-AW Manual, the maximum authorized outdoor antenna gain is 14 dBi, corresponding to a typical Multi-Element Yagi-Directional antenna. The Table below shows the results of the calculated ERP this case, neglecting cable losses.

Frequency	Power Out	Ant Gain	EIRP	ERP	Limit
1710-1755 MHz	30.0 dBm	14 dBi	44.0 dBm	15,316 mW	3.0 W

As shown in the above table, the level exceeds the allowable limit and must be evaluated for minimum separation distances in order to comply with the exposure limits of 1.1310 of the FCC rules.

Using the guidelines in FCC OET Bulletin 65 and Supplement C, the power density at a reasonable distance from the maximum gain antenna was calculated. The minimum safe distance was also determined based on the uncontrolled exposure limits defined in Table 1B of FCC rules 1.1311. The following assumptions are made concerning these calculations:

Cellular Band
Po = 1000 mw average
Cable Loss = 0 dB
Ant Gain = 14 dBi
Frequency = 1725 MHz
Main Beam (worst-case)
Rooftop 100% reflection
Reasonable Distance = 6 feet (183 cm)

Therefore, from OET Bulletin 65,

$$S = (PG)/4\pi R^2 \quad \text{or} \quad S = \text{EIRP}/4\pi R^2$$

For 100% reflection, a doubling of the field strength can be expected. The above equation can be modified to,

$$S = (2)^2 PG/4\pi R^2 = \text{EIRP}/\pi R^2$$

Solving for S at a distance of 6 feet (183 cm) gives,

$$S = (1000) (25) / \pi (183)^2 = 0.24 \text{ mw/cm}^2$$

From FCC rules 1.1311, Table 1B, the allowable limit for uncontrolled exposure is $f(\text{MHz}) / 1500$. For frequencies above 1500 MHz the limit is 1.0 mw/cm^2 .

The calculated values of 0.24 is below both the limit thereby showing compliance under worst-case operating conditions.

As in the case of the downlink, the Cautions in the Model CSI-DSP85-25X-AW manual clearly define the antenna selection and installation criteria in order to maintain a conservative 6-foot separation.