

*Safety Precautions*

**CAUTION**



For **INDOOR** use, an Omni-Directional Antenna with a maximum gain of 8dBi is authorized for use with this unit. Inside antennas must be positioned to observe minimum separation of 20 cm. (~ 8 in.) from all users and bystanders. For the protection of personnel working in the vicinity of inside (downlink) antennas, the following guidelines for minimum distances between the human body and the antenna must be observed.

The installation of an **INDOOR** antenna must be such that, under normal conditions, all personnel cannot come within 20 cm. (~ 8.0 in.) from any inside antenna. Exceeding this minimum separation will ensure that the employee or bystander does not receive RF-exposure beyond the Maximum Permissible Exposure according to section 1.1310 i.e. limits for General Population/Uncontrolled Exposure.



For **OUTDOOR** use, a Directional Antenna up to a maximum gain of 13dBi is authorized for use with this unit. The Outside antenna must be positioned to observe minimum separation of 20 cm. (~ 8 in.) from all users and bystanders. For the protection of personnel working in the vicinity of outside (uplink) antennas, the following guidelines for minimum distances between the human body and the antenna must be observed.

The installation of an **OUTDOOR** antenna must be such that, under normal conditions, all personnel cannot come within 20 cm. (~ 8 in.) from the outside antenna. In all installations, the antenna should never be mounted such that the main beam is directed toward an area where workers or bystanders may be present. Exceeding this minimum separation will ensure that the worker or bystander does not receive RF-exposure beyond the Maximum Permissible Exposure according to FCC RF exposure requirements i.e. limits for General Population/Uncontrolled Exposure.