

**Evaluation of the CSI Model 610-AP BDA
For
Compliance with FCC Guidelines
For Human Exposure to Radio Frequency
Electromagnetic Fields**

22 June 2006

General

The CSI Model 610-AP Bi-directional amplifier is considered to be a dual-band “mobile” device operating in both the Cellular Service authorized under subpart H of part 22 and in the Personal Communication Service authorized under part 24. As such, the equipment is required to be evaluated for RF exposure if operated below 1.5 GHz with an effective radiated power (ERP) of 1.5 watts or more or if operated above 1.5 GHz with an effective radiated power (ERP) of 3.0 watts or more, as defined in 2.1091 of FCC rules.

Downlink

For the downlink portion of the Model 610-AP BDA, the maximum rated output power is +28dbm (631 mW) in the Cellular Band (<1.5 GHz) and 25 dBm (316 mW) in the PCS band (>1.5 GHz). As stated in the Model 610-AP Manual, the maximum authorized indoor antenna gain is 3 dBi, corresponding to a typical Multi-Band Omni-Directional antenna. The Table below shows the results of the calculated ERP for both cases, neglecting cable losses.

Frequency	Power Out	Ant Gain	EIRP	ERP	Limit
869-894 MHz	28 dBm	3 dBi	31 dBm	768 mW	1.5 W
1930-1990 MHz	25 dBm	3 dBi	28 dBm	385 mW	3.0 W

In both the above cases the ERP is well below the allowable limits excluding the downlink from routine evaluation.

The Cautions in the Model 610-AP manual clearly define the antenna selection and installation criteria in order to maintain a minimum 20-centimeter separation.

Uplink

For the downlink portion of the Model 610-AP BDA, the maximum rated output power is +26dbm (398 mW) in the Cellular Band (<1.5 GHz) and 21 dBm (126 mW) in the PCS band (>1.5 GHz). As stated in the Model 610-AP Manual, the maximum authorized outdoor antenna gain is 11 dBi, corresponding to a typical Multi-Element Yagi-Directional antenna. The Table below shows the results of the calculated ERP for both cases, neglecting cable losses.

Frequency	Power Out	Ant Gain	EIRP	ERP	Limit
824-849 MHz	28 dBm	11 dBi	39 dBm	4840 mW	1.5 W
1850-1910 MHz	25 dBm	11 dBi	36 dBm	2430 mW	3.0 W

As shown in the above table, only the Cellular (824-849) exceeds the allowable limit and must be evaluated for minimum separation distances in order to comply with the exposure limits of 1.1310 of the FCC rules.

Using the guidelines in FCC OET Bulletin 65 and Supplement C, the power density at a reasonable distance from the maximum gain antenna was calculated. The minimum safe distance was also determined based on the uncontrolled exposure limits defined in Table 1B of FCC rules 1.1311. The following assumptions are made concerning these calculations:

Po = 631 mw average
Cable Loss = 0 dB
Ant Gain = 11 dBi
Frequency = 836.5 MHz \pm 12.5 MHz
Main Beam (worst-case)
Rooftop 100% reflection
Reasonable Distance = 4 feet (120 cm)

Therefore, from OET Bulletin 65,

$$S = (PG)/4\pi R^2 \quad \text{or} \quad S = \text{EIRP}/4\pi R^2$$

For 100% reflection, a doubling of the field strength can be expected. The above equation can be modified to,

$$S = (2)^2 PG/4\pi R^2 = \text{EIRP}/\pi R^2$$

Solving for S at a distance of 4 feet (120 cm) gives,

$$S = (631) (12.6) / \pi (120)^2 = \boxed{0.18 \text{ mw/cm}^2}$$

From FCC rules 1.1311, Table 1B, the allowable limit for uncontrolled exposure is $f(\text{MHz}) / 1500$. At 836.5 MHz this corresponds to a level of 0.56 mw/cm^2 .

The calculated value of 0.18 is below the limit of 0.56 thereby showing compliance under worst-case operating conditions.

When the above equation is solved for minimum separation at the exposure limit,

$$R = \sqrt{(631) (12.6) / \pi (0.54)} = 68 \text{ cm (2.2 feet)}.$$

As in the case of the downlink, the Cautions in the Model 610-AP manual clearly define the antenna selection and installation criteria in order to maintain a conservative 4-foot separation.