

6. Measurement Data (continued)

6.7. Public Exposure to Radio Frequency Energy Levels 1.1307 (b)(1), RSS-GEN, Issue 4 Section 3.2, RSS 102

Center Frequency (MHz)	MPE Distance (cm)	DUT Output Power (dBm)	DUT Antenna Gain (dBi)	Power Density		FCC Limit (mW/cm ²)	IC Limit (W/m ²)
				(mW/cm ²)	(W/m ²)		
	(1)	(2)	(3)	(4)		(5)	(6)
1715	20.0	29.66	0.00	0.1839629	1.8396286	1	4.25
1733	20.0	29.95	0.00	0.1966664	1.9666639	1	4.28
1750	20.0	29.92	0.00	0.1953125	1.9531255	1	4.31
2115	20.0	30.07	3.00	0.4033947	4.0339466	1	4.91
2133	20.0	30.25	3.00	0.4204653	4.2046528	1	4.93
2150	20.0	30.36	3.00	0.4312510	4.3125103	1	4.96

$$PD = \frac{OP + AG}{(4 \times \pi \times d^2)}$$

1. Reference CFR 2.1093(b): For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.
2. Section 6.1.2 of this test report. Note that the value has been adjusted to include the cable insertion loss.
3. Data supplied by the client for combination of cable loss and antenna gain.
4. Power density is calculated from field strength measurement and antenna gain.
5. Reference CFR 1.1310, Table 1: Limits for Maximum Permissible Exposure (MPE), Section (B): Limits for General Population/Uncontrolled Exposure.
6. Reference IC RSS-102 Section 4 Table 4 General Public (Uncontrolled Environment) for equipment operating from 300 to 6000 MHz, the W/m² limit is determined by the formula 0.2619 * F (MHz) ^ 0.6834