

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Snap Cam Wearable HD Video Camera, Snap Cam HD Sport Camera

**Model No.: 1045, 1045X, 1049, 1049X, 1050, 1050X, 1074, 1075, 1076,
1077, 1078, 1079**

FCC ID: NW71045

Trademark: iON

Report No.: ES150706041E2

Issue Date: August 04, 2015

Prepared for

**World Wide Licenses Ltd.
Suite D, 16/F., ON Hing Building, NO 1. ON Hing Terrace, Central Hong
Kong China**

Prepared by

**SHENZHEN EMTEK CO., LTD.
Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China
TEL: +86-755-26954280
FAX: +86-755-26954282**

**This report shall not be reproduced, except in full, without the written approval of
SHENZHEN EMTEK CO., LTD.**


VERIFICATION OF COMPLIANCE

Applicant:	World Wide Licenses Ltd. Suite D, 16/F., ON Hing Building, NO 1. ON Hing Terrace, Central Hong Kong China
Manufacturer:	World Wide Licenses Ltd. Suite D, 16/F., ON Hing Building, NO 1. ON Hing Terrace, Central Hong Kong China
Product Description:	Snap Cam Wearable HD Video Camera, Snap Cam HD Sport Camera
Trade Mark:	iON
Model Number:	1045, 1045X, 1049, 1049X, 1050, 1050X, 1074, 1075, 1076, 1077, 1078, 1079 (Note: The samples are the same except model number. So 1045 was selected for full test.)

We hereby certify that:

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2014).

Date of Test : July 01, 2015 to August 01, 2015

Prepared by : 
Ivy Huang/Editor

Reviewer : 
Hong Yang/Supervisor

Approved & Authorized Signer : 
Sam Lv/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	ES150706041E2

Table of Contents

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 TEST PROCEDURE	7
2.4 CONFIGURATION OF TESTED SYSTEM	7
3. DESCRIPTION OF TEST MODES.....	8
4. SUMMARY OF TEST RESULTS.....	9
5. TEST FACILITY.....	10
6. CONDUCTED EMISSIONS TEST	11
6.1 MEASUREMENT PROCEDURE	11
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	11
6.3 MEASUREMENT EQUIPMENT USED	11
6.4 CONDUCTED EMISSION LIMIT	11
6.5 MEASUREMENT RESULT	11
7. RADIATED EMISSION TEST.....	14
7.1 MEASUREMENT PROCEDURE	14
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	15
7.3 MEASUREMENT EQUIPMENT USED	16
7.4 RADIATED EMISSION LIMIT	17
7.5 MEASUREMENT RESULT	18
8. 6DB BANDWIDTH TEST	27
8.1 MEASUREMENT PROCEDURE	27
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	27
8.3 MEASUREMENT EQUIPMENT USED	27
8.4 MEASUREMENT RESULTS	27
9. MAXIMUM PEAK OUTPUT POWER TEST	34
9.1 MEASUREMENT PROCEDURE	34
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	34
9.3 MEASUREMENT EQUIPMENT USED	34
9.4 PEAK POWER OUTPUT LIMIT	34
9.5 MEASUREMENT RESULTS	34
10. BAND EDGE TEST	35
10.1 MEASUREMENT PROCEDURE	35
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	36
10.3 MEASUREMENT EQUIPMENT USED	36
10.4 MEASUREMENT RESULTS	36
11. POWER DENSITY	46
11.1 TEST EQUIPMENT	46
11.2 MEASURING INSTRUMENTS AND SETTING.....	46
11.3 TEST PROCEDURES	46
11.4 BLOCK DIAGRAM OF TEST SETUP	46
11.5 LIMIT.....	46
11.6 TEST RESULT	47

12.	ANTENNA PORT EMISSION.....	53
12.1	TEST EQUIPMENT	53
12.2	MEASURING INSTRUMENTS AND SETTING.....	53
12.3	TEST PROCEDURES.....	53
12.4	BLOCK DIAGRAM OF TEST SETUP	53
12.5	TEST RESULT	53
13.	ANTENNA APPLICATION	59
13.1	ANTENNA REQUIREMENT	59
13.2	RESULT.....	59

APPENDIX I (PHOTOS OF EUT)(4 PAGES)

1. General Information

1.1 Product Description

Product Name	Snap Cam Wearable HD Video Camera, Snap Cam HD Sport Camera	
Model number	1045	
Power Supply	DC 5V, 1A	
Technical Description		
	Bluetooth 4.0	WiFi
Operation Frequency	2402-2480MHz	2412-2462MHZ
Modulation	GFSK	802.11b:DSSS(DBPSK/DQPSK/CCK) 802.11g/n: OFDM(BPSK/QPSK/16QAM/64QAM)
Number of Channel	40	11 for 20MHz bandwidth;
Channel space	2MHz	5MHz
Max RF Output Power	1.64dBm(0.001459W)	16.48dBm(0.04446W)
Antenna Type	Ceramic Antenna	Internal Antenna
Antenna Gain	2dBi	1.1dBi

Note: for more details, please refer to the User's manual of the EUT.

1.2 Support Equipment

Adapter : Model : YSV6-0501000 US
Input: AC 120V, 60Hz
Output: DC 5V, 1000mA

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. Emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	Snap Cam Wearable HD Video Camera	iON	1045	NW71045	EUT

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column, device(s) used in tested system is a support equipment.

3. Description of Test Modes

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20) : MCS0 were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(2)	6dB bandwidth	Pass
§15.247(b)(3)	Max Peak output Power test	Pass
§15.247(e)	Power density	Pass
§15.247(d)	Band edge test	Pass
§15.207	AC Power Conducted Emission	Pass
§15.247(d), §15.209	Radiated Emission	Pass
§15.247(d)	Antenna Port Emission	Pass
§15.247(b)&§15.203	Antenna Application	Pass

5. Test Facility

Site Description

EMC Lab.

: Accredited by CNAS, 2013.10.29
The certificate is valid until 2016.10.28
The Laboratory has been assessed and proved to be
in compliance with CNAS-CL01:2006 (identical to ISO/IEC
17025:2005)
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2010.5.25
The Laboratory has been assessed according to the
requirements ISO/IEC 17025.

Accredited by FCC, April 17, 2013
The Certificate Registration Number is 709623

Accredited by Industry Canada, November 15, 2010
The Certificate Registration Number is 46405-4480.

Name of Firm

Site Location


: SHENZHEN EMTEK CO., LTD.
: Bldg 69, Majialong Industry Zone,
Nanshan District, Shenzhen, Guangdong, China

6. Conducted Emissions Test

6.1 Measurement Procedure

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Last Cal.	Due date
Test Receiver	Rohde & Schwarz	ESCS30	100018	03/16/2015	03/15/2016
L.I.S.N	Rohde & Schwarz	ENV216	100017	03/16/2015	03/15/2016
RF Switching Unit	CDS	RSU-M2	38401	03/16/2015	03/15/2016
Coaxial Cable	CDS	79254	46107086	03/16/2015	03/15/2016

6.4 Conducted Emission Limit


Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.5 Measurement Result

Pass.

Please refer to the following pages.




Site site #1
 Limit: (CE)FCC PART 15 class B_QP
 Mode: WIFI(2412)
 Note:

Phase: **L1**
 Power: AC 120V/60Hz
 Temperature: 24
 Humidity: 55 %

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.4470	34.51	0.00	34.51	56.93	-22.42	QP	
2	0.4470	14.86	0.00	14.86	46.93	-32.07	AVG	
3	0.9510	33.62	0.00	33.62	56.00	-22.38	QP	
4	0.9510	11.79	0.00	11.79	46.00	-34.21	AVG	
5	1.4415	32.85	0.00	32.85	56.00	-23.15	QP	
6	1.4415	14.04	0.00	14.04	46.00	-31.96	AVG	
7	2.2800	32.45	0.00	32.45	56.00	-23.55	QP	
8	2.2800	15.28	0.00	15.28	46.00	-30.72	AVG	
9	21.6000	37.14	0.00	37.14	60.00	-22.86	QP	
10	21.6000	17.01	0.00	17.01	50.00	-32.99	AVG	
11 *	28.9000	38.54	0.00	38.54	60.00	-21.46	QP	
12	28.9000	18.25	0.00	18.25	50.00	-31.75	AVG	

*:Maximum data x:Over limit l:over margin Comment: Factor build in receiver.



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.4920	32.14	0.00	32.14	56.13	-23.99	QP	
2	0.4920	9.55	0.00	9.55	46.13	-36.58	AVG	
3	1.1085	32.45	0.00	32.45	56.00	-23.55	QP	
4	1.1085	8.57	0.00	8.57	46.00	-37.43	AVG	
5 *	1.3154	34.57	0.00	34.57	56.00	-21.43	QP	
6	1.3154	9.40	0.00	9.40	46.00	-36.60	AVG	
7	1.9545	33.15	0.00	33.15	56.00	-22.85	QP	
8	1.9545	11.42	0.00	11.42	46.00	-34.58	AVG	
9	20.8500	36.14	0.00	36.14	60.00	-23.86	QP	
10	20.8500	14.81	0.00	14.81	50.00	-35.19	AVG	
11	29.9000	37.54	0.00	37.54	60.00	-22.46	QP	
12	29.9000	15.03	0.00	15.03	50.00	-34.97	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver.

7. Radiated Emission Test

7.1 Measurement Procedure

1. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured was complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

7.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.03	03/16/2015	1 Year
2.	Bilog Antenna	Schwarzbeck	VULB9163	000141	03/16/2015	1 Year
3.	Power Amplifier	CDS	RSU-M352	818	03/16/2015	1 Year
4.	Power Amplifier	HP	8447F	OPT H64	03/16/2015	1 Year
5.	Color Monitor	SUNSPO	SP-140A	N/A	03/16/2015	1 Year
6.	Single Line Filter	JIANLI	XL-3	N/A	03/16/2015	1 Year
7.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	03/16/2015	1 Year
8.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	03/16/2015	1 Year
9.	DC Power Filter	JIANLI	DL-2X50B	N/A	03/16/2015	1 Year
10.	Cable	Schwarzbeck	PLF-100	549489	03/16/2015	1 Year
11.	Cable	Rosenberger	CIL02	A0783566	03/16/2015	1 Year
12.	Cable	Rosenberger	RG 233/U	525178	03/16/2015	1 Year
13.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	12/29/2014	1 Year
14.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	12/29/2014	1 Year
15.	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	12/29/2014	1 Year
16.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
17.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
18.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year

7.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Remark 1. Emission level in dBuV/m=20 log (uV/m)

- :
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.5 Measurement Result

Below 30MHz:

All the modulation modes were tested the data of the test mode are recorded in the following pages.

Operation Mode:	TX Mode	Test Date :	July 20, 2015
Frequency Range:	9KHz~30MHz	Temperature :	28℃
Test Result:	PASS	Humidity :	60 %
Measured Distance:	3m	Test By:	WOLF

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor.

Below 1000MHz:

All the modulation modes were tested the data of the worst mode (TX 802.11b) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following test plots:



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		32.9100	28.46	-14.46	14.00	40.00	-26.00	QP		
2	*	36.7900	31.20	-13.95	17.25	40.00	-22.75	QP		
3		42.6100	30.02	-13.49	16.53	40.00	-23.47	QP		
4		56.1900	32.64	-17.84	14.80	40.00	-25.20	QP		
5		110.5686	26.58	-17.53	9.05	43.50	-34.45	QP		
6		132.8200	27.71	-16.39	11.32	43.50	-32.18	QP		

*:Maximum data x:Over limit !:over margin

Operator: John




Site Chamber #1 Polarization: **Vertical** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2412
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		33.8800	41.25	-14.31	26.94	40.00	-13.06	QP		
2		36.7900	44.68	-13.95	30.73	40.00	-9.27	QP		
3		39.7146	45.90	-13.70	32.20	40.00	-7.80	QP		
4	*	43.5800	47.64	-13.37	34.27	40.00	-5.73	QP		
5		50.3700	38.05	-15.58	22.47	40.00	-17.53	QP		
6		86.2600	40.39	-21.59	18.80	40.00	-21.20	QP		

*:Maximum data x:Over limit !:over margin


Operator: John



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		30.9700	37.36	-14.90	22.46	40.00	-17.54	QP		
2		36.7900	44.64	-13.95	30.69	40.00	-9.31	QP		
3	*	43.5800	47.92	-13.37	34.55	40.00	-5.45	QP		
4		48.4300	39.41	-14.74	24.67	40.00	-15.33	QP		
5		53.2800	38.05	-16.70	21.35	40.00	-18.65	QP		
6		86.2600	40.50	-21.59	18.91	40.00	-21.09	QP		

*:Maximum data x:Over limit !:over margin


Operator: John



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		36.7900	43.90	-13.95	29.95	40.00	-10.05	QP		
2	*	41.6400	45.36	-13.58	31.78	40.00	-8.22	QP		
3		43.5800	44.67	-13.37	31.30	40.00	-8.70	QP		
4		48.4300	39.41	-14.74	24.67	40.00	-15.33	QP		
5		53.2800	38.62	-16.70	21.92	40.00	-18.08	QP		
6		86.2600	40.50	-21.59	18.91	40.00	-21.09	QP		

*:Maximum data x:Over limit !:over margin


Operator: John



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		32.9791	28.32	-14.45	13.87	40.00	-26.13	QP		
2		36.7900	30.09	-13.95	16.14	40.00	-23.86	QP		
3	*	40.6700	32.61	-13.64	18.97	40.00	-21.03	QP		
4		42.6100	31.43	-13.49	17.94	40.00	-22.06	QP		
5		56.1900	33.45	-17.84	15.61	40.00	-24.39	QP		
6		85.2980	32.73	-21.77	10.96	40.00	-29.04	QP		

*:Maximum data x:Over limit !:over margin

Operator: John



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		35.8200	44.94	-14.08	30.86	40.00	-9.14	QP		
2		39.7000	46.03	-13.71	32.32	40.00	-7.68	QP		
3	*	42.6100	48.50	-13.49	35.01	40.00	-4.99	QP		
4		45.5200	42.57	-13.76	28.81	40.00	-11.19	QP		
5		48.4300	41.30	-14.74	26.56	40.00	-13.44	QP		
6		52.7600	39.34	-16.49	22.85	40.00	-17.15	QP		

*:Maximum data x:Over limit !:over margin

Operator: John

Above 1GHz:

Operation Mode: 802.11b Lowest
Test Voltage: AC 120V/60Hz

Test Date : July 20, 2015
Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	64.35	45.25	74	54	-9.65	-8.75
7236	V	62.18	44.05	74	54	-11.82	-9.95
9648	V	61.72	43.62	74	54	-12.28	-10.38
12060	V	60.28	42.17	74	54	-13.72	-11.83
14472	V	59.72	41.07	74	54	-14.28	-12.93
16884	V	58.34	40.28	74	54	-15.66	-13.72
4824	H	65.35	44.36	74	54	-8.65	-9.64
7236	H	64.08	43.62	74	54	-9.92	-10.38
9648	H	63.89	42.18	74	54	-10.11	-11.82
12060	H	62.17	41.07	74	54	-11.83	-12.93
14472	H	60.28	40.75	74	54	-13.72	-13.25
16884	H	59.37	38.79	74	54	-14.63	-15.21

Operation Mode: 802.11b Middle
Test Voltage: AC 120V/60Hz

Test Date : July 20, 2015
Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	65.35	44.35	74	54	-8.65	-9.65
7236	V	62.42	43.62	74	54	-11.58	-10.38
9648	V	61.08	42.17	74	54	-12.92	-11.83
12060	V	60.87	41.08	74	54	-13.13	-12.92
14472	V	59.35	40.72	74	54	-14.65	-13.28
16884	V	58.47	38.49	74	54	-15.53	-15.51
4824	H	64.35	45.72	74	54	-9.65	-8.28
7236	H	63.28	44.62	74	54	-10.72	-9.38
9648	H	61.74	43.29	74	54	-12.26	-10.71
12060	H	60.28	42.07	74	54	-13.72	-11.93
14472	H	59.85	41.72	74	54	-14.15	-12.28
16884	H	58.49	38.49	74	54	-15.51	-15.51

Operation Mode: 802.11b Highest

Test Date : July 20, 2015

Test Voltage: AC 120V/60Hz

Test by: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824	V	66.35	44.35	74	54	-7.65	-9.65
7236	V	65.28	42.18	74	54	-8.72	-11.82
9648	V	64.17	41.72	74	54	-9.83	-12.28
12060	V	62.08	40.35	74	54	-11.92	-13.65
14472	V	61.72	39.58	74	54	-12.28	-14.42
16884	V	59.38	38.79	74	54	-14.62	-15.21
4824	H	63.2	45.72	74	54	-10.8	-8.28
7236	H	62.17	44.36	74	54	-11.83	-9.64
9648	H	61.08	43.62	74	54	-12.92	-10.38
12060	H	60.75	42.17	74	54	-13.25	-11.83
14472	H	59.38	41.08	74	54	-14.62	-12.92
16884	H	58.29	40.75	74	54	-15.71	-13.25

All emissions not reported were more than 20dB below the specified limit or in the noise floor.

No others harmonics emissions are higher than 20 dB below the limits of 47 CFR Part 15.247.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown “ – ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


8. 6dB Bandwidth Test

8.1 Measurement Procedure

The EUT was operating in IEEE 802.11b, 802.11g, 802.11n(HT20), 802.11n(HT40) mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequency) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	03/16/2015	03/15/2016

8.4 Measurement Results


6 Bandwidth Test Data Chart:



Refer to attached data chart.

Spectrum Detector: PK
 Test By: Andy
 Test Result: PASS


Test Date : July 20, 2015
 Temperature : 28°C
 Humidity : 60%



IEEE 802.11b			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	10073	>500	Pass
2437	10055	>500	
2462	10055	>500	








IEEE 802.11g			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	16346	>500	Pass
2437	16346	>500	
2462	16352	>500	





IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)	Result
2412	17592	>500	Pass
2437	17580	>500	
2462	17586	>500	





9. Maximum Peak Output Power Test

9.1 Measurement Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used

EQUIPMENT TYPE	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Power meter	ML2495A	0824006	03/16/2015	03/15/2016
Power sensor	MA2411B	0738172	03/16/2015	03/15/2016

9.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

9.5 Measurement Results

Spectrum Detector:	PK	Test Date :	July 20, 2015
Test By:	Andy	Temperature :	28°C
Test Result:	PASS	Humidity :	60%

Test Channel	Average Output Power (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	16.22	16.48	14.40	30	Pass
Middle	14.94	15.22	15.00		
Highest	14.79	15.11	14.85		

10. Band Edge Test

10.1 Measurement Procedure

For Conducted Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

For Radiated emission Test

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Repeat above procedures until all frequency measured were complete.


When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz.

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	AVG
Trace	Max hold

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used


EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	03/16/2015	03/15/2016

10.4 Measurement Results


1. Conducted Test

Please refer to the following pages.


Test mode: 802.11b



Lowest Channel




Middle Channel




Highest Channel


Test mode: 802.11g



Lowest Channel




Middle Channel




Highest Channel


Test mode: 802.11n(HT20)



Lowest Channel





Middle Channel





Highest Channel



Test mode: 802.11b



Test mode: 802.11g



Test mode: 802.11n(HT20)



2. Radiated emission Test

Spectrum Detector: PK/AV Test Date : July 20, 2015
Test By: Andy Temperature : 28 °C
Humidity : 65 %

IEEE 802.11b							
Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
	(H/V)	PK	AV	PK	AV	PK	AV
<2400	H	64.35	45.27	74	54	-9.65	-8.73
<2400	V	60.72	40.38	74	54	-13.28	-13.62
>2483.5	H	65.72	44.08	74	54	-8.28	-9.92
>2483.5	V	59.38	38.49	74	54	-14.62	-15.51

IEEE 802.11g							
Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
	(H/V)	PK	AV	PK	AV	PK	AV
<2400	H	63.05	46.35	74	54	-10.95	-7.65
<2400	V	59.72	42.08	74	54	-14.28	-11.92
>2483.5	H	64.38	45.07	74	54	-9.62	-8.93
>2483.5	V	58.29	38.72	74	54	-15.71	-15.28

IEEE 802.11n(HT20)							
Frequency (MHz)	Antenna polarization	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
	(H/V)	PK	AV	PK	AV	PK	AV
<2400	H	66.35	44.35	74	54	-7.65	-9.65
<2400	V	60.28	40.17	74	54	-13.72	-13.83
>2483.5	H	65.17	43.92	74	54	-8.83	-10.08
>2483.5	V	59.38	37.05	74	54	-14.62	-16.95

11. Power Density

11.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	03/16/2015	03/15/2016

11.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3kHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

11.3 Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyzer.
- Set analyzer center frequency to DTS channel center frequency.
- Set the analyzer span to a minimum of 1.5 times the DTS bandwidth.
- Set the RBW ≥ 3 kHz. Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

11.4 Block Diagram of Test Setup




11.5 Limit



The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3 kHz bandwidth.

11.6 Test Result


Spectrum Detector:	PK	Test Date :	July 20, 2015
Test By:	Andy	Temperature :	28°C
Test Result:	PASS	Humidity :	60%



IEEE 802.11b			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-6.63	8	Pass
2437	-6.97		
2462	-6.89		








IEEE 802.11g			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-13.71	8	Pass
2437	-14.76		
2462	-14.63		





IEEE 802.11n(HT20)			
Channel frequency (MHz)	Measurement level (dBm)	Limit(dBm)	Result
2412	-14.80	8	Pass
2437	-13.45		
2462	-13.97		





12. Antenna Port Emission

12.1 Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Agilent	FSV30	1321.3008K	03/16/2015	03/15/2016

12.2 Measuring Instruments and Setting


The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
RB	100kHz
VB	300kHz
Detector	Peak
Trace	Max hold

12.3 Test Procedures

The conducted spurious emissions were measured conducted using a spectrum analyzer at low, Middle, and high channels, the limit was determined by attenuation 20dB of the RF peak power output.

12.4 Block Diagram of Test setup




12.5 Test Result


PASS.

Please refer to following pages.


Test Mode: 802.11b



Lowest Channel




Middel Channel




Highest Channel


Test Mode: 802.11g



Lowest Channel




Middle Channel




Highest Channel


Test Mode: 802.11n(HT20)



Lowest Channel



Middle Channel



Highest Channel

13. Antenna Application


13.1 Antenna Requirement


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2 Result



The EUT'S antenna is an internal antenna. The antenna's gain is 1.1 dBi and meets the requirement.

APPENDIX I (PHOTOS OF EUT)






WiFi Antenna







BT Antenna