NEUTRON EMC L	LA	B
---------------	----	---

FCC ID:NW7M5P

## Attachment

User's Manual

## **WARNING**

Note: This equipment has been tested and found to comply with the limits for a Class B device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- · Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver in connected.
- Consult the dealer or an experienced radio / TV technician for technician for help.

## <u>Notice:</u>

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

## TREMON ENTERPRISES CO., LTD.

Model No.: MUOSP

Description: 2 keys 420 DPI Printed Mouse, PS/2 Mouse.

Cable: 5 feet in length with Mini-DIN 6 pin connector.

Oscillation Frequency: External resistor 30 K Ohm +/- 5% pull low for 35 Khz

oscillation.

Power Consumption: Maximum 75 mW, 15 mA at 5V DC.

Installation Procedures: 1.) Power-off PC.

2.) Connect PS/2 mouse to PC<sup>+</sup>s PS/2 mouse port.

3.) Power-on PC.

4.) Install standard PS/2 driver from system or diskette.

5.) Reboot PC to make driver effect.

Hardware Resolution up to 420 DPI.

Optical / Mechanical Interrupt Wheel design for smooth tracking pickups.

Non-Toxic substrate and fancy picture printed.