

Test Data

TDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.04 MHz
CHANNEL: 0991 (Low)
MEASURED OUTPUT POWER: 28.712 dBm = 0.743 W
MODULATION SIGNAL: TDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10}(W) =$ 41.71 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 1648.08 | -84.51 | V | 70.0 |
| 2472.12 | -96.57 | V | 77.1 |
| 3296.16 | -100.23 | V | 77.8 |
| 4120.20 | -105.71 | V | 79.0 |
| 4944.24 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

TDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.49 MHz
 CHANNEL: 0383 (Mid)
 MEASURED OUTPUT POWER: 28.712 dBm = 0.745 W
 MODULATION SIGNAL: TDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 41.72 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 1672.98 | -84.22 | V | 69.2 |
| 2509.47 | -95.92 | V | 76.8 |
| 3345.96 | -99.75 | V | 76.9 |
| 4182.45 | -103.68 | V | 77.2 |
| 5018.94 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

TDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.97 MHz
 CHANNEL: 0799 (High)
 MEASURED OUTPUT POWER: 28.712 dBm = 0.743 W
 MODULATION SIGNAL: TDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 41.71 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 1697.94 | -89.54 | V | 71.0 |
| 2546.91 | -99.08 | V | 76.5 |
| 3395.88 | -103.47 | V | 77.0 |
| 4244.85 | -105.42 | V | 79.1 |
| 5093.82 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.04 MHz
 CHANNEL: 0991 (Low)
 MEASURED OUTPUT POWER: 24.348 dBm = 0.273 W
 MODULATION SIGNAL: ST (Signalling Tone)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.36 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 1648.08 | -89.43 | V | 70.1 |
| 2472.12 | -99.81 | V | 76.0 |
| 3296.16 | -105.10 | V | 78.1 |
| 4120.20 | -106.64 | V | 76.0 |
| 4944.24 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.49 MHz
 CHANNEL: 0383 (Mid)
 MEASURED OUTPUT POWER: 24.348 dBm = 0.273 W
 MODULATION SIGNAL: ST (Signalling Tone)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.36 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 1672.98 | -88.23 | V | 69.0 |
| 2509.47 | -99.73 | V | 76.1 |
| 3345.96 | -105.84 | V | 78.9 |
| 4182.45 | -107.34 | V | 76.2 |
| 5018.94 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

AMPS Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.97 MHz
 CHANNEL: 0799 (High)
 MEASURED OUTPUT POWER: 24.348 dBm = 0.273 W
 MODULATION SIGNAL: ST (Signalling Tone)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 37.36 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 1697.94 | -89.23 | V | 70.3 |
| 2546.91 | -100.23 | V | 76.0 |
| 3395.88 | -106.04 | V | 78.1 |
| 4244.85 | -108.63 | V | 79.0 |
| 5093.82 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

PCS TDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1850.01 MHz
 CHANNEL: 0002 (Low)
 MEASURED OUTPUT POWER: 28.225 dBm = 0.665 W
 MODULATION SIGNAL: TDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 41.23 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 3700.02 | -99.37 | V | 71.9 |
| 5550.03 | -114.44 | V | 82.0 |
| 7400.04 | -117.20 | V | 81.8 |
| 9250.05 | < -130 | | |
| 11100.06 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

PCS TDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
 CHANNEL: 1000 (Mid)
 MEASURED OUTPUT POWER: 28.225 dBm = 0.665 W
 MODULATION SIGNAL: TDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 41.23 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 3760.00 | -99.00 | V | 71.3 |
| 5640.00 | -116.29 | V | 83.2 |
| 7520.00 | -117.15 | V | 80.2 |
| 9400.00 | < -130 | | |
| 11280.00 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

Test Data

PCS TDMA Radiated Measurements

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1909.56 MHz
 CHANNEL: 1998 (High)
 MEASURED OUTPUT POWER: 28.225 dBm = 0.665 W
 MODULATION SIGNAL: TDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10}(W) =$ 41.23 dBc

| FREQ. (MHz) | LEVEL (dBm) | POL (H/V) | (dBc) |
|----------------|----------------|--------------|-------|
| 3819.12 | -99.00 | V | 71.3 |
| 5728.68 | -116.29 | V | 83.2 |
| 7638.24 | -117.15 | V | 80.2 |
| 9547.80 | < -130 | | |
| 11457.36 | < -130 | | |
| | | | |

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603 (rev.1998):

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This spurious level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.