



849 NW STATE ROAD 45
NEWBERRY, FL 32669 USA
PH: 888.472.2424 OR
352.472.5500
FAX: 352.472.2030
EMAIL: INFO@TIMCOENGR.COM
[HTTP:// WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

RF Exposure Evaluation Report

APPLICANT	BARON SERVICES INC.
	4930 Research Dr. Huntsville, Alabama 35805
FCC ID	NX5-GEN3-350CM
MODEL NUMBER	GEN3-350CM
PRODUCT DESCRIPTION	S BAND RADAR
STANDARD APPLIED	CFR 47 Part 2.1091
PREPARED BY	Tim Royer

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

GENERAL REMARKS

Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, FL 32669

Authorized Signatory Name:



Sr. EMC Engineer
EMC-003838-NE



Tested by:

Name and Title: Tim Royer, Project Manager/Testing Engineer

Date: 02/ 26/ 2018

Applicant: BARON SERVICES INC.
FCC ID: NX5-GEN3-350CM
Report: 1676AUT17RF EXP MPE RPT.DOCX

RF Exposure Requirements

General information

Device type: S BAND RADAR

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d (mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.1310, Table 1.

Minimum Separation Distance for Mobile or Fixed Devices			
General Population/Uncontrolled Exposure			

Insert values in yellow highlighted boxes to determine Minimum Separation Distance

Max Power	350000	W	<i>equals</i>	Max Power	350000000	mW
Duty Cycle	0.07	%	<i>equals</i>	Duty Factor	0.0007	numeric
Antenna Gain	0	dBi	<i>equals</i>	Gain numeric	1	numeric
Coax Loss	0	dB		Gain - Coax Loss	1	numeric
Power Density	1	mW/cm ²				

Enter power Density from the chart to the right

Rule Part 1.1310, Table 1 (B)

Frequency	5800	MHz		Frequency range	Power density	Enter this value
				MHz	mW/cm²	mW/cm²
				0.3-1.34	100	100
				1.34-30	180/f ²	0.0
				30-300	0.2	0.2
				300-1,500	f/1500	3.9
				1,500-100,000	1	1

f = frequency in MHz

Minimum Separation Distance	140 cm	1.40 m
------------------------------------	---------------	---------------

Minimum Separation in Inches	54.93036 Inches
------------------------------	-----------------