



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

<b>APPLICANT</b>	BARON SERVICES INC.
	4930 Research Dr. Huntsville, Alabama 35805
<b>FCC ID</b>	NX5-GEN3-350CM
<b>MODEL NUMBER</b>	GEN3-350CM
<b>PRODUCT DESCRIPTION</b>	S BAND RADAR
<b>STANDARD APPLIED</b>	CFR 47 Part 2.1091
<b>PREPARED BY</b>	Tim Royer

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

## GENERAL REMARKS

### Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**

**Authorized Signatory Name:**



Sr. EMC Engineer  
EMC-003838-NE



**Tested by:**

Name and Title: Tim Royer, Project Manager/Testing Engineer

**Date: 02/26/2018**

Applicant: BARON SERVICES INC.  
FCC ID: NX5-GEN3-350CM  
Report: 1676AUT17RF EXP MPE RPT.DOCX

## RF Exposure Requirements

### General information

Device type: S BAND RADAR

### MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.1310, Table 1.

<b>Minimum Separation Distance for Mobile or Fixed Devices General Population/Uncontrolled Exposure</b>			
---	--	--	--

**Insert values in yellow highlighted boxes to determine Minimum Separation Distance**

Max Power	350000	W	<i>equals</i>	Max Power	350000000	mW
Duty Cycle	0.07	%	<i>equals</i>	Duty Factor	0.0007	numeric
Antenna Gain	45	dBi	<i>equals</i>	Gain numeric	31622.7766	numeric
Coax Loss	2.5	dB		Gain - Coax Lo	17782.7941	numeric
Power Density	1	mW/cm <sup>2</sup>				

**Enter power Density from the chart to the right**

**Rule Part 1.1310, Table 1 (B)**

Frequency	5800	MHz		<b>Frequency range</b>	<b>Power density</b>	<b>Enter this value</b>
				MHz	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>
				0.3-1.34	100	<b>100</b>
				1.34-30	180/f <sup>2</sup>	<b>0.0</b>
				30-300	0.2	<b>0.2</b>
				300-1,500	f/1500	<b>3.9</b>
				1,500-100,000	1	<b>1</b>

f = frequency in MHz

<b>Minimum Separation Distance</b>	<b>18620 cm</b>	<b>186.20 m</b>
------------------------------------	-----------------	-----------------

Minimum Separation in Inches	7325.082	Inches
------------------------------	----------	--------