

FCC Test Report

Applicant : MYLAPS BV

Address : Zuiderhoutlaan 4, Haarlem, 2012PJ,
Netherlands

Product Name : RFID module

Report Date : Jul. 21, 2023



Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	6
1.1. Client Information	6
1.2. Description of Device (EUT)	6
1.3. Auxiliary Equipment Used During Test	7
1.4. Description of Test Modes	7
1.5. Description Of Test Setup	8
1.6. Test Equipment List	9
1.7. Measurement Uncertainty	10
1.8. Description of Test Facility	10
2. Summary of Test Results	11
3. Conducted Emission Test	12
3.1. Test Standard and Limit	12
3.2. Test Setup	12
3.3. Test Procedure	12
3.4. Test Data	12
4. Radiation Spurious Emission and Band Edge	15
4.1. Test Standard and Limit	15
4.2. Test Setup	15
4.3. Test Procedure	16
4.4. Test Data	17
5. Maximum Peak Output Power Test	23
5.1. Test Standard and Limit	23
5.2. Test Setup	23
5.3. Test Procedure	23
5.4. Test Data	23
6. 20dB Occupy Bandwidth Test	25
6.1. Test Standard	25
6.2. Test Setup	25
6.3. Test Procedure	25
6.4. Test Data	25
7. Carrier Frequency Separation Test	27
7.1. Test Standard and Limit	27
7.2. Test Setup	27
7.3. Test Procedure	27
7.4. 7.4. Test Data	27
8. Number of Hopping Channel Test	29
8.1. Test Standard and Limit	29



8.2. Test Setup	29
8.3. Test Procedure	29
8.4. Test Data	29
9. Dwell Time Test	31
9.1. Test Standard and Limit	31
9.2. Test Setup	31
9.3. Test Procedure	31
9.4. Test Data	31
10. 100kHz Bandwidth of Frequency Band Edge Requirement	33
10.1. Test Standard and Limit	33
10.2. Test Setup	33
10.3. Test Procedure	33
10.4. Test Data	33
11. Antenna Requirement	36
11.1. Test Standard and Requirement	36
11.2. Antenna Connected Construction	36
APPENDIX I -- TEST SETUP PHOTOGRAPH	37
APPENDIX II -- EXTERNAL PHOTOGRAPH	37
APPENDIX III -- INTERNAL PHOTOGRAPH	37



TEST REPORT

Applicant : MYLAPS BV
Manufacturer : MYLAPS BV
Product Name : RFID module
Model No. : SIM7300
Trade Mark : N/A
Rating(s) : Input: DC 5V/3A

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2020

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of receipt

Jun. 13, 2023

Date of Test

Jun. 13 ~ Jul. 07, 2023

Prepared by

Nian xiu Chen

(Nianxiu Chen)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jul. 21, 2023



1. General Information

1.1. Client Information

Applicant	:	MYLAPS BV
Address	:	Zuiderhoutlaan 4, Haarlem, 2012PJ, Netherlands
Manufacturer	:	MYLAPS BV
Address	:	Zuiderhoutlaan 4, Haarlem, 2012PJ, Netherlands
Factory	:	MYLAPS BV
Address	:	Zuiderhoutlaan 4, Haarlem, 2012PJ, Netherlands

1.2. Description of Device (EUT)

Product Name	:	RFID module
Model No.	:	SIM7300
Trade Mark	:	N/A
Test Power Supply	:	DC 5V from Debug board input AC 120V, 60Hz for Adapter
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A
RF Specification		
Support Technology	:	<input checked="" type="checkbox"/> LoRa
Operation Mode	:	<input type="checkbox"/> DSSS <input checked="" type="checkbox"/> FHSS
Support Bandwidth	:	<input checked="" type="checkbox"/> 125KHz <input type="checkbox"/> 250KHz <input type="checkbox"/> 500KHz
Operation Frequency	:	902.75~927.25MHz
Number of Channel	:	50 Channels
Modulation Type	:	ASK
Antenna Type	:	Polarized antenna
Antenna Gain(Peak)	:	4.99 dBi(Provided by customer)
<p>Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.</p> <p>2) EUT is continuously transmitting through the antenna port connector and is attached to the spectrum analyzer through appropriate cables and attenuation. Per manufacturer the AC voltage is varied to the PoE injector.</p>		



1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
acer	Model: N19W3 Input: 19V/3.42A;20V/3.25A CMIIT ID:2020AJ3862
Adapter	Model: PA-1650-58 Input: AC100-240~50/60Hz, 1.6A CMIIT KP06503020

1.4. Description of Test Modes



Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
01	902.75	02	903.25	03	903.75	04	904.25	05	904.75
06	905.25	07	905.75	08	906.25	09	906.75	10	907.25
11	907.75	12	908.25	13	908.75	14	909.25	15	909.75
16	910.25	17	910.75	18	911.25	19	911.75	20	912.25
21	912.75	22	913.25	23	913.75	24	914.25	25	914.75
26	915.25	27	915.75	28	916.25	29	916.75	30	917.25
31	917.75	32	918.25	33	918.75	34	919.25	35	919.75
36	920.25	37	920.75	38	921.25	39	921.75	40	922.25
41	922.75	42	923.25	443	923.75	44	924.25	45	924.75
46	925.25	47	925.75	48	926.25	49	926.75	50	927.25

Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with Channel 1, 25 and 50.



1.5. Description Of Test Setup



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G-45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-KF	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	Oct. 19, 2022	1 Year
19.	Power Meter	Agilent	N1914A	MY50001102	Oct.26, 2022	1 Year



1.7. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
	:	Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(2)	Conducted Peak Output Power	PASS
15.247(a)(1)(i)	20dB Occupied Bandwidth	PASS
15.247(a)(1)	Carrier Frequencies Separation	PASS
15.247(a)(1)(i)	Hopping Channel Number	PASS
15.247(a)(1)(i), 15.247(f)	Dwell Time	PASS
15.247(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		



3. Conducted Emission Test


3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: 914.75MHz
 Test Specification: DC 5V from Debug board input AC 120V, 60Hz for Adapter
 Comment: Live Line
 Temp.(°C)/Hum.(%RH): 24.2°C/63%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.2940	27.68	19.83	47.51	60.41	-12.90	QP	
2	0.2940	23.29	19.83	43.12	50.41	-7.29	AVG	
3	0.4740	12.53	19.84	32.37	46.44	-14.07	AVG	
4	0.6260	22.42	19.86	42.28	56.00	-13.72	QP	
5	0.6260	14.08	19.86	33.94	46.00	-12.06	AVG	
6	0.9580	13.75	19.85	33.60	46.00	-12.40	AVG	
7	1.0540	23.62	19.85	43.47	56.00	-12.53	QP	
8	1.5500	22.41	19.84	42.25	56.00	-13.75	QP	
9	1.5500	14.06	19.84	33.90	46.00	-12.10	AVG	
10	1.8860	11.27	19.83	31.10	46.00	-14.90	AVG	
11	1.9700	20.17	19.83	40.00	56.00	-16.00	QP	
12	2.4700	18.36	19.83	38.19	56.00	-17.81	QP	



Conducted Emission Test Data

Test Site: 1# Shielded Room
 Operating Condition: 914.75MHz
 Test Specification: DC 5V from Debug board input AC 120V, 60Hz for Adapter
 Comment: Neutral Line
 Temp.(°C)/Hum.(%RH): 24.2°C/63%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.3020	27.12	19.83	46.95	60.19	-13.24	QP	
2	0.3339	16.41	19.82	36.23	49.35	-13.12	AVG	
3	1.2540	14.92	19.84	34.76	46.00	-11.24	AVG	
4	1.2940	24.17	19.84	44.01	56.00	-11.99	QP	
5	1.5859	13.77	19.84	33.61	46.00	-12.39	AVG	
6	1.6580	21.45	19.84	41.29	56.00	-14.71	QP	
7	2.4300	10.36	19.83	30.19	46.00	-15.81	AVG	
8	3.0100	18.64	19.84	38.48	56.00	-17.52	QP	
9	9.9100	17.26	19.98	37.24	60.00	-22.76	QP	
10	13.8740	15.45	20.14	35.59	50.00	-14.41	AVG	
11	15.8580	20.37	20.21	40.58	60.00	-19.42	QP	
12	15.8580	15.65	20.21	35.86	50.00	-14.14	AVG	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all modes, only the worst case is recorded in the report.



Test Results (30~1000MHz)

Test Mode: 914.75MHz
 Power Source: DC 5V from Debug board input AC 120V, 60Hz for Adapter
 Polarization: Horizontal
 Temp.(°C)/Hum.(%RH): 22.9°C/40%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	129.0146	38.11	-22.64	15.47	43.50	-28.03	QP			
2	202.1005	35.00	-22.29	12.71	43.50	-30.79	QP			
3	368.1116	30.88	-16.04	14.84	46.00	-31.16	QP			
4	612.0642	30.69	-10.55	20.14	46.00	-25.86	QP			
5	962.1623	43.10	-5.44	37.66	54.00	-16.34	QP			
6	993.0114	48.59	-4.90	43.69	54.00	-10.31	QP			



Test Results (30~1000MHz)

Test Mode: 914.75MHz
 Power Source: DC 5V from Debug board input AC 120V, 60Hz for Adapter
 Polarization: Vertical
 Temp.(°C)/Hum.(%RH): 22.9°C/40%RH



No.	Freq. (MHz)	Reading (dBUV)	Factor (dB/m)	Result (dBUV/m)	Limit (dBUV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	45.8553	29.26	-15.17	14.09	40.00	-25.91	QP			
2	62.4314	30.08	-18.38	11.70	40.00	-28.30	QP			
3	90.8554	27.35	-17.51	9.84	43.50	-33.66	QP			
4	129.0146	36.28	-21.32	14.96	43.50	-28.54	QP			
5	962.1623	41.68	-5.44	36.24	54.00	-17.76	QP			
6	1000.0000	29.72	15.23	44.95	54.00	-9.05	QP			



Test Results (1GHz-25GHz)

Test channel: Lowest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1805.50	28.77	15.27	44.04	74.00	-29.96	Vertical
2708.25	29.94	18.09	48.03	74.00	-25.97	Vertical
3611.00	31.08	23.76	54.84	74.00	-19.17	Vertical
4513.75	*			74.00		Vertical
5416.50	*			74.00		Vertical
1805.50	29.15	15.27	44.42	74.00	-29.58	Horizontal
2708.25	29.82	18.09	47.91	74.00	-26.09	Horizontal
3611.00	29.13	23.76	52.89	74.00	-21.11	Horizontal
4513.75	*			74.00		Horizontal
5416.50	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1805.50	18.15	15.27	33.42	54.00	-20.58	Vertical
2708.25	18.97	18.09	37.06	54.00	-16.94	Vertical
3611.00	20.10	23.76	43.86	54.00	-10.15	Vertical
4513.75	*			54.00		Vertical
5416.50	*			54.00		Vertical
1805.50	17.50	15.27	32.77	54.00	-21.23	Horizontal
2708.25	18.88	18.09	36.97	54.00	-17.03	Horizontal
3611.00	18.44	23.76	42.20	54.00	-11.80	Horizontal
4513.75	*			54.00		Horizontal
5416.50	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test channel: Middle						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1829.50	28.79	15.42	44.21	74.00	-29.79	Vertical
2744.25	29.79	18.02	47.81	74.00	-26.19	Vertical
3659.00	30.09	23.80	53.89	74.00	-20.12	Vertical
4573.75	*			74.00		Vertical
5488.50	*			74.00		Vertical
1829.50	28.85	15.42	44.27	74.00	-29.73	Horizontal
2744.25	29.81	18.02	47.83	74.00	-26.17	Horizontal
3659.00	28.83	23.80	52.63	74.00	-21.37	Horizontal
4573.75	*			74.00		Horizontal
5488.50	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1829.50	17.88	15.42	33.30	54.00	-20.70	polarization
2744.25	19.07	18.02	37.09	54.00	-16.91	Vertical
3659.00	19.96	23.80	43.76	54.00	-10.25	Vertical
4573.75	*			54.00		Vertical
5488.50	*			54.00		Vertical
1829.50	17.41	15.42	32.83	54.00	-21.17	Vertical
2744.25	18.44	18.02	36.46	54.00	-17.54	Horizontal
3659.00	18.95	23.80	42.75	54.00	-11.25	Horizontal
4573.75	*			54.00		Horizontal
5488.50	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test channel: Highest						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1854.50	29.06	15.58	44.64	74.00	-29.36	Vertical
2781.75	29.80	17.93	47.73	74.00	-26.27	Vertical
3709.00	30.64	23.83	54.47	74.00	-19.54	Vertical
4636.25	*			74.00		Vertical
5563.50	*			74.00		Vertical
1854.50	28.92	15.58	44.50	74.00	-29.50	Horizontal
2781.75	29.84	17.93	47.77	74.00	-26.23	Horizontal
3709.00	29.51	23.83	53.34	74.00	-20.66	Horizontal
4636.25	*			74.00		Horizontal
5563.50	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
1854.50	19.00	15.58	34.58	54.00	-19.42	Vertical
2781.75	20.08	17.93	38.01	54.00	-15.99	Vertical
3709.00	20.51	23.83	44.34	54.00	-9.67	Vertical
4636.25	*			54.00		Vertical
5563.50	*			54.00		Vertical
1854.50	18.85	15.58	34.43	54.00	-19.57	Horizontal
2781.75	19.81	17.93	37.74	54.00	-16.26	Horizontal
3709.00	18.85	23.83	42.68	54.00	-11.32	Horizontal
4636.25	*			54.00		Horizontal
5563.50	*			54.00		Horizontal

Remark:

- 1.Result =Reading + Factor
2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.




5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(2)
Test Limit	For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

5.2. Test Setup



5.3. Test Procedure


- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above,
- Spectrum Setting:
 - RBW > the 20 dB bandwidth of the emission being measured
 - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 - VBW ≥ RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold

5.4. Test Data


Test Item	:	Max. peak output power	Test Mode	:	CH Low ~ CH High
Test Voltage	:	DC 5V from Debug board input AC 120V, 60Hz for Adapter	Temperature	:	23.6° C
Test Result	:	PASS	Humidity	:	49 %

Test Channel	Peak Power output (dBm)	Limit (dBm)	Results
Low	29.711	30.00	PASS
Middle	29.895	30.00	PASS
High	29.230	30.00	PASS






Low Channel



Mid Channel



High Channel




6. 20dB Occupy Bandwidth Test

6.1. Test Standard

Test Standard	FCC Part15 C Section 15.247 (a)(1)(i)
Limit	Less than 250KHz

6.2. Test Setup



6.3. Test Procedure

Using the following spectrum analyzer settings:


1. Span= approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel.
2. Set the RBW $\geq 1\%$ of the 20 dB bandwidth.
3. Set the VBW \geq RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

6.4. Test Data


Test Item	: 20dB BW	Test Mode	: CH Low ~ CH High
Test Voltage	: DC 5V from Debug board input AC 120V, 60Hz for Adapter	Temperature	: 23.6°C
Test Result	: PASS	Humidity	: 53 %

Test Channel	Bandwidth (kHz)	Limit (kHz)	Results
Low	58.87	≤ 250	PASS
Middle	58.87	≤ 250	PASS
High	58.09	≤ 250	PASS






Low Channel



Mid Channel



High Channel




7. Carrier Frequency Separation Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(1)
Test Limit	> 25 kHz or the 20 dB bandwidth whichever is greater.

7.2. Test Setup



7.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer settings:


1. Span= Wide enough to capture the peaks of two adjacent channels
2. Set the RBW =approximately 30% of the channel spacing.
3. Set the VBW \geq RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

7.4. 7.4. Test Data

Test Item	:	Frequency Separation	Test Mode	:	Hopping
Test Voltage	:	DC 5V from Debug board input AC 120V, 60Hz for Adapter	Temperature	:	23.6° C
Test Result	:	PASS	Humidity	:	49 %

Mode	Frequency (MHz)	Separation Read Value (kHz)	Limit (kHz)	Result
Hopping	914.75	500	58.87	PASS





Hopping




8. Number of Hopping Channel Test

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247(a)(1)(i)
Test Limit	≥ 50 channels for 20 dB bandwidth less than 250KHz ≥ 25 channels for 20 dB bandwidth greater than 250KHz

8.2. Test Setup



8.3. Test Procedure

The EUT must have its hopping function enabled. Using the following spectrum analyzer setting:


1. Span= the frequency band of operation
2. Set the RBW = less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
3. Set the VBW \geq RBW.
4. Sweep time = auto couple.
5. Detector function = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.

8.4. Test Data

Test Item	:	Number of Hopping Frequency	Test Mode	:	Hopping
Test Voltage	:	DC 5V from Debug board input AC 120V, 60Hz for Adapter	Temperature	:	23.6° C
Test Result	:	PASS	Humidity	:	49 %

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
902-928MHz	50	≥ 50





Hopping




9. Dwell Time Test

9.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247(a)(1)(i), 15.247(f)
Test Limit	<p>15.247(a)(1)(i): if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.</p> <p>15.247(f): For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned-off, shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4</p>

9.2. Test Setup



9.3. Test Procedure


The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span= zero span, centered on a hopping channel
2. Set the RBW = 100 KHz.
3. Set the VBW = 300 KHz.
4. Sweep time = as necessary to capture the entire dwell time per hopping channel.
5. Detector function = peak.
6. Trace mode = clear write.

9.4. Test Data

Test Item	:	Time of Occupancy	Test Mode	:	Hopping
Test Voltage	:	DC 5V from Debug board input AC 120V, 60Hz for Adapter	Temperature	:	23.6° C
Test Result	:	PASS	Humidity	:	49 %





Hopping




10. 100kHz Bandwidth of Frequency Band Edge Requirement

10.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

10.2. Test Setup



10.3. Test Procedure

The EUT must have its hopping/Non-hopping function enabled. Using the following spectrum analyzer setting:


1. Set the RBW = 100kHz.
2. Set the VBW = 300kHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

10.4. Test Data


Test Item	:	Band edge	Test Mode	:	CH Low, CH High
Test Voltage	:	DC 5V from Debug board input AC 120V, 60Hz for Adapter	Temperature	:	23.6° C
Test Result	:	PASS	Humidity	:	49 %




Band edge measurements




For Low channel Non-Hopping Mode



For High channel Non-Hopping Mode




For Low channel Hopping Mode




For High channel Hopping Mode




Conducted Emission Method



Low Channel



Mid Channel



High Channel



11. Antenna Requirement

11.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	<p>1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.</p>

11.2. Antenna Connected Construction

The antenna is Polarized antenna which permanently attached, and the best case gain of the antenna is 4.99dBi. It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

