

# TEST REPORT



**CTK Co., Ltd.**  
(Ho-dong), 113, Yejik-ro, Cheoin-gu,  
Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

Report No.:  
CTK-2019-02112  
Page (1) / (10) Pages

## 1. Client

- Name : SEOYON ELECTRONICS CO., LTD.
- Address : 100, Saneop-ro, 156beon-gil, Gwonseon-gu, Suwon-si, Gyeonggi-do, South Korea
- Date of Receipt : 2019-05-22

## 2. Manufacturer

- Name : SEOYON ELECTRONICS CO., LTD.
- Address : 100, Saneop-ro, 156beon-gil, Gwonseon-gu, Suwon-si, Gyeonggi-do, South Korea

**3. Use of Report :** For FCC Certification

**4. Test Sample / Model :** Wireless Charging System / SYECWPC1906



**5. Date of Test :** 2019-05-29

**6. Test Standard(method) used :** FCC 47 CFR part 2 subpart J 2.1091

**7. Testing Environment:** Temp.: (23 ± 1) °C, Humidity: (48 ± 5) % R.H

**8. Test Results :** Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Gwanyong Kim:  (Signature)	Technical Manager Young-taek Lee:  (Signature)
-------------	---------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------

2019-06-12

Republic of KOREA **CTK Co., Ltd.**



**CTK Co., Ltd.**  
(Ho-dong), 113, Yejik-ro, Cheoin-gu,  
Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

Report No.:  
CTK-2019-02112  
Page (2) / (10) Pages

## REPORT REVISION HISTORY

Date	Revision	Page No
2019-06-12	Issued (CTK-2019-02112)	all

***This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.***



**CTK Co., Ltd.**  
(Ho-dong), 113, Yejik-ro, Cheoin-gu,  
Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

Report No.:  
CTK-2019-02112  
Page (3) / (10) Pages

## **CONTENTS**

1. General Product Description .....	4
1.1 Client Information .....	4
1.2 Product Information.....	4
2. Facility and Accreditations.....	5
2.1 Test Facility.....	5
2.2 Laboratory Accreditations and Listings .....	5
2.3 Calibration Details of Equipment Used for Measurement .....	5
3. RF Exposure Assessment .....	6
3.1 Maximum Permissible Exposure.....	6
APPENDIX A – Test Equipment Used For Tests .....	9
APPENDIX B – Test Photos .....	10



**CTK Co., Ltd.**  
(Ho-dong), 113, Yejik-ro, Cheoin-gu,  
Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

Report No.:  
CTK-2019-02112  
Page (4) / (10) Pages

## 1. General Product Description

### 1.1 Client Information

<b>Company</b>	SEYON ELECTRONICS CO., LTD.
<b>Contact Point</b>	100, Saneop-ro, 156beon-gil, Gwonseon-gu, Suwon-si, Gyeonggi-do, South Korea
<b>Contact Person</b>	Name : Hee tack Ryu E-mail : shadow@seoyonelec.com Tel : +82-31-420-3481

### 1.2 Product Information

<b>FCC ID</b>	NYOSYECWPC1906
<b>Product Description</b>	Wireless Charging System
<b>Model name</b>	SYECWPC1906
<b>Variant Model name</b>	-
<b>Operating Frequency Range</b>	112 kHz - 148 kHz
<b>Charging Frequency</b>	115 kHz
<b>RF Output Power</b>	89.3 dBuV/m @ 3 m
<b>Power Transfer Method</b>	Magnetic induction and only single primary coil coupling secondary coil
<b>Output power from each primary coil</b>	<15W
<b>That may have multiple primary coils</b>	No
<b>Antenna Type</b>	Coil
<b>Charging Method</b>	Directly contact
<b>Power Source</b>	DC 12 V



**CTK Co., Ltd.**  
(Ho-dong), 113, Yejik-ro, Cheoin-gu,  
Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501

Report No.:  
CTK-2019-02112  
Page (5) / (10) Pages

## 2. Facility and Accreditations

### 2.1 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea.

### 2.2 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	8737A-2
KOREA	NRRA	KR0025

### 2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.



**CTK Co., Ltd.**  
 (Ho-dong), 113, Yejik-ro, Cheoin-gu,  
 Yongin-si, Gyeonggi-do, Korea  
 Tel: +82-31-339-9970  
 Fax: +82-31-624-9501

Report No.:  
 CTK-2019-02112  
 Page (6) / (10) Pages

### 3. RF Exposure Assessment

#### 3.1 Maximum Permissible Exposure

##### Limit

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	-	-	f/300	6
1,500-100,000	-	-	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	-	-	f/1500	30
1,500-100,000	-	-	1.0	30

Note 1 : f = frequency in MHz; \*Plane-wave equivalent power density  
 Note 2 : For the applicable limit, see FCC 1.1310


##### Test method

- a) Performed aggregate both leakage E-field and H-field at surrounding the device from all simultaneous transmitting coils.
- b) During testing, the EUT was placed on a non-conductive table top and the ancillary equipment (e.g., mobile phone) was placed on the EUT for charging. Maximum E-field and H-field measurement were tested 15cm from each side of the EUT. Along the side of the EUT to center of E-field probe and H-field probe were positioned at the location to search maximum field strength.

##### The Worst Condition

Ancillary Equipment	Charging Condition
Fixture Load	Charging Mode

## Test Setup





**CTK Co., Ltd.**  
 (Ho-dong), 113, Yejik-ro, Cheoin-gu,  
 Yongin-si, Gyeonggi-do, Korea  
 Tel: +82-31-339-9970  
 Fax: +82-31-624-9501

Report No.:  
 CTK-2019-02112  
 Page (8) / (10) Pages

## Test results

Maximum Permissible Exposure				
Charging Condition	Separation	Probe from EUT Side	E-field (V/m)	H-field (A/m)
Operating	15 cm	Left	0.70	0.003
Operating	15 cm	Right	0.99	0.003
Operating	15 cm	Top	1.28	0.003
Operating	15 cm	Bottom	1.31	0.003
Operating	15 cm	Y-axis above EUT	<b>1.77</b>	<b>0.009</b>
<b>Limit</b>			<b>614</b>	<b>1.63</b>
<b>Margin Limit</b>			0.29 %	0.55 %





**CTK Co., Ltd.**  
(Ho-dong), 113, Yejik-ro, Cheoin-gu,  
Yongin-si, Gyeonggi-do, Korea  
Tel: +82-31-339-9970  
Fax: +82-31-624-9501


Report No.:  
CTK-2019-02112  
Page (9) / (10) Pages

## APPENDIX A – Test Equipment Used For Tests

No.	Name of Equipment	Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date
1	Exposure Level Probe	Narda	ELT-400	M-0626	2019-05-22	2020-05-22
2	Exposure Level Meter	Narda	ELT-400	N-0181	2019-05-22	2020-05-22
3	Electric Field Probe & Meter	SCHAFFNER-CHASE	EMC-20	R-0029	2018-06-29	2019-06-29

## APPENDIX B – Test Photos

**H-field**



**E-field**

