



## FCC TEST REPORT

for

### PART 15, SUBPART B CLASS B

**EQUIPMENT** : Internet Access Server

**MODEL NO.** : CA-300, CA-320

**F C C I D** : NYTAGS-CA3XX

**FILING TYPE** : CERTIFICATION

**APPLICANT** : **ARGUS TECHNOLOGIES CO., LTD.**  
9F, 111, SEC. 4, SAN HO RD., SAN CHUNG CITY,  
TAIPEI COUNTY, TAIWAN, R. O. C.

- The test result refers exclusively to the test presented test model / sample.
- Without the written authorization of the test lab., the Test Report may not be copied.

### **SPORTON INTERNATIONAL INC.**

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

**TABLE OF CONTENT**

<b>SECTION TITLE</b>	<b>PAGE</b>
<b>CERTIFICATE OF COMPLIANCE .....</b>	<b>3</b>
<b>1. GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST .....</b>	<b>4</b>
1.1. APPLICANT : .....	4
1.2. MANUFACTURER : .....	4
1.3. BASIC DESCRIPTION OF EQUIPMENT UNDER TEST .....	4
1.4. FEATURE OF EQUIPMENT UNDER TEST .....	4
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>5</b>
2.1. TEST MANNER .....	5
2.2. DESCRIPTION OF TEST SYSTEM .....	5
2.3. CONNECTION DIAGRAM OF TEST SYSTEM .....	7
<b>3. TEST SOFTWARE .....</b>	<b>8</b>
<b>4. GENERAL INFORMATION OF TEST .....</b>	<b>9</b>
4.1. TEST FACILITY .....	9
4.2. STANDARD FOR METHODS OF MEASUREMENT .....	9
4.3. TEST IN COMPLIANCE WITH .....	9
4.4. FREQUENCY RANGE INVESTIGATED .....	9
4.5. TEST DISTANCE .....	9
<b>5. TEST OF CONDUCTED POWERLINE .....</b>	<b>10</b>
5.1. MAJOR MEASURING INSTRUMENTS .....	10
5.2. TEST PROCEDURES .....	11
5.3. TEST RESULT OF AC POWERLINE CONDUCTED EMISSION .....	12
5.4. PHOTOGRAPHS OF CONDUCTED POWERLINE TEST CONFIGURATION .....	13
<b>6. TEST OF RADIATED EMISSION .....</b>	<b>15</b>
6.1. MAJOR MEASURING INSTRUMENTS .....	15
6.2. TEST PROCEDURES .....	16
6.3. TYPICAL TEST SETUP LAYOUT OF RADIATED EMISSION .....	17
6.4. TEST RESULT OF RADIATED EMISSION .....	18
6.5. PHOTOGRAPHS OF RADIATED EMISSION TEST CONFIGURATION .....	19
<b>7. ANTENNA FACTOR AND CABLE LOSS .....</b>	<b>20</b>
<b>8. LIST OF MEASURING EQUIPMENT USED .....</b>	<b>21</b>



## CERTIFICATE OF COMPLIANCE

for

### FCC PART 15, SUBPART B CLASS B

EQUIPMENT : Internet Access Server

MODEL NO. : CA-300, CA-320


F C C I D : NYTAGS-CA3XX

FILING TYPE : CERTIFICATION

APPLICANT : **ARGUS TECHNOLOGIES CO., LTD.**  
9F, 111, SEC. 4, SAN HO RD., SAN CHUNG CITY,  
TAIPEI COUNTY, TAIWAN, R. O. C.

### I HEREBY CERTIFY THAT :

The measurement shown in this report were made in accordance with the procedures given in **ANSI C63.4 -1992** and the energy emitted by this equipment was **passed** both radiated and conducted emissions **Class B** limits. Testing was carried out on **June 25, 1998** at **SPORTON International Inc.**

  
W. L. Huang  
General Manager

### **SPORTON INTERNATIONAL INC.**

6F, No. 106, Hsin Tai Wu Rd., Sec. 1, Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## **1. GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST**

### **1.1. APPLICANT :**

**ARGUS TECHNOLOGIES CO., LTD.**  
9F, 111, SEC. 4, SAN HO RD., SAN CHUNG CITY,  
TAIPEI COUNTY, TAIWAN, R.O.C.

### **1.2. MANUFACTURER :**

Same as 1.1

### **1.3. BASIC DESCRIPTION OF EQUIPMENT UNDER TEST**

EQUIPMENT : Internet Access Server  
MODEL NO. : CA -300, CA -320  
TRADE NAME : **ARGUS**  
TP DATA CABLE : Non-shielded  
FCC ID : NYTAGS-CA3XX  
IAS MODEM CABLE : Non-shielded  
POWER SUPPLY TYPE : Linear  
POWER CORD : Non-shielded

### **1.4. FEATURE OF EQUIPMENT UNDER TEST**

- Built-in DHCP server can automatically assign your network clients their IP information and gateway.
- Dial-on-Demand eliminates the need for dial-up utilities and also dials-out only when needed saving on phone and ISP charges.
- Idle-Time out automatically disconnects the connection if there has been no traffic for a set period of time.
- Flash ROM allows firmware to be easily upgraded
- Internal Firewall prevents unauthorized access to your network
- 460Kbps baud rate easily supports 128Kbps ISDN Tas or 56Kbps analog modems

---

**2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST****2.1. TEST MANNER**

- a. The EUT has been associated with personal computer and peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner, which is tended to maximize its emission characteristics in a typical application.
- b. The SONY monitor, DELL keyboard, GENIUS PS2 mouse, HP printer, two ACEEX modems, and EUT were connected to the F.I.C. P.C. for EMI test.
- c. Frequency range investigated : Conduction 450 KHz to 30 MHz, Radiation 30 MHz to 1000MHz.

**2.2. DESCRIPTION OF TEST SYSTEM**

## Support Device 1. --- P.C. (FIC)

FCC ID : N/A  
Model No. : P55T2P4  
Serial No. : SP1003  
Data Cable : Shielded  
Power Cord : Non-shielded  
Power Supply Type : Switching

( Remark : This support device was tested to comply with FCC standards and authorized under a declaration of conformity.)

## Support Device 2. --- MONITOR (SONY)

FCC ID : AK8GDM17SE2T  
Model No. : GDM-17SE2T  
Serial No. : SP1006  
Data Cable : Shielded, 360 degree via metal backshells, 1.7m  
Power Supply Type : Switching  
Power Cord : Non-shielded

## Support Device 3. --- KEYBOARD (DELL)

FCC ID : GYUM92SK  
Model No. : AT101 (DE8M)  
Serial No. : SP1009  
Data Cable : Shielded, 360 degree via metal backshells, 1.9m

## Support Device 4. -- PS/2 MOUSE (GENIUS)

FCC ID : FSUGMZF6  
Model No. : NETMOUSE  
Serial No. : SP1034  
Data Cable : Non-shielded, 1.4m


## Support Device 5. --- PRINTER (HP)

FCC ID : B94C2642X  
Model No. : DESK JET 400  
Serial No. : SP0037  
Data Cable : Shielded, 360 degree via metal backshells, 1.35m  
Power Supply Type : Linear

## Support Device 6. -- MODEMS (ACEEX)

FCC ID : IFAXDM1414  
Model No. : DM1414  
Power Supply Type : Linear, AC Adapter  
Power Cord : Non-shielded  
Serial No. : SP1019  
Data Cable : Shielded, 1.15m

2.3. CONNECTION DIAGRAM OF TEST SYSTEM



1. The TP cable is connected from the EUT to the support device 1.
2. The I/O cable is connected to the support device 2.
3. The I/O cable is connected to the support device 3.
4. The I/O cable is connected to the support device 4.
5. The I/O cable is connected to the support device 5.
6. The I/O cables are connected from the EUT to the support device 6.

### 3. TEST SOFTWARE

An executive program, EMITEST.EXE under WIN98, which generates a complete line of continuously repeating " H " pattern is used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The PC reads the test program from the floppy disk drive and runs it.
- c. The PC sends " H " messages to the monitor, and the monitor displays " H " patterns on the screen.
- d. The PC sends " H " messages to the printer, then the printer prints them on the paper.
- e. The PC sends " H " messages to the modem.
- a. The PC sends " H " messages to the internal Hard Disk, then the hard disk reads and writes the message.
- f. Repeat the steps from b to f.



## **4. GENERAL INFORMATION OF TEST**

### **4.1. TEST FACILITY**

This test was carried out by SPORTON INTERNATIONAL INC. in an openarea test site.

Openarea Test Site Location : No. 30-1, Lin 6, Diing-Fwu Tsuen, Lin-Kou-Hsiang,  
Taipei Hsien, Taiwan, R.O.C.

TEL : 886-2-2601-1640

FAX : 886-2-2601-1695

### **4.2. STANDARD FOR METHODS OF MEASUREMENT**

ANSI C63.4-1992

### **4.3 .TEST IN COMPLIANCE WITH**

FCC PART 15, SUBPART B CLASS B

### **4.4. FREQUENCY RANGE INVESTIGATED**

a. Conduction : from 450 KHz to 30 MHz

b. Radiation : from 30 MHz to 1000 MHz.

### **4.5. TEST DISTANCE**

The test distance of radiated emission from antenna to EUT is 3M.

## **5. TEST OF CONDUCTED POWERLINE**

Conducted Emissions were measured from 450 KHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-1992 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in Figure 5-3. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

### **5.1. MAJOR MEASURING INSTRUMENTS**

• Test Receiver	( HP 85462A )
Attenuation	0 dB
Start Frequency	0.45 MHz
Stop Frequency	30 MHz
Step MHz	0.007 MHz
IF Bandwidth	9 KHz

**5.2. TEST PROCEDURES**

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room and was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network ( LISN ).
- c. All the support units are connect to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm , 50 microhenry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 450 KHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- i. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported otherwise the emissions which do not have 6 dB margin will be retested on by one using the quasi-peak method and reported.

**5.3. TEST RESULT OF AC POWERLINE CONDUCTED EMISSION**

- Frequency Range of Test : from 0.45 MHz to 30 MHz
- All emissions not reported here are more than 10 dB below the prescribed limit.
- Temperature : 25°C
- Relative Humidity : 56 % RH
- Test Date : June 25, 1998

**The Conducted Emission test was passed Line 25.00 MHz/ 39.30 dBuV.**

Frequency ( MHz )	Line / Neutral	Meter Reading			Limits ( uV )	Margin ( dB )
		( dBuV )	( uV )	( dBuV )		
0.45	L	37.70	76.74	48.00	251.19	-10.30
0.63	L	38.80	87.10	48.00	251.19	-9.20
25.00	L	39.30	92.26	48.00	251.19	-8.70
0.47	N	37.50	74.99	48.00	251.19	-10.50
0.62	N	37.50	74.99	48.00	251.19	-10.50
22.57	N	38.00	79.43	48.00	251.19	-10.00

Test Engineer : Alex Wu

Alex Wu

## **6. TEST OF RADIATED EMISSION**

Radiated emissions from 30 MHz to 1000 MHz were measured with a bandwidth of 120 KHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in Figure 6-3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

### **6.1. MAJOR MEASURING INSTRUMENTS**

- RF Preselector
 

Attenuation	0 dB
RF Gain	20 dB
Signal Input	Input 2 ( for 20 MHz to 2 GHz )
  
- Spectrum Analyzer
 


	8560E
Attenuation	0 dB
Start Frequency	30 MHz
Stop Frequency	1000 MHz
Resolution Bandwidth	1 MHz
Video Bandwidth	1 MHz
Signal Input	Input 1 ( for 30 mHz to 2.9 GHz )
  
- Quasi-Peak Adapter
 

Resolution Bandwidth	120 KHz
Frequency Band	30 MHz to 1 GHz
Quasi-Peak Detector	ON for Quasi-Peak Mode OFF for Peak Mode

**6.2. TEST PROCEDURES**

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower ( from 1 M to 4 M ) and turn table ( from 0 degree to 360 degrees ) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported otherwise the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

6.3. TYPICAL TEST SETUP LAYOUT OF RADIATED EMISSION



**6.4. TEST RESULT OF RADIATED EMISSION**

- Equipment meets the technical specifications of 15.109
- Frequency Range of Test : from 30 MHz to 1000 MHz
- Test Distance : 3 M
- Temperature : 35°C
- Relative Humidity : 55 % RH
- Test Date : June 19, 1998
  
- Emission level ( dBuV/m ) = 20 log Emission level ( uV/m )
- Sample Calculation at 50.00 MHz  
Corrected Reading = 2.39 + 1.00 + 32.81 = 36.20 (dBuV/m )

**The Radiated Emission test was passed at minimum margin**

**Vertical 50.00 MHz / 36.20 dBuV**

**Antenna Height 1.5 Meter , Turntable Degree 360°**

Frequency ( MHz )	Polarity	Antenna Factor ( dB )	Cable Loss ( dB )	Reading ( dBuV )	Limits ( dBuV )	Emission ( uV )	Level ( dBuV )	Margin ( dB )
46.26	V	1.57	1.00	31.36	40.00	100	33.93	49.72 -6.07
50.00	V	2.39	1.00	32.81	40.00	100	36.20	64.57 -3.80
137.43	V	11.25	1.88	24.87	43.50	150	38.00	79.43 -5.50
175.15	V	12.63	2.26	23.89	43.50	150	38.78	86.90 -4.72
50.07	H	2.40	1.00	30.67	40.00	100	34.07	50.52 -5.93
75.15	H	6.14	1.30	26.21	40.00	100	33.65	48.14 -6.35

Test Engineer : \_\_\_\_\_

*Jack Deng*

JACK DENG



**7. ANTENNA FACTOR AND CABLE LOSS**

Frequency ( MHz )	Antenna Factor ( dB )	Cable Loss ( dB )
30	-1.91	0.90
35	-0.50	0.92
40	0.61	1.04
45	1.40	1.28
50	2.39	1.10
55	3.54	1.11
60	4.40	1.30
65	4.84	1.40
70	5.59	1.37
75	6.21	1.24
80	7.60	1.51
85	7.73	1.60
90	8.22	1.60
95	8.90	1.70
100	9.36	1.70
110	10.01	1.70
120	10.41	1.90
130	10.84	1.90
140	11.42	1.91
150	11.91	2.01
160	12.25	2.11
170	12.72	2.21
180	13.02	2.30
190	13.50	2.30
200	14.05	2.40
220	15.11	2.50
240	16.81	2.60
260	17.51	2.71
280	17.70	2.90
300	17.89	2.91
320	18.00	3.10
340	18.33	3.20
360	19.44	3.30
380	20.31	3.40
400	21.19	3.50
450	21.10	3.70
500	22.21	4.10
550	23.42	4.30
600	24.01	4.50
650	25.11	4.70
700	26.00	4.90
750	26.41	5.11
800	27.10	5.50
850	27.51	5.60
900	27.90	5.80
950	28.01	5.90

## 8. LIST OF MEASURING EQUIPMENT USED

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Receiver RF section (site 1)	HP	85462A	3325A00108	9 KHz - 6.5 GHz	Oct. 22, 1997	Conduction
RF Filter section (site 1)	HP	85460A	3308A00104	9 KHz - 6.5 GHz	Oct. 22, 1997	Conduction
LISN (EUT) (site 1)	EMCO	3850/2	1035	50 ohm / 50 uH	Oct. 27, 1997	Conduction
LISN (Support Unit) (site 1)	KYORITSU	KNW-407	8-693-10	50 ohm / 50 uH	Oct. 04, 1997	Conduction
EMI Filter (site 1)	CORCOM	MRI-2030	N/A	480 VAC / 30 A	N/A	Conduction
Spectrum Analyzer (Site 4)	HP	8560E	3728A03186	30MHz - 2.9GHz	Sep. 24, 1997	Radiation
Amplifier (Site 4)	HP	8447D	2944A09072	0.1MHz -1.3GHz	Sep. 17, 1997	Radiation
Test Receiver (Site 4)	R&S	ESVP	893610/003	20MHz - 1.3GHz	April 13, 1998	Radiation
Bilog Antenna (Site 4)	CHASE	CBL6112A	2288	30MHz -2GHz	Jul. 14, 1998	Radiation
Half-wave dipole antenna (Site 4)	EMCO	3121C	9705-1285	28 M - 1GHz	May 19, 1998	Radiation
Turn Table (site 4)	EMCO	2080	9711-1090	0 ~ 360 degree	N/A	Radiation
Antenna Mast (site 4)	EMCO	2075	9711-2114	1 m- 4 m	N/A	Radiation