

DIGITAL EMC CO., LTD

DUT: Dipole 450 MHz; Type: D450V2; Serial: D450V2 - SN:1011

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 450$ MHz; $\sigma = 0.853$ mho/m; $\epsilon_r = 44.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

Probe: ET3DV6 - SN1702; ConvF(7.7, 7.7, 7.7); Calibrated: 2004-02-17; Electronics: DAE3 Sn519

Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223

Measurement SW: DASY4, V4.4 Build 3; Postprocessing SW: SEMCAD, V1.8 Build 130

Test Date: 2004-12-22; Ambient Temp: 23.0; Tissue Temp: 20.9

Dipole Validation


Area Scan (61x141x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.87 W/kg

SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.763 mW/g



0 dB = 1.2mW/g

DIGITAL EMC CO., LTD

DUT: Dipole 450 MHz; Type: D450V2; Serial: 1011

Communication System: CW; Frequency: 450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 450$ MHz; $\sigma = 0.918$ mho/m; $\epsilon_r = 57.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

Probe: ET3DV6 - SN1702; ConvF(7.6, 7.6, 7.6); Calibrated: 2004-02-17; Electronics: DAE3 Sn519

Phantom: SAM with 835MHz; Type: SAM; Serial: TP-1223

Measurement SW: DASY4, V4.4 Build 3; Postprocessing SW: SEMCAD, V1.8 Build 130

Test Date: 2004-12-23; Ambient Temp: 23.0; Tissue Temp: 21.9

Dipole Validation


Area Scan (61x141x1): Measurement grid: dx=15mm, dy=15mm

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Power Drift = 0.02 dB

Peak SAR (extrapolated) = 2.03 W/kg

SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.789 mW/g



0 dB = 1.25mW/g