



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road,

Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 27 TEST REPORT

FCC Part 27

Report Reference No.: GTS20211222005-1-3

FCC ID.: O39IHAND55

Compiled by

(position+printed name+signature) : File administrators Jimmy Wang

Jimmy Wang

Aaron Tan
* Jason Hu

Supervised by

(position+printed name+signature) : Test Engineer Aaron Tan

Approved by

(position+printed name+signature) : Manager Jason Hu

Date of issue: Dec. 22, 2021

Representative Laboratory Name: Shenzhen Global Test Service Co.,Ltd.

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name: Hi-Target Surveying Instrument Co., Ltd

Address: Plant 202, BLDG 13, Tian'An HQ Center No.555 North Panyu RD. Donghuan Block, Panyu District, 511400 Guangzhou, China.

Test specification:

FCC CFR Title 47 Part 2, Part 27

Standard: EIA/TIA 603-D: 2010

KDB 971168 D01

TRF Originator: Shenzhen Global Test Service Co.,Ltd.

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Handheld Controller

Trade Mark: 

Manufacturer: Hi-Target Surveying Instrument Co., Ltd

Model/Type reference: iHand55

Listed Models: N/A

Modulation Type: QPSK, 16QAM

Rating: DC 3.70V

Hardware version: A

Software version: V1.0.0

Result: **PASS**

TEST REPORT

Equipment under Test : Handheld Controller

Model /Type : iHand55

Listed Models : N/A

Applicant : **Hi-Target Surveying Instrument Co., Ltd**

Address : Plant 202, BLDG 13, Tian'An HQ Center No.555 North Panyu RD. Donghuan Block, Panyu District, 511400 Guangzhou, China.

Manufacturer : **Hi-Target Surveying Instrument Co., Ltd**

Address : Plant 202, BLDG 13, Tian'An HQ Center No.555 North Panyu RD. Donghuan Block, Panyu District, 511400 Guangzhou, China.

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS</u>	4
<u>2.</u>	<u>SUMMARY</u>	5
2.1.	General Remarks	5
2.2.	Product Description	5
2.3.	Equipment under Test	5
2.4.	Short description of the Equipment under Test (EUT)	5
2.5.	EUT configuration	5
2.6.	Related Submittal(s) / Grant (s)	5
2.7.	Modifications	6
2.8.	Test Environment	6
<u>3.</u>	<u>TEST ENVIRONMENT</u>	6
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Test Description	7
3.5.	Equipments Used during the Test	9
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	10
4.1.	Output Power	10
4.2.	Peak-to-Average Ratio (PAR)	23
4.3.	Occupied Bandwidth and Emission Bandwidth	24
4.4.	Band Edge compliance	25
4.5.	Spurious Emission on Antenna Port	27
4.6.	Radiated Spurious Emission	29
4.7.	Frequency Stability	36
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	41
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	41

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Part 27\(10-1-12 Edition\): MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES](#)

[TIA/EIA 603 D June 2010: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.](#)

[47 CFR FCC Part 15 Subpart B: - Unintentional Radiators](#)

[FCC Part 2: FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS](#)

[ANSI C63.4:2014: Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz](#)

[FCC KDB971168D01 Power Meas License Digital Systems](#)

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Nov. 19, 2021
Testing commenced on	:	Nov. 19, 2021
Testing concluded on	:	Dec. 22, 2021

2.2. Product Description

Name of EUT	Handheld Controller
Model Number	iHand55
Antenna Type	FPC Antenna
LTE Release Version	R9
Type Of Modulation	QPSK/16QAM
Support Band	E-UTRA Band 7/ E-UTRA Band 38/ E-UTRA Band 40/ E-UTRA Band 41
Power Class	Class 12
Extreme temp. Tolerance	-30°C to +50°C
Extreme vol. Limits	3.40VDC to 4.20VDC (nominal: 3.70VDC)
Antenna gain:	Band 7 :1.36 dbi ,Band 38:1.59 dbi; Band 40:1.75 dbi; Band 41:1.75 dbi
Testing sample ID:	GTS20211222005-1# (Engineer sample), GTS20211222005-2# (Normal sample)

2.3. Equipment under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 120V/ 60 Hz	<input type="radio"/> 115V/60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 3.70V from battery and DC 5V From Adapter

2.4. Short description of the Equipment under Test (EUT)

This is a Handheld Controller .

For more details, refer to the user's manual of the EUT.

2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer

- supplied by the lab

<input type="radio"/> /	M/N :	/
	Manufacturer:	/

2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: O39IHAND55 filing to comply with FCC Part 27, Rules.

2.7. Modifications

No modifications were implemented to meet testing criteria.

2.8. Test Environment

EnvironmentParameter	SelectedValuesDuringTests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
	VL	3.40V
Voltage	VN	3.80V
	VH	4.20V

NOTE: VL=lower extreme test voltage VN=nominal voltage
 VH=upper extreme test voltage TN=normal temperature

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 165725

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 4758.01

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

CNAS-Lab Code: L8169

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2024.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Test Description

Band 7 (2500-2570MHz paired with 2620-2690MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §27.50(h)	FCC: EIRP ≤ 2W.	Pass
Peak-Average Ratio	§2.1046, §27.50(a)	Limit≤13dB	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §27.53(m)	More details specified in §27.53(m)(4)	Pass
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	More details specified in §27.53(m)(4)	Pass
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	More details specified in §27.53(m)(4)	Pass
Frequency Stability	§2.1055, §27.54	≤ ±2.5ppm.	Pass

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

Band 38 (2570-2620MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	ERP ≤ 2W;	PASS
Peak-Average Ratio	§2.1046, §27.50	Limit≤13dB	PASS
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	PASS
Band Edges Compliance	§2.1051, §27.53(m)	≤ -13dBm/1%*EBW,in 1 MHz bands immediately outside and adjacent to The frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	≤ -13dBm/1MHz, from 9kHz to 10th harmonics but outside authorized Operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiated spurious emission	§2.1053, §27.53(m)	≤ -25dBm/1MHz.	PASS

NOTE 1: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".

Band 40 (2305-2315 MHz and 2350-2360 MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	ERP ≤ 2W;	PASS
Peak-Average Ratio	§2.1046, §27.50	Limit≤13dB	PASS
Modulation Characteristics	§2.1047	Digitalmodulation	N/A
Bandwidth	§2.1049	OBW: Nolimit. EBW: Nolimit.	PASS
BandEdges Compliance	§2.1051, §27.53(m)	≤ -13dBm/1%*EBW,in 1 MHz bands immediately outside and adjacent to The frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	≤ -13dBm/1MHz, from 9kHz to 10th harmonics but outside authorized Operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiated spurious emission	§2.1053, §27.53(m)	≤ -25dBm/1MHz.	PASS

NOTE 1:For the verdict, the "N/A"denotes "not applicable",the "N/T"de notes "not tested".

Band 41(2496-2690MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	ERP ≤ 2W;	PASS
Peak-Average Ratio	§2.1046, §27.50	Limit≤13dB	PASS
Modulation Characteristics	§2.1047	Digitalmodulation	N/A
Bandwidth	§2.1049	OBW: Nolimit. EBW: Nolimit.	PASS
BandEdges Compliance	§2.1051, §27.53(m)	≤ -13dBm/1%*EBW,in 1 MHz bands immediately outside and adjacent to The frequency block.	PASS
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	≤ -13dBm/1MHz, from 9kHz to 10th harmonics but outside authorized Operating frequency ranges.	PASS
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	PASS
Radiated spurious emission	§2.1053, §27.53(m)	≤ -25dBm/1MHz.	PASS

NOTE 1:For the verdict, the "N/A"denotes "not applicable",the "N/T"de notes "not tested".

3.5. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.08	2021/09/18	2022/09/17
LISN	R&S	ESH2-Z5	893606/008	2021/09/18	2022/09/17
EMI Test Receiver	R&S	ESPI3	101841-cd	2021/09/18	2022/09/17
EMI Test Receiver	R&S	ESCI7	101102	2021/09/18	2022/09/17
Spectrum Analyzer	Agilent	N9020A	MY48010425	2021/09/18	2022/09/17
Spectrum Analyzer	R&S	FSV40	100019	2021/09/18	2022/09/17
Vector Signal generator	Agilent	N5181A	MY49060502	2021/09/18	2022/09/17
Signal generator	Agilent	E4421B	3610AO1069	2021/09/18	2022/09/17
Climate Chamber	ESPEC	EL-10KA	A20120523	2021/09/18	2022/09/17
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2021/09/18	2022/09/17
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	15006	2021/10/10	2022/10/09
Bilog Antenna	Schwarzbeck	VULB9163	000976	2021/05/25	2022/05/24
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2021/09/18	2022/09/17
Amplifier	Schwarzbeck	BBV 9743	#202	2021/09/18	2022/09/17
Amplifier	Schwarzbeck	BBV9179	9719-025	2021/09/18	2022/09/17
Amplifier	EMCI	EMC051845B	980355	2021/09/18	2022/09/17
Temperature/Humidity Meter	Gangxing	CTH-608	02	2021/09/18	2022/09/17
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	KL142031	2021/09/18	2022/09/17
High-Pass Filter	K&L	41H10-1375/U12750-O/O	KL142032	2021/09/18	2022/09/17
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2021/09/18	2022/09/17
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2021/09/18	2022/09/17
Data acquisition card	Agilent	U2531A	TW53323507	2021/09/18	2022/09/17
Power Sensor	Agilent	U2021XA	MY5365004	2021/09/18	2022/09/17
Test Control Unit	Tonscend	JS0806-1	178060067	2021/06/19	2022/06/18
Automated filter bank	Tonscend	JS0806-F	19F8060177	2021/06/19	2022/06/18
Universal Radio Communication	R&S	CMU200	114353	2021/09/18	2022/09/17
Wireless Communication Tester	R&S	CMW500	125408	2021/09/18	2022/09/17
EMI Test Software	Tonscend	JS1120-1	Ver 2.6.8.0518	/	/
EMI Test Software	Tonscend	JS1120-3	Ver 2.5.77.0418	/	/
EMI Test Software	Tonscend	JS32-CE	Ver 2.5	/	/
EMI Test Software	Tonscend	JS32-RE	Ver 2.5.1.8	/	/

Note: The calibration interval was one year.

4. TEST CONDITIONS AND RESULTS


4.1. Output Power

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits

4.1.1. Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

Conducted Power Measurement:

- Place the EUT on a bench and set it in transmitting mode.
- Connect a low loss RF cable from the antenna port to a CMW500 by an Att.
- EUT Communicate with CMW500 then selects a channel for testing.
- Add a correction factor to the display CMW500, and then test.

TEST RESULTS

Remark:

- We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 41.

LTE FDD Band 7				
TX Channel Bandwidth	Frequency (MHz)	RB Size/Offset	Average Power [dBm]	
			QPSK	16QAM
5 MHz	2502.5	1 RB low	22.13	21.48
		1 RB mid	22.25	21.48
		1 RB high	21.98	21.25
		50% RB low	21.37	20.67
		50% Rb mid	21.41	20.68
		50% RB high	21.28	20.57
		100% RB	20.94	20.17
		1 RB low	22.17	21.45
10 MHz	2535.0	1 RB mid	22.11	21.47
		1 RB high	22.27	21.65
		50% RB low	21.43	20.75
		50% Rb mid	21.59	20.86
		50% RB high	21.52	20.78
		100% RB	21.13	20.39
		1 RB low	22.16	21.44
		1 RB mid	22.24	21.55
20 MHz	2567.5	1 RB high	22.24	21.46
		50% RB low	21.67	21.04
		50% Rb mid	21.62	20.90
		50% RB high	21.73	21.09
		100% RB	21.19	20.55
		1 RB low	22.41	21.76
		1 RB mid	22.39	21.63

		1 RB high	22.35	21.62
		50% RB low	21.92	21.17
		50% Rb mid	21.69	20.97
		50% RB high	21.72	21.06
		100% RB	21.34	20.62
		1 RB low	22.37	21.69
		1 RB mid	22.34	21.67
		1 RB high	22.45	21.84
		50% RB low	22.56	21.77
		50% Rb mid	21.59	20.83
	2535.0	50% RB high	21.68	20.99
		100% RB	21.31	20.67
		1 RB low	22.43	21.78
		1 RB mid	22.45	21.77
		1 RB high	22.37	21.66
		50% RB low	21.57	20.91
		50% Rb mid	21.56	20.85
		50% RB high	21.63	20.92
		100% RB	21.06	20.36
		1 RB low	22.31	21.64
	2507.5	1 RB mid	22.46	21.78
		1 RB high	22.28	21.58
		50% RB low	21.59	20.86
		50% Rb mid	21.61	20.87
		50% RB high	21.45	20.75
		100% RB	21.14	20.53
		1 RB low	22.42	21.69
		1 RB mid	22.40	21.66
		1 RB high	22.38	21.64
		50% RB low	21.42	20.75
	2535.0	50% Rb mid	21.47	20.72
		50% RB high	21.38	20.60
		100% RB	21.17	20.38
		1 RB low	22.43	21.69
		1 RB mid	22.63	21.94
		1 RB high	22.40	21.70
		50% RB low	21.71	21.04
		50% Rb mid	21.59	20.95
		50% RB high	21.48	20.83
		100% RB	21.22	20.52
	2510.0	1 RB low	22.61	21.94
		1 RB mid	22.56	21.85
		1 RB high	22.64	22.02
		50% RB low	21.80	21.17
		50% Rb mid	21.78	21.10
		50% RB high	21.72	20.95
		100% RB	21.40	20.69
		1 RB low	22.80	22.13
		1 RB mid	22.84	22.15
		1 RB high	22.81	22.08
	2535.0	50% RB low	21.86	21.13
		50% Rb mid	21.97	21.33
		50% RB high	21.88	21.10
		100% RB	21.58	20.90
		1 RB low	22.74	22.03
		1 RB mid	22.79	22.06
		1 RB high	22.74	22.11
		50% RB low	21.80	21.18
		50% Rb mid	21.97	21.22
		50% RB high	21.74	21.03
	2560.0	100% RB	21.58	20.88

LTE TDD Band 38				
TX Channel Bandwidth	Frequency (MHz)	RB Size/Offset	Average Power [dBm]	
			QPSK	16QAM
5	2572.5	1 RB low	21.26	20.53
		1 RB mid	21.44	20.74
		1 RB high	21.20	20.56
		50% RB low	22.49	21.81
		50% Rb mid	22.40	21.72
		50% RB high	22.34	21.66
		100% RB	22.37	21.69
	2595.0	1 RB low	21.83	21.14
		1 RB mid	21.91	21.19
		1 RB high	21.68	20.96
		50% RB low	22.81	22.13
		50% Rb mid	22.87	22.12
		50% RB high	22.83	22.14
		100% RB	22.75	21.97
10	2617.5	1 RB low	22.67	22.04
		1 RB mid	22.79	22.03
		1 RB high	22.73	22.01
		50% RB low	22.71	21.99
		50% Rb mid	22.76	22.09
		50% RB high	22.82	22.15
		100% RB	22.75	22.06
	2575.0	1 RB low	21.29	20.66
		1 RB mid	21.64	20.94
		1 RB high	21.43	20.75
		50% RB low	22.46	21.77
		50% Rb mid	22.42	21.72
		50% RB high	22.45	21.82
		100% RB	22.44	21.67
	2595.0	1 RB low	21.90	21.18
		1 RB mid	22.24	21.55
		1 RB high	21.78	21.07
		50% RB low	22.87	22.14
		50% Rb mid	22.90	22.25
		50% RB high	22.84	22.15
		100% RB	22.81	22.15
15	2615.0	1 RB low	22.88	22.18
		1 RB mid	21.01	20.29
		1 RB high	22.80	22.02
		50% RB low	22.95	22.28
		50% Rb mid	22.86	22.14
		50% RB high	22.81	22.16
		100% RB	22.84	22.14
	2577.5	1 RB low	21.20	20.47
		1 RB mid	21.44	20.72
		1 RB high	21.51	20.79
		50% RB low	20.54	19.82
		50% Rb mid	20.49	19.76
		50% RB high	20.60	19.91
		100% RB	20.62	19.90
	2595.0	1 RB low	21.69	21.02
		1 RB mid	21.97	21.27
		1 RB high	21.49	20.86
		50% RB low	22.90	22.26
		50% Rb mid	22.86	22.15
		50% RB high	22.89	22.25
		100% RB	21.94	21.28
	2612.5	1 RB low	21.09	20.48

		1 RB mid	22.81	22.18
		1 RB high	22.69	22.02
		50% RB low	22.61	22.00
		50% RB mid	22.93	22.17
		50% RB high	22.98	22.28
		100% RB	22.99	22.37
20	2580.0	1 RB low	21.11	20.34
		1 RB mid	21.68	20.95
		1 RB high	21.52	20.78
		50% RB low	22.47	21.80
		50% RB mid	22.50	21.82
		50% RB high	21.51	20.87
		100% RB	22.49	21.87
		1 RB low	21.44	20.78
	2595.0	1 RB mid	22.15	21.42
		1 RB high	21.10	20.40
		50% RB low	22.80	22.05
		50% RB mid	22.76	21.98
		50% RB high	22.63	21.93
		100% RB	22.68	22.04
		1 RB low	21.27	20.61
		1 RB mid	21.13	20.42
2610.0	2610.0	1 RB high	22.36	21.69
		50% RB low	22.12	21.36
		50% RB mid	20.11	19.38
		50% RB high	22.63	21.92
		100% RB	22.89	22.22

LTE TDD Band 40(lower)				
BW (MHz)	Frequency (MHz)	RB Size/Offset	Average Power [dBm]	
			QPSK	16QAM
5	2307.5	1 RB low	21.72	21.07
		1 RB mid	21.92	21.20
		1 RB high	21.84	21.18
		50% RB low	22.86	22.11
		50% RB mid	22.87	22.15
		50% RB high	22.87	22.18
		100% RB	22.92	22.25
		1 RB low	22.26	21.55
10	2310.0	1 RB mid	21.95	21.17
		1 RB high	22.15	21.38
		50% RB low	21.19	20.50
		50% RB mid	21.27	20.52
		50% RB high	21.04	20.32
		100% RB	21.11	20.36
		1 RB low	22.99	22.33
		1 RB mid	22.93	22.29
2312.5	2312.5	1 RB high	21.07	20.43
		50% RB low	22.05	21.36
		50% RB mid	22.10	21.43
		50% RB high	22.16	21.42
		100% RB	22.10	21.34
		1 RB low	22.21	21.53
		1 RB mid	21.91	21.27
		1 RB high	21.83	21.12
2310.0	2310.0	50% RB low	22.86	22.18
		50% RB mid	22.93	22.20
		50% RB high	22.92	22.21
		100% RB	22.93	22.16

LTE TDD Band 40(upper)				
BW (MHz)	Frequency (MHz)	RB Size/Offset	Average Power [dBm]	
			QPSK	16QAM
5	2352.5	1 RB low	21.78	21.08
		1 RB mid	21.88	21.13
		1 RB high	21.82	21.19
		50% RB low	22.81	22.03
		50% Rb mid	22.78	22.13
		50% RB high	22.80	22.10
		100% RB	22.92	22.20
	2355.0	1 RB low	22.22	21.51
		1 RB mid	21.95	21.25
		1 RB high	22.20	21.55
		50% RB low	21.11	20.37
		50% Rb mid	21.14	20.38
		50% RB high	20.99	20.30
		100% RB	21.06	20.40
10	2357.5	1 RB low	22.97	22.25
		1 RB mid	22.85	22.13
		1 RB high	21.05	20.37
		50% RB low	22.11	21.38
		50% Rb mid	22.12	21.38
		50% RB high	22.09	21.39
		100% RB	22.11	21.44
	2355.0	1 RB low	22.20	21.49
		1 RB mid	21.92	21.26
		1 RB high	21.76	21.07
		50% RB low	22.93	22.23
		50% Rb mid	23.03	22.40
		50% RB high	22.94	22.25
		100% RB	22.98	22.23

LTE TDD Band 41				
BW (MHz)	Frequency (MHz)	RB Size/Offset	Average Power [dBm]	
			QPSK	16QAM
5	2498.5	1 RB low	21.69	21.02
		1 RB mid	21.92	21.16
		1 RB high	21.80	21.17
		50% RB low	22.80	22.09
		50% Rb mid	22.81	22.12
		50% RB high	22.83	22.11
		100% RB	22.93	22.22
	2593.0	1 RB low	22.22	21.58
		1 RB mid	21.92	21.20
		1 RB high	22.15	21.49
		50% RB low	21.17	20.48
		50% Rb mid	21.19	20.52
		50% RB high	21.06	20.41
		100% RB	21.12	20.43
10	2687.5	1 RB low	22.95	22.30
		1 RB mid	22.91	22.18
		1 RB high	21.02	20.29
		50% RB low	22.05	21.38
		50% Rb mid	22.05	21.34
		50% RB high	22.10	21.38
	2501.0	100% RB	22.09	21.35
		1 RB low	22.23	21.57
		1 RB mid	21.92	21.26


		1 RB high	21.79	21.10
		50% RB low	22.94	22.18
		50% Rb mid	22.96	22.26
		50% RB high	22.91	22.18
		100% RB	22.97	22.27
	2593.0	1 RB low	22.31	21.68
		1 RB mid	21.80	21.13
		1 RB high	22.37	21.66
		50% RB low	21.02	20.35
		50% Rb mid	21.20	20.56
		50% RB high	21.13	20.45
		100% RB	21.08	20.35
		1 RB low	21.10	20.38
	2685.0	1 RB mid	21.00	20.23
		1 RB high	22.93	22.25
		50% RB low	22.13	21.40
		50% Rb mid	22.08	21.41
		50% RB high	22.13	21.38
		100% RB	22.16	21.42
		1 RB low	21.63	20.97
		1 RB mid	21.86	21.09
15	2503.5	1 RB high	21.70	20.96
		50% RB low	22.76	22.06
		50% Rb mid	20.96	20.28
		50% RB high	22.79	22.17
		100% RB	21.08	20.37
		1 RB low	22.15	21.47
		1 RB mid	21.48	20.72
		1 RB high	22.22	21.48
	2593.0	50% RB low	22.94	22.26
		50% Rb mid	22.88	22.17
		50% RB high	22.13	21.46
		100% RB	21.20	20.44
		1 RB low	22.86	22.12
		1 RB mid	21.24	20.53
		1 RB high	20.96	20.26
		50% RB low	22.25	21.56
	2682.5	50% Rb mid	21.99	21.31
		50% RB high	22.91	22.19
		100% RB	22.16	21.46
		1 RB low	21.63	20.86
		1 RB mid	22.29	21.65
		1 RB high	21.49	20.82
		50% RB low	22.86	22.07
		50% Rb mid	22.91	22.16
	2506.0	50% RB high	22.86	22.17
		100% RB	22.89	22.10
		1 RB low	22.00	21.33
		1 RB mid	21.25	20.53
		1 RB high	22.40	21.75
		50% RB low	22.73	22.07
		50% Rb mid	21.12	20.45
		50% RB high	21.12	20.36
20	2593.0	100% RB	22.95	22.19
		1 RB low	22.86	22.18
		1 RB mid	22.87	22.26
		1 RB high	22.25	21.55
		50% RB low	22.99	22.28
		50% Rb mid	22.68	21.95
		50% RB high	20.99	20.25
		100% RB	22.83	22.10

4.1.2. Radiated Output Power

LIMIT

Per Part 27.50(h) (2) specifies Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} + G_a$$

We used SMF100A microwave signal generator which signal level can up to 33dBm, so we not used power Amplifier for substitution test; The measurement results are amend as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{cl} + G_a$$

6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.

7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{ dBi}$.

TEST RESULTS

Remark:

1. We measured all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.; recorded worst case for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.
2. $EIRP = P_{Mea}(\text{dBm}) - P_{cl}(\text{dB}) + P_{Ag}(\text{dB}) + G_a(\text{dBi})$
3. We measured both Horizontal and Vertical direction, recorded worst case direction.

LTE FDD Band 7_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2502.5	-18.26	3.06	9.68	34.8	23.16	33.01	9.85	V
2535	-18.23	3.17	9.68	34.8	23.08	33.01	9.93	V
2567.5	-18.11	3.22	9.75	34.8	23.22	33.01	9.79	V

LTE FDD Band 7_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2505	-18.35	3.06	9.68	34.8	23.07	33.01	9.94	V
2535	-18.30	3.17	9.68	34.8	23.01	33.01	10.00	V
2565	-18.19	3.22	9.75	34.8	23.14	33.01	9.87	V

LTE FDD Band 7_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2507.5	-18.48	3.06	9.68	34.8	22.94	33.01	10.07	V
2535	-18.12	3.17	9.68	34.8	23.19	33.01	9.82	V
2562.5	-18.97	3.22	9.75	34.8	22.36	33.01	10.65	V

LTE FDD Band 7_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2510	-18.69	3.06	9.68	34.8	22.73	33.01	10.28	V
2535	-18.20	3.17	9.68	34.8	23.11	33.01	9.90	V
2560	-18.82	3.22	9.75	34.8	22.51	33.01	10.50	V

LTE FDD Band 7_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2502.5	-19.47	3.06	9.68	34.8	21.95	33.01	11.06	V
2535	-19.06	3.17	9.68	34.8	22.25	33.01	10.76	V
2567.5	-19.71	3.22	9.75	34.8	21.62	33.01	11.39	V

LTE FDD Band 7_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2505	-19.73	3.06	9.68	34.8	21.69	33.01	11.32	V
2535	-19.71	3.17	9.68	34.8	21.60	33.01	11.41	V
2565	-19.27	3.22	9.75	34.8	22.06	33.01	10.95	V

LTE FDD Band 7_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2507.5	-19.42	3.06	9.68	34.8	22.00	33.01	11.01	V
2535	-19.36	3.17	9.68	34.8	21.95	33.01	11.06	V
2562.5	-19.04	3.22	9.75	34.8	22.29	33.01	10.72	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2510	-19.22	3.06	9.68	34.8	22.20	33.01	10.81	V
2535	-19.58	3.17	9.68	34.8	21.73	33.01	11.28	V
2560	-19.06	3.22	9.75	34.8	22.27	33.01	10.74	V

LTE TDD Band 38_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2572.5	-18.19	4.34	6.88	36.20	20.55	33.01	-12.46	V
2595.0	-18.65	4.36	6.55	36.26	19.80	33.01	-13.21	V
2617.5	-18.02	4.47	6.35	36.50	20.36	33.01	-12.65	V

LTE TDD Band 38_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2575.0	-18.09	4.34	6.88	36.20	20.65	33.01	12.36	V
2595.0	-18.80	4.36	6.55	36.26	19.65	33.01	13.36	V
2615.0	-18.58	4.47	6.35	36.50	19.80	33.01	13.21	V

LTE TDD Band 38_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2577.5	-18.81	4.34	6.88	36.20	19.93	33.01	13.08	V
2595.0	-18.19	4.36	6.55	36.26	20.26	33.01	12.75	V
2612.5	-18.44	4.47	6.35	36.50	19.94	33.01	13.07	V

LTE TDD Band 38_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2580.0	-18.79	4.34	6.88	36.20	19.95	33.01	13.06	V
2595.0	-18.21	4.36	6.55	36.26	20.24	33.01	12.77	V
2610.0	-18.01	4.47	6.35	36.50	20.37	33.01	12.64	V

LTE TDD Band 38_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2572.5	-19.12	4.34	6.88	36.20	19.62	33.01	13.39	V
2595.0	-19.54	4.36	6.55	36.26	18.91	33.01	14.10	V
2617.5	-19.00	4.47	6.35	36.50	19.38	33.01	13.63	V

LTE TDD Band 38_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2575.0	-19.56	4.34	6.88	36.20	19.18	33.01	13.83	V
2595.0	-19.19	4.36	6.55	36.26	19.26	33.01	13.75	V
2615.0	-19.83	4.47	6.35	36.50	18.55	33.01	14.46	V

LTE TDD Band 38_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2577.5	-19.29	4.34	6.88	36.20	19.45	33.01	13.56	V
2595.0	-18.93	4.36	6.55	36.26	19.52	33.01	13.49	V
2612.5	-19.62	4.47	6.35	36.50	18.76	33.01	14.25	V

LTE TDD Band 38_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2580.0	-19.73	4.34	6.88	36.20	19.01	33.01	14.00	V
2595.0	-19.35	4.36	6.55	36.26	19.10	33.01	13.91	V
2610.0	-19.29	4.47	6.35	36.50	19.09	33.01	13.92	V

LTE TDD Band 40_Channel Bandwidth 5MHz_QPSK (lower)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2307.5	-18.83	3.04	7.68	34.20	20.01	33.01	13.00	V
2310.0	-18.72	3.15	7.68	34.26	20.07	33.01	12.94	V
2312.5	-18.29	3.20	7.57	34.32	20.40	33.01	12.61	V

LTE TDD Band 40_Channel Bandwidth 10MHz_QPSK (lower)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2310.0	-18.09	3.15	7.68	34.26	20.70	33.01	12.31	V

LTE TDD Band 40_Channel Bandwidth 5MHz_16QAM (lower)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2307.5	-18.60	3.04	7.68	34.20	20.24	33.01	12.77	V
2310.0	-18.84	3.15	7.68	34.26	19.95	33.01	13.06	V
2312.5	-18.29	3.20	7.57	34.32	20.40	33.01	12.61	V

LTE TDD Band 40_Channel Bandwidth 10MHz_16QAM (lower)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2310.0	-18.87	3.15	7.68	34.26	19.92	33.01	13.09	V

LTE TDD Band 40_Channel Bandwidth 5MHz_QPSK (upper)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2352.5	-19.78	3.04	7.68	34.20	19.06	33.01	13.95	V
2355.0	-19.17	3.15	7.68	34.26	19.62	33.01	13.39	V
2357.5	-19.67	3.20	7.57	34.32	19.02	33.01	13.99	V

LTE TDD Band 40_Channel Bandwidth 10MHz_QPSK (upper)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2355.0	-19.29	3.15	7.68	34.26	19.50	33.01	13.51	V

LTE TDD Band 40_Channel Bandwidth 5MHz_16QAM (upper)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2352.5	-18.98	3.04	7.68	34.20	19.86	33.01	13.15	V
2355.0	-19.62	3.15	7.68	34.26	19.17	33.01	13.84	V
2357.5	-19.25	3.20	7.57	34.32	19.44	33.01	13.57	V

LTE TDD Band 40_Channel Bandwidth 10MHz_16QAM (upper)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2355.0	-19.62	3.15	7.68	34.26	19.17	33.01	13.84	V

LTE TDD Band 41_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2498.5	-18.27	4.32	6.8	36.13	20.34	33.01	12.67	V
2593.0	-18.62	4.36	6.55	36.26	19.83	33.01	13.18	V
2687.5	-18.13	4.51	6.37	36.54	20.27	33.01	12.74	V

LTE TDD Band 41_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2501.0	-18.72	4.32	6.8	36.13	19.89	33.01	13.12	V
2593.0	-18.92	4.36	6.55	36.26	19.53	33.01	13.48	V
2685.0	-18.82	4.51	6.37	36.54	19.58	33.01	13.43	V

LTE TDD Band 41_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2503.5	-18.56	4.32	6.8	36.13	20.05	33.01	12.96	V
2593.0	-18.01	4.36	6.55	36.26	20.44	33.01	12.57	V
2682.5	-18.03	4.51	6.37	36.54	20.37	33.01	12.64	V

LTE TDD Band 41_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2506.0	-18.65	4.32	6.8	36.13	19.96	33.01	13.05	V
2593.0	-18.61	4.36	6.55	36.26	19.84	33.01	13.17	V
2680.0	-18.37	4.51	6.37	36.54	20.03	33.01	12.98	V

LTE TDD Band 41_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2498.5	-19.44	4.32	6.8	36.13	19.17	33.01	13.84	V
2593.0	-19.21	4.36	6.55	36.26	19.24	33.01	13.77	V
2687.5	-19.60	4.51	6.37	36.54	18.80	33.01	14.21	V

LTE TDD Band 41_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2501.0	-19.17	4.32	6.8	36.13	19.44	33.01	13.57	V
2593.0	-19.28	4.36	6.55	36.26	19.17	33.01	13.84	V
2685.0	-19.38	4.51	6.37	36.54	19.02	33.01	13.99	V

LTE TDD Band 41_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2503.5	-19.59	4.32	6.8	36.13	19.02	33.01	13.99	V
2593.0	-19.14	4.36	6.55	36.26	19.31	33.01	13.70	V
2682.5	-19.47	4.51	6.37	36.54	18.93	33.01	14.08	V

LTE TDD Band 41_Channel Bandwidth 20MHz_16QAM


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
2506.0	-19.02	4.32	6.8	36.13	19.59	33.01	13.42	V
2593.0	-19.05	4.36	6.55	36.26	19.40	33.01	13.61	V
2680.0	-19.48	4.51	6.37	36.54	18.92	33.01	14.09	V

4.2. Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
2. Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
3. Set the number of counts to a value that stabilizes the measured CCDF curve;
4. Set the measurement interval as follows:
 - 1). for continuous transmissions, set to 1 ms,
 - 2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
5. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

Remark: We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41; recorded worst case for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.

For E-UTRA Band 7, please refer to Appendix A: Section A.1

For E-UTRA Band 38, please refer to Appendix B: Section B.1

For E-UTRA Band 41, please refer to Appendix C: Section C.1


For E-UTRA Band 40, please refer to Appendix D: Section D.1

4.3. Occupied Bandwidth and Emission Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded. Set RBW was set to about 1% of emission BW, $VBW \geq 3$ times RBW.

-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

Remark: We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41; recorded worst case for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.

For E-UTRA Band 7, please refer to Appendix A: Section A.2

For E-UTRA Band 38, please refer to Appendix B: Section B.2

For E-UTRA Band 41, please refer to Appendix C: Section C.2

For E-UTRA Band 40, please refer to Appendix D: Section D.2

4.4. Band Edge compliance

LIMIT

For LTE FDD Band 7: Per FCC §27.53 (m)(4): For mobile digital stations, the attenuation factor shall be not less than:

- $40 + 10 \log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge,
- $43 + 10 \log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge, and
- $55 + 10 \log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB). [§ 27.53(m)(4)]


In addition, the attenuation factor (fixed limit) shall not be less than:

- $43 + 10 \log P$ dB on all frequencies between 2490.5 MHz and 2496 MHz, and
- $55 + 10 \log P$ dB at or below 2490.5 MHz. [§ 27.53(m)(4)]

For LTE TDD Band 38/40/41: Per §27.53 (m)(6) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed; for mobile digital stations, in the 1 megahertz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed, except when the 1 megahertz band is 2495 - 2496 MHz, in which case a resolution bandwidth of at least one percent may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 megahertz or 1 percent of emission bandwidth, as specified; or 1 megahertz or 2 percent for mobile digital stations, except in the band 2495 - 2496 MHz). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. With respect to television operations, measurements must be made of the separate visual and aural operating powers at sufficiently frequent intervals to ensure compliance with the rules.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. Show citation box.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output port was connected to base station.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.
3. Set EUT at maximum power through base station.
4. Select lowest and highest channels for each band and different modulation.
5. Measure Band edge using RMS (Average) detector by spectrum

TEST RESULTS

Remark: The EUT supports two SIM card SIM1 and SIM2. For GSM, the SIM 1 and SIM 2 both support GSM. For WCDMA/LTE, Only SIM 1 support WCDMA/LTE. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41; recorded worst case for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.

For E-UTRA Band 7, please refer to Appendix A: Section A.3

For E-UTRA Band 38, please refer to Appendix B: Section B.3

For E-UTRA Band 41, please refer to Appendix C: Section C.3

For E-UTRA Band 40, please refer to Appendix D: Section D.3

4.5. Spurious Emission on Antenna Port

LIMIT

For LTE FDD Band 7: Per FCC §27.53 (m)(4): For mobile digital stations, the attenuation factor shall be not less than:

- $40 + 10 \log P$ dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge,
- $43 + 10 \log P$ dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge, and
- $55 + 10 \log P$ dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB). [§ 27.53(m)(4)]

In addition, the attenuation factor (fixed limit) shall not be less than:


- $43 + 10 \log P$ dB on all frequencies between 2490.5 MHz and 2496 MHz, and
- $55 + 10 \log P$ dB at or below 2490.5 MHz. [§ 27.53(m)(4)]

For LTE TDD Band 38/40/41: Per §27.53 (m)(6) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed; for mobile digital stations, in the 1 megahertz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed, except when the 1 megahertz band is 2495 - 2496 MHz, in which case a resolution bandwidth of at least one percent may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 megahertz or 1 percent of emission bandwidth, as specified; or 1 megahertz or 2 percent for mobile digital stations, except in the band 2495 - 2496 MHz). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. With respect to television operations, measurements must be made of the separate visual and aural operating powers at sufficiently frequent intervals to ensure compliance with the rules.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. Show citation box.

For LTE FDD Band 66: Per § 27.53(h): For operations in the 1710 - 1780 MHz and 2110 - 2200 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- c. EUT Communicate with CMW500, then select a channel for testing.
- d. Add a correction factor to the display of spectrum, and then test.
- e. The resolution bandwidth of the spectrum analyzer was set sufficient scans were taken to show the out of band Emission if any up to 10th harmonic.
- f. Please refer to following tables for test antenna conducted emissions.

Working Frequency	Sub range (GHz)	RBW	VBW	Sweep time (s)
LTE FDD Band 7	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~1	1 MHz	3 MHz	Auto
	1~3	1 MHz	3 MHz	Auto
	3~26.5	1 MHz	3 MHz	Auto
LTE TDD Band 38	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~1	1 MHz	3 MHz	Auto
	1~3	1 MHz	3 MHz	Auto
	3~26.5	1 MHz	3 MHz	Auto
LTE TDD Band 41	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~1	1 MHz	3 MHz	Auto
	1~3	1 MHz	3 MHz	Auto
	3~26.5	1 MHz	3 MHz	Auto
LTE TDD Band 40	0.000009~0.000015	1KHz	3KHz	Auto
	0.000015~0.03	10KHz	30KHz	Auto
	0.03~1	1 MHz	3 MHz	Auto
	1~3	1 MHz	3 MHz	Auto
	3~26.5	1 MHz	3 MHz	Auto

TEST RESULTS

Remark: We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41; recorded worst case for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.

For E-UTRA Band 7, please refer to Appendix A: Section A.4

For E-UTRA Band 38, please refer to Appendix B: Section B.4

For E-UTRA Band 41, please refer to Appendix C: Section C.4

For E-UTRA Band 40, please refer to Appendix D: Section D.4

4.6. Radiated Spurious Emission

LIMIT

For LTE FDD Band 7: Per FCC §27.53 (m)(4): For mobile digital stations, the attenuation factor shall be not less than:

- 40+10logP dB (-10 dBm, 100 nW) on all frequencies between the channel edge and 5 MHz from the channel edge,
- 43+10logP dB (-13 dBm, 50 nW) on all frequencies between 5 MHz and X MHz from the channel edge, and
- 55+10logP dB (-25 dBm, 3 nW) on all frequencies more than X MHz from the channel edge, where X is the greater of 6 MHz or the actual emission bandwidth (26 dB). [§ 27.53(m)(4)]


In addition, the attenuation factor (fixed limit) shall not be less than:


- $43 + 10 \log P$ dB on all frequencies between 2490.5 MHz and 2496 MHz, and
- $55 + 10 \log P$ dB at or below 2490.5 MHz. [§ 27.53(m)(4)]

For LTE TDD Band 38/40/41: Per §27.53 (m)(6) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed; for mobile digital stations, in the 1 megahertz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed, except when the 1 megahertz band is 2495-2496 MHz, in which case a resolution bandwidth of at least one percent may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 megahertz or 1 percent of emission bandwidth, as specified; or 1 megahertz or 2 percent for mobile digital stations, except in the band 2495-2496 MHz). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. With respect to television operations, measurements must be made of the separate visual and aural operating powers at sufficiently frequent intervals to ensure compliance with the rules.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. Show citation box.

TEST CONFIGURATION





TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 meter. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} + G_a$$
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.
8. In order to make sure test results more clearly, we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
LTE FDD Band 7	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3

	18~20	1 MHz	3 MHz	2
	20~26	1 MHz	3 MHz	2
LTE TDD Band 38	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2
	20~26	1 MHz	3 MHz	2
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
LTE TDD Band 41	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2
	20~26	1 MHz	3 MHz	2
	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
LTE TDD Band 40	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2
	20~26	1 MHz	3 MHz	2

TEST LIMITS

According to 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Frequency	Channel	Frequency Range	Verdict
LTE FDD Band 7	Low	9KHz -26GHz	PASS
	Middle	9KHz -26GHz	PASS
	High	9KHz -26GHz	PASS
LTE TDD Band 38	Low	9KHz -26GHz	PASS
	Middle	9KHz -26GHz	PASS
	High	9KHz -26GHz	PASS
LTE TDD Band 41	Low	9KHz -26GHz	PASS
	Middle	9KHz -26GHz	PASS
	High	9KHz -26GHz	PASS
LTE TDD Band 40	Low	9KHz -26GHz	PASS
	Middle	9KHz -26GHz	PASS
	High	9KHz -26GHz	PASS

Radiated Measurement:

Remark:

1. We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41; recorded worst case for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.

2 EIRP=PMea(dBm)-Pcl(dB) +Ga(dBi)

3 We were not recorded other points as values lower than limits.

4 Margin = Limit – EIRP

LTE FDD Band 7_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5020.00	-55.90	5.11	3.00	13.38	-47.63	-25.00	22.63	H
7530.00	-55.63	6.02	3.00	13.98	-47.67	-25.00	22.67	H
5020.00	-58.14	5.11	3.00	13.38	-49.87	-25.00	24.87	V
7530.00	-52.80	6.02	3.00	13.98	-44.84	-25.00	19.84	V

LTE FDD Band 7_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070.00	-53.72	5.11	3.00	13.38	-45.45	-25.00	20.45	H
7605.00	-58.50	6.02	3.00	13.98	-50.54	-25.00	25.54	H
5070.00	-56.47	5.11	3.00	13.38	-48.20	-25.00	23.20	V
7605.00	-54.43	6.02	3.00	13.98	-46.47	-25.00	21.47	V

LTE FDD 7_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5120.00	-56.68	5.11	3.00	13.38	-48.41	-25.00	23.41	H
7680.00	-57.94	6.02	3.00	13.98	-49.98	-25.00	24.98	H
5120.00	-56.30	5.11	3.00	13.38	-48.03	-25.00	23.03	V
7680.00	-53.56	6.02	3.00	13.98	-45.60	-25.00	20.60	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5020.00	-56.96	5.11	3.00	13.38	-48.69	-25.00	23.69	H
7530.00	-56.44	6.02	3.00	13.98	-48.48	-25.00	23.48	H
5020.00	-59.84	5.11	3.00	13.38	-51.57	-25.00	26.57	V
7530.00	-55.27	6.02	3.00	13.98	-47.31	-25.00	22.31	V

LTE FDD Band 7_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5070.00	-54.73	5.11	3.00	13.38	-46.46	-25.00	21.46	H
7605.00	-57.55	6.02	3.00	13.98	-49.59	-25.00	24.59	H
5070.00	-56.49	5.11	3.00	13.38	-48.22	-25.00	23.22	V
7605.00	-52.92	6.02	3.00	13.98	-44.96	-25.00	19.96	V

LTE FDD 7_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5120.00	-55.21	5.11	3.00	13.38	-46.94	-25.00	21.94	H
7680.00	-57.99	6.02	3.00	13.98	-50.03	-25.00	25.03	H
5120.00	-59.06	5.11	3.00	13.38	-50.79	-25.00	25.79	V
7680.00	-55.95	6.02	3.00	13.98	-47.99	-25.00	22.99	V

LTE TDD Band 38_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5160.0	-54.03	7.10	3.00	9.78	-51.35	-25.00	26.35	H
7740.0	-53.65	8.32	3.00	10.86	-51.11	-25.00	26.11	H
5160.0	-48.46	7.10	3.00	9.78	-45.78	-25.00	20.78	V
7740.0	-53.44	8.32	3.00	10.86	-50.90	-25.00	25.90	V

LTE TDD Band 38_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5190.0	-51.79	7.10	3.00	9.78	-49.11	-25.00	24.11	H
7785.0	-52.82	8.32	3.00	10.86	-50.28	-25.00	25.28	H
5190.0	-49.25	7.10	3.00	9.78	-46.57	-25.00	21.57	V
7785.0	-52.65	8.32	3.00	10.86	-50.11	-25.00	25.11	V

LTE TDD Band 38_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5220.0	-53.56	7.10	3.00	9.78	-50.88	-25.00	25.88	H
7830.0	-51.03	8.32	3.00	10.86	-48.49	-25.00	23.49	H
5220.0	-48.50	7.10	3.00	9.78	-45.82	-25.00	20.82	V
7830.0	-55.85	8.32	3.00	10.86	-53.31	-25.00	28.31	V

LTE TDD Band 38_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5160.0	-54.19	7.10	3.00	9.78	-51.51	-25.00	26.51	H
7740.0	-53.15	8.32	3.00	10.86	-50.61	-25.00	25.61	H
5160.0	-48.32	7.10	3.00	9.78	-45.64	-25.00	20.64	V
7740.0	-53.78	8.32	3.00	10.86	-51.24	-25.00	26.24	V

LTE TDD Band 38_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5190.0	-52.02	7.10	3.00	9.78	-49.34	-25.00	24.34	H
7785.0	-50.42	8.32	3.00	10.86	-47.88	-25.00	22.88	H
5190.0	-49.87	7.10	3.00	9.78	-47.19	-25.00	22.19	V
7785.0	-52.95	8.32	3.00	10.86	-50.41	-25.00	25.41	V

LTE TDD Band 38_Channel Bandwidth 20MHz_16QAM_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5220.0	-51.83	7.10	3.00	9.78	-49.15	-25.00	24.15	H
7830.0	-52.78	8.32	3.00	10.86	-50.24	-25.00	25.24	H
5220.0	-49.18	7.10	3.00	9.78	-46.50	-25.00	21.50	V
7830.0	-55.06	8.32	3.00	10.86	-52.52	-25.00	27.52	V

LTE TDD Band 40_Channel Bandwidth 10MHz_QPSK_Middle Channel (lower)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
4620.0	-55.89	6.25	3.00	12.28	-49.86	-25.00	24.86	H
6390.0	-54.19	7.04	3.00	12.28	-48.95	-25.00	23.95	H
4620.0	-53.94	6.25	3.00	12.28	-47.91	-25.00	22.91	V
6390.0	-51.19	7.04	3.00	12.28	-45.95	-25.00	20.95	V

LTE TDD Band 40_Channel Bandwidth 10MHz_16QAM_Middle Channel (lower)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
4620.0	-51.26	6.25	3.00	12.28	-45.23	-25.00	20.23	H
6390.0	-53.27	7.04	3.00	12.28	-48.03	-25.00	23.03	H
4620.0	-55.84	6.25	3.00	12.28	-49.81	-25.00	24.81	V
6390.0	-53.73	7.04	3.00	12.28	-48.49	-25.00	23.49	V

LTE TDD Band 40_Channel Bandwidth 10MHz_QPSK_Middle Channel (upper)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
4710.0	-51.61	6.25	3.00	12.28	-45.58	-25.00	20.58	H
7065.0	-54.22	7.04	3.00	12.28	-48.98	-25.00	23.98	H
4710.0	-53.05	6.25	3.00	12.28	-47.02	-25.00	22.02	V
7065.0	-53.79	7.04	3.00	12.28	-48.55	-25.00	23.55	V

LTE TDD Band 40_Channel Bandwidth 10MHz_16QAM_Middle Channel (upper)

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
4710.0	-55.17	6.25	3.00	12.28	-49.14	-25.00	24.14	H
7065.0	-55.52	7.04	3.00	12.28	-50.28	-25.00	25.28	H
4710.0	-51.35	6.25	3.00	12.28	-45.32	-25.00	20.32	V
7065.0	-51.61	7.04	3.00	12.28	-46.37	-25.00	21.37	V

LTE TDD Band 41_Channel Bandwidth 20MHz_QPSK_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5012.0	-51.75	7.15	3.00	9.88	-49.02	-25.00	24.02	H
7518.0	-51.32	8.36	3.00	11.36	-48.32	-25.00	23.32	H
5012.0	-51.07	7.15	3.00	9.88	-48.34	-25.00	23.34	V
7518.0	-53.22	8.36	3.00	11.36	-50.22	-25.00	25.22	V

LTE TDD Band 41_Channel Bandwidth 20MHz_QPSK_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5186.0	-53.04	7.15	3.00	9.88	-50.31	-25.00	25.31	H
7779.0	-53.02	8.36	3.00	11.36	-50.02	-25.00	25.02	H
5186.0	-48.35	7.15	3.00	9.88	-45.62	-25.00	20.62	V
7779.0	-53.75	8.36	3.00	11.36	-50.75	-25.00	25.75	V

LTE TDD Band 41_Channel Bandwidth 20MHz_QPSK_High Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5360.0	-51.60	7.15	3.00	9.88	-48.87	-25.00	23.87	H
8040.0	-52.26	8.36	3.00	11.36	-49.26	-25.00	24.26	H
5360.0	-48.11	7.15	3.00	9.88	-45.38	-25.00	20.38	V
8040.0	-55.45	8.36	3.00	11.36	-52.45	-25.00	27.45	V

LTE TDD Band 41_Channel Bandwidth 20MHz_16QAM_Low Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5012.0	-54.31	7.15	3.00	9.88	-51.58	-25.00	26.58	H
7518.0	-53.03	8.36	3.00	11.36	-50.03	-25.00	25.03	H
5012.0	-51.53	7.15	3.00	9.88	-48.80	-25.00	23.80	V
7518.0	-54.67	8.36	3.00	11.36	-51.67	-25.00	26.67	V

LTE TDD Band 41_Channel Bandwidth 20MHz_16QAM_Middle Channel

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5186.0	-53.00	7.15	3.00	9.88	-50.27	-25.00	25.27	H
7779.0	-50.26	8.36	3.00	11.36	-47.26	-25.00	22.26	H
5186.0	-51.15	7.15	3.00	9.88	-48.42	-25.00	23.42	V
7779.0	-52.41	8.36	3.00	11.36	-49.41	-25.00	24.41	V

LTE TDD Band 41_Channel Bandwidth 20MHz_16QAM_High Channel


Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	Diatance	G _a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
5360.0	-51.24	7.15	3.00	9.88	-48.51	-25.00	23.51	H
8040.0	-51.95	8.36	3.00	11.36	-48.95	-25.00	23.95	H
5360.0	-51.69	7.15	3.00	9.88	-48.96	-25.00	23.96	V
8040.0	-52.70	8.36	3.00	11.36	-49.70	-25.00	24.70	V

4.7. Frequency Stability

LIMIT

According to §27.54, §2.1055 requirement, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation and should not exceed 2.5ppm.

TEST CONFIGURATION



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Frequency Stability Under Temperature Variations:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 4, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

Frequency Stability Under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Remark: We were tested all RB Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41; recorded worst case for each Channel Bandwidth of LTE FDD Band 7; LTE TDD Band 38; LTE TDD Band 40; LTE TDD Band 41.

LTE Band 7, QPSK, 5MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 7					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	-9	-0.0036	2.50	PASS
3.80	20	24	0.0096	2.50	PASS
4.20	20	17	0.0067	2.50	PASS
3.80	-30	7	0.0029	2.50	PASS
3.80	-20	16	0.0064	2.50	PASS
3.80	-10	2	0.0010	2.50	PASS
3.80	0	-11	-0.0043	2.50	PASS
3.80	10	29	0.0115	2.50	PASS
3.80	20	5	0.0020	2.50	PASS
3.80	30	-7	-0.0026	2.50	PASS
3.80	40	2	0.0010	2.50	PASS
3.80	50	24	0.0093	2.50	PASS

LTE Band 7, 16QAM, 5MHz bandwidth (worst case of all bandwidths and modulation type)

LTE FDD Band 7					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	21	0.0084	2.50	PASS
3.80	20	25	0.0097	2.50	PASS
4.20	20	27	0.0107	2.50	PASS
3.80	-30	20	0.0078	2.50	PASS
3.80	-20	4	0.0015	2.50	PASS
3.80	-10	-6	-0.0023	2.50	PASS
3.80	0	-4	-0.0014	2.50	PASS
3.80	10	31	0.0122	2.50	PASS
3.80	20	0	-0.0001	2.50	PASS
3.80	30	13	0.0051	2.50	PASS
3.80	40	28	0.0110	2.50	PASS
3.80	50	16	0.0061	2.50	PASS

LTE Band 38, 5MHz bandwidth, QPSK (worst case of all bandwidths)

LTE TDD Band 38					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	6	0.0022	2.50	PASS
3.80	20	-8	-0.0032	2.50	PASS
4.20	20	20	0.0075	2.50	PASS
3.80	-30	13	0.0050	2.50	PASS
3.80	-20	-5	-0.0020	2.50	PASS
3.80	-10	29	0.0110	2.50	PASS
3.80	0	29	0.0112	2.50	PASS
3.80	10	-9	-0.0036	2.50	PASS
3.80	20	28	0.0110	2.50	PASS
3.80	30	8	0.0030	2.50	PASS
3.80	40	-11	-0.0044	2.50	PASS
3.80	50	-3	-0.0010	2.50	PASS

LTE Band 38, 5MHz bandwidth, 16QAM (worst case of all bandwidths)

LTE TDD Band 38					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	11	0.0044	2.50	PASS
3.80	20	22	0.0083	2.50	PASS
4.20	20	22	0.0085	2.50	PASS
3.80	-30	26	0.0102	2.50	PASS
3.80	-20	34	0.0130	2.50	PASS
3.80	-10	6	0.0023	2.50	PASS
3.80	0	17	0.0066	2.50	PASS
3.80	10	13	0.0049	2.50	PASS
3.80	20	-14	-0.0056	2.50	PASS
3.80	30	19	0.0074	2.50	PASS
3.80	40	30	0.0115	2.50	PASS
3.80	50	-10	-0.0040	2.50	PASS

LTE Band 40, 5MHz bandwidth, QPSK (lower; worst case of all bandwidths)

LTE TDD Band 40					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	1	0.0002	2.50	PASS
3.80	20	-5	-0.0022	2.50	PASS
4.20	20	-12	-0.0051	2.50	PASS
3.80	-30	8	0.0037	2.50	PASS
3.80	-20	9	0.0037	2.50	PASS
3.80	-10	26	0.0112	2.50	PASS
3.80	0	30	0.0129	2.50	PASS
3.80	10	18	0.0077	2.50	PASS
3.80	20	3	0.0014	2.50	PASS
3.80	30	31	0.0133	2.50	PASS
3.80	40	3	0.0015	2.50	PASS
3.80	50	2	0.0010	2.50	PASS

LTE Band 40, 5MHz bandwidth, 16QAM (lower; worst case of all bandwidths)

LTE TDD Band 40					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	-6	-0.0028	2.50	PASS
3.80	20	4	0.0019	2.50	PASS
4.20	20	-11	-0.0048	2.50	PASS
3.80	-30	22	0.0095	2.50	PASS
3.80	-20	13	0.0058	2.50	PASS
3.80	-10	22	0.0097	2.50	PASS
3.80	0	-14	-0.0060	2.50	PASS
3.80	10	-5	-0.0020	2.50	PASS
3.80	20	-8	-0.0034	2.50	PASS
3.80	30	-12	-0.0052	2.50	PASS
3.80	40	4	0.0016	2.50	PASS
3.80	50	27	0.0116	2.50	PASS

LTE Band 40, 5MHz bandwidth, QPSK (upper; worst case of all bandwidths)

LTE TDD Band 40					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	14	0.0058	2.50	PASS
3.80	20	29	0.0124	2.50	PASS
4.20	20	32	0.0134	2.50	PASS
3.80	-30	10	0.0042	2.50	PASS
3.80	-20	7	0.0031	2.50	PASS
3.80	-10	22	0.0095	2.50	PASS
3.80	0	13	0.0054	2.50	PASS
3.80	10	-12	-0.0050	2.50	PASS
3.80	20	6	0.0026	2.50	PASS
3.80	30	-14	-0.0061	2.50	PASS
3.80	40	28	0.0119	2.50	PASS
3.80	50	-4	-0.0018	2.50	PASS

LTE Band 40, 5MHz bandwidth, 16QAM (upper; worst case of all bandwidths)

LTE TDD Band 40					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	-12	-0.0051	2.50	PASS
3.80	20	31	0.0131	2.50	PASS
4.20	20	5	0.0020	2.50	PASS
3.80	-30	18	0.0078	2.50	PASS
3.80	-20	29	0.0123	2.50	PASS
3.80	-10	22	0.0094	2.50	PASS
3.80	0	-13	-0.0054	2.50	PASS
3.80	10	-8	-0.0035	2.50	PASS
3.80	20	2	0.0008	2.50	PASS
3.80	30	20	0.0083	2.50	PASS
3.80	40	26	0.0110	2.50	PASS
3.80	50	30	0.0129	2.50	PASS


LTE Band 41, 5MHz bandwidth, QPSK (worst case of all bandwidths)

LTE TDD Band 41					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	16	0.0062	2.50	PASS
3.80	20	28	0.0108	2.50	PASS
4.20	20	-7	-0.0028	2.50	PASS
3.80	-30	-11	-0.0043	2.50	PASS
3.80	-20	25	0.0097	2.50	PASS
3.80	-10	10	0.0039	2.50	PASS
3.80	0	5	0.0020	2.50	PASS
3.80	10	-6	-0.0023	2.50	PASS
3.80	20	14	0.0054	2.50	PASS
3.80	30	21	0.0082	2.50	PASS
3.80	40	32	0.0124	2.50	PASS
3.80	50	-5	-0.0021	2.50	PASS

LTE Band 41, 5MHz bandwidth, 16QAM (worst case of all bandwidths)

LTE TDD Band 41					
DC Power	Temperature (°C)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
3.40	20	15	0.0057	2.50	PASS
3.80	20	-7	-0.0026	2.50	PASS
4.20	20	26	0.0099	2.50	PASS
3.80	-30	13	0.0050	2.50	PASS
3.80	-20	-9	-0.0036	2.50	PASS
3.80	-10	-7	-0.0028	2.50	PASS
3.80	0	10	0.0040	2.50	PASS
3.80	10	22	0.0086	2.50	PASS
3.80	20	28	0.0109	2.50	PASS
3.80	30	33	0.0127	2.50	PASS
3.80	40	-8	-0.0031	2.50	PASS
3.80	50	-7	-0.0027	2.50	PASS

5. Test Setup Photos of the EUT



6. External and Internal Photos of the EUT

Reference to the test report No. **GTS20211222005-1-4**

.....**End of Report**.....