

Qmini M series GIS Data Collection Operation Manual

I. Device Overview



- ① Touch Screen
- ② Communication Port
- ③ Keyboard
- ④ Camera
- ⑤ Belt Hole
- ⑥ Microphone

Note: When power on, press  to switch on/off backlight.

II. Turning the device on:

Hold  for 1 second to enter the power-on interface(figure 1),windows system will automatically load after releasing the power button, Windows system will get start within 10 seconds .

III. Hibernation:

When power on, short press  with 1 second, device will turn into hibernation, once again, awoken.

IV. Turning the device off:

Hold  over 3 seconds. And then click "Power Off" to close the device.



Figure 1: Splash Screen

V. Data Acquisition

① Install "Microsoft ActiveSync"

Please find this software from CDs in the package. Double click "MSASYNC45.exe" and install software

Qmini M series GIS Data Collection Operation Manual

following instruction. After successful installation, find and run the software on your Windows "Start"→ "Program" →"Microsoft ActiveSync". Tick "Allow USB connections" under "Connection Setting" of this software (Figure 2) .

② Hardware connection

Turn on the device and enter Windows system. Use data cable to connect device with PC (figure 3)



Figure 2: Connection setting



Figure 3: Connection

③ Software connection

After Cable connection, "Microsoft ActiveSync" will prompt "device is connecting", then system will pop-up the synchronous setup wizard, then choose "cancel"

④ Data Download

Click "Browse" in "Microsoft ActiveSync", open "My Windows mobile devices", and then enter "NandFlash" folder, you can finish the data download by copying the data to PC

Note: Data or new installed software must be save in NandFlash or MicroSD card, otherwise there is no record, after restarting.
