

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594

Email: ee.shenzhen@sgs.com

Report No.: SZEM140600335402

Page: 1 of 7

RF Exposure Evaluation Report

Application No.:	SZEM1406003354RF
Applicant:	Hi-Target Surveying Instrument Co., Ltd
Manufacturer:	Hi-Target Surveying Instrument Co., Ltd
Factory:	Hi-Target Surveying Instrument Co., Ltd
Product Name:	GNSS RTK
Model No.(EUT):	V60
Trade Mark:	Hi-Target
FCC ID:	O39ZHDV60
Standards:	47 CFR Part 1.1307(2013) 47 CFR Part 2.1093 (2013) KDB447498D01 General RF Exposure Guidance v05
Date of Receipt:	2014-09-11
Date of Test:	2014-10-16 to 2014-11-13
Date of Issue:	2014-11-20

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2014-11-20		Original

Authorized for issue by:			
Tested By	 (Chris Zhong) /Project Engineer		2014-11-13
Prepared By	 (Hedy Wen) /Clerk		2014-11-20
Checked By	 (Emen Li) /Reviewer		2014-11-24
			Date
			Date
			Date

3 Contents

	Page
1 COVER PAGE	1
2 VERSION.....	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST LOCATION	5
4.4 TEST FACILITY.....	5
4.5 DEVIATION FROM STANDARDS	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
5.1.1 <i>Limits</i>	6
5.1.2 <i>Test Procedure</i>	6
4.1.3 EUT RF EXPOSURE EVALUATION.....	7

4 General Information

4.1 Client Information

Applicant:	Hi-Target Surveying Instrument Co., Ltd
Address of Applicant:	Plant 202, BLDG 13, Tian'An HQ Center, No.555 North Panyu RD.Donghuan Block, Panyu District, 511400 Guangzhou, China
Manufacturer:	Hi-Target Surveying Instrument Co., Ltd
Address of Manufacturer:	Plant 202, BLDG 13, Tian'An HQ Center, No.555 North Panyu RD.Donghuan Block, Panyu District, 511400 Guangzhou, China
Factory:	Hi-Target Surveying Instrument Co., Ltd
Address of Factory:	Plant 202, BLDG 13, Tian'An HQ Center, No.555 North Panyu RD.Donghuan Block, Panyu District, 511400 Guangzhou, China

4.2 General Description of EUT

Product Name:	GNSS RTK	
Model No.:	V60	
Trade Mark:	Hi-Target	
Sample Type:	Fixed production	
EUT Function:	GNSS RTK	
Test Power Grade:	0(manufacturer declare)	
Test Software of EUT:	adb (manufacturer declare)	
Antenna Type:	Integral	
Antenna Gain:	For Bluetooth:2dBi For 2G 3G: :2dBi	
Power Supply:	AC/DC adapter:	Model: GM26-120200-D Input: AC 100~240 V 50/60Hz 1.0A Output: 12V 2.0A
	Battery:	Model: BL-5000 7.4V 5000mAh 3.7Wh Max Charging Voltage: 8.4V
USB Cable:	156cm (Shielded)	
DC Cable:	150cm (Shielded)	
Eight-core socket and protection plug:	138cm (Shielded)	
Five-core socket and protection plug:	202cm (Shielded)	
Single modular For 2G 3G:	FCC ID:RI7HE910NA	
Note: The AC/DC adapter is only for the battery charger		

4.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

Antenna Gain: 2dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.5849 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

For Bluetooth:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 100 cm (mW/cm ²)	Limit	Result
Highest	2480	3.92	2.466	0.000020	1.0	PASS

For GSM850:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 100 cm (mW/cm ²)	Limit	Result
Lowest	824.2	32.38	1729.816	0.000256	0.55	PASS

For GSM1900:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 100 cm (mW/cm ²)	Limit	Result
Lowest	1850.2	29.21	833.681	0.000248	1.0	PASS

For WCDMA850:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 100 cm (mW/cm ²)	Limit	Result
Lowest	846.6	26.43	439.542	0.000209	0.56	PASS

For WCDMA1900:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 100 cm (mW/cm ²)	Limit	Result
Lowest	1852.4	26.44	440.555	0.000226	1.0	PASS

Note: For Bluetooth please refer to report No. SZEM140600335401 for EUT test Max Conducted Peak Output Power value; for GSM&WCDMA please refer to **FCC ID :RI7HE910NA** for EUT test Max Conducted Output Power value.

The distance (4th column) calculated from the Friis transmission formula is far greater than 100 cm separation requirement.