

FCC TEST REPORT

for

47 CFR, Part 15, Subpart C

Equipment : Wireless Mouse

Model No. : PT-2003-B; PT-2000-MB1; M-RZ84

FCC ID : O3L-PT-00-MB1

Filing Type : Certification

Applicant : **Paten Wireless Technology Inc.**
4F, No. 50, Lane 10, Jihu Road, Neihu, Taipei 114,
Taiwan, R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

History of this test report.....	ii
CERTIFICATE OF COMPLIANCE.....	1
1. General Description of Equipment under Test.....	2
1.1. Applicant.....	2
1.2. Manufacturer	2
1.3. Basic Description of Equipment under Test	2
1.4. Feature of Equipment under Test	2
2. Test Configuration of Equipment under Test.....	3
2.1. Test Manner	3
2.2. Description of Test System	3
2.3. Band edge compliance plot per 15.227(b).	5
2.4. Connection Diagram of Test System	6
3. General Information of Test.....	7
3.1. Test Facility	7
3.2. Test Voltage	7
3.3. Standard for Methods of Measurement.....	7
3.4. Frequency Range Investigated	7
3.5. Frequency Range Investigated	7
3.6. Test Distance	7
4. Test of Conducted Powerline	8
5. Test of Radiated Emission.....	9
5.1. Major Measuring Instruments.....	9
5.2. Test Procedures.....	10
5.3. Typical Test Setup Layout of Radiated Emission.....	11
5.4. Test Result of Radiated Emission	12
6. EMI Suppression Component List.....	14
7. Antenna Factor & Cable Loss	15
8. List of Measuring Equipments Used	16
9. Uncertainty of Test Site	17

History of this test report

Original Report Issue Date: Feb. 14, 2003

☒ No additional attachment.

☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

CERTIFICATE OF COMPLIANCE

for

47 CFR, Part 15, Subpart C

Equipment : Wireless Mouse
Model No. : PT-2003-B; PT-2000-MB1; M-RZ84
FCC ID : O3L-PT-00-MB1
Filing Type : Certification
Applicant : **Paten Wireless Technology Inc.**
4F, No. 50, Lane 10, Jihu Road, Neihu, Taipei 114,
Taiwan, R.O.C.

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 1992** and the energy emitted by this equipment was **passed** both radiated and conducted emission limits. Testing was carried out on Jan. 24, 2003 at **SPORTON International Inc.** LAB.


K. J. Lin
Manager

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. General Description of Equipment under Test

1.1. Applicant

Paten Wireless Technology Inc.
4F, No. 50, Lane 10, Jihu Road, Neihu, Taipei 114, Taiwan, R.O.C.

1.2. Manufacturer

WEI FU MOLD PLASTIC & METAL FACTORY
Da-Ning Industrial Zone, Humen, Dongguan, Guangdong, CHINA

1.3. Basic Description of Equipment under Test

Equipment	: Wireless Mouse
Model No.	: PT-2003-B; PT-2000-MB1; M-RZ84
FCC ID	: O3L-PT-00-MB1
Trade Name	: Paten; Labtec
Power Supply Type	: From Battery (3V)
AC Power Cord	: N/A

1.4. Feature of Equipment under Test

- Channel (With Multi Task, Paten's Patent)
- Security ID: 256 Sets
- Cordless Technology: Radio Frequency (TDMA technology)
- Carry Frequency: 27.045MHz
- Modulation: FSK (Frequency Shift Key)
- Transfer Rate: 10 kbps
- Input Power: 3VDC (2*AAA)
- Rated Output Power Level (Max): 10 mA
- RF Power: 500uv/m at 3m
- Buttons: 2 Buttons, Scroll Button (3-Button Type)
- Encoder Technology: IR&PT
- Resolution: 400 CPI
- Indicator LED: 1 LED (Red, Blinking)
- Operation Switch: 1 Link Switch
- Effective Distance: 1.5M
- Battery Life: 2 Months

2. Test Configuration of Equipment under Test

2.1. Test Manner

- a. The EUT has been associated with peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The complete test system included HP PC, LOGITECH PS/2 Keyboard, HP Printer, ACEEX Modem, VIEWSONIC Monitor, Paten Wireless Mouse Receiver and EUT for EMI test.
- c. Frequency range investigated: radiation 30 MHz to 1000MHz.

2.2. Description of Test System

Support Unit 1. -- Personal Computer (HP)

FCC ID	: N/A
Model No.	: VECTRA VL420 DT
Power Supply Type	: Switching
Power Cord	: Non-Shielded
Serial No.	: SP0040
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

Support Unit 2. -- PS/2 Keyboard (LOGITECH)

FCC ID	: N/A
Model No.	: Y-SJ17
Serial No.	: SP0054
Data Cable	: Shielded, 1.7m
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

Support Unit 3. -- Printer (HP)

FCC ID	: B94C2642X
Model No.	: DJ 400
Power Supply Type	: Linear
Power Cord	: Non-Shielded
Serial No.	: SP0014
Data Cable	: Shielded, 360 degree via metal backshells, 1.35m

Support Unit 4. -- Modem (ACEEX)

FCC ID	: IFAXDM1414
Model No.	: DM1414
Power Supply Type	: Linear
Power Cord	: Non-Shielded
Serial No.	: SP0015
Data Cable	: Shielded, 360 degree via metal backshells, 1.15m

Support Unit 5. -- Monitor (VIEWSONIC)

FCC ID	: N/A
Model No.	: VCDTS21553-3P
Power Supply Type	: Switching
Power Cord	: Non-Shielded
Serial No.	: SP0013
Data Cable	: Shielded, 360 degree via metal backshells, 1.7m
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

Support Unit 6. -- Wireless Mouse Receiver (Paten)

FCC ID	: N/A
Model No.	: PT-2003-B
Remark	: This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

2.3. Band edge compliance plot per 15.227(b).

<HORIZONTAL>



<VERTICAL>




Mark 1: 26.96MHz

Mark 3: 27.28MHz

RBW:120KHz,VBW:300KHz

Conformation of the fundamental frequency

2.4. Connection Diagram of Test System



1. The I/O cable is connected from PC to the support unit 2.
2. The I/O cable is connected from PC to the support unit 3.
3. The I/O cable is connected from PC to the support unit 4.
4. The I/O cable is connected from PC to the support unit 5.

3. General Information of Test

3.1. Test Facility

Test Site Location : No. 52, Hwa Ya 1St Road, Hwa Ya Technology Park,
Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
TEL : 886-3-3273456
FAX : 886-3-3180055
Test Site No. : 03CH03-HY

3.2. Test Voltage

DC 3V

3.3. Standard for Methods of Measurement

ANSI C63.4-1992

3.4. Frequency Range Investigated

FCC Part 15, Subpart C

3.5. Frequency Range Investigated

a. Radiation: from 30 MHz to 1000 MHz

3.6. Test Distance

The test distance of radiated emission from antenna to EUT is 3 M.

4. Test of Conducted Powerline

The power supply of the EUT is from Battery.

So Conducted Powerline test is not applicable to this equipment.

5. Test of Radiated Emission

Radiated emissions from 30 MHz to 1 GHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 5.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.


5.1. Major Measuring Instruments

- Amplifier (HP 8447D)
 - RF Gain 30 dB
 - Signal Input 100 KHz to 1.3 GHz
- Spectrum Analyzer (R&S FSP)
 - Attenuation 10 dB
 - Start Frequency 30 MHz
 - Stop Frequency 1000 MHz
 - Resolution Bandwidth 120 KHz
 - Signal Input 9 KHz to 7 GHz

5.2. Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.

5.3. Typical Test Setup Layout of Radiated Emission



5.4. Test Result of Radiated Emission

- Test Distance: 3 M
- Temperature: 21°C
- Relative Humidity: 57 %
- Test Date: Jan. 24, 2003
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

■ The test was passed at the minimum margin that marked under gray area in the following table, and its antenna height is 1 m, turn table degree is 50°

- Spurious Emissions:

Frequency (MHz)	Polarity	Antenna Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits (dBuV/m)	(uV/m)	Emission Level (dBuV/m) (uV/m)		Margin (dB)	Detect Mode
108.300	H	9.62	1.99	7.93	43.50	149.62	19.54	9.48	-23.96	Peak
118.020	H	9.91	2.06	7.56	43.50	149.62	19.53	9.47	-23.97	Peak
162.300	H	7.91	2.45	9.55	43.50	149.62	19.91	9.90	-23.59	Peak
377.700	H	13.92	4.00	12.87	46.00	199.53	30.79	34.63	-15.21	Peak
405.000	H	14.71	4.12	14.00	46.00	199.53	32.83	43.80	-13.17	Peak
957.300	H	19.61	7.11	3.00	46.00	199.53	29.72	30.62	-16.28	Peak
108.300	V	9.62	1.99	4.49	43.50	149.62	16.10	6.38	-27.40	Peak
189.300	V	7.44	2.67	3.19	43.50	149.62	13.30	4.62	-30.20	Peak
243.300	V	11.25	3.11	3.10	46.00	199.53	17.46	7.46	-28.54	Peak
323.800	V	12.15	3.65	4.25	46.00	199.53	20.05	10.06	-25.95	Peak
377.700	V	13.92	4.00	5.11	46.00	199.53	23.03	14.17	-22.97	Peak
405.000	V	14.71	4.12	6.54	46.00	199.53	25.37	18.56	-20.63	Peak

- Field strength of fundamental and harmonics:

Frequency (MHz)	Antenna Polarity	Cable Factor	Reading Loss	Limits (dBuV)	Limits (dBuV/m)	Limits (uV/m)	Emission Level		Margin	Detect
		(dB/m)	(dB)	(dBuV)	(dBuV/m)	(uV/m)	(dBuV/m)	(uV/m)	(dB)	Mode
27.040	H	15.40	0.93	31.33	80.00	10000.00	47.66	241.55	-32.34	Peak
27.040	V	15.40	0.93	26.49	80.00	10000.00	42.82	138.36	-37.18	Peak

Test Engineer: 
Jay Zhong

6. EMI Suppression Component List

No EMI suppression components.

7. Antenna Factor & Cable Loss

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)
30	15.35	1.00
35	13.63	1.08
40	11.11	1.18
45	10.59	1.24
50	6.47	1.30
55	5.83	1.38
60	5.18	1.44
65	4.81	1.52
70	4.43	1.59
75	5.10	1.68
80	5.91	1.75
85	7.33	1.77
90	8.74	1.83
95	9.05	1.85
100	9.36	1.90
110	9.65	2.01
120	9.97	2.06
130	10.51	2.16
140	10.32	2.24
150	9.42	2.34
160	8.09	2.42
170	7.43	2.56
180	7.60	2.62
190	7.43	2.67
200	7.26	2.76
220	9.11	2.92
240	10.88	3.09
260	11.75	3.23
280	11.55	3.38
300	11.36	3.51
320	12.03	3.63
340	12.69	3.73
360	13.33	4.03
380	14.00	4.00
400	14.63	4.09
450	15.33	4.31
500	16.03	4.64
550	16.65	5.09
600	17.29	5.49
650	17.64	5.82
700	18.00	5.94
750	18.39	6.16
800	18.79	6.58
850	19.10	6.72
900	19.42	6.81
950	19.58	7.10
1000	19.75	7.41

8. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP7	838858/013	9KHz – 7GHz	Jan. 29, 2003	Radiation (03CH03-HY)
Amplifier	HP	8447D	2944A09072	100KHz – 1.3GHz	Oct. 21, 2002	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL6112B	2687	30MHz –2GHz	Dec. 21, 2002	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Half-wave dipole antenna	R&S	HZ12 HZ13	83924403 83924503	30MHz - 1GHz	Sep. 23, 2002	Radiation (03CH03-HY)

※ Calibration Interval of instruments listed above is one year.

9. Uncertainty of Test Site

Uncertainty of Radiated Emission Measurement

Contribution	Probability Distribution	3m
Antenna factor calibration	normal(k=2)	±1
cable loss calibration	normal(k=2)	±0.3
RCV/SPA specification	rectangular	±2
Antenna Directivity	rectangular	±3
Antenna Factor V.S. Height	rectangular	±2
Antenna Factor Interpolation for Frequency	rectangular	±0.25
site imperfection	rectangular	±2
Mismatch Receiver VSWR $\Gamma_1=0.09$ Antenna VSWR $\Gamma_2=0.67$ Uncertainty= $20\log(1-\Gamma_1\Gamma_2)$	U-shaped	±0.54
combined standard uncertainty $U_e(y)$	normal	±2.7
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	±5.4

$U = \sqrt{\{(1/2)^2 + (0.3/2)^2 + (2^2 + 0.5^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\}} = 2.2$ for 10m test distance

$U = \sqrt{\{(1/2)^2 + (0.3/2)^2 + (2^2 + 3^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\}} = 2.7$ for 3m test distance

Uncertainty of Conducted Emission Measurement

Contribution	Probability Distribution	150KHz – 30MHz
Cable and I/P attenuator calibration	normal(k=2)	±0.3
RCV/SPA specification	rectangular	±2
LISN coupling specification	rectangular	±1.5
Transducer factor frequency interpolation	rectangular	±0.2
Mismatch Receiver VSWR $\Gamma_1=0.09$ LISN VSWR $\Gamma_2=0.33$ Uncertainty= $20\log(1-\Gamma_1\Gamma_2)$	U-shaped	0.2
combined standard uncertainty $U_e(y)$	normal	±1.66
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	±3.32

$U = \sqrt{\{(0.3/2)^2 + (2^2 + 1.5^2 + 0.2^2)/3 + (0.2)^2/2\}} = 1.66$