

1.1 Applicable Standard

KDB 447498 D01 General RF Exposure Guidance v05

1.2 Specification Limits

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/150	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

NOTE: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The limit value 1.0mW/cm² is available for this EUT.

1.3 MPE Calculation Method

$$S = PG/(4 \pi R^2)$$

$$R = [PG/(4 \pi S)]^{0.5}$$

where: S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

(the measured power value see Report: F12124 Section 6.6)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

1.4 Calculated Result

2.4.1 Radio Frequency Radiation Exposure Evaluation

Frequency	Output Power to Antenna	Antenna Gain		Power Density	Limit
(MHz)	(mW)	(dBi)	(Numeric)	(mW/cm ²)	(mW/cm ²)
2405	2.37	-3	0.50	0.0002359	1.
2450	2.41	-3	0.50	0.0002398	1.
2480	2.43	-3	0.50	0.0002418	1.

Separation distance R= 20cm.

Frequency	Output Power to Antenna	Antenna Gain		Limit	Distance
(MHz)	(mW)	(dBi)	(Numeric)	(mW/cm ²)	(cm
2405	2.37	-3	0.50	1.0	0.3072
2450	2.41	-3	0.50	1.0	0.3097
2480	2.43	-3	0.50	1.0	0.3110

The antenna used for this transmitter must be installed to provide a separation distance of at least 0.3072cm from all persons.
