

EMV TESTHAUS

test report

Customer:
DewertOkin GmbH

Weststraße 1
32278 Kirchlengern
Germany
Tel.: +49 5223 979-0
Fax: +49 5223 751-82

RF test report

170062-AU01+W02



Industry Canada Industrie Canada

DewertOkin GmbH

control unit

CU170

(BLE mode)



The test result refers exclusively to the model tested.

This test report may not be copied or published in extracts without the written authorization of the accreditation agency and/or EMV TESTHAUS GmbH



EMV **TESTHAUS** GmbH

Gustav-Hertz-Straße 35
94315 Straubing
Germany
Tel.: +49 9421 56868-0
Fax: +49 9421 56868-100
Email: info@emv-testhaus.com

Accreditation:



FCC facility registration number: 221458
Test Firm Type "2.948 listed": Valid until 2017-07-12
Test Firm Type "accredited": Valid until 2017-06-09
MRA US-EU, FCC designation number: DE0010
BNetzA-CAB-02/21-02/04 Valid until 2018-11-27

Industry Canada test site numbers with registration expiry date:
3472A-1, expiring 2018-11-09
3472A-2, expiring 2018-11-12

Test laboratory:

EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

The technical accuracy is guaranteed through the quality management of
EMV TESTHAUS GmbH.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

Table of contents

1	Summary of test results	6
2	Referenced publications	8
3	Equipment under test (EUT)	9
4	Test configuration and mode of operation.....	10
4.1	Test configuration	10
4.2	Mode of operation.....	10
5	Measurement Procedures	11
5.1	AC power line conducted emissions 150 kHz to 30 MHz	11
5.2	20 dB bandwidth (DTS)	12
5.3	6 dB bandwidth (DTS)	12
5.4	Occupied bandwidth (99%).....	13
5.5	Maximum conducted output power (DTS).....	13
5.6	Power spectral density.....	14
5.7	Band-edge compliance (radiated)	15
5.8	Spurious radiated emissions 9 kHz to 10 th harmonic.....	15
5.9	Conducted emissions at antenna connector	15
5.10	Radiated emissions	16
6	Test results.....	20
6.1	AC power line conducted emissions 150 kHz to 30 MHz	21
6.2	20 dB bandwidth.....	26
6.3	6 dB bandwidth.....	29
6.4	Occupied bandwidth	32
6.5	Maximum conducted output power	35
6.6	Power spectral density.....	38
6.7	Band-edge compliance (radiated)	43
6.8	Spurious radiated emissions 9 kHz to 10th harmonic.....	49
6.9	Radio frequency radiation exposure evaluation for mobile devices	63
7	Equipment calibration status.....	68
8	Measurement uncertainties	69
9	Revision history	70
10	Additional documents	70



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

List of figures

Figure 1: Test setup for AC power line conducted emissions 150 kHz to 30 MHz	11
Figure 2: Setup for conducted emission test at antenna connector.....	15
Figure 3: Setup for radiated emission test below 30 MHz	16
Figure 4: Setup for radiated emission test from 30 MHz to 1 GHz	17
Figure 5: Setup for radiated emission test above 1 GHz.....	18
Figure 6: Chart of AC power line conducted emissions 150 kHz to 30 MHz – phase L1	22
Figure 7: Final results of AC power line conducted emissions 150 kHz to 30 MHz – phase L1.....	23
Figure 8: Chart of AC power line conducted emissions 150 kHz to 30 MHz – phase N.....	24
Figure 9: Final results of AC power line conducted emissions 150 kHz to 30 MHz – phase N	25
Figure 10: Chart of 20 dB bandwidth test, channel 0	27
Figure 11: Chart of 20 dB bandwidth test, channel 19	27
Figure 12: Chart of 20 dB bandwidth test, channel 39	28
Figure 13: Chart of 6 dB bandwidth test, channel 0	30
Figure 14: Chart of 6 dB bandwidth test, channel 19	30
Figure 15: Chart of 6 dB bandwidth test, channel 39	31
Figure 16: Chart of occupied bandwidth test, channel 0	33
Figure 17: Chart of occupied bandwidth test, channel 19	33
Figure 18: Chart of occupied bandwidth test, channel 39	34
Figure 19: Chart of carrier electric field strength, channel 0	36
Figure 20: Chart of carrier electric field strength, channel 19	36
Figure 21: Chart of carrier electric field strength, channel 39	37
Figure 22: Chart of carrier electric field strength / 3 kHz, channel 0 - complete carrier	39
Figure 23: Chart of carrier electric field strength / 3 kHz, channel 0 - zoom to maximum	39
Figure 24: Chart of carrier electric field strength / 3 kHz, channel 19 - complete carrier.....	40
Figure 25: Chart of carrier electric field strength / 3 kHz, channel 19 - zoom to maximum	40
Figure 26: Chart of carrier electric field strength / 3 kHz, channel 39 - complete carrier.....	41
Figure 27: Chart of carrier electric field strength / 3 kHz, channel 39 - zoom to maximum	41
Figure 28: Chart of band edge compliance test, lower band edge - PK	46
Figure 29: Chart of band edge compliance test, lower band edge - AV	46
Figure 30: Chart of band edge compliance test, upper band edge - PK.....	47
Figure 31: Chart of band edge compliance test, upper band edge - AV	47
Figure 32: Chart of spurious radiated emission test 9 kHz - 30 MHz, channel 0	51
Figure 33: Chart of spurious radiated emission test 9 kHz - 30 MHz, channel 19	52
Figure 34: Chart of spurious radiated emission test 9 kHz - 30 MHz, channel 39	52
Figure 35: Chart of spurious radiated emission test 30 MHz - 1 GHz, channel 0	53
Figure 36: Chart of spurious radiated emission test 30 MHz - 1 GHz, channel 19	55
Figure 37: Chart of spurious radiated emission test 30 MHz - 1 GHz, channel 39	57
Figure 38: 1 st Chart of spurious radiated emission test 1 GHz to 10 th harmonic, channel 0	60
Figure 39: 2 nd Chart of spurious radiated emission test 1 GHz to 10 th harmonic, channel 0	60
Figure 40: 1 st Chart of spurious radiated emission test 1 GHz to 10 th harmonic, channel 19.....	61
Figure 41: 2 nd Chart of spurious radiated emission test 1 GHz to 10 th harmonic, channel 19	61
Figure 42: 1 st Chart of spurious radiated emission test 1 GHz to 10 th harmonic, channel 39.....	62
Figure 43: 2 nd Chart of spurious radiated emission test 1 GHz to 10 th harmonic, channel 39	62



List of tables

Table 1: Devices used for testing	10
Table 2: Ports of EUT and appropriate cables	10
Table 3: Final results of 20 dB bandwidth test	28
Table 4: Final results of 6 dB bandwidth test	31
Table 5: Final results of occupied bandwidth test	34
Table 6: Final results of maximum conducted output power test.....	37
Table 7: Final results of power spectral density test	42
Table 8: Final result of band edge compliance test, lower band edge	48
Table 9: Final result of band edge compliance test, upper band edge	48
Table 10: Final result of spurious radiated emission test 30 MHz - 1 GHz, channel 0	54
Table 11: Final result of spurious radiated emission test 30 MHz - 1 GHz, channel 19	56
Table 12: Final result of spurious radiated emission test 30 MHz - 1 GHz, channel 39	58
Table 13: Final result of spurious radiated emission test 1 GHz to 10 th harmonic, channel 0	60
Table 14: Final result of spurious radiated emission test 1 GHz to 10 th harmonic, channel 19	61
Table 15: Final result of spurious radiated emission test 1 GHz to 10 th harmonic, channel 39	62
Table 16: Limits for maximum permissible exposure (MPE) according to table 1 of §1.1310(e).....	64
Table 17: RF field strength limits according to table 4 of RSS-102	64
Table 18: Calculated results @ 2402.0 MHz compared to RF field strength limits	66
Table 19: Equipment calibration status	68
Table 20: Measurement uncertainty	69



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

1 Summary of test results

System type: Digital transmission system (DTS)

<i>47 CFR part and section</i>	<i>Test</i>	<i>Equivalent to IC radio standard(s)</i>	<i>Page</i>	<i>Result</i>	<i>Note(s)</i>
15.207	AC power line conducted emissions 150 kHz to 30 MHz	RSS-Gen Issue 4, section 8.8	21	Passed	---
15.247(a)(1) KDB 558074, section 8	20 dB bandwidth	RSS-247 Issue 2, section 5.1(b)	26	Passed	---
15.247(a)(2) KDB 558074, section 8	6 dB bandwidth	RSS-247 Issue 2, section 5.2(a)	29	Passed	1
2.202(a) ANSI C63.10	Occupied bandwidth (99 %)	RSS-Gen Issue 4, section 6.6	32	For reference only	1
15.247(b) KDB 558074, section 9	Maximum conducted output power	RSS-Gen Issue 4, section 6.12 RSS-247 Issue 2, section 5.4	35	Passed	---
15.247(e) KDB 558074, section 10	Power spectral density	RSS-247 Issue 2, section 5.2(b)	38	Passed	---
15.247(d) KDB 558074, sections 11 & 12	Antenna-port conducted measurements	RSS-247 Issue 2, section 5.5	---	Passed	2
15.247(d) KDB 558074, section 13	Band-edge compliance (radiated)	RSS-247 Issue 2, section 5.5	43	Passed	---
15.247(d) KDB 558074, sections 11 & 12	Spurious radiated emissions 9 kHz to 10 th harmonic	RSS-Gen Issue 4, section 6.13 RSS-247 Issue 2, section 5.5	49	Passed	---
2.1091	RF exposure evaluation for mobile devices	RSS-Gen Issue 4, section 3.2 (exempted from SAR and RF evaluation)	63	Passed	---

Notes:

- 1 For systems using digital modulation techniques the 6 dB bandwidth (DTS bandwidth) is regarded as the occupied bandwidth.
- 2 Spurious radiated emissions 9 kHz to 10th harmonic performed



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

Straubing, May 2, 2017



Martin Müller
Test engineer
EMV **TESTHAUS** GmbH



Rainer Heller
Head of EMC / radio department
EMV **TESTHAUS** GmbH



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

2 Referenced publications

Publication	Title
CFR 47 Part 2 October 2016	Code of Federal Regulations, Title 47 (Telecommunication), Part 2 (Frequency allocation and radio treaty matters; General rules and regulations) of the Federal Communication Commission (FCC)
CFR 47 Part 15 October 2016	Code of Federal Regulations, Title 47 (Telecommunication), Part 15 (Radio Frequency Devices) of the Federal Communication Commission (FCC)
KDB Publication no. 412172 August 7, 2015	Guidelines for determining the Effective Radiated Power (ERP) and Equivalent Isotropically Radiated Power (EIRP) of an RF transmitting system
KDB Publication no. 447498 October 23, 2015	RF exposure procedures and equipment authorization policies for mobile and portable devices
KDB Publication no. 558074 April 8, 2016	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
ANSI C63.10 June 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
RSS-Gen, Issue 4 November 2014	Spectrum Management and Telecommunications - Radio Standards Specification - General Requirements for Compliance of Radio Apparatus
RSS-102, Issue 5 March 2015	Spectrum Management and Telecommunications - Radio Standards Specification - Radio Frequency Exposure Compliance of Radiocommunications Apperatus
RSS-247, Issue 2 February 2017	Spectrum Management and Telecommunications - Radio Standards Specification - Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

3 Equipment under test (EUT)

Product type: control unit
Model name: CU170
Serial number(s): 123456 0007
Applicant: DewertOkin GmbH
Manufacturer: DewertOkin GmbH
Version: Hardware: ----
Software: ----
Additional modifications: None
FCC ID: O3YCU170
IC registration number: 10744A-CU170
Application frequency band: 2400.0 MHz - 2483.5 MHz
Frequency range: 2402.0 MHz - 2480.0 MHz
Operating frequencies: 2402.0 MHz - 2480.0 MHz
Channel spacing: 2 MHz
Number of RF channels: 37 data channels
3 advertising channels
System type: Digital transmission system (DTS)
Modulation type(s): GFSK
Class of emission: F1D
Antenna type(s): PCB antenna (F-Antenna layouted)
Antenna gain(s): approximately 0 dBi
Power supply: DC supply
Nominal voltage: 24 V
Minimum voltage: 24 V
Maximum voltage: 29 V
Nominal frequency: ---
Temperature range: 0 °C to +40 °C
Device type: Portable Mobile Fixed



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

4 Test configuration and mode of operation

4.1 Test configuration

Device	Type designation	Serial or inventory no.	Manufacturer
<i>EUT</i>			
control unit	CU170	123456 0007	DewertOkin GmbH
<i>Peripheral devices</i>			
Power supply EUT	PD12	Z56014285301601448	Phoenix Mecano
Notebook	Lifebook A531	E00521	Fujitsu
Power supply notebook	ADP-65JH AD	S26113-E557-V55-01	Fujitsu
AC power supply (120V / 60Hz)	61602	ABP000000730	Chroma ATE

Table 1: Devices used for testing

Port	Classification	Cable type	Cable length	
			used	maximum ¹
DC power	dc power	Shielded	1.5 m	---
USB (mounted for test purposes only)	signal/control	Shielded	1.5 m	---

Table 2: Ports of EUT and appropriate cables

4.2 Mode of operation

EUT was tested in following mode(s) of operation:

BLE mode

Channel 0 -> 2402.0 MHz (unmodulated)
Channel 19 -> 2440.0 MHz (unmodulated)
Channel 39 -> 2480.0 MHz (unmodulated)

Channel 0 -> 2402.0 MHz (modulated -> PRBS9, 37byte)
Channel 19 -> 2440.0 MHz (modulated -> PRBS9, 37byte)
Channel 39 -> 2480.0 MHz (modulated -> PRBS9, 37byte)

Applied Software: NRFgo studio

¹ As specified by applicant



5 Measurement Procedures

5.1 AC power line conducted emissions 150 kHz to 30 MHz




Figure 1: Test setup for AC power line conducted emissions 150 kHz to 30 MHz

The AC power line conducted emissions test method refers to section 6.2 of ANSI C63.10 and shall be as follows.

The tests of conducted emission is carried out in a shielded room using a line impedance stabilization network (LISN) 50 μ H/50 Ohms and a EMI test receiver. The EMI test receiver is connected to the LISN and set to a measurement bandwidth of 9 kHz in the frequency range from 0.15 MHz to 30 MHz. The EUT is placed on a wooden table and connected to the LISN.

To accelerate the measurement the detector of the EMI test receiver is set to peak. A prescan is performed covering the whole frequency range from 0.15 MHz to 30 MHz. After that all peak values with less margin than 10 dB to quasi-peak limit or exceeding the limit are marked and re-measured with quasi-peak detector. If all values are below the average limit no additional measurement is necessary. In case of there are values between quasi-peak and average limit these values are re-measured using an average detector.

All peripheral devices are additionally decoupled by means of a line stabilization network.

5.2 20 dB bandwidth (DTS)

The 20 dB bandwidth test method for DTS systems shall be analog to the 6 dB bandwidth test method for DTS systems.

For test setup see clause 5.10.

5.3 6 dB bandwidth (DTS)

The 6 dB bandwidth (DTS bandwidth) test method for DTS systems refers to section 8.0 of KDB 558074 D01 and shall be as follows.

Spectrum analyzer settings:

Span = centered on a channel, wide enough to capture the whole channel

RBW = 100 kHz

VBW \geq 3 x RBW

Sweep time = auto coupled

Detector function = peak

Trace mode = max hold

Reference level: more than $10\log(\text{OBW}/\text{RBW})$ dB above peak of spectral envelope

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

If possible, use the automatic bandwidth measurement capability of the spectrum analyzer using the X dB bandwidth mode with X set to 6 dB. Submit this plot(s).

In case of antenna-port conducted tests cannot be performed on an EUT (e.g., portable or handheld devices with integral antenna), then according to section 3.0 of KDB 558074 D01 radiated tests are performed for demonstrating compliance.

For test setup see clause 5.10.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

5.4 Occupied bandwidth (99%)

The occupied bandwidth test method refers to section 6.9.3 of ANSI C63.10 and shall be as follows.

Spectrum analyzer settings:

Span = between 1.5 times and 5.0 times of the OBW, centered on a channel

RBW \geq in the range of 1% to 5% of the OBW

VBW \geq approximately three times the RBW

Sweep time = auto coupled

Detector function = peak

Trace mode = max hold

Reference level: more than $10\log(\text{OBW}/\text{RBW})$ dB above peak of spectral envelope

Use the 99% power bandwidth function of the spectrum analyzer and report the measured bandwidth.

In case of antenna-port conducted tests cannot be performed on an EUT (e.g., portable or handheld devices with integral antenna), then according to section 3.0 of KDB 558074 D01 radiated tests are performed for demonstrating compliance.

For test setup see clause 5.10.

5.5 Maximum conducted output power (DTS)

The maximum conducted output power test method for DTS systems refers to section 9.1.1 of KDB 558074 D01 and shall be as follows.

Spectrum analyzer settings:

Span $\geq 3 \times$ RBW, centered on a channel

RBW \geq DTS bandwidth

VBW $\geq 3 \times$ RBW

Sweep time = auto coupled

Detector function = peak

Trace mode = max hold

Reference level: more than $10\log(\text{OBW}/\text{RBW})$ dB above peak of spectral envelope

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the maximum conducted output power. Submit this plot(s).

In case of antenna-port conducted tests cannot be performed on an EUT (e.g., portable or handheld devices with integral antenna), then according to section 3.0 of KDB 558074 D01 radiated tests are performed for demonstrating compliance to the conducted emission requirements.

The radiated field strength or power level is then converted to EIRP according to annex G of ANSI C63.10. The equivalent conducted output power is then determined by subtracting the EUT transmit antenna gain from the EIRP (assuming logarithmic representation).

For test setup see clause 5.10.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

5.6 Power spectral density

The power spectral density test method refers to section 10.2 of KDB 558074 D01 and shall be as follows.

Spectrum analyzer settings:

Span = 1.5 times the DTS bandwidth, centered on a channel

RBW: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$

VBW $\geq 3 \times \text{RBW}$

Sweep time = auto coupled or $\geq \text{span}/\text{RBW}$ in seconds, whichever is greater

Detector function = peak

Trace mode = max hold

Reference level: more than $10\log(\text{OBW}/\text{RBW})$ dB above peak of spectral envelope

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the power spectral density. Submit this plot(s).

In case of antenna-port conducted tests cannot be performed on an EUT (e.g., portable or handheld devices with integral antenna), then according to section 3.0 of KDB 558074 D01 radiated tests are performed for demonstrating compliance to the conducted emission requirements.

The radiated field strength or power level is then converted to EIRP according to annex G of ANSI C63.10. The equivalent power spectral density is then determined by subtracting the EUT transmit antenna gain from the EIRP (assuming logarithmic representation).

For test setup see clause 5.10.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

5.7 Band-edge compliance (radiated)

For test setup and test method see clause 5.10.

5.8 Spurious radiated emissions 9 kHz to 10th harmonic

For test setup and test method see clause 5.10.

5.9 Conducted emissions at antenna connector




Figure 2: Setup for conducted emission test at antenna connector

The RF signal of the EUT is measured at the antenna connector. In case of no permanent antenna connector, a temporary antenna connector is supplied by the manufacturer. The specific insertion loss of the signal path, which is matched to 50 Ohm, is evaluated within a calibration. The test receiver is set to analyzer mode with pre-selector activated. The measurement readings on the test receiver are corrected by the signal path loss.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

5.10 Radiated emissions

5.10.1 Radiated emissions below 30 MHz




Figure 3: Setup for radiated emission test below 30 MHz

The test method for radiated emissions below 30 MHz refers to section 6.4 of ANSI C63.10 and shall be as follows:

1. EUT is configured according to ANSI C63.10. It is placed on the turntable 0.8 meter above ground. The receiving antenna is located 3 meters from the EUT. The test setup is placed inside a compact diagnostic chamber.
2. EUT and all peripherals are powered on.
3. The loop antenna is set in parallel with the antenna of the EUT.
4. The EMI receiver performs a scan from 9 kHz to 30 MHz with peak detector and measurement bandwidth set to 200 Hz for frequencies up to 150 kHz and 9 or 10 kHz for frequencies above.
5. The turn table is rotated to 8 different positions ($360^\circ / 8$).
6. The antenna is set in line with the antenna of the EUT and steps 4 and 5 are repeated.
7. Then the test setup is placed in an OATS with 3 m distance and all peak values over the limit or with less margin than 10 dB are marked and re-measured with a quasi-peak detector except for the frequency bands 9 to 90 kHz and 110 to 490 kHz, where average detector applies.
8. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
9. The highest value for each frequency is recorded.

5.10.2 Radiated emissions from 30 MHz to 1 GHz




Figure 4: Setup for radiated emission test from 30 MHz to 1 GHz

The test method for radiated emissions from 30 MHz to 1 GHz refers to section 6.5 of ANSI C63.10 and shall be as follows:

1. EUT is configured according to ANSI C63.10. It is placed on the turntable 0.8 meter above ground. The receiving antenna is located 3 meters from the EUT. The test setup is placed inside a compact diagnostic chamber.
2. EUT and all peripherals are powered on.
3. The broadband antenna is set to vertical polarization.
4. The EMI receiver performs a scan from 30 MHz to 1000 MHz with peak detector and measurement bandwidth set to 120 kHz.
5. The turn table is rotated to 6 different positions ($360^\circ / 6$).
6. The antenna polarization is changed to horizontal and steps 4 and 5 are repeated.
7. Then the test setup is placed in an OATS at 3 m distance and all peak values over the limit or with less margin than 10 dB are marked and re-measured with a quasi-peak detector.
8. The turntable is rotated by 360 degrees to determine the position of the highest radiation.
9. The height of the broadband receiving antenna is varied between 1 meter and 4 meters above ground to find the maximum emission field strength of both horizontal and vertical polarization.
10. The highest value for each frequency is recorded.



5.10.3 Radiated emissions above 1 GHz




Figure 5: Setup for radiated emission test above 1 GHz

The test method for radiated emissions above 1 GHz refers to section 6.6 of ANSI C63.10 and shall be as follows:

1. EUT is configured according to ANSI C63.10. It is placed on the turntable 1.5 meter above ground. The test setup is placed inside a semi-anechoic chamber with RF absorbers on the floor.
2. EUT and all peripherals are powered on.
3. To identify the critical frequencies, extrapolatory radiated emission tests are performed at a closer distance than 3 meters (e.g. 1 meter). The critical frequencies found are noted.
4. For pre-scan the receiving antenna is located 3 meters from the EUT.
5. The broadband horn antenna is set to vertical polarization.
6. The EMI receiver performs a scan from 1 GHz to the 10th harmonic of the fundamental frequency with peak and average detector activated simultaneously and measurement bandwidth set to 1 MHz. The trace data is recorded using the max hold function.
7. The turntable is rotated in steps of 15°.
8. After a full turn by 360° the antenna polarization is changed to horizontal and steps 4 and 5 are repeated.
9. After the scan all peak values over the limit or with less margin than 10 dB are marked. If critical frequencies recorded during extrapolatory radiated emission tests are not contained, they are added to this list.
10. Emission levels at listed frequencies are maximized by moving the turntable and varying the antenna height until maximum of emission is found.
11. The turntable is rotated by 360 degrees to determine the position of the highest radiation.

12. The height of the broadband receiving antenna is varied between 1 meter and the upper height above ground to find the maximum emission field strength of both horizontal and vertical polarization. For equipment that is tested in multiple orientations, the upper height is limited to 2.5 meters or 0.5 meters above the top of the EUT, whichever is higher. For all other equipment the upper height is 4 meters.
13. The highest value for each frequency is recorded.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6 Test results

This clause gives details about the test results as collected in the summary of test results on page 6.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.1 AC power line conducted emissions 150 kHz to 30 MHz

47 CFR part and section: 15.207
Equivalent to IC radio standard(s) RSS-Gen Issue 4, section 8.8
Measurement procedure: See 5.1

Performed by:	Martin Müller	Date of test:	April 4, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.1.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> Shielded room	P92007	Siemens Matsushita	E00107
<input type="checkbox"/> EMI test receiver	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input checked="" type="checkbox"/> EMI test receiver	ESCS 30	Rohde & Schwarz	E00003
<input checked="" type="checkbox"/> Artificial mains network	ESH2-Z5	Rohde & Schwarz	E00004
<input checked="" type="checkbox"/> Artificial mains network	ESH2-Z5	Rohde & Schwarz	E00005
<input checked="" type="checkbox"/> Attenuator (10 dB)	50FHB-010-10	JFW Industries	E00471
<input checked="" type="checkbox"/> Measurement software	E10	ib comPLAN	E00443

6.1.2 Limits

Frequency [MHz]	Quasi-peak [dB μ V]	Average [dB μ V]
0.15 – 0.5	66 – 56	56 – 46
0.5 – 5.0	56	46
5 – 30	60	50



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.1.3 Test results

Frequency range	Step size	IF Bandwidth	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
150 kHz – 30 MHz	4 kHz	9 kHz	PK	AV	1 ms	1 s	off
150 kHz – 30 MHz	4 kHz	9 kHz	PK	QPK	1 ms	1 s	off




Figure 6: Chart of AC power line conducted emissions 150 kHz to 30 MHz – phase L1



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

Interference Voltage Test

Freq. [MHz]	U_CISPR [dB μ V]	Limit [dB μ V]	delta_U [dB]	U_AV [dB μ V]	Limit [dB μ V]	delta_U [dB]	Corr. [dB]	Remark
0,16	42,5	65,3	22,8	10,2	55,3	45,1	0,0	
0,18	38,3	64,4	26,1	25,1	54,4	29,3	0,0	
0,20	37,5	63,6	26,2	18,2	53,6	35,4	0,0	
0,22	35,0	62,9	27,9	15,7	52,9	37,2	0,0	
0,23	28,3	62,6	34,3	10,5	52,6	42,1	0,0	
0,24	33,9	62,1	28,3	4,1	52,1	48,0	0,0	
0,26	29,4	61,5	32,1	13,4	51,5	38,1	0,0	
0,26	25,3	61,4	36,1	18,7	51,4	32,7	0,0	
0,29	25,6	60,4	34,8	-2,4	50,4	52,7	0,0	
0,31	23,9	60,0	36,1	20,4	50,0	29,6	0,0	
0,35	23,0	59,0	36,1	15,0	49,0	34,0	0,0	
0,38	18,6	58,2	39,6	1,8	48,2	46,4	0,0	
0,49	20,1	56,1	36,1	14,7	46,1	31,5	0,0	
0,59	20,6	56,0	35,5	10,7	46,0	35,3	0,0	
0,67	26,7	56,0	29,3	25,5	46,0	20,5	0,0	
0,88	20,6	56,0	35,4	17,8	46,0	28,2	0,0	
0,98	18,2	56,0	37,8	13,5	46,0	32,5	0,0	
1,06	10,1	56,0	45,9	-0,5	46,0	46,5	0,0	
1,27	21,7	56,0	34,3	19,1	46,0	26,9	0,0	
1,36	22,0	56,0	34,0	19,2	46,0	26,8	0,0	
1,45	20,2	56,0	35,8	11,9	46,0	34,1	0,0	
1,55	19,5	56,0	36,5	2,9	46,0	43,1	0,0	
1,95	13,9	56,0	42,1	3,6	46,0	42,4	0,0	
2,14	19,4	56,0	36,6	5,3	46,0	40,7	0,0	
3,40	19,9	56,0	36,1	11,2	46,0	34,8	0,0	
3,59	19,2	56,0	36,8	8,2	46,0	37,8	0,0	
4,08	19,3	56,0	36,7	6,2	46,0	39,8	0,0	
4,10	20,2	56,0	35,8	9,4	46,0	36,6	0,0	
4,79	20,2	56,0	35,9	13,5	46,0	32,5	0,0	
13,99	22,3	60,0	37,7	6,5	50,0	43,5	0,0	
14,14	23,6	60,0	36,4	8,5	50,0	41,5	0,0	
14,75	23,5	60,0	36,5	8,7	50,0	41,3	0,0	
16,82	19,3	60,0	40,7	9,3	50,0	40,7	0,0	


Figure 7: Final results of AC power line conducted emissions 150 kHz to 30 MHz – phase L1



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

Interference Voltage Test



REGULATIONS:

47 CFR, 15.207

PEAK / CISPR / AV

TEST EQUIPMENT:

R&S ESCS30 (E00003)

R&S ESH2-Z5 (E00004)

ORDER NO.:

170062-AU01+W02

EUT:

DewertOkin GmbH

control unit

CU170

12345 6 0007

OPERATION MODE:

channel sweep

PRBS 9, 37byte

Mains 120V AC /60Hz

Neutral

TEST FACILITY:

EMV TESTHAUS GmbH

Gustav-Hertz-Straße 35

94315 Straubing

DATE / TIME:

2017-04-07 12:01:34

TEST ENGINEER:

Martin Müller

StoSp_N_E10

Figure 8: Chart of AC power line conducted emissions 150 kHz to 30 MHz – phase N



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

Interference Voltage Test

Freq. [MHz]	U_CISPR [dB μ V]	Limit [dB μ V]	delta_U [dB]	U_AV [dB μ V]	Limit [dB μ V]	delta_U [dB]	Corr. [dB]	Remark
0,15	41,1	66,0	24,9	10,4	56,0	45,6	0,0	
0,16	42,4	65,3	22,9	11,0	55,3	44,3	0,0	
0,16	42,0	65,3	23,3	8,4	55,3	46,9	0,0	
0,17	41,8	65,1	23,3	9,8	55,1	45,3	0,0	
0,18	40,0	64,4	24,4	25,7	54,4	28,7	0,0	
0,20	37,6	63,6	26,0	18,2	53,6	35,4	0,0	
0,22	35,5	62,9	27,5	13,7	52,9	39,2	0,0	
0,29	26,8	60,4	33,6	-0,5	50,4	51,0	0,0	
0,31	25,7	59,9	34,2	19,5	49,9	30,4	0,0	
0,35	17,5	58,9	41,4	12,4	48,9	36,5	0,0	
0,51	20,7	56,0	35,3	2,0	46,0	44,1	0,0	
0,59	20,2	56,0	35,8	7,4	46,0	38,6	0,0	
0,67	24,3	56,0	31,7	22,8	46,0	23,2	0,0	
0,94	17,9	56,0	38,2	-0,8	46,0	46,8	0,0	
1,28	21,0	56,0	35,0	18,7	46,0	27,3	0,0	
1,37	20,2	56,0	35,8	14,7	46,0	31,3	0,0	
1,45	19,4	56,0	36,6	8,2	46,0	37,8	0,0	
1,53	18,8	56,0	37,2	4,3	46,0	41,8	0,0	
2,01	17,1	56,0	38,9	11,0	46,0	35,1	0,0	
2,45	19,7	56,0	36,3	8,7	46,0	37,3	0,0	
3,06	19,1	56,0	36,9	3,6	46,0	42,4	0,0	
4,09	19,5	56,0	36,5	6,9	46,0	39,1	0,0	
4,68	18,6	56,0	37,4	10,6	46,0	35,4	0,0	
13,63	21,8	60,0	38,2	8,3	50,0	41,7	0,0	
14,39	23,9	60,0	36,1	7,8	50,0	42,2	0,0	
14,74	24,2	60,0	35,8	9,5	50,0	40,5	0,0	
15,18	20,9	60,0	39,1	9,0	50,0	41,0	0,0	
15,47	20,2	60,0	39,8	9,4	50,0	40,6	0,0	

Figure 9: Final results of AC power line conducted emissions 150 kHz to 30 MHz – phase N



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.2 20 dB bandwidth

47 CFR part and section: 15.247 (a)(1)
Equivalent to IC radio standard(s) RSS-247 Issue 2, section 5.1(b)
Measurement procedure (DTS): See 5.2

Performed by:	Martin Müller	Date of test:	April 21, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.2.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input type="checkbox"/> Laboratory environment	---	---	---
<input checked="" type="checkbox"/> Anechoic Chamber (AC)	---	EMV TESTHAUS	E00100
<input type="checkbox"/> EMI test receiver	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052

6.2.2 Limits for digital transmission systems

None -> results recorded for information only.



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.2.3 Test results




Figure 10: Chart of 20 dB bandwidth test, channel 0




Figure 11: Chart of 20 dB bandwidth test, channel 19



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 12: Chart of 20 dB bandwidth test, channel 39

f [MHz]	20dB-BW [MHz]	f _{lower} [MHz]	f _{upper} [MHz]	Lower band edge [MHz]	Upper band edge [MHz]	Result
2401.970	1.278	2401.336	2402.614	2400.0	2483.5	within band
2439.960	1.258	2439.336	2440.594	2400.0	2483.5	within band
2479.965	1.243	2479.336	2480.579	2400.0	2483.5	within band

Table 3: Final results of 20 dB bandwidth test



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

DewertOkin GmbH
 control unit
CU170
 (BLE mode)

6.3 6 dB bandwidth

47 CFR part and section: 15.247 (a)(2)
Equivalent to IC radio standard(s) RSS-247 Issue 2, section 5.2(a)
Measurement procedure (DTS): See 5.3

Performed by:	Martin Müller	Date of test:	April 21, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.3.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input type="checkbox"/> Laboratory environment	---	---	---
<input checked="" type="checkbox"/> Anechoic Chamber (AC)	---	EMV TESTHAUS	E00100
<input type="checkbox"/> EMI test receiver	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052

6.3.2 Limits for digital transmission systems

The minimum 6 dB bandwidth shall be at least 500 kHz.

In addition the 6 dB bandwidth must be contained within the designated frequency band.



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.3.3 Test results




Figure 13: Chart of 6 dB bandwidth test, channel 0




Figure 14: Chart of 6 dB bandwidth test, channel 19



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 15: Chart of 6 dB bandwidth test, channel 39

f [MHz]	6dB-BW [MHz]	f _{lower} [MHz]	f _{upper} [MHz]	Lower band edge [MHz]	Upper band edge [MHz]	Result
2401.965	0.699	2401.595	2402.295	2400.0	2483.5	Pass
2439.955	0.709	2439.595	2440.305	2400.0	2483.5	Pass
2479.965	0.689	2479.605	2480.295	2400.0	2483.5	Pass

Table 4: Final results of 6 dB bandwidth test



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

DewertOkin GmbH
 control unit
CU170
 (BLE mode)

6.4 Occupied bandwidth

47 CFR part and section: 2.202 (a)
Equivalent to IC radio standard(s) RSS-Gen Issue 4, section 6.6
Measurement procedure: See 5.4

Performed by:	Martin Müller	Date of test:	April 21, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.4.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input type="checkbox"/> Laboratory environment	---	---	---
<input checked="" type="checkbox"/> Anechoic Chamber (AC)	---	EMV TESTHAUS	E00100
<input type="checkbox"/> EMI test receiver	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052

6.4.2 Limits

None -> results recorded for setting the proper reference level.



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.4.3 Test results




Figure 16: Chart of occupied bandwidth test, channel 0




Figure 17: Chart of occupied bandwidth test, channel 19



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 18: Chart of occupied bandwidth test, channel 39

f [MHz]	Occ. BW [MHz]	f _{lower} [MHz]	f _{upper} [MHz]	Lower band edge [MHz]	Upper band edge [MHz]	Result
2401.965	1.194	2401.376	2402.569	2400.0	2483.5	within band
2439.960	1.284	2439.321	2440.604	2400.0	2483.5	within band
2479.955	1.304	2479.316	2480.619	2400.0	2483.5	within band

Table 5: Final results of occupied bandwidth test



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

DewertOkin GmbH
 control unit
CU170
 (BLE mode)

6.5 Maximum conducted output power

47 CFR part and section: 15.247 (b)
Equivalent to IC radio standard(s) RSS-Gen Issue 4, section 6.12
RSS-247 Issue 2, section 5.4
Measurement procedure (DTS): See 5.5

Performed by:	Martin Müller	Date of test:	April 21, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.5.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input type="checkbox"/> Laboratory environment	---	---	---
<input checked="" type="checkbox"/> Anechoic Chamber (AC)	---	EMV TESTHAUS	E00100
<input type="checkbox"/> EMI test receiver	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052

6.5.2 Limits for digital transmission systems

1 watt (30 dBm).



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.5.3 Test results




Figure 19: Chart of carrier electric field strength, channel 0




Figure 20: Chart of carrier electric field strength, channel 19



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

DewertOkin GmbH
 control unit
CU170
 (BLE mode)




Figure 21: Chart of carrier electric field strength, channel 39

Calculation of EIRP according to ANSI C63.10, sections 11.3 and annex G with derived formula as noted in section 12.7.3:

$$\text{EIRP[dBm]} = \text{E[dB}\mu\text{V/m]} + 20 \cdot \log(\text{d}_{\text{measure}}[\text{m}]) - 104.77$$

$$\text{With } \text{d}_{\text{measure}} = 3 \text{ m} \Rightarrow \text{EIRP[dBm]} = \text{E[dB}\mu\text{V/m]} - 95.23$$

Calculation of “maximum conducted output power”:

$$\text{Maximum conducted output power[dBm]} = \text{EIRP[dBm]} - g[\text{dBi}]$$

f [MHz]	E _{meas} [dB μ V/m]	EUT position	Polarization	EIRP [dBm]	g [dBi]	Maximum conducted output power [dBm]	Limit [dBm]	Result
2402.000	96.40	1	H	1.17	0	1.17	30.0	Pass
2440.000	95.46	1	H	0.23	0	0.23	30.0	Pass
2480.000	95.22	1	H	-0.01	0	-0.01	30.0	Pass

Table 6: Final results of maximum conducted output power test



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.6 Power spectral density

47 CFR part and section: 15.247 (e)
Equivalent to IC radio standard(s) RSS-247 Issue 2, section 5.2(b)
Measurement procedure: See 5.6

Performed by:	Martin Müller	Date of test:	April 21, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.6.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input type="checkbox"/> Laboratory environment	---	---	---
<input checked="" type="checkbox"/> Anechoic Chamber (AC)	---	EMV TESTHAUS	E00100
<input type="checkbox"/> EMI test receiver	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052

6.6.2 Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.6.3 Test results




Figure 22: Chart of carrier electric field strength / 3 kHz, channel 0 - complete carrier




Figure 23: Chart of carrier electric field strength / 3 kHz, channel 0 - zoom to maximum



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

DewertOkin GmbH
 control unit
CU170
 (BLE mode)




Figure 24: Chart of carrier electric field strength / 3 kHz, channel 19 - complete carrier




Figure 25: Chart of carrier electric field strength / 3 kHz, channel 19 - zoom to maximum



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 26: Chart of carrier electric field strength / 3 kHz, channel 39 - complete carrier




Figure 27: Chart of carrier electric field strength / 3 kHz, channel 39 - zoom to maximum



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

DewertOkin GmbH
 control unit
CU170
 (BLE mode)

Calculation of EIRP according to ANSI C63.10, sections 11.3 and annex G with derived formula as noted in section 12.7.3:

$$\text{EIRP[dBm]} = \text{E[dB}\mu\text{V/m]} + 20 \cdot \log(\text{d}_{\text{measure}}[\text{m}]) - 104.77$$

$$\text{With } \text{d}_{\text{measure}} = 3 \text{ m} \Rightarrow \text{EIRP[dBm]} = \text{E[dB}\mu\text{V/m]} - 95.23$$

Calculation of “power spectral density”:

$$\text{Power spectral density[dBm / 3 kHz]} = \text{EIRP[dBm]} - \text{g[dBi]}$$

f [MHz]	E _{meas} [dB μ V/m]	EUT position	Polarization	EIRP [dBm]	g [dBi]	Power spectral density [dBm / 3 kHz]	Limit [dBm / 3 kHz]	Result
2401.948	83.56	1	H	-11.67	0	-11.67	8.0	Pass
2439.947	82.59	1	H	-12.64	0	-12.64	8.0	Pass
2479.948	82.45	1	H	-12.78	0	-12.78	8.0	Pass

Table 7: Final results of power spectral density test



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.7 Band-edge compliance (radiated)

47 CFR part and section: 15.247 (d)
Equivalent to IC radio standard(s) RSS-247 Issue 2, section 5.5
Measurement procedure: See 5.7

Performed by:	Martin Müller	Date of test:	April 21, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.7.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input type="checkbox"/> Compact Diagnostic Chamber (CDC)	VK041.0174	Albatross Projects	E00026
<input type="checkbox"/> Open Area Test Site (OATS)	---	EMV TESTHAUS	E00354
<input type="checkbox"/> Semi Anechoic Chamber (SAC)	---	Albatross Projects	E00716
<input checked="" type="checkbox"/> Anechoic Chamber (AC)	---	EMV TESTHAUS	E00100
<input type="checkbox"/> EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00001
<input type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/> EMI test receiver (SAC)	ESR 7	Rohde & Schwarz	E00739
<input type="checkbox"/> EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00552
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input type="checkbox"/> Preamplifier	AMF-5D-00501800	Miteq	W00089
<input type="checkbox"/> Preamplifier	AMF-6F-16002650	Miteq	W00090
<input type="checkbox"/> Loop antenna	HFH2-Z2	Rohde & Schwarz	E00060
<input type="checkbox"/> TRILOG broadband antenna (CDC)	VULB 9163	Schwarzbeck	E00012
<input type="checkbox"/> TRILOG broadband antenna (OATS)	VULB 9163	Schwarzbeck	E00013
<input type="checkbox"/> TRILOG broadband antenna (SAC)	VULB 9162	Schwarzbeck	E00643
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052
<input type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00053
<input type="checkbox"/> Horn antenna	BBHA 9170	Schwarzbeck	W00055
<input type="checkbox"/> Measurement software	E10	ib comPLAN	E00443
<input type="checkbox"/> Measurement software	EMC 32	Rohde & Schwarz	E00777



EMV TESTHAUS GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.7.2 Limits

- < -20 dBc outside restricted bands
- < 54 dB μ V/m (average detector) inside restricted bands
- < 74 dB μ V/m (peak detector) inside restricted bands



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.7.3 Test results

Test distance: Prescan: 1 m 3 m m
Final scan: 3 m 10 m m
Polarisation: horizontal vertical
EUT Position: Position 1 Position 2 Position 3

Frequency range	Step size	IF Band-width	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
2.30 GHz – 2.51 GHz	250 kHz	1 MHz	PK	PK	100 ms	100 ms	30 dB
2.30 GHz – 2.51 GHz	250 kHz	1 MHz	AV	AV	100 ms	100 ms	30 dB



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 28: Chart of band edge compliance test, lower band edge - PK




Figure 29: Chart of band edge compliance test, lower band edge - AV



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 30: Chart of band edge compliance test, upper band edge - PK




Figure 31: Chart of band edge compliance test, upper band edge - AV



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

f[MHz]	E _{meas} [dBμV/m]	Detector	Restricted Band	Limit [dBμV/m]	Result
2310.000	52.00	PK	Yes	74	Pass
2310.000	38.86	AV		54	Pass
2333.250	62.58	PK		74	Pass
2333.250	39.51	AV		54	Pass
2389.500	63.15	PK		74	Pass
2389.500	39.79	AV		54	Pass
2402.000	96.40	PK	No	----	Carrier
2402.000	92.25	AV		----	Carrier

Table 8: Final result of band edge compliance test, lower band edge

f[MHz]	E _{meas} [dBμV/m]	Detector	Restricted Band	Limit [dBμV/m]	Result
2480.000	95.39	PK	No	----	Carrier
2480.000	91.24	AV		----	Carrier
2483.500	57.99	PK	Yes	74	Pass
2483.500	39.88	AV		54	Pass
2491.500	56.58	PK		74	Pass
2491.500	39.25	AV		54	Pass
2500.000	58.25	PK		74	Pass
2500.000	39.21	AV		54	Pass

Table 9: Final result of band edge compliance test, upper band edge



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.8 Spurious radiated emissions 9 kHz to 10th harmonic

47 CFR part and section: 15.247 (d)
Equivalent to IC radio standard(s) RSS-Gen Issue 4, section 6.13
RSS-247 Issue 2, section 5.5
Measurement procedure: See 5.8

Performed by:	Martin Müller	Date of test:	April 21, 2017
Result	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.8.1 Test equipment

Type	Designation	Manufacturer	Inventory no.
<input checked="" type="checkbox"/> Compact Diagnostic Chamber (CDC)	VK041.0174	Albatross Projects	E00026
<input checked="" type="checkbox"/> Open Area Test Site (OATS)	---	EMV TESTHAUS	E00354
<input type="checkbox"/> Semi Anechoic Chamber (SAC)	---	Albatross Projects	E00716
<input checked="" type="checkbox"/> Anechoic Chamber (AC)	---	EMV TESTHAUS	E00100
<input checked="" type="checkbox"/> EMI test receiver (CDC)	ESCI 3	Rohde & Schwarz	E00001
<input checked="" type="checkbox"/> EMI test receiver	ESU 26	Rohde & Schwarz	W00002
<input type="checkbox"/> EMI test receiver (SAC)	ESR 7	Rohde & Schwarz	E00739
<input checked="" type="checkbox"/> EMI test receiver (OATS)	ESCI 3	Rohde & Schwarz	E00552
<input checked="" type="checkbox"/> EMI test receiver	ESW 44	Rohde & Schwarz	E00895
<input type="checkbox"/> Preamplifier	AMF-5D-00501800	Miteq	W00089
<input checked="" type="checkbox"/> Preamplifier	AMF-6F-16002650	Miteq	W00090
<input checked="" type="checkbox"/> Loop antenna	HFH2-Z2	Rohde & Schwarz	E00060
<input checked="" type="checkbox"/> TRILOG broadband antenna (CDC)	VULB 9163	Schwarzbeck	E00012
<input checked="" type="checkbox"/> TRILOG broadband antenna (OATS)	VULB 9163	Schwarzbeck	E00013
<input type="checkbox"/> TRILOG broadband antenna (SAC)	VULB 9162	Schwarzbeck	E00643
<input checked="" type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00052
<input type="checkbox"/> Horn antenna	BBHA 9120D	Schwarzbeck	W00053
<input checked="" type="checkbox"/> Horn antenna	BBHA 9170	Schwarzbeck	W00054
<input checked="" type="checkbox"/> Measurement software	E10	ib comPLAN	E00443
<input type="checkbox"/> Measurement software	EMC 32	Rohde & Schwarz	E00777



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.8.2 Limits < 1 GHz

Frequency [MHz]	Field strength F_s [μ V/m]	Field strength [dB μ V/m]	Measurement distance d [m]
0.009 – 0.490	266.6 – 4.9	48.5 – 13.8	300
0.490 – 1.705	48.98 – 14.08	33.8 – 22.97	30
1.705 – 30.0	30	29.54	30
30 – 88	100	40	3
88 – 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

Recalculation factor is determined according to ANSI C63.10, section 6.4.4.2 “Extrapolation from the measurement of a single point”:

$$d_{\text{near field}} = 47.77 / f_{\text{MHz}}, \text{ or}$$

$$f_{\text{MHz}} = 47.77 / d_{\text{near field}}$$

The frequency f_{MHz} at which the near field distance is equal to the limit and/or test distance is important for selection of the right formula for determining the recalculation factor:

$$f_{\text{MHz}}(300 \text{ m}) \approx 0.159 \text{ MHz}$$

$$f_{\text{MHz}}(30 \text{ m}) \approx 1.592 \text{ MHz}$$

$$f_{\text{MHz}}(3 \text{ m}) \approx 15.923 \text{ MHz}$$

For $9 \text{ kHz} \leq f \leq 159 \text{ kHz}$ and $490 \text{ kHz} < f \leq 1.592 \text{ MHz}$:

$$\text{Recalculation factor} = -40 \log(d_{\text{limit}} / d_{\text{measure}})$$

For $159 \text{ kHz} < f \leq 490 \text{ kHz}$ and $1.592 \text{ MHz} < f \leq 15.923 \text{ MHz}$:

$$\text{Recalculation factor} = -40 \log(d_{\text{near field}} / d_{\text{measure}}) - 20 \log(d_{\text{limit}} / d_{\text{near field}})$$

For $f > 15.923 \text{ MHz}$:

$$\text{Recalculation factor} = -20 \log(d_{\text{limit}} / d_{\text{measure}})$$

The limits in the graphics and value lists are derived from the general radiated emission limits as specified in 15.209 using the recalculation factor as described above.

6.8.3 Limits > 1 GHz

< -20 dBc outside restricted bands

< 54d B μ V/m (average detector) inside restricted bands

< 74d B μ V/m (peak detector) inside restricted bands



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.8.4 Test results from 9 kHz to 30 MHz

Test distance: Prescan: 3 m
 Final scan: 3 m 10 m m
 Polarisation: parallel in line angle:°
 EUT Position: Position 1 Position 2 Position 3

Frequency range	Step size	IF Bandwidth	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
9 kHz – 90 kHz	80 Hz	200 Hz	PK	AV	1 ms	1 s	off
90 kHz – 110 kHz	80 Hz	200 Hz	PK	QPK	1 ms	1 s	off
110 kHz – 150 kHz	80 Hz	200 Hz	PK	AV	1 ms	1 s	off
150 kHz – 490 kHz	4 kHz	9 kHz	PK	AV	1 ms	1 s	off
490 kHz – 30 MHz	4 kHz	9 kHz	PK	QPK	1 ms	1 s	off




Figure 32: Chart of spurious radiated emission test 9 kHz - 30 MHz, channel 0



EMV **TESTHAUS** GmbH
 Gustav-Hertz-Straße 35
 94315 Straubing
 Germany

DewertOkin GmbH
 control unit
CU170
 (BLE mode)




Figure 33: Chart of spurious radiated emission test 9 kHz - 30 MHz, channel 19




Figure 34: Chart of spurious radiated emission test 9 kHz - 30 MHz, channel 39



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.8.5 Test results from 30 MHz to 1 GHz

Test distance: Prescan: 3 m
 Final scan: 3 m 10 m m
 Polarisation: horizontal vertical
 EUT Position: Position 1 Position 2 Position 3

Frequency range	Step size	IF Band-width	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
30 MHz – 1 GHz	60 kHz	120 kHz	PK	QPK	1 ms	1 s	20 dB




Figure 35: Chart of spurious radiated emission test 30 MHz - 1 GHz, channel 0



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

f [MHz]	E _{final} [dBµV/m]	Limit [dBµV/m]	Height [cm]	TT [°]	Polarisation	Result
32.64	27.19	40.00	116	0	V	Pass
47.88	31.76	40.00	105	313	V	Pass
58.08	28.23	40.00	116	128	V	Pass
69.78	23.30	40.00	103	320	V	Pass
168.30	34.29	43.52	100	138	H	Pass
180.18	27.97	43.52	100	359	H	Pass
192.84	35.77	43.52	100	107	H	Pass
215.70	32.29	43.52	100	251	H	Pass
232.38	26.37	46.02	100	106	V	Pass
240.00	35.03	46.02	100	98	H	Pass
249.12	33.91	46.02	100	54	H	Pass
265.56	32.66	46.02	100	46	H	Pass
279.12	33.52	46.02	100	85	H	Pass
289.32	24.63	46.02	100	32	V	Pass
313.68	30.74	46.02	100	31	V	Pass
348.54	40.15	46.02	112	11	V	Pass
383.40	34.28	46.02	100	11	V	Pass
419.82	28.26	46.02	100	358	V	Pass
487.92	32.84	46.02	100	356	V	Pass
558.72	26.73	46.02	100	36	H	Pass
570.78	24.15	46.02	100	95	H	Pass
629.76	25.18	46.02	100	133	V	Pass
699.84	28.05	46.02	100	58	H	Pass
734.70	24.41	46.02	100	47	H	Pass
766.68	27.91	46.02	100	48	H	Pass

Table 10: Final result of spurious radiated emission test 30 MHz - 1 GHz, channel 0



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 36: Chart of spurious radiated emission test 30 MHz - 1 GHz, channel 19

 <p>EMV TESTHAUS GmbH Gustav-Hertz-Straße 35 94315 Straubing Germany</p>	<p>DewertOkin GmbH control unit CU170 (BLE mode)</p>

f [MHz]	E _{final} [dBµV/m]	Limit [dBµV/m]	Height [cm]	TT [°]	Polarisation	Result
32.10	29.51	40.00	106	101	V	Pass
48.00	32.17	40.00	130	211	V	Pass
57.78	27.72	40.00	106	98	V	Pass
167.82	35.52	43.52	121	125	H	Pass
192.84	35.83	43.52	100	116	H	Pass
215.46	34.42	43.52	100	260	H	Pass
241.92	33.20	46.02	100	78	H	Pass
266.52	32.10	46.02	100	48	H	Pass
278.88	34.30	46.02	100	84	H	Pass
288.18	31.03	46.02	100	19	H	Pass
314.88	30.40	46.02	100	26	V	Pass
348.54	38.53	46.02	104	20	V	Pass
384.84	33.46	46.02	100	6	V	Pass
399.84	29.52	46.02	100	7	V	Pass
418.20	27.62	46.02	100	360	V	Pass
489.78	31.34	46.02	100	354	V	Pass
627.24	24.52	46.02	100	332	H	Pass
697.02	31.24	46.02	100	34	V	Pass
734.76	25.50	46.02	100	40	V	Pass
769.74	27.67	46.02	100	49	H	Pass
836.34	25.76	46.02	100	50	H	Pass

Table 11: Final result of spurious radiated emission test 30 MHz - 1 GHz, channel 19



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 37: Chart of spurious radiated emission test 30 MHz - 1 GHz, channel 39



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

f [MHz]	E _{final} [dBµV/m]	Limit [dBµV/m]	Height [cm]	TT [°]	Polarisation	Result
31.80	32.75	40.00	106	45	V	Pass
36.00	29.13	40.00	104	104	V	Pass
37.02	29.79	40.00	106	103	V	Pass
48.12	31.36	40.00	108	229	V	Pass
57.78	29.40	40.00	108	115	V	Pass
167.82	24.81	43.52	100	136	H	Pass
191.88	36.27	43.52	108	105	H	Pass
216.84	36.80	46.02	100	360	H	Pass
233.22	28.82	46.02	199	156	V	Pass
243.36	33.97	46.02	100	61	H	Pass
265.62	32.18	46.02	100	52	H	Pass
279.60	33.55	46.02	100	97	H	Pass
288.00	31.35	46.02	100	29	H	Pass
348.54	37.77	46.02	108	262	H	Pass
384.84	33.57	46.02	100	13	V	Pass
398.34	28.83	46.02	100	5	V	Pass
489.84	32.03	46.02	100	356	V	Pass
557.58	26.39	46.02	100	98	H	Pass
629.82	26.84	46.02	100	275	V	Pass
664.74	23.34	46.02	177	360	H	Pass
699.78	28.88	46.02	100	61	H	Pass
734.70	24.17	46.02	100	45	H	Pass
769.74	26.30	46.02	100	49	H	Pass

Table 12: Final result of spurious radiated emission test 30 MHz - 1 GHz, channel 39



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.8.6 Test results from 1 GHz to 10th harmonic

Test distance:	Prescan:	<input checked="" type="checkbox"/> 1 m	<input checked="" type="checkbox"/> 3 m	<input type="checkbox"/> m
	Final scan:	<input checked="" type="checkbox"/> 3 m	<input type="checkbox"/> 10 m	<input type="checkbox"/> m
Polarisation:		<input checked="" type="checkbox"/> horizontal	<input checked="" type="checkbox"/> vertical	
EUT Position:	<input checked="" type="checkbox"/> Position 1	<input checked="" type="checkbox"/> Position 2	<input type="checkbox"/> Position 3	

Frequency range	Step size	IF Band-width	Detector		Measurement Time		Preamplifier
			Prescan	Final scan	Prescan	Final scan	
1 GHz – 16 GHz	250 kHz	1 MHz	PK	PK	100 ms	100 ms	30 dB
1 GHz – 16 GHz	250 kHz	1 MHz	AV	AV	100 ms	100 ms	30 dB
16 GHz – 26 GHz	250 kHz	1 MHz	PK	PK	100 ms	100 ms	external
16 GHz – 26 GHz	250 kHz	1 MHz	AV	AV	100 ms	100 ms	external



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)




Figure 38: 1st Chart of spurious radiated emission test 1 GHz to 10th harmonic, channel 0




Figure 39: 2nd Chart of spurious radiated emission test 1 GHz to 10th harmonic, channel 0

f[GHz]	E _{meas} [dB μ V/m]	EUT-Pos	Polarization	Table [°]	Height [cm]	Detector	Restr. Band	Limit [dB μ V/m]	Result
2.4020	96.44	1	H	150	124	PK	No	---	Carrier
2.4020	92.30					AV		---	Carrier
4.8045	59.92	2	V	44	147	PK	Yes	74	Pass
4.8040	52.29					AV		54	Pass

Table 13: Final result of spurious radiated emission test 1 GHz to 10th harmonic, channel 0




Figure 40: 1st Chart of spurious radiated emission test 1 GHz to 10th harmonic, channel 19




Figure 41: 2nd Chart of spurious radiated emission test 1 GHz to 10th harmonic, channel 19

f[GHz]	E _{meas} [dB μ V/m]	EUT-Pos	Polarization	Table [°]	Height [cm]	Detector	Restr. Band	Limit [dB μ V/m]	Result
2.4400	95.50	1	H	154	126	PK	No	---	Carrier
2.4400	91.36					AV		---	Carrier
4.8795	60.56	2	V	19	151	PK	Yes	74	Pass
4.8800	52.80					AV		54	Pass

Table 14: Final result of spurious radiated emission test 1 GHz to 10th harmonic, channel 19




Figure 42: 1st Chart of spurious radiated emission test 1 GHz to 10th harmonic, channel 39




Figure 43: 2nd Chart of spurious radiated emission test 1 GHz to 10th harmonic, channel 39

f[GHz]	E _{meas} [dBμV/m]	EUT-Pos	Polarization	Table [°]	Height [cm]	Detector	Restr. Band	Limit [dBμV/m]	Result
2.4800	95.22	1	H	155	161	PK	No	---	Carrier
2.4800	91.07					AV		---	Carrier
4.9605	59.95	2	V	2	151	PK	Yes	74	Pass
4.9598	51.94					AV		54	Pass

Table 15: Final result of spurious radiated emission test 1 GHz to 10th harmonic, channel 39

6.9 Radio frequency radiation exposure evaluation for mobile devices

Reference(s):
47 CFR Part 2, §2.1091
KDB 447498 D01, section 7
RSS Gen Issue 4, section 3.2
RSS-102 Issue 5, section 2.5.2

Performed by:	Martin Müller	Date of test:	April 26, 2017
Result:	<input checked="" type="checkbox"/> Test passed	<input type="checkbox"/> Test not passed	

6.9.1 Data of equipment under test (EUT)

Antenna connector (see clause 3):	<input type="checkbox"/> permanent	<input type="checkbox"/> temporary	<input checked="" type="checkbox"/> none
Antenna detachable:	<input type="checkbox"/> yes	<input checked="" type="checkbox"/> no	
Tune-up function:	<input type="checkbox"/> yes	<input checked="" type="checkbox"/> no	
Maximum antenna gain (see clause 3):	logarithmic 0.0 dBi	numeric 1.0	
Maximum conducted output power (see clause 6.5):	logarithmic 1.17 dBm	numeric 1.31 mW	
Maximum equivalent isotropically radiated power:	logarithmic 1.17 dBm	numeric 1.31 mW	
Maximum operation frequency (see clause 3):	2480.000 MHz		

6.9.2 Requirements

This estimation follows the general guidelines for RF Exposure according to KDB 447498.

As noted in §2.1091(b) a mobile device is defined as “a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a **separation distance of at least 20 centimeters** is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.”

According to §2.1091(c) the limits to be used for evaluation are defined in §1.1310.

As specified in §1.1310(d)(2) at operating frequencies less than or equal to 6 GHz, the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 of §1.1310(e) may be used.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

Table 16 below shows the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 - 3.0	614	1.63	*100	6
3.0 - 30	1842/f	4.89/f	*900/f ²	6
30 - 300	61.4	0.163	1.0	6
300 - 1500			f/300	6
1500 - 100000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 - 1.34	614	1.63	*100	30
1.34 - 30	824/f	2.19/f	*180/f ²	30
30 - 300	27.5	0.073	0.2	30
300 - 1500			f/1500	30
1500 - 100000			1.0	30

Table 16: Limits for maximum permissible exposure (MPE) according to table 1 of §1.1310(e)

Notes:

1. f = frequency in MHz.
2. * = Plane-wave equivalent power density.

Appropriate RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment) can be found in table 4 of RSS-102, section 4:

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/f	-	6**
1.1-10	87/f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/f ^{0.25}	0.1540/f ^{0.25}	8.944/f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}

Note: f is frequency in MHz.
***Based on nerve stimulation (NS).**
**** Based on specific absorption rate (SAR).**

Table 17: RF field strength limits according to table 4 of RSS-102



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.9.3 Results

Maximum peak value of electric field strength measured at 2402.0 MHz in a distance of 3 m:
 $E_{\text{meas}}(3 \text{ m}) = \underline{96.40 \text{ dB}\mu\text{V/m}}$ (see clause 6.5)

For far-field conditions wave impedance in free space is about $120 \cdot \pi \Omega$ (51.5 dB). Therefore, magnetic field strength results in:

$$H_{\text{meas}}(3 \text{ m}) = E_{\text{meas}}(3 \text{ m}) - 51.5 \text{ dB} = 96.40 \text{ dB}\mu\text{V/m} - 51.5 \text{ dB} = \underline{44.90 \text{ dB}\mu\text{A/m}}$$

Worst case field strength is calculated for a separation distance of 20 centimeters.

Using an extrapolation factor of 20 dB/decade ($\sim r^{-1}$) results in:

$$E_{\text{calc}}(20 \text{ cm}) = 96.40 \text{ dB}\mu\text{V/m} - 20 \cdot \log(0.2 \text{ m} / 3 \text{ m}) = 96.40 \text{ dB}\mu\text{V/m} + 23.52 \text{ dB}$$

$$E_{\text{calc}}(20 \text{ cm}) = 119.92 \text{ dB}\mu\text{V/m} = \underline{0.991 \text{ V/m}}$$

Using an extrapolation factor of 20 dB/decade ($\sim r^{-1}$) results in:

$$H_{\text{calc}}(20 \text{ cm}) = 44.90 \text{ dB}\mu\text{A/m} - 20 \cdot \log(0.2 \text{ m} / 3 \text{ m}) = 44.90 \text{ dB}\mu\text{A/m} + 23.52 \text{ dB}$$

$$H_{\text{calc}}(20 \text{ cm}) = 68.42 \text{ dB}\mu\text{A/m} = \underline{2.636 \cdot 10^{-3} \text{ A/m}}$$



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

Worst case power density is calculated for a separation distance of 20 centimeters by using the respective field strengths as calculated above:

$$S_{\text{calc}}(20 \text{ cm}) = E_{\text{calc}}(20 \text{ cm}) \cdot H_{\text{calc}}(20 \text{ cm}) = 0.991 \text{ V/m} \cdot 0.0026 \text{ A/m}$$

$$S_{\text{calc}}(20 \text{ cm}) = \underline{0.0026 \text{ W/m}^2} = \underline{0.00026 \text{ mW/cm}^2}$$

Comparing the calculated results to the limits for general population/uncontrolled exposure at 2402.0 MHz shows that even with worst case calculation using peak values the limits are kept.

E-field			
$E_{\text{calc}}(20 \text{ cm})$ (V/m)	Limit 47 CFR Par 1, §1.1310(e) (V/m)	Limit RSS-102, table 2 (V/m)	
0.991	---	44.911	
H-field			
$H_{\text{calc}}(20 \text{ cm})$ (A/m)	Limit 47 CFR Par 1, §1.1310(e) (A/m)	Limit RSS-102, table 2 (A/m)	
0.0026	---	0.119	
Power density			
$S_{\text{calc}}(20 \text{ cm})$ (mW/cm ²)	Limit 47 CFR Par 1, §1.1310(e) (mW/cm ²)	$S_{\text{calc}}(20 \text{ cm})$ (W/m ²)	Limit RSS-102, table 2 (W/m ²)
0.00026	1.0	0.0026	5.351

Table 18: Calculated results @ 2402.0 MHz compared to RF field strength limits



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

6.9.4 Requirements for simultaneous transmission

According to customer, simultaneous transmission of SRD and BLE is not intended to be used. However, the following calculations show that MPE and RF field strength limits would be kept even with simultaneous transmission of SRD and BLE.

6.9.4.1 Requirements

As noted in KDB 447498 D01, section 7.2, simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modeled, or measured field strengths or power density.

In case of simultaneous transmission the standalone results are used for calculation according to the following formulas:

$$\sum_{i=SRD}^{BLE} \frac{E_i}{E_{limit\ i}} \leq 1 \Leftrightarrow \frac{E_{SRD}(V/m)}{E_{limit\ SRD}(V/m)} + \frac{E_{BLE}(V/m)}{E_{limit\ BLE}(V/m)} \leq 1$$

$$\sum_{i=SRD}^{BLE} \frac{H_i}{H_{limit\ i}} \leq 1 \Leftrightarrow \frac{H_{SRD}(A/m)}{H_{limit\ SRD}(A/m)} + \frac{H_{BLE}(A/m)}{H_{limit\ BLE}(A/m)} \leq 1$$

$$\sum_{i=SRD}^{BLE} \frac{S_i}{S_{limit\ i}} \leq 1 \Leftrightarrow \frac{S_{SRD}(W/m^2)}{S_{limit\ SRD}(W/m^2)} + \frac{S_{BLE}(W/m^2)}{S_{limit\ BLE}(W/m^2)} \leq 1$$

Note: As for power density using the limit according to RSS-102, table 2, gives the worst case ratio, the values in W/m^2 are selected.

6.9.4.2 Results

With values for SRD mode taken from clause 6.9.3 of test report no. 170062-AU01+W01 the results are:

$$\frac{E_{SRD}(V/m)}{E_{limit\ SRD}(V/m)} + \frac{E_{BLE}(V/m)}{E_{limit\ BLE}(V/m)} = \frac{1.024\ V/m}{44.916\ V/m} + \frac{0.991\ V/m}{44.911\ V/m} \approx 0.045 \leq 1 \checkmark$$

$$\frac{H_{SRD}(A/m)}{H_{limit\ SRD}(A/m)} + \frac{H_{BLE}(A/m)}{H_{limit\ BLE}(A/m)} = \frac{0.0028\ A/m}{0.119\ A/m} + \frac{0.0026\ A/m}{0.119\ A/m} \approx 0.045 \leq 1 \checkmark$$

$$\frac{S_{SRD}(W/m^2)}{S_{limit\ SRD}(W/m^2)} + \frac{S_{BLE}(W/m^2)}{S_{limit\ BLE}(W/m^2)} = \frac{0.0028\ W/m^2}{5.352\ W/m^2} + \frac{0.0026\ W/m^2}{5.351\ W/m^2} \approx 0.001 \leq 1 \checkmark$$



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

7 Equipment calibration status

Description	Modell number	Serial number	Inventory number(s)	Last calibration	Next calibration
Test receiver	ESCI 3	100013	E00001	2016-02	2018-02
Test receiver	ESCI 3	100328	E00552	2016-09	2018-09
Test receiver	ESCS 30	825442/0002	E00003	2016-04	2018-04
Test receiver	ESU 26	100026	W00002	2016-02	2018-02
Test receiver	ESR 7	101059	E00739	2016-02	2018-02
Test receiver	ESW 44	101538	E00895	2016-12	2018-12
Broadband horn antenna	BBHA 9120D	9120D-592	W00052	2017-04	2020-04
Broadband horn antenna	BBHA 9170	9170-332	W00054	2017-04	2020-04
Preamplifier	AMF-6F-16002650-25-10P	1317552	W00090	2015-06	2017-06
LISN	ESH2-Z5	881362/037	E00004	2016-10	2018-10
LISN	ESH2-Z5	893406/009	E00005	2016-02	2018-02
Loop antenna	HFH2-Z2	871398/0050	E00060	2016-09	2018-09
Broadband antenna	VULB 9163	9163-228	E00012	2016-04	2019-04
Broadband antenna	VULB 9163	9163-114	E00013	2015-09	2017-09
Shielded room	P92007	B83117C1109T211	E00107	N/A	
Compact diagnostic chamber (CDC)	VK041.0174	D62128-A502-A69-2-0006	E00026	N/A	
Open area test site (OATS)	---	---	E00354	2015-10	2017-10
Semi anechoic chamber (SAC)	SAC3	C62128-A520-A643-x-0006	E00716	2015-09	2017-09
Climatic chamber 340 I	VC³ 4034	58566123250010	C00015	2016-10	2018-10
Cable set shielded room	Cable no. 30	---	E00424	2016-07	2018-07
Cable set CDC	Cables no. 37 and 38	---	E00459 E00460	2015-05	2017-05
Cable set OATS 3 m	Cables no. 19, 34 and 36	---	E00453 E00456 E00458	2015-11	2017-11
Cable set SAC 3 m	Cables no. 57, 58 and 59	---	E00453 E00455 E00458	2015-10	2017-10

Table 19: Equipment calibration status

Note 1: Expiration date of measurement facility registration (OATS) by

- FCC (registration number 221458): 2017-07
- Industry Canada (test sites number 3472A-1 and 3472A-2): 2018-11

Note 2: Expiration date of test firm accreditation for OATS and SAC:

FCC test firm type "accredited": 2017-06



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

8 Measurement uncertainties

Description	Max. deviation	k=
Conducted emission AMN (9kHz to 30 MHz)	± 4.1 dB	2
Carrier frequency separation Number of hopping frequencies Time of occupancy (dwell time)	± 5.0 %	2
Bandwidth tests	± 2.0 %	2
Maximum conducted output power	± 1.5 dB	2
Power spectral density	± 3.0 dB	2
Spurious RF conducted emissions	± 3.0 dB	2
Radiated emission open field or semi-anechoic chamber 9 kHz to 30 MHz 30 MHz to 300 MHz 300MHz to 1 GHz	± 4.8 dB ± 5.4 dB ± 5.9 dB	2
Radiated emission anechoic chamber <td>± 4.5 dB</td> <td>2</td>	± 4.5 dB	2

Table 20: Measurement uncertainty

The uncertainty stated is the expanded uncertainty obtained by multiplying the standard uncertainty by the coverage factor k. For a confidence level of 95 % the coverage factor k is 2.



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)

9 Revision history

Revision	Date	Issued by	Description of modifications
0	2017-05-02	Martin Müller	First edition

10 Additional documents

- Annex A: Pictures of test setup and EUT-positions
- Annex B: Pictures of EUT (external)
- Annex C: Pictures of EUT (internal)



EMV **TESTHAUS** GmbH
Gustav-Hertz-Straße 35
94315 Straubing
Germany

DewertOkin GmbH
control unit
CU170
(BLE mode)