

FCC Part 15C

Measurement and Test Report

For

DewertOkin GmbH

Weststr. 1, 32278 Kirchlengern, Germany

FCC ID: O3YRF075E

| | | |
|--------------------------------------|---|-------------------|
| FCC Rules: | <u>FCC Part 15.249</u> | |
| Product Description: | <u>REMOTE CONTROL ECO TX</u> | |
| Tested Model: | <u>RF075E</u> | |
| Report No.: | <u>STR12098004I</u> | |
| Tested Date: | <u>2012-09-03 to 2012-09-11</u> | |
| Issued Date: | <u>2012-09-11</u> | |
| Tested By: | <u>Seven Song / Engineer</u> | <i>Seven Song</i> |
| Reviewed By: | <u>Lahm Peng / EMC Manager</u> | <i>Lahm peng</i> |
| Approved & Authorized By: | <u>Jandy so / PSQ Manager</u> | <i>Jandyso</i> |
| Prepared By: | SEM.Test Compliance Service Co., Ltd 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C. (518101) Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn | |

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by SEM.Test Compliance Service Co., Ltd

TABLE OF CONTENTS

| | |
|---|-----------|
| 1. GENERAL INFORMATION..... | 3 |
| 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)..... | 3 |
| 1.2 TEST STANDARDS..... | 4 |
| 1.3 TEST METHODOLOGY..... | 4 |
| 1.4 TEST FACILITY..... | 4 |
| 1.5 EUT SETUP AND TEST MODE..... | 5 |
| 2. SUMMARY OF TEST RESULTS..... | 6 |
| 3. ANTENNA REQUIREMENTS..... | 7 |
| 3.1 STANDARD APPLICABLE..... | 7 |
| 3.2 TEST RESULT..... | 7 |
| 4. RADIATED EMISSIONS..... | 8 |
| 4.1 MEASUREMENT UNCERTAINTY..... | 8 |
| 4.2 STANDARD APPLICABLE..... | 8 |
| 4.3 TEST EQUIPMENT LIST AND DETAILS..... | 8 |
| 4.4 TEST PROCEDURE..... | 9 |
| 4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION..... | 9 |
| 4.6 ENVIRONMENTAL CONDITIONS..... | 9 |
| 4.7 SUMMARY OF TEST RESULTS/PLOTS..... | 10 |
| 5. OUT OF BAND EMISSIONS..... | 18 |
| 5.1 STANDARD APPLICABLE..... | 18 |
| 5.2 TEST EQUIPMENT LIST AND DETAILS..... | 18 |
| 5.3 TEST PROCEDURE..... | 18 |
| 5.4 ENVIRONMENTAL CONDITIONS..... | 18 |
| 5.5 SUMMARY OF TEST RESULTS/PLOTS..... | 18 |
| 6. EMISSION BANDWIDTH..... | 21 |
| 6.1 STANDARD APPLICABLE..... | 21 |
| 6.2 TEST EQUIPMENT LIST AND DETAILS..... | 21 |
| 6.3 TEST PROCEDURE..... | 21 |
| 6.4 ENVIRONMENTAL CONDITIONS..... | 21 |
| 6.5 SUMMARY OF TEST RESULTS/PLOTS..... | 21 |


1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: DewertOkin GmbH
 Address of applicant: Weststr. 1, 32278 Kirchlengern, Germany

Manufacturer: Shenzhen C&D Electronics Co., Ltd.
 Address of manufacturer: Building 2, XiaYouSong Mountaintop Industrial District, YouSong Village, Longhua Town, BaoAn District, ShenZhen, Guangdong, China

| General Description of EUT | |
|---|---|
| Product Name: | REMOTE CONTROL ECO TX |
| Trade Name: |  |
| Model No.: | RF075E |
| Rated Voltage: | Battery DC 3V |
| Comment: | Manual Operation Device |
| <p><i>Note: The test data is gathered from a production sample, provided by the manufacturer. The products (same model) have different color appearance without circuit and electronic construction changed, declared by the manufacturer</i></p> | |

| Technical Characteristics of EUT | |
|-----------------------------------|-------------------------------|
| Frequency Range: | 2404-2477MHz |
| Max. Field Strength: | 89.47 dBuV/m (at 3m distance) |
| Max. Radiated Power: | 0.000267W |
| Antenna Type: | PCB Antenna |
| Antenna Gain: | -0.20 dBi |
| Modulation: | GFSK |
| Quantity of Channels: | 77 |
| Channel Separation: | 1MHz |
| Lowest Internal Frequency of EUT: | 16MHz |
| Device Category: | Portable Device |

1.2 Test Standards

The following report is prepared on behalf of the DewertOkin GmbH in accordance with FCC Part 15, Subpart B, Subpart C, and section 15.107, 15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.107,15.203, 15.205, 15.207, 15.209 and 15.249 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 994117**

SEM.Test Compliance Services Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 994117.

- **Industry Canada (IC) Registration No.: 7673A**

The 3m Semi-anechoic chamber of SEM.Test Compliance Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 7673A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Electronics Service Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 3/F, Jinbao Commerce Building, Xin'an Fanshen Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

| Test Mode List | | |
|-----------------------|----------------|---------|
| Test Mode | Description | Remark |
| TM1 | Low Channel | 2404MHz |
| TM2 | Middle Channel | 2441MHz |
| TM3 | High Channel | 2477MHz |

| Special Cable List and Details | | | |
|---------------------------------------|------------|---------------------|------------------------|
| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
| / | / | / | / |

| Auxiliary Equipment List and Details | | | |
|---|--------------|-------|---------------|
| Description | Manufacturer | Model | Serial Number |
| / | / | / | / |

2. SUMMARY OF TEST RESULTS

| FCC Rules | Description of Test Item | Result |
|---------------------------|---------------------------------|---------------|
| § 15.203 | Antenna Requirement | Compliant |
| § 15.207(a) | Conducted Emission | N/A* |
| §15.205§15.209§15.249 (a) | Radiated Emission | Compliant |
| §15.249(d) | Out of Band Emission | Compliant |
| §15.215 (c) | Emission Bandwidth | Compliant |

Note: N/A is not applicable.

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a PCB antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

4.2 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Fundamental Frequency | Field strength of fundamental (milli-volts/meter) | Field strength of fundamental (micro-volts/meter) |
|-----------------------|---|---|
| 902-928 MHz | 50 | 500 |
| 2400-2483.5 MHz | 50 | 500 |
| 5725-5875 MHz | 50 | 500 |
| 24.0-24.25 GHz | 250 | 2500 |

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.3 Test Equipment List and Details


| Description | Manufacturer | Model | Serial Number | Cal. Date | Due. Date |
|--------------------------|----------------------|-----------|---------------|------------|------------|
| Spectrum Analyzer | R&S | FSP | 836079/035 | 2012-03-28 | 2013-03-27 |
| EMI Test Receiver | R&S | ESVB | 825471/005 | 2012-03-28 | 2013-03-27 |
| Pre-amplifier | Agilent | 8447F | 3113A06717 | 2012-03-28 | 2013-03-27 |
| Pre-amplifier | Compliance Direction | PAP-0118 | 24002 | 2012-03-28 | 2013-03-27 |
| Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 9163-333 | 2012-02-25 | 2013-02-24 |
| Horn Antenna | ETS | 3117 | 00086197 | 2012-02-25 | 2013-02-24 |
| Loop Antenna | SCHWARZECK | HFRA 5165 | 9365 | 2012-02-25 | 2013-02-24 |

4.4 Test Procedure

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBµV means the emission is 6dBµV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.6 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 60 % |
| ATM Pressure: | 1012 mbar |

4.7 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.249 standards, and had the worst margin of:


-5.66 dB μ V at 887.6099 MHz in the **Horizontal polarization, **Middle Channel of Antenna 1, 9 kHz to 25 GHz,**
3Meters**

Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: REMOTE CONTROL ECO TX
Tested Model: RF075E
Operating Condition: Transmitting below 1GHz Low Channel 2404MHz
Comment:


Test Specification: Horizontal

Horizontal:



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|-----------------|------------------|----------------|-----------------|----------------|-------------|------------|-------------|--------|
| 1 | 38.6161 | 15.04 | 9.46 | 24.50 | 40.00 | -15.50 | 360 | 100 | peak |
| 2 | 744.8661 | 14.90 | 17.95 | 32.85 | 46.00 | -13.15 | 360 | 100 | peak |
| 3 | 875.2470 | 16.34 | 18.80 | 35.14 | 46.00 | -10.86 | 360 | 100 | peak |

Vertical:




| No. | Frequency (MHz) | Reading (dBuV/m) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|-----------------|------------------|----------------|-----------------|----------------|-------------|------------|-------------|--------|
| 1 | 42.8998 | 16.21 | 8.79 | 25.00 | 40.00 | -15.00 | 360 | 100 | peak |
| 2 | 93.4402 | 16.35 | 5.22 | 21.57 | 43.50 | -21.93 | 360 | 100 | peak |
| 3 | 750.1083 | 17.24 | 17.78 | 35.02 | 46.00 | -10.98 | 360 | 100 | peak |
| 4 | 881.4067 | 16.31 | 19.03 | 35.34 | 46.00 | -10.66 | 360 | 100 | peak |

Operating Condition: *Transmitting*
 Comment: *below 1GHz Low Channel 2441MHz*


Test Specification: *Horizontal*

Horizontal:



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct dB/m | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1 | 30.0000 | 23.63 | 8.04 | 31.67 | 40.00 | -8.33 | 360 | 100 | peak |
| 2 | 39.4372 | 16.55 | 9.60 | 26.15 | 40.00 | -13.85 | 360 | 100 | peak |
| 3 | 102.3597 | 15.55 | 6.61 | 22.16 | 43.50 | -21.34 | 360 | 100 | peak |

Vertical:




| No. | Frequency (MHz) | Reading (dBuV/m) | Correct dB/m | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|-----------------|----------------|--------|
| 1 | 30.0000 | 20.10 | 8.04 | 28.14 | 40.00 | -11.86 | 360 | 100 | peak |
| 2 | 744.8661 | 15.73 | 17.95 | 33.68 | 46.00 | -12.32 | 360 | 100 | peak |
| 3 | 912.8620 | 18.64 | 18.93 | 37.57 | 46.00 | -8.43 | 360 | 100 | peak |

Operating Condition: Transmitting
 Comment: below 1GHz Low Channel 2477MHz


Test Specification: Horizontal

Horizontal:



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|-----------------|------------------|----------------|-----------------|----------------|-------------|------------|-------------|--------|
| 1 | 42.8998 | 16.93 | 8.79 | 25.72 | 40.00 | -14.28 | 360 | 100 | peak |
| 2 | 729.3583 | 16.56 | 17.31 | 33.87 | 46.00 | -12.13 | 360 | 100 | peak |
| 3 | 900.1474 | 16.74 | 19.38 | 36.12 | 46.00 | -9.88 | 360 | 100 | peak |

Vertical:



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Degree (°) | Height (cm) | Remark |
|-----|-----------------|------------------|----------------|-----------------|----------------|-------------|------------|-------------|--------|
| 1 | 30.0000 | 19.06 | 8.04 | 27.10 | 40.00 | -12.90 | 360 | 100 | peak |
| 2 | 739.6605 | 15.33 | 18.07 | 33.40 | 46.00 | -12.60 | 360 | 100 | peak |
| 3 | 893.8567 | 16.62 | 19.27 | 35.89 | 46.00 | -10.11 | 360 | 100 | peak |

Spurious Emissions Above 1GHz

| Frequency | Reading | Correct | Result | Limit | Margin | Polar | Detector |
|------------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz) | (dBuV/m) | dB/m | (dBuV/m) | (dBuV/m) | (dB) | H/V | |
| Low Channel-2402MHz | | | | | | | |
| 2404 | 92.01 | -11.75 | 80.26 | 94.00 | -13.74 | H | AV |
| 2404 | 95.59 | -11.75 | 83.84 | 94.00 | -10.16 | V | AV |
| 4808* | 40.94 | -3.11 | 37.83 | 54.00 | -16.17 | H | AV |
| 4808* | 40.29 | -3.11 | 37.18 | 54.00 | -16.82 | V | AV |
| 7212 | 37.16 | 1.49 | 38.65 | 54.00 | -15.35 | H | AV |
| 7212 | 35.06 | 1.49 | 36.55 | 54.00 | -17.45 | V | AV |
| 2404 | 99.26 | -11.75 | 87.51 | 114.00 | -26.49 | H | PK |
| 2404 | 101.22 | -11.75 | 89.47 | 114.00 | -24.53 | V | PK |
| 4808* | 60.26 | -3.11 | 57.15 | 74.00 | -16.85 | H | PK |
| 4808* | 59.35 | -3.11 | 56.24 | 74.00 | -17.76 | V | PK |
| 7212 | 56.97 | 1.49 | 58.46 | 74.00 | -15.54 | H | PK |
| 7212 | 51.95 | 1.49 | 53.44 | 74.00 | -20.56 | V | PK |
| Middle Channel-2441MHz | | | | | | | |
| 2441 | 91.96 | -11.75 | 80.21 | 94.00 | -13.79 | H | AV |
| 2441 | 93.98 | -11.75 | 82.23 | 94.00 | -11.77 | V | AV |
| 4882* | 42.98 | -3.74 | 39.24 | 54.00 | -14.76 | H | AV |
| 4882* | 42.41 | -3.74 | 38.67 | 54.00 | -15.33 | V | AV |
| 7323* | 35.05 | 1.49 | 36.54 | 54.00 | -17.46 | H | AV |
| 7323* | 35.53 | 1.49 | 37.02 | 54.00 | -16.98 | V | AV |
| 2441 | 98.72 | -11.75 | 86.97 | 114.00 | -27.03 | H | PK |
| 2441 | 101.03 | -11.75 | 89.28 | 114.00 | -24.72 | V | PK |
| 4882* | 62.56 | -3.74 | 58.82 | 74.00 | -15.18 | H | PK |
| 4882* | 61.69 | -3.74 | 57.95 | 74.00 | -16.05 | V | PK |
| 7323* | 54.85 | 1.49 | 56.34 | 74.00 | -17.66 | H | PK |
| 7323* | 53.66 | 1.49 | 55.15 | 74.00 | -18.85 | V | PK |

| Frequency | Reading | Correct | Result | Limit | Margin | Polar | Detector |
|---------------------|----------|---------|----------|----------|--------|-------|----------|
| (MHz) | (dBuV/m) | dB/m | (dBuV/m) | (dBuV/m) | (dB) | H/V | |
| Low Channel-2480MHz | | | | | | | |
| 2477 | 92.43 | -11.76 | 80.67 | 94.00 | -13.33 | H | AV |
| 2477 | 95.09 | -11.76 | 83.33 | 94.00 | -10.67 | V | AV |
| 4954* | 39.03 | -2.46 | 36.57 | 54.00 | -17.43 | H | AV |
| 4954* | 41.26 | -2.46 | 38.80 | 54.00 | -15.2 | V | AV |
| 7431* | 33.08 | 1.49 | 34.57 | 54.00 | -19.43 | H | AV |
| 7431* | 32.13 | 1.49 | 33.62 | 54.00 | -20.38 | V | AV |
| 2477 | 98.55 | -11.76 | 86.79 | 114.00 | -27.21 | H | PK |
| 2477 | 101.09 | -11.76 | 89.33 | 114.00 | -24.67 | V | PK |
| 4954* | 60.78 | -2.46 | 58.32 | 74.00 | -15.68 | H | PK |
| 4954* | 58.17 | -2.46 | 55.71 | 74.00 | -18.29 | V | PK |
| 7431* | 53.96 | 1.49 | 55.45 | 74.00 | -18.55 | H | PK |
| 7431* | 54.64 | 1.49 | 56.13 | 74.00 | -17.87 | V | PK |

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The measurements greater than 20dB below the limit from 9kHz to 30MHz.

“” frequency falling into the § 15.205 restricted band*

Radiated Power

| Frequency (MHz) | Power(dBm) | Power (W) |
|-----------------|------------|-----------|
| 2404 | -7.69 | 0.000170 |
| 2404 | -5.73 | 0.000267 |
| 2441 | -8.23 | 0.000150 |
| 2441 | -5.92 | 0.000256 |
| 2477 | -8.41 | 0.000144 |
| 2477 | -5.87 | 0.000259 |

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Equipment List and Details

| Description | Manufacturer | Model | Serial Number | Cal. Date | Due. Date |
|--------------------------|----------------------|----------|---------------|------------|------------|
| Spectrum Analyzer | R&S | FSP | 836079/035 | 2012-03-28 | 2013-03-27 |
| EMI Test Receiver | R&S | ESVB | 825471/005 | 2012-03-28 | 2013-03-27 |
| Pre-amplifier | Agilent | 8447F | 3113A06717 | 2012-03-28 | 2013-03-27 |
| Pre-amplifier | Compliance Direction | PAP-0118 | 24002 | 2012-03-28 | 2013-03-27 |
| Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 9163-333 | 2012-02-25 | 2013-02-24 |
| Horn Antenna | ETS | 3117 | 00086197 | 2012-02-25 | 2013-02-24 |

5.3 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

5.4 Environmental Conditions

| | |
|--------------------|-----------|
| Temperature: | 24 °C |
| Relative Humidity: | 60 % |
| ATM Pressure: | 1012 mbar |


5.5 Summary of Test Results/Plots

| Test mode | Frequency | Limit | Result |
|-----------|-----------|------------|--------|
| | MHz | dBuV / dBc | |
| Lowest | 2310.00 | <54 dBuV | Pass |
| | 2390.00 | <54 dBuV | Pass |
| | 2400.00 | >50 dBc | Pass |
| Highest | 2483.50 | <54 dBuV | Pass |
| | 2500.00 | <54 dBuV | Pass |

The edge emissions are below the FCC 15.209 Limits or complies with the 15.247(d) requirements.


Please refer to the test plots as below.

Lowest Bandedge



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct (dB/m) | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|-----------------|------------------|----------------|-----------------|----------------|-------------|---------------|
| 1 | 2310.000* | 32.46 | -11.72 | 20.74 | 54.00 | -33.26 | Ave Detector |
| | 2310.000* | 44.97 | -11.72 | 33.25 | 74.00 | -40.75 | Peak Detector |
| 2 | 2390.000* | 32.96 | -11.75 | 21.21 | 54.00 | -32.79 | Ave Detector |
| | 2390.000* | 46.25 | -11.75 | 34.50 | 74.00 | -39.5 | Peak Detector |
| 3 | 2400.000 | 47.37 | -11.75 | 35.62 | 54.00 | -18.38 | Ave Detector |
| | 2400.000 | 50.00 | -11.75 | 38.25 | 74.00 | -35.75 | Peak Detector |
| 4 | 2404.000 | 95.59 | -11.75 | 83.84 | / | / | Ave Detector |

Highest Bandedge



| No. | Frequency (MHz) | Reading (dBuV/m) | Correct dB/m | Result (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Remark |
|-----|--------------------|---------------------|-----------------|--------------------|-------------------|----------------|---------------|
| 1 | 2483.500* | 33.84 | -11.78 | 22.06 | 54.00 | -31.94 | Ave Detector |
| | 2483.500* | 48.30 | -11.78 | 36.52 | 74.00 | -37.48 | Peak Detector |
| 2 | 2500.000* | 32.87 | -11.78 | 21.09 | 54.00 | -32.91 | Ave Detector |
| | 2500.000* | 48.91 | -11.78 | 37.13 | 74.00 | -36.87 | Peak Detector |

“*” frequency falling into the § 15.205 restricted band

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Equipment List and Details

| Description | Manufacturer | Model | Serial Number | Cal. Date | Due. Date |
|-------------------|--------------|-------------|---------------|------------|------------|
| Spectrum Analyzer | Agilent | E4402B | US41192821 | 2012-03-28 | 2013-03-27 |
| Attenuator | ATTEN | ATS100-4-20 | / | 2012-03-28 | 2013-03-27 |

6.3 Test Procedure

According to the ANSI 63.4-2003, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW \geq 1% 20dB Bandwidth, VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.4 Environmental Conditions


| | |
|--------------------|-----------|
| Temperature: | 25 °C |
| Relative Humidity: | 53% |
| ATM Pressure: | 1018 mbar |

6.5 Summary of Test Results/Plots


| Channel | Frequency MHz | 20dB Bandwidth kHz | 99% Bandwidth kHz |
|----------------|------------------|-----------------------|----------------------|
| Low Channel | 2404 | 1697 | 1816.0 |
| Middle Channel | 2442 | 1525 | 1773.0 |
| High Channel | 2477 | 1688 | 1821.3 |

Please refer to the following test plots


Low Channel:



Middle Channel:



High Channel:



***** END OF REPORT *****