

# Radiofrequency Radiation Exposure Evaluation

This exposure evaluation is intended for **FCC ID: O4GH3**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances  $\leq 50$  mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR

>> The fundamental frequency of the EUT is 2402-2480MHz,  
the test separation distance is  $\leq 50$ mm.  
(Manufacturer specified the separation distance is: 20mm)  
(5mm is the worst case according to the KDB)

Step b)

>> Numeric threshold (2402MHz),  $\text{mW} / 5\text{mm} * \sqrt{2.402\text{GHz}} \leq 3.0$   
Numeric threshold (2402MHz)  $\leq 9.678\text{mW}$

>> Numeric threshold (2440MHz),  $\text{mW} / 5\text{mm} * \sqrt{2.440\text{GHz}} \leq 3.0$   
Numeric threshold (2440MHz)  $\leq 9.602\text{mW}$

>> Numeric threshold (2480MHz),  $\text{mW} / 5\text{mm} * \sqrt{2.480\text{GHz}} \leq 3.0$   
Numeric threshold (2480MHz)  $\leq 9.525\text{mW}$

## The Power according to the RF Report No: 60.790.23.011.01R01

>> The power (measured + tune up tolerance) of EUT at 2402MHz is:  $-1.00\text{dBm} = 0.79\text{mW}$   
The power (measured + tune up tolerance) of EUT at 2440MHz is:  $-1.34\text{dBm} = 0.73\text{mW}$   
The power (measured + tune up tolerance) of EUT at 2480MHz is:  $-1.18\text{dBm} = 0.76\text{mW}$

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.

Reviewed by:

Prepared by:



Eric LI  
Section Manager



Kevin DU  
EMC Project Engineer