



Remark: 測試規範
 防水測試: 用2Bar內压浸水看汽泡 (適用於 3 bar 手錶).
 絲印黏附力測試: 用3M透明膠紙(#600) 压貼在表面拉3次.
 噴塗粘附力測試: 用3M透明膠紙(#600) 压貼在表面拉3次.
 鏡面压力測試: 用15kg分別压在3/6/9/12位置觀察超聲處有否爆裂.
 抗腐測試(SUS316L): 浸24小時5%鹽水後不可出現腐蝕現象.
 表扣拉力測試: 用2.5kg直拉15秒表扣不可鬆脫.
 所有物料須符合 RoHS , PAHs, Reach 規格

Scale 1.5:1

DAYTON INDUSTRIAL CO. LTD.		 3rd angle projection	unit: mm	LINEAR ± 0.10
KENDY ENTERPRISE LTD.				ANGULAR ± 0.50
TITLE: Cosmetic	MODEL NAME: QI Multiwatch		UNSPECIFIED TOLERANCE	VERSION NO: 1.1
PART NO: B9-DA5480100	MODEL NO: DA54801			DATE: 10/9/2013
MAT'L: ABS	SCALE: 1:1	DOC CONTROL NO: 005-0446		SHEET 1 OF 1
FINISH:	QTY: 1	DWN	CHKD	APPD