



FCC / IC – Test report

Report Number : **60/790.14.026.01** Date of Issue: November 27, 2014

Model : TRANSMITR

Product Type : Remote

Applicant : DAYTON INDUSTRIAL CO.,LTD

Address : 2-12 Kwai Fat Road, 11-AKwai Chung, New Territories, Hong Kong

Production Facility : KENDY ELECTRONICE(DONGGUAN)CO,LTD

Address : XIN SI HUANG TANG VILLAGE, HENG LI TOWN , DONGGUAN CITY, GUANGDONG, CHINA

Test Result : **Positive** **Negative**

Total pages including Appendices : 13

TÜV SÜD Hong Kong Ltd. is a subcontractor to TÜV Product Service, GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Hong Kong Ltd. reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Hong Kong Ltd. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Hong Kong Ltd. issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.



1. Table of Contents

1. Table of Contents	2
2. Details about the Test Laboratory	3
3. Description of the Equipment Under Test	4
4. Summary of Test Standards	5
5. Summary of Test Standards and Results	6
6. General Remarks	7
7. Emission Test Results	8
7.1 Radiated Emission Test	8
7.2 20dB& 99% bandwidth measurement	11
8. Test Equipment List	12
9. System Measurement Uncertainty	13



Hong Kong

2. Details about the Test Laboratory

Details about the Test Laboratory

Test site 1

Company name: TÜV SÜD HONG KONG LTD.
3/F, West Wing, Lakeside 2,
10 Science Park West Avenue,
Science Park, Shatin
HK.

Telephone: 852 2776 1323

Fax: 852 2776 1372

Test site 2

Company name: Shenzhen Academy of Metrology and Quality Inspection
No.4 TongFa Road, Xili TownNanshan District, Shenzhen, China
Test Firm FCC Registration number:994606

National Digital Electronic Product Test
No.4 TongFa Road, Xili TownNanshan District, Shenzhen, China
IC Assigned Code: 11177A



3. Description of the Equipment Under Test

Description of the Equipment Under Test

Product:	Remote
Model no.:	TRANSMITR
Serial number:	NIL
Options and accessories:	NIL
FCC ID:	O4GTKRMTE
IC:	7666A- REMOTE
Rated Voltage:	3VDC
Rated Current:	NIL
Rated Power:	NIL
Frequency:	2457MHz
RF Transmission Frequency:	2457MHz
Antenna gain:	0 dBi
No. of Operated Channel:	1
Modulation:	GFSK
Description of the EUT:	Battery operated –1x 3.0V CR2032 battery



4. Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C, Intentional Radiators, 10-1-12 Edition	PART 15 – RADIO FREQUENCY DEVICES Subpart C – Intentional Radiators
RSS-Gen Issue 4 November 2014	General Requirements and Information for the Certification of Radio Apparatus
RSS-210 Issue 8 December 2010	RSS-210 — Licence-exempt Radio Apparatus (All Frequency Bands): Category I Equipment

5. Summary of Test Standards and Results

Emission Tests					
Test Condition	Pages	Test site	Test Result		
			Pass	Fail	N/A
Conducted Emission (47 CFR 15.207, 15.209&RSS-GEN 8.8)	NIL	/	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/> *
Radiated Emission (47 CFR 15.249, 15.209 & RSS-210 A2.9, RSS-GEN 8.9)	8	Site 2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20dB Bandwidth (47 CFR 15.215)	11	Site 2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
99% occupied bandwidth (RSS-GEN 6.6)	11	Site 2	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark: 1.NA: Battery operated only.

2.ForSpurious Radiated Emissions test, three set-up directions(X,Y,Z) were pretested, but only direction X test data was recorded in this report for it is the worst case.

6. General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: O4GTKRMTE complies with the FCC Part 15, Subpart C Rules.

This submittal(s) (test report) is intended for IC:7666A- REMOTE, complies with the IC RSS 210 and RSS-GEN Rules.

All the configurations of the product were tested and only the worst test results are listed in the report.

SUMMARY:

All tests according to the regulations cited on page 6 were

- Performed
- **Not** Performed

The Equipment Under Test

- **Fulfills** the general approval requirements.
- **Does not** fulfill the general approval requirements.

Sample Received Date: November 15, 2014

Testing Start Date: November 18, 2014

Testing End Date: November 22, 2014

- TÜV SÜD HONG KONG LTD. -

Reviewed by:


Edmond FUNG



Prepared by:


CHAN Kwong Ngai

7. Emission Test Results

7.1 Radiated Emission Test

Date of test : November 18, 2014
 Test requirement : FCC Part 15
 Test method : ANSI C63.4-2014
 Operating mode : Transmit mode
 Frequency channel : 2457MHz
 Remarks : Fundamental

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency (MHz)	Polarity (H/V)	Factor (dB)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
2457.000	H	31.8	82.11	114	-31.89	Peak
2457.000	V	31.8	84.35	114	-29.56	Peak
2457.000	H	31.8	77.16	94	-16.84	Average
2457.000	V	31.8	79.92	94	-14.08	Average

Remark: 1.The EUT was placed on the top of the turntable in test site area.
 The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
 For emissions measurement, the receiving antenna was placed 3 meters far away from the turntable. The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.
 Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.
 Adjust the emission and slightly height of the antenna to locate the position with maximum reading.

Date of test : November 18, 2014

Test requirement : FCC Part 15

Test method : ANSI C63.4-2014


Operating mode : Transmit mode

Frequency channel : 2457MHz

Remarks : 9kHz-1GHz(Spurious)

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Horizontal& Vertical



Frequency (MHz)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
35.6	-36.5	12.1	40	-27.9	QP	H
57.7	-34.6	13.5	40	-26.5	QP	H
106.1	-34.1	11.9	43.5	-31.6	QP	H
315.5	-32.6	10.8	46	-35.2	QP	H
610.1	-27.2	20.6	46	-25.4	QP	H
677.8	-27.2	21.1	46	-24.9	QP	H
35.6	-36.5	11.8	40	-28.2	QP	V
57.7	-34.6	13.5	40	-26.5	QP	V
106.1	-34.1	12.4	43.5	-31.1	QP	V
315.5	-32.6	13.3	46	-32.7	QP	V
610.1	-27.2	22.2	46	-23.8	QP	V
677.8	-27.2	23.7	46	-22.3	QP	V

Date of test : November 18, 2014
 Test requirement : FCC Part 15
 Test method : CISPR 16-1-4:2010
 Operating mode : Transmit mode
 Frequency channel : 2457MHz
 Remarks : 1GHz-25GHz(Harmonics and spurious)

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

Frequency (MHz)	Polarity (H/V)	Factor (dB)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector
4914.000	H	5.4	55.8	74.00	18.2	Peak
4914.000	H	5.4	48.1	54.00	5.9	Average
7371.000	H	2.2	53.6	74.00	20.4	Peak
7371.000	H	2.2	47.2	54.00	6.8	Average
4914.000	V	5.4	54.9	74.00	19.1	Peak
4914.000	V	5.4	49.6	54.00	4.4	Average
7371.000	V	2.2	50.5	74.00	23.5	Peak
7371.000	V	2.2	44.8	54.00	9.2	Average


Remark: 1.The EUT was placed on the top of the turntable in test site area.
 The test shall be made in the operation mode. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
 For emissions measurement, the receiving antenna was placed 3 meters far away from the turntable.
 The antenna was fixed on the same height with the EUT to find each suspected emissions of both horizontal and vertical polarization.
 Adjust the emission and slightly rotate the turntable to locate the position with maximum reading.
 Adjust the emission and slightly height of the antenna to locate the position with maximum reading.
 2.Average value=Peak value + duty cycle factor= Peak value-26.2

7.2 20dB& 99% bandwidth measurement

Date of test : November 22, 2014
 Test requirement : FCC Part 15
 Operating mode : Transmit mode
 Frequency channel : 2457MHz
 Remarks : NIL

Test Result	
<input checked="" type="checkbox"/>	Passed
<input type="checkbox"/>	Not Passed

20 dB Bandwidth	99% OBW	Result
kHz	kHz	
173.204	174.8540	Pass



8. Test Equipment List

DESCRIPTION	Type No.	Serial No.	Calibrated date	Calibrated until
EMI Test Receiver	ESU40	SB8501/09	2014.05.16	2015.05.15
Bilog Antenna	Schwarzbeck	SB8501/04	2014.01.20	2015.01.19
Horn Antenna	HF906	SB3435	2014.01.20	2015.01.19
Amplifier(1-18GHz)	--	SB3435/01	2014.01.20	2015.01.19
Amplifier(18-40GHz)	--	SB3435/02	2014.01.20	2015.01.19
Horn Antenna	AT4560	SB5392/02	2014.05.16	2015.05.15
3m Semi-anechoic chamber	9X6X6	SB3450/01	2014.10.12	2015.10.11
Loop Antenna	6512	29604	2014.09.25	2015.09.24
RF cable(0.4m)	/	S02-1404-09-065	2014.05.11	2015.05.10
RF cable(3.5m)	/	S02-1404-09-047	2014.05.11	2015.05.10
RF cable(1.2m)	/	S02-1404-09-052	2014.05.11	2015.05.10
Spectrum Analyzer	E4445A	MY46181814	2013.12.11	2014.12.10
Amplifier	150A250	326446	2014.03.19	2015.03.17
Temp. & Humid. Chamber	FACT5-2.0	4166	2014.11.22	2015.11.21

N.C.R: No calibration request

9. System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

Items		Extended Uncertainty
RE	Field strength (dB μ V/m)	U=3.59dB(9kHz-30MHz) U=5.08dB(30MHz-1GHz) U=4.56dB (1GHz-18GHz) U=4.42dB (18GHz-25GHz)
CE	Disturbance Voltage (dB μ V)	U=2.7dB