

RDR-2 Product specifications

External proximity reader, compatible with the Prox-in-a-Box (PIAB) access control system. The system is designed to limit access to restricted areas, while permitting authorized people to enter.

The reader is 26-bit Wiegand compatible proximity reader and can be used with any other compatible access control system.

It is recommended to install the reader on a wall outside the protected area, and the PIAB control unit inside the protected area.

Proximity access cards or tags are used as keys to open these doors. When in the presence of the reader, the access card emits a coded RF signal that is read by the proximity reader.

Format: 26-bit Wiegand serial communication

Indicators: Tri-color LED (green, red, amber).

Frequency: 125 kHz

Tag reading range:

RDR-2: 50 - 100 mm (2 - 4 in.)

Current Drain: Nominal 50mA, Max. 70mA @12VDC

Operating temperature: -20°C to 50°C (-4°F to 122°F)

Dimensions (L x W x D):

RDR-2: 116 x 70 x 16.8 mm (4 - 1/2 x 2 - 3/8 x 5/8 in.)



Tyco Security Products
23 Habarzel Street
Tel-Aviv 69710, Israel

Tele: +972 3 768 1400
Fax: +972 3 768 1415
www.tycosecurityproducts.com

We, the undersigned,

Company: **Elpas Solutions, Ltd.**, part of the Security Products business unit of Tyco
Address: **23 Habarzel Street, Tel Aviv 69710**
Country: **Israel**
Telephone number: **+972-3-768-1400**
Fax number: **+972-3-768-1415**

certify and declare under our sole responsibility that all devices below are electrically-electronically identical to tested unit RDR-2 Model Number 3-6302-0 :

Part Number	Description	Differences
3-6304-0	Proximity reader RDR-4	Compatible with AXS-100 (Networkable 2-Door controller)
3-6301-2	Proximity reader RDR-1B	Compatible with TIAB KIT2 (Networkable Single Door controller)

Reissued by:

Tel-Aviv, Israel
August 28, 2013

Michael Wasserstein
General Manager