## FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE **EXPOSURE (MPE)**

## **Applicable Standard**

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure									
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)					
0.3–1.34	614	1.63	*(100)	30					
1.34–30	824/f	2.19/f	*(180/f²)	30					
30–300	27.5	0.073	0.2	30					
300–1500	1	1	f/1500	30					
1500–100,000	1	1	1.0	30					

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

## **Calculated Formulary:**

Predication of MPE limit at a given distance

S = PG/ $4\pi$ R<sup>2</sup> = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain; R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \leq 1$$

Report No.: RDG170414008B Page 10 of 33

## **Calculated Data:**

Mode	Frequency (MHz)	Antenna Gain		Maximum Power including tolerance		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm <sup>2</sup> )
		(dBi)	(numeric)	(dBm)	(mW)	(- )	,	( - ,
FHSS	2410-2472	0	1.00	2	1.58	20.00	0.0003	1.0
DTS	2412-2462	0	1.00	23	199.53	20.00	0.0397	1.0

Note: The tune-up power including tolerance is declared by manufacturer.

The 2.4GHz FHSS and DTS can transmit simultaneously:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}}$$

 $=S_{FHSS}/S_{limit-FHSS} + S_{DTS}/S_{limit-DTS}$ 

=0.0003/1+0.0397/1

=0.04

< 1.0

**Result: Compliance**, The device meets MPE requirement for Devices Used by the General Public (Uncontrolled Environment) at distance ≥20 cm.

Report No.: RDG170414008B Page 11 of 33