



# FCC PART 22H, PART 24E

## TEST REPORT

For

### SWAGTEK

10205 NW 19th Street, STE 101, Miami, FL33172, United States

**FCC ID: O55182317**

<b>Report Type:</b> Original Report	<b>Product Type:</b> 3G Feature Phone
<b>Report Number:</b>	RSZ170616003-00C
<b>Report Date:</b>	2017-07-24
<b>Reviewed By:</b>	Engineer <i>Oscar Ye</i>
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....3**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....3

    OBJECTIVE .....3

    RELATED SUBMITTAL(S)/GRANT(S).....3

    TEST METHODOLOGY .....3

    MEASUREMENT UNCERTAINTY.....4

    TEST FACILITY .....4

**SYSTEM TEST CONFIGURATION .....5**

    DESCRIPTION OF TEST CONFIGURATION .....5

    EQUIPMENT MODIFICATIONS .....5

    SUPPORT EQUIPMENT LIST AND DETAILS .....5

    BLOCK DIAGRAM OF TEST SETUP .....5

**SUMMARY OF TEST RESULTS .....6**

**TEST EQUIPMENT LIST .....7**

**FCC §1.1307 & §2.1093 - RF EXPOSURE.....8**

    APPLICABLE STANDARD .....8

    TEST RESULT .....8

**FCC §2.1047 - MODULATION CHARACTERISTIC .....9**

**FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....10**

    APPLICABLE STANDARD .....10

    TEST PROCEDURE .....10

    TEST DATA .....10

**FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH .....15**

    APPLICABLE STANDARD .....15

    TEST PROCEDURE .....15

    TEST DATA .....15

**FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS .....21**

    APPLICABLE STANDARD .....21

    TEST PROCEDURE .....21

    TEST DATA .....21

**FCC § 2.1053; § 22.917 (A);§ 24.238 (A) SPURIOUS RADIATED EMISSIONS .....27**

    APPLICABLE STANDARD .....27

    TEST PROCEDURE .....27

    TEST DATA .....27

**FCC § 22.917 (A); § 24.238 (A) - BAND EDGES.....29**

    APPLICABLE STANDARD .....29

    TEST PROCEDURE .....29

    TEST DATA .....29

**FCC § 2.1055; § 22.355; § 24.235 - FREQUENCY STABILITY .....38**

    APPLICABLE STANDARD .....38

    TEST PROCEDURE .....38

    TEST DATA .....39

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The SWAGTEK's product, model number: *LOGIC B3G (FCC ID: 055182317)* or the "EUT" in this report was a *3G Feature Phone*, which was measured approximately: 21.7 cm (L) × 5.5 cm (W) × 1.7 cm (H), rated with input voltage: DC 3.7V rechargeable battery or DC 5.0V from adapter.

Adapter Information:

Model: B3G

Input: AC100-240V, 50/60Hz, 0.2 A

Output: DC5.0V, 500mA

*Notes: This series products model: iSWAG Star-G, UNONU UM3G and LOGIC B3G are identical; they have the identical schematics, only named differently. Model LOGIC B3G was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.*

*\*All measurement and test data in this report was gathered from production sample serial number: 1701370 (Assigned by BACL, Kunshan). The EUT supplied by the applicant was received on 2017-06-16.*

### Objective

This type approval report is prepared on behalf of SWAGTEK in accordance with Part 2, Part 22-Subpart H, Part 24-Subpart E of the Federal Communication Commission's rules.

The objective is to determine the compliance of EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, and band edge.

### Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS submissions with FCC ID: 055182317.

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-Part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
RF conducted test with spectrum		±0.9dB
Radiated emission	30MHz~1GHz	±5.91dB
	Above 1G	±4.92dB
Occupied Bandwidth		±0.5kHz
Temperature		±1.0°C
Humidity		±6%

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China

Bay Area Compliance Laboratories Corp. (Kunshan) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L9963). And accredited to ISO/IEC 17025 by A2LA(Lab code: 4323.01), the FCC Designation No. CN1185 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Kunshan) was registered with ISED Canada under ISED Canada Registration Number 3062E.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.


### Equipment Modifications

No modification was made to the EUT.

### Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605

### Block Diagram of Test Setup



## **SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: \* Please refer to SAR report released by BACL, report number: RSZ170616003-20.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test</b>					
Sonoma Instrument	Amplifier	330	171377	2016-10-21	2017-10-21
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2016-11-25	2017-11-25
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2016-01-09	2019-01-08
Sunol Sciences	Broadband Antenna	JB3	A090314-1	2016-01-09	2019-01-08
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-09-08	2017-09-08
EMCO	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2016-11-25	2017-11-25
ETS	Horn Antenna	3115	6229	2016-12-12	2019-12-12
ETS	Horn Antenna	3115	9311-4159	2016-01-11	2019-01-10
R&S	Auto test Software	EMC32	V 09.10.0	NCR	NCR
haojintech	Coaxial Cable	Cable-1	001	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-2	002	2016-12-12	2017-12-12
haojintech	Coaxial Cable	Cable-3	003	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-4	004	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-5	005	2016-12-12	2017-12-12
MICRO-COAX	Coaxial Cable	Cable-7	007	2016-12-12	2017-12-12
HP	Signal Generator	8341B	2624A00116	2016-08-29	2017-08-29
<b>RF Conducted test</b>					
BACL	TS 8997 Cable-01	T-KS-EMC086	T-KS-EMC086	2016-12-09	2017-12-08
BACL	RF cable	KS-LAB-012	KS-LAB-012	2016-12-15	2017-12-14
WEINSCHEL	3dB Attenuator	5326	N/A	2017-06-18	2018-06-18
Rohde & Schwarz	OSP120 BASE UNIT	OSP120	101247	2016-07-04	2017-07-03
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2016-09-21	2017-09-21
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	110605	2016-11-25	2017-11-25
HONOVA	Power Splitter	ZFRSC-14-S+	019411452	2017-06-12	2018-06-12

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

---

## **FCC §1.1307 & §2.1093 - RF EXPOSURE**

---

### **Applicable Standard**

FCC§1.1310 and §2.1093.

### **Test Result**

Compliance, please refer to the SAR report: RSZ170616003-20.



---

## **FCC §2.1047 - MODULATION CHARACTERISTIC**

---

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

**FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER**

**Applicable Standard**


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

**Test Procedure**

*Conducted method:*

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



*Radiated method:*

TIA 603-D section 2.2.17

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Nefertari Xu on 2017-07-21.*

**Conducted Power**

**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.00	38.45
	190	836.6	32.00	38.45
	251	848.8	32.48	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	32.04	30.10	28.27	27.39	38.45
	190	836.6	31.99	30.11	28.33	27.43	38.45
	251	848.8	32.47	30.24	28.46	27.51	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		21.65	21.81	21.56
		HSDPA	1	20.34	20.75	20.62
			2	20.30	20.66	20.56
			3	20.37	20.87	20.70
			4	20.39	20.63	20.54
		HSUPA	1	20.38	20.58	20.42
			2	20.37	20.48	20.36
			3	20.47	20.64	20.52
			4	20.31	20.48	20.32
			5	20.46	20.68	20.47

**PCS Band (Part 24E)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	28.83	33
	661	1880.0	28.53	33
	810	1909.8	28.72	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	28.83	26.70	25.11	23.96	33
	661	1880.0	28.53	26.40	24.70	23.73	33
	810	1909.8	28.74	26.29	24.61	23.66	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		21.23	20.85	20.90
		HSDPA	1	20.65	20.44	20.52
			2	20.62	20.32	20.40
			3	20.78	20.47	20.57
			4	20.54	20.33	20.49
		HSUPA	1	20.69	20.41	20.41
			2	20.59	20.31	20.35
			3	20.81	20.52	20.54
			4	20.62	20.36	20.35
			5	20.75	20.46	20.48

**PAR**

**Cellular Band (Part 22H)**

Mode	Channel	PAR (dB)	Limit (dBm)
GSM	Low	0.45	13
	Middle	0.38	13
	High	0.46	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.85	13
	Middle	3.76	13
	High	3.87	13
HSDPA (16QAM)	Low	3.89	13
	Middle	3.74	13
	High	3.82	13
HSUPA (BPSK)	Low	3.89	13
	Middle	3.77	13
	High	3.84	13

**PCS Band (Part 24E)**

Mode	Channel	PAR (dB)	Limit (dBm)
GSM	Low	0.49	13
	Middle	0.35	13
	High	0.43	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	3.75	13
	Middle	3.53	13
	High	3.71	13
HSDPA (16QAM)	Low	3.78	13
	Middle	3.56	13
	High	3.77	13
HSUPA (BPSK)	Low	3.79	13
	Middle	3.59	13
	High	3.73	13

**Radiated Power**

**GSM Mode:**

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for Cellular Band (Part 22H), Middle Channel										
836.60	95.01	20	2.5	H	25.3	0.26	4.75	29.79	38.45	8.66
836.60	95.93	133	2.3	V	22.2	0.26	4.75	26.69	38.45	11.76
EIRP for PCS Band (Part 24E), Middle Channel										
1880.00	80.09	176	1.6	H	18.6	0.45	8.84	26.99	33	6.01
1880.00	79.52	17	1.7	V	15.8	0.45	8.84	24.19	33	8.81

**WCDMA Mode:**

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H/24E	
			Height (m)	Polar (H/V)	Substituted Level (dBm)	Cable loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
ERP for WCDMA Band V (Part 22H), Middle Channel										
85.71	80.24	141	1.9	H	16.0	0.26	4.75	20.49	38.45	17.96
86.93	78.36	317	2.2	V	13.2	0.26	4.75	17.69	38.45	20.76
EIRP for WCDMA Band II (Part 24E), Middle Channel										
1880.00	74.59	130	1.2	H	13.1	0.45	8.84	21.49	33	11.51
1880.00	74.42	302	1.4	V	10.7	0.45	8.84	19.09	33	13.91

**Note:**

All above data were tested with no amplifier.

Absolute Level = Substituted Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

**FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH**


**Applicable Standard**

FCC §2.1049, §22.917, §22.905 and §24.238.

**Test Procedure**

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 5 kHz (GSM) & 100 kHz (WCDMA) and the 26 dB & 99% bandwidth was recorded.



**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	57 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Nefertari Xu on 2017-07-20.*

*EUT operation mode: Transmitting*

Test Result: Compliance. Please refer to the following tables and plots.

**Cellular Band (Part 22H)**

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	248.5	320.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.108	4.669
HSUPA (BPSK)	836.6	4.088	4.689
HSDPA (16QAM)	836.6	4.128	4.669

**PCS Band (Part 24E)**


Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	248.5	324.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.108	4.689
HSUPA (BPSK)	1880.0	4.108	4.709
HSDPA (16QAM)	1880.0	4.108	4.689




**Cellular Band (Part 22H)**


**26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode**




**26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode**



**26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**




**26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**




**PCS Band (Part 24E)**


**26 dB Emissions & 99% Occupied Bandwidth for GSM (GMSK) Mode**




**26 dB Emissions & 99% Occupied Bandwidth for RMC (BPSK) Mode**



**26 dB Emissions & 99% Occupied Bandwidth for HSUPA (BPSK) Mode**



**26 dB Emissions & 99% Occupied Bandwidth for HSDPA (16QAM) Mode**



**FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS**


**Applicable Standard**

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

**Test Procedure**

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10<sup>th</sup> harmonic.



**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	57 %
<b>ATM Pressure:</b>	101.0 kPa


*The testing was performed by Nefertari Xu on 2017-07-20.*

*EUT operation mode: Transmitting*

*Test result: Compliance, please refer to the following plots.*


Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




Fundamental test

1 GHz – 10 GHz (GSM Mode)



### 30 MHz – 1 GHz (WCDMA Mode)


	Marker 1 [T1]	RBW	1 MHz	RF Att	40 dB
Ref Lvl	-32.96 dBm	VBW	3 MHz		
34.5 dBm	984.44889780 MHz	SWT	5 ms	Unit	dBm



Date: 20.JUL.2017 09:44:17

### 1 GHz – 10 GHz (WCDMA Mode)


	Marker 1 [T1]	RBW	1 MHz	RF Att	10 dB
Ref Lvl	-48.04 dBm	VBW	3 MHz		
7.5 dBm	1.64929860 GHz	SWT	52 ms	Unit	dBm




Date: 20.JUL.2017 09:43:26

PCS Band (Part 24E)

30 MHz – 1 GHz (GSM Mode)




1 GHz – 2 GHz (GSM Mode)






### 2 GHz – 20 GHz (GSM Mode)



### 30 MHz – 1 GHz (WCDMA Mode)





## **FCC § 2.1053; § 22.917 (a);§ 24.238 (a) SPURIOUS RADIATED EMISSIONS**

### **Applicable Standard**

FCC § 2.1053, §22.917(a) and § 24.238(a).

### **Test Procedure**

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TX pwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log<sub>10</sub> (power out in Watts)

Spurious attenuation limit in dB = 55 + 10 Log<sub>10</sub> (power out in Watts)

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	46 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Layne Li on 2017-07-07.*

*EUT operation mode: Transmitting*

Pre-scan with Low, Middle and High channel, the worst case as below:

**30 MHz ~ 10 GHz:**

**Cellular Band (Part 22H)**

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Substituted Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
<b>GSM Mode, Middle channel</b>										
248.36	42.26	120	1.3	H	-62.7	0.14	2.05	-60.79	-13	47.79
248.36	40.40	86	1.8	V	-65.0	0.14	2.05	-63.09	-13	50.09
1673.20	52.00	273	1.8	H	-49.8	0.40	8.52	-41.68	-13	28.68
1673.20	57.87	196	1.1	V	-45.9	0.40	8.52	-37.78	-13	24.78
<b>WCDMA Mode, Middle channel</b>										
248.36	42.26	78	1.2	H	-62.7	0.14	2.05	-60.79	-13	47.79
248.36	40.80	303	1.8	V	-64.6	0.14	2.05	-62.69	-13	49.69
1673.20	42.20	7	1.9	H	-59.6	0.40	8.52	-51.48	-13	38.48
1673.20	48.67	279	1.9	V	-55.1	0.40	8.52	-46.98	-13	33.98

**30 MHz ~ 20 GHz:**

**PCS Band (Part 24E)**

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	Substituted Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
<b>GSM Mode, Middle channel</b>										
248.36	42.36	30	1.9	H	-62.6	0.14	2.05	-60.69	-13	47.69
248.36	40.90	69	1.7	V	-64.5	0.14	2.05	-62.59	-13	49.59
3760	54.92	358	1.7	H	-41.1	0.59	9.72	-31.97	-13	18.97
3760	49.91	310	1.7	V	-47.2	0.59	9.72	-38.07	-13	25.07
<b>WCDMA Mode, Middle channel</b>										
248.36	42.26	148	1.9	H	-62.7	0.14	2.05	-60.79	-13	47.79
248.36	40.40	251	1.2	V	-65.0	0.14	2.05	-63.09	-13	50.09
3760	55.22	304	1.1	H	-40.8	0.59	9.72	-31.67	-13	18.67
3760	50.21	140	1.3	V	-46.9	0.59	9.72	-37.77	-13	24.77

**Note:**

- 1) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

**FCC § 22.917 (a); § 24.238 (a) - BAND EDGES**

**Applicable Standard**


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

**Test Procedure**

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



**Test Data**

**Environmental Conditions**


<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	57 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Nefertari Xu on 2017-07-20.*


*EUT operation mode: Transmitting*

*Test Result: Compliance. Please refer to the following plots.*


**Cellular Band, Left Band Edge for GSM (GMSK) Mode**




**Cellular Band, Right Band Edge for GSM (GMSK) Mode**




**Cellular Band, Left Band Edge for WCDMA (BPSK) Mode**




**Cellular Band, Right Band Edge for WCDMA (BPSK) Mode**



### Cellular Band, Left Band Edge for HSDPA (16QAM) Mode




### Cellular Band, Right Band Edge for HSDPA (16QAM) Mode







**Cellular Band, Left Band Edge for HSUPA (BPSK) Mode**




**Cellular Band, Right Band Edge for HSUPA (BPSK) Mode**




**PCS Band, Left Band Edge for GSM (GMSK) Mode**




**PCS Band, Right Band Edge for GSM (GMSK) Mode**




**PCS Band, Left Band Edge for WCDMA (BPSK) Mode**




**PCS Band, Right Band Edge for WCDMA (BPSK) Mode**




### PCS Band, Left Band Edge for HSDPA (16QAM) Mode




### PCS Band, Right Band Edge for HSDPA (16QAM) Mode



**PCS Band, Left Band Edge for HSUPA (BPSK) Mode**



**PCS Band, Right Band Edge for HSUPA (BPSK) Mode**



**FCC § 2.1055; § 22.355; § 24.235 - FREQUENCY STABILITY**

**Applicable Standard**

FCC § 2.1055, §22.355, §24.235.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile > 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

**Test Procedure**

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	57 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Nefertari Xu on 2017-07-20.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

**Cellular Band (Part 22H)**

**GSM Mode**

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	-25	-0.02988	2.5
-20		-25	-0.02988	2.5
-10		-18	-0.02152	2.5
0		-18	-0.02152	2.5
10		-18	-0.02152	2.5
20		-15	-0.01793	2.5
30		20	-0.02391	2.5
40		25	-0.02988	2.5
50		-30	-0.03586	2.5
25		V min.= 3.5	-30	-0.03586
25	V max.= 4.2	-32	-0.03825	2.5

**WCDMA Mode**

Middle Channel, $f_0 = 836.6\text{MHz}$				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	5	0.00598	2.5
-20		5	0.00598	2.5
-10		3	0.00359	2.5
0		3	0.00359	2.5
10		3	0.00359	2.5
20		1	0.00120	2.5
30		3	0.00359	2.5
40		3	0.00359	2.5
50		5	0.00598	2.5
25		V min.= 3.5	9	0.01076
25	V max.= 4.2	10	0.01195	2.5

**PCS Band (Part 24E)**

**GSM Mode**

Middle Channel, $f_0 = 1880.0\text{ MHz}$				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.7	-30	-0.01596	pass
-20		-30	-0.01596	pass
-10		-25	-0.01330	pass
0		-25	-0.01330	pass
10		-25	-0.01330	pass
20		-22	-0.01170	pass
30		-25	-0.01330	pass
40		-30	-0.01596	pass
50		-32	-0.01702	pass
25		V min.= 3.5	-35	-0.01862
25	V max.= 4.2	-41	-0.02181	pass



**WCDMA Mode**

<b>Middle Channel, <math>f_0 = 1880.0</math> MHz</b>				
<b>Temperature (°C)</b>	<b>Power Supplied (V<sub>DC</sub>)</b>	<b>Frequency Error (Hz)</b>	<b>Frequency Error (ppm)</b>	<b>Result</b>
-30	3.7	7	0.00372	pass
-20		7	0.00372	pass
-10		6	0.00319	pass
0		6	0.00319	pass
10		6	0.00319	pass
20		5	0.00266	pass
30		7	0.00372	pass
40		9	0.00479	pass
50		10	0.00532	pass
25	V min.= 3.5	12	0.00638	pass
25	V max.= 4.2	14	0.00745	pass

**\*\*\*\*\* END OF REPORT \*\*\*\*\***