

FCC Part 15B Measurement and Test Report

For

Swagtek

10205 NW 19th Street, STE101, Miami, FL, 33172, USA

FCC ID: O55552416

Test Rule(s):	<u>FCC Part 15 Subpart B</u>
Product Description:	<u>4G Smart Phone</u>
Tested Model:	<u>L5.5E</u>
Report No.:	<u>STR16078163I-6</u>
Tested Date:	<u>2016-07-25 to 2016-08-05</u>
Issued Date:	<u>2016-08-05</u>
Tested By:	<u>Iven Guo / Engineer</u> <i>Iven Guo</i>
Reviewed By:	<u>Silin Chen / EMC Manager</u> <i>Silin chen</i>
Approved & Authorized By:	<u>Jandy so / PSQ Manager</u> <i>Jandyso</i>
Prepared By:	

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND OPERATION MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS	7
3. CONDUCTED EMISSIONS	8
3.1 TEST PROCEDURE.....	8
3.2 BASIC TEST SETUP BLOCK DIAGRAM.....	8
3.3 ENVIRONMENTAL CONDITIONS.....	8
3.4 SUMMARY OF TEST RESULTS/PLOTS.....	8
3.5 CONDUCTED EMISSIONS TEST DATA.....	9
4. RADIATED EMISSIONS	13
4.1 TEST PROCEDURE.....	13
4.2 TEST RECEIVER SETUP.....	14
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	14
4.4 ENVIRONMENTAL CONDITIONS.....	14
4.5 SUMMARY OF TEST RESULTS/PLOTS.....	14

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Swagtek
Address of applicant: 10205 NW 19th Street, STE101, Miami, FL, 33172, USA

Manufacturer: Swagtek
Address of manufacturer: 10205 NW 19th Street, STE101, Miami, FL, 33172, USA

General Description of EUT	
Product Name:	4G Smart Phone
Trade Name:	LOGIC
Model No.:	L5.5E
Adding Model(s):	/
Hardware Version:	S6T050S2_V002 (A570_MB_V4.0)
Software Version:	MRA58K test-keys
IMEI:	357835050862125/357835050862133
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. All test data carry on SIM1 which is the worst case.</i>	

Technical Characteristics of EUT	
Rated Voltage:	DC 3.8V
Rated Current:	/
Rated Power:	/
Power Adapter Model:	L5.5E
	Input: 100-240V~50/60Hz; Output: DC5V /1.0A
Lowest Internal Frequency:	32.768kHz
Highest Internal Frequency:	1.3GHz
Classification of ITE:	Class B

1.2 Test Standards

The following report is prepared on behalf of the Swagtek in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart B, and section 15.205, 15.107, and 15.109 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Operation Mode

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted according to the operation manual for use, more detailed description as follows:

Test Mode List:

Test Mode	Description	Remark
TM1	Charging + Playing	/
TM2	Downloading	/
TM3	Charging + Camera	/

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.0	Shielded	Without Ferrite
Earphone	1.2	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Conducted Emissions	Conducted	±2.88dB
Transmitter Spurious Emissions	Radiated	±5.1dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	ETS	3116B	00088203	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.107 (a)	Conducted Emissions	Compliant
§ 15.109 (a)	Radiated Emissions	Compliant


N/A: not applicable

3. Conducted Emissions

3.1 Test Procedure

Test is conducting under the description of ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

3.2 Basic Test Setup Block Diagram



3.3 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

3.4 Summary of Test Results/Plots


According to the data in section 3.5, the EUT complied with the FCC Part 15.107(a) Conducted margin for a Class B device, with the *worst* margin reading of:

-1.15 dB at 0.5780 MHz in the **Line, Peak** detector, 0.15-30MHz

3.5 Conducted Emissions Test Data


Plot of Conducted Emissions Test Data

EUT: 4G Smart Phone
 Tested Model: L5.5E
 Operating Condition: TM1
 Comment: AC 120V/60Hz; Adapter DC 5V
 Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	29.50	9.50	39.00	55.56	-16.56	AVG
2	0.1620	50.82	9.50	60.32	65.36	-5.04	peak
3	0.5860	25.15	9.58	34.73	46.00	-11.27	AVG
4*	0.5900	43.40	9.58	52.98	56.00	-3.02	peak
5	0.6940	43.12	9.61	52.73	56.00	-3.27	peak
6	0.6980	22.45	9.61	32.06	46.00	-13.94	AVG


Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1540	30.63	9.50	40.13	55.78	-15.65	AVG
2	0.1580	50.31	9.50	59.81	65.57	-5.76	peak
3	0.5700	28.40	9.58	37.98	46.00	-8.02	AVG
4*	0.5780	45.27	9.58	54.85	56.00	-1.15	peak
5	1.0060	42.74	9.68	52.42	56.00	-3.58	peak
6	1.0060	24.56	9.68	34.24	46.00	-11.76	AVG


Plot of Conducted Emissions Test Data

EUT: 4G Smart Phone
 Tested Model: L5.5E
 Operating Condition: TM2
 Comment: AC 120V/60Hz; USB 5V
 Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5220	32.37	5.80	38.17	56.00	-17.83	peak
2	0.5380	19.92	5.80	25.72	46.00	-20.28	AVG
3	1.2540	18.26	5.75	24.01	46.00	-21.99	AVG
4	1.2780	31.69	5.75	37.44	56.00	-18.56	peak
5	4.2460	33.04	5.68	38.72	56.00	-17.28	peak
6*	4.2460	23.58	5.68	29.26	46.00	-16.74	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.5380	20.36	5.80	26.16	46.00	-19.84	AVG
2	0.5460	33.21	5.80	39.01	56.00	-16.99	peak
3	0.9100	33.37	5.77	39.14	56.00	-16.86	peak
4	0.9100	19.93	5.77	25.70	46.00	-20.30	AVG
5*	4.2420	27.10	5.68	32.78	46.00	-13.22	AVG
6	4.4420	35.67	5.67	41.34	56.00	-14.66	peak


4. Radiated Emissions

4.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.109 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.



4.2 Test Receiver Setup

Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for a Class B device. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15.109(a) Limit}$$

4.4 Environmental Conditions

Temperature:	23 °C
Relative Humidity:	55 %
ATM Pressure:	1011 mbar


4.5 Summary of Test Results/Plots

According to the data, the EUT complied with the FCC Part 15.109(a) rule, and had the worst margin of:

-5.39 dB at 80.9275 MHz in the Vertical polarization, TM1 mode, **30MHz to 6 GHz, 3Meters**


Plot of Radiated Emissions Test Data

EUT: 4G Smart Phone
 Tested Model: L5.5E
 Operating Condition: TM1
 Comment: AC 120V/60Hz; Adapter DC 5V
 Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	81.4970	30.54	1.98	32.52	40.00	-7.48	58	100	peak
2	140.8351	29.76	3.12	32.88	43.50	-10.62	326	100	peak
3	169.0054	34.45	2.46	36.91	43.50	-6.59	29	100	peak
4	185.7882	28.67	2.70	31.37	43.50	-12.13	209	100	peak
5	289.0021	19.70	11.52	31.22	46.00	-14.78	359	100	peak
6	447.9822	25.31	12.71	38.02	46.00	-7.98	180	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.3534	21.36	4.94	26.30	40.00	-13.70	51	100	peak
2	80.9275	32.74	1.87	34.61	40.00	-5.39	308	100	peak
3	140.8351	28.47	3.12	31.59	43.50	-11.91	120	100	peak
4	168.4138	33.18	2.47	35.65	43.50	-7.85	21	100	peak
5	186.4409	31.18	2.73	33.91	43.50	-9.59	359	100	peak
6	642.8613	17.01	18.00	35.01	46.00	-10.99	180	100	peak


Plot of Radiated Emissions Test Data

EUT: 4G Smart Phone
 Tested Model: L5.5E
 Operating Condition: TM2
 Comment: USB: DC5V
 Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	59.6493	20.90	5.03	25.93	40.00	-14.07	180	100	peak
2	174.4241	33.39	2.46	35.85	43.50	-7.65	352	100	peak
3	245.0900	24.13	9.13	33.26	46.00	-12.74	178	100	peak
4	480.5276	23.58	12.58	36.16	46.00	-9.84	189	100	peak
5	668.1423	18.55	18.03	36.58	46.00	-9.42	27	100	peak
6	836.2443	22.34	15.96	38.30	46.00	-7.70	350	100	peak


Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	54.0711	18.29	5.04	23.33	40.00	-16.67	185	100	peak
2	61.1316	22.61	4.80	27.41	40.00	-12.59	278	100	peak
3	167.8243	29.55	2.47	32.02	43.50	-11.48	180	100	peak
4	194.4534	27.90	3.10	31.00	43.50	-12.50	185	100	peak
5	480.5276	22.22	12.58	34.80	46.00	-11.20	357	100	peak
6	665.8035	16.75	17.90	34.65	46.00	-11.35	355	100	peak


Plot of Radiated Emissions Test Data

EUT: 4G Smart Phone
 Tested Model: L5.5E
 Operating Condition: TM3
 Comment: AC 120V/60Hz; Adapter DC 5V
 Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	80.9275	30.85	1.87	32.72	40.00	-7.28	180	100	peak
2	140.3421	29.89	3.14	33.03	43.50	-10.47	196	100	peak
3	168.4138	33.62	2.47	36.09	43.50	-7.41	352	100	peak
4	183.2005	29.34	2.58	31.92	43.50	-11.58	308	100	peak
5	229.2931	20.97	8.25	29.22	46.00	-16.78	355	100	peak
6	455.9058	23.39	12.92	36.31	46.00	-9.69	321	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	80.9275	32.12	1.87	33.99	40.00	-6.01	100	100	peak
2	140.3421	28.02	3.14	31.16	43.50	-12.34	355	100	peak
3	165.4867	33.16	2.45	35.61	43.50	-7.89	180	100	peak
4	185.7882	31.81	2.70	34.51	43.50	-8.99	180	100	peak
5	231.7179	21.99	8.40	30.39	46.00	-15.61	351	100	peak
6	663.4729	16.39	17.76	34.15	46.00	-11.85	182	100	peak

Note: Testing is carried out with frequency rang 9kHz to the 6GHz, which above 1GHz is close to the noise base even antenna close up to 1meter distance according the measurement of ANSI C63.4.

The measurements greater than 20dB below the limit from 9kHz to 30MHz and test data are not provided.

***** END OF REPORT *****