

**FCC 47 CFR PART 15 SUBPART C**

**CERTIFICATION TEST REPORT**

*For*

Bluetooth Keyboard

MODEL No.: BKC700

FCC ID: O57BKC700

Trademark: Lenovo

REPORT NO.: ES160920006E

ISSUE DATE: October 9, 2016

*Prepared for*

Lenovo(Shanghai) Electronics Technology Co., Ltd.

NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone,  
200131, China

*Prepared by*

EMTEK (SHENZHEN) CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,  
Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

## Table of Contents

1	TEST RESULT CERTIFICATION .....	3
2	EUT TECHNICAL DESCRIPTION.....	4
3	SUMMARY OF TEST RESULT .....	5
4	TEST METHODOLOGY .....	6
4.1	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	6
4.2	MEASUREMENT EQUIPMENT USED.....	6
4.3	DESCRIPTION OF TEST MODES .....	8
5	FACILITIES AND ACCREDITATIONS .....	9
5.1	FACILITIES .....	9
5.2	LABORATORY ACCREDITATIONS AND LISTINGS.....	9
6	TEST SYSTEM UNCERTAINTY .....	10
7	SETUP OF EQUIPMENT UNDER TEST .....	11
7.1	RADIO FREQUENCY TEST SETUP 1 .....	11
7.2	RADIO FREQUENCY TEST SETUP 2 .....	11
7.3	CONDUCTED EMISSION TEST SETUP .....	13
7.4	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	14
7.5	SUPPORT EQUIPMENT .....	14
8	Frequency Hopping System Requirements.....	15
8.1	Standard Applicable .....	15
8.2	EUT Pseudorandom Frequency Hopping Sequence.....	15
8.3	Equal Hopping Frequency Use .....	16
8.4	Frequency Hopping System .....	16
9	TEST REQUIREMENTS .....	17
9.1	20DB BANDWIDTH .....	17
9.2	CARRIER FREQUENCY SEPARATION .....	20
9.3	NUMBER OF HOPPING FREQUENCIES.....	23
9.4	AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	25
9.5	MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	28
9.6	CONDUCTED SUPRIIOUS EMISSION .....	31
9.7	RADIATED SPURIOUS EMISSION .....	38
9.8	CONDUCTED EMISSION TEST .....	51
9.9	ANTENNA APPLICATION.....	54

## 1 TEST RESULT CERTIFICATION

Applicant:	Lenovo(Shanghai) Electronics Technology Co., Ltd. NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot Free Trade Zone, 200131, China
Manufacturer:	Lenovo PC HK Limited 23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong
Factory:	Shenzhen Doking Technology Co., Ltd 21F Jiayu Building Songgang Town Baoan District Shenzhen China  Building 1-3 Dingfeng Hi-Tech Park Shapuwe Industrial Zone, Songgang Town Baoan District Shenzhen China
Product Description:	Bluetooth Keyboard
Model Number:	BKC700
File Number:	ES160920006E
Date of Test:	September 20, 2016 to October 9, 2016

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test : September 20, 2016 to October 9, 2016

Prepared by : Joanna Jiao /Editor

Reviewer : Joe Xia /Supervisor

Approve & Authorized Signer : Lisa Wang/Manager

## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Data Rate	1Mbps
Modulation:	GFSK
Operating Frequency Range(s):	2402-2480MHz
Number of Channels:	79 Channels
Transmit Power Max:	5.313 dBm
Antenna Type	PCB antenna
Antenna Gain	1.87dBi
Power supply	<input checked="" type="checkbox"/> DC supply: DC3.7V from lithium battery and DC5V from USB Port
	<input type="checkbox"/> Adaptor supply: N/A
Temperature Range:	-10°C ~ +50°C

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
15.247(b)	Antenna Application	PASS	
NOTE1: N/A (Not Applicable)			

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: O57BKC700 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:  
FCC 47 CFR Part 2, Subpart J  
FCC 47 CFR Part 15, Subpart C  
DA 00-705

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Conducted Emission Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Test Receiver	R & S	ESCI	26115-010-0027	May 28, 2016	1 Year
L.I.S.N.	R & S	ENV216	101161	May 28, 2016	1 Year
50Ω Coaxial Switch	Anritsu	MP59B	6100175589	May 29, 2016	1 Year
Voltage Probe	R & S	ESH2-Z3	100122	May 29, 2016	1 Year

#### 4.2.2 Radiated Emission Test Equipment

##### For 3m Radiated Emission Measurement 9K-30M

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	R & S	ESU	1302.6005.26	May 29, 2016	1 Year
Loop Antenna	Schwarzbeck	FMZB 1519	1519-012	May 28, 2016	1 Year
Cable		3M SF104-26.5	295838/4	May 29, 2016	1 Year
Cable		6M SF104-26.5	295840/4	May 29, 2016	1 Year

##### For 3m Radiated Emission Measurement 30M-1G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	R & S	ESU	1302.6005.26	May 29, 2016	1 Year
Pre-Amplifier	HP	8447F	2944A07999	May 28, 2016	1 Year
Bilog Antenna	Schwarzbeck	VULB9163	142	May 28, 2016	1 Year
Cable	Schwarzbeck	AK9513	ACRX1	May 29, 2016	1 Year
Cable	Rosenberger	N/A	FP2RX2	May 29, 2016	1 Year
Cable	Schwarzbeck	AK9513	CRPX1	May 29, 2016	1 Year
Cable	Schwarzbeck	AK9513	CRRX2	May 29, 2016	1 Year

##### For 3m Radiated Emission Measurement 1G-18G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	R & S	ESU	1302.6005.26	May 29, 2016	1 Year
Pre-Amplifier	A.H.	PAM-0126	1415261	May 28, 2016	1 Year
Horn Antenna	Schwarzbeck	BBHA 9120	707	May 28, 2016	1 Year
Cable	H+B	0.5M SF104-26.5	289147/4	May 29, 2016	1 Year
Cable	H+B	3M SF104-26.5	295838/4	May 29, 2016	1 Year
Cable	H+B	6M SF104-26.5	295840/4	May 29, 2016	1 Year

#### For 3m Radiated Emission Measurement 18G-26.5G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	R & S	ESU	1302.6005.26	May 29, 2016	1 Year
Pre-Amplifier	A.H.	PAM-0126	1415261	May 28, 2016	1 Year
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	May 29, 2016	1 Year
Cable	H+B	0.5M SF104-26.5	289147/4	May 29, 2016	1 Year
Cable	H+B	3M SF104-26.5	295838/4	May 29, 2016	1 Year
Cable	H+B	6M SF104-26.5	295840/4	May 29, 2016	1 Year

#### For 3m Radiated Emission Measurement 26.5G-40G

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
EMI Test Receiver	R & S	FSV40	132.1-3008K39- 100967-AP	May 28, 2016	1 Year
Pre-Amplifier	Lunar EM	LNA26G40-40	J101313102800 1	May 28, 2016	1 Year
Horn Antenna	AHS/USA	SAS-573	184	May 29, 2016	1 Year
Cable	A.H	SAC-40G-1	414	May 29, 2016	1 Year
Cable	A.H	SAC-40G-1	413	May 29, 2016	1 Year

#### 4.2.3 Radio Frequency Test Equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
Spectrum Analyzer	Agilent	E4407B	88156318	May 28, 2016	1 Year
Power meter	Anritsu	ML2495A	0824006	May 28, 2016	1 Year
Power sensor	Anritsu	MA2411B	0738172	May 28, 2016	1 Year
Spectrum Analyzer	Agilent	N9010A	My53470879	May 28, 2016	1 Year
Spectrum Analyzer	R & S	FSV40	100967	May 28, 2016	1 Year

**Remark:** Each piece of equipment is scheduled for calibration once a year.

### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth BR GFSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	...	...
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	...	...	...	78	2480
Note: $f_c = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ $k=1$ to 79					

Test Frequency and channel for Bluetooth:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480



## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

- EMC Lab.
- : Accredited by CNAS, 2013.10.29  
The certificate is valid until 2016.10.28  
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)  
The Certificate Registration Number is L2291
  - : Accredited by TUV Rheinland Shenzhen, 2010.5.25  
The Laboratory has been assessed according to the requirements ISO/IEC 17025.
  - : Accredited by FCC, July 06, 2016  
The Certificate Registration Number is 406365.
  - : Accredited by Industry Canada, November 24, 2015  
The Certificate Registration Number is 4480A

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


#### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (Perfect Share Mini) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



#### 7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



#### 7.5 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

### 8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.



## 9 TEST REQUIREMENTS

### 9.1 20DB BANDWIDTH

#### 9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

#### 9.1.2 Conformance Limit

No limit requirement.

#### 9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.1.4 Test Procedure

The EUT was operating in Bluetooth mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.

### Test Results


Temperature:	24°C	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	00	2402	914.3	N/A	PASS
	39	2441	914.7	N/A	PASS
	78	2480	916.0	N/A	PASS
Note: N/A (Not Applicable)					

Test Model	20dB Bandwidth	GFSK Modulation
	Bluetooth DSS	
	Channel 0: 2402MHz	



Test Model	20dB Bandwidth	GFSK Modulation
	Bluetooth DSS	
	Channel 39: 2441MHz	



Test Model	20dB Bandwidth
	Bluetooth DSS
	Channel 78: 2480MHz
	GFSK Modulation



## 9.2 CARRIER FREQUENCY SEPARATION

### 9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

### 9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### 9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.2.4 Test Procedure

■ According to FCC Part 15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Set the RBW = 100kHz. Set VBW = 300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.


Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

### Test Results


Temperature:	24 °C	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	0	2402	1005.0	>914.3	PASS
	39	2441	1002.0	>914.7	PASS
	78	2480	978.0	>916.0	PASS
Note: GFSK Limit=20dB bandwidth, output power is less than 1000mW (30dBm).					


Test Model	<div>Carrier Frequency Separation</div> <div>Bluetooth DSS</div> <div>Channel 0: 2402MHz</div> <div>GFSK Modulation</div>
------------	---



Test Model	<div>Carrier Frequency Separation</div> <div>Bluetooth DSS</div> <div>Channel 39: 2441MHz</div> <div>GFSK Modulation</div>
------------	--



Test Model	Carrier Frequency Separation Bluetooth DSS Channel 78: 2480MHz	GFSK Modulation
------------	--	-----------------



### 9.3 NUMBER OF HOPPING FREQUENCIES

#### 9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and DA 00-705

#### 9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

#### 9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.3.4 Test Procedure

- According to FCC Part 15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2400-2483.5MHz)

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold


Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

#### Test Results

Temperature:	24 °C	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480	79	> 15

Test Model	Number Of Hopping Frequencies	
	Bluetooth DSS	
	Span: 2400-2483.5MHz	





## 9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

### 9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and DA 00-705

### 9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

### 9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.4.4 Test Procedure

- According to FCC Part 15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

### 9.4.5 Test Results


Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Temperature:	24 °C	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong


  

Modulation Mode	Channel Number	Packet type	Pulse width (ms)	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	0	DH1	0.364	116.48	<400	PASS
	0	DH3	1.617	258.72	<400	PASS
	0	DH5	2.850	304.00	<400	PASS
Note: Dwell Time(DH1)=PW*(1600/2/79)*31.6 Dwell Time(DH3)=PW*(1600/4/79)*31.6 Dwell Time(DH5)=PW*(1600/6/79)*31.6						


Test Model	Average Time Of Occupancy (Dwell Time)	
	Bluetooth DSS	GFSK DH1
	CH 0: 2402MHz	



Test Model	Average Time Of Occupancy (Dwell Time)	
	Bluetooth DSS	GFSK DH3
	CH 0: 2402MHz	



Test Model	Average Time Of Occupancy (Dwell Time)	
	Bluetooth DSS	GFSK DH5



## 9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and DA 00-705

### 9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.5.4 Test Procedure

■ According to FCC Part 15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel (about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured (about 3MHz)

Set VBW  $\geq$  RBW

Set Sweep = auto

Set Detector function = peak

Set Trace = max hold

Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.

## Test Results


Temperature:	24°C	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
GFSK	0	2402	5.244	30	PASS
	39	2441	4.988	30	PASS
	78	2480	5.313	30	PASS
Note: N/A					

Test Model	Maximum Peak Conducted Output Power	
	Bluetooth DSS	GFSK
	Channel 0: 2402MHz	



Test Model	Maximum Peak Conducted Output Power	
	Bluetooth DSS	GFSK
	Channel 39: 2441MHz	



Test Model	Maximum Peak Conducted Output Power	
	Bluetooth DSS	GFSK
	Channel 78: 2480MHz	



## 9.6 CONDUCTED SUPRIIOUS EMISSION

### 9.6.1 Applicable Standard

According to FCC Part 15.247(d) and DA 00-705

### 9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW  $\geq 3 \times$  RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conduceted level.

Note that the channel found to contain the maximum conduceted level can be used to establish the reference level.

#### ■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW  $\geq 1\%$  of the span=100kHz Set VBW  $\geq$  RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.

The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

#### ■ Conduceted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz). Set RBW = 100 kHz Set VBW  $\geq$  RBW


Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


### 9.6.5 Test Results

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Test Model	Maximum Conducted Level RBW=100kHz	
	Bluetooth DSS	GFSK
	Channel 0: 2402MHz	




Test Model	Conducted Spurious RF Conducted Emission	
	Bluetooth DSS	GFSK
	Channel 0: 2402MHz	






Test Model	Band-edge Conducted Emissions	
	Bluetooth DSS	GFSK
	Channel 0: 2402MHz	



Test Model	Maximum Conducted Level RBW=100kHz	
	Bluetooth DSS	GFSK
	Channel 39: 2441MHz	



Test Model	Conduceted Spurious RF Conducted Emission	
	Bluetooth DSS	GFSK
	Channel 39: 2441MHz	




Test Model	Maximum Conduceted Level RBW=100kHz	
	Bluetooth DSS	GFSK
	Channel 78: 2480MHz	



Test Model	Conduceted Spurious RF Conducted Emission	
	Bluetooth DSS	GFSK
	Channel 78: 2480MHz	




Test Model	Band-edge Conducted Emissions	
	Bluetooth DSS	GFSK
	Channel 78: 2480MHz	




Test Model

Maximum Conduceted Level RBW=100kHz  
Bluetooth DSS  
Hopping GFSK



Test Model


Conduceted Spurious RF Conducted Emission  
Bluetooth DSS  
Hopping GFSK



Test Model

Band-edge Conducted Emissions  
Bluetooth DSS  
Hopping


GFSK



Test Model

Band-edge Conducted Emissions  
Bluetooth DSS  
Hopping

GFSK



## 9.7 RADIATED SPURIOUS EMISSION

### 9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

### 9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).  
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

## 9.7.5 Test Results

### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	24°C	Test Date:	N/A
Humidity:	53 %	Test By:	KK
Test mode:	TX Mode		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance}/\text{test distance})$  (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Temperature:	24℃	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4790.61	V	43.31	26.98	74.00	54.00	-30.69	-27.02
7202.14	V	49.32	34.24	74.00	54.00	-24.68	-19.76
9570.07	V	47.75	32.51	74.00	54.00	-26.25	-21.49
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4807.66	H	44.96	29.18	74.00	54.00	-29.04	-24.82
7202.08	H	50.20	35.85	74.00	54.00	-23.80	-18.15
9008.97	H	47.50	31.83	74.00	54.00	-26.50	-22.17

Temperature:	24℃	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong
Test mode:	GFSK	Frequency:	Channel 39: 2441MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4858.74	V	51.39	35.47	74.00	54.00	-22.61	-18.53
7340.64	V	49.95	34.44	74.00	54.00	-24.05	-19.56
10349.61	V	49.80	36.23	74.00	54.00	-24.20	-17.77
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4892.55	H	50.42	35.94	74.00	54.00	-23.58	-18.06
7304.19	H	47.53	31.22	74.00	54.00	-26.47	-22.78
10179.60	H	49.49	34.93	74.00	54.00	-24.51	-19.07

Temperature:	24℃	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong
Test mode:	GFSK	Frequency:	Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4958.21	V	46.64	31.34	74.00	54.00	-27.36	-22.66
7445.05	V	51.12	35.46	74.00	54.00	-22.88	-18.54
10551.19	V	49.00	34.83	74.00	54.00	-25.00	-19.17
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4960.60	H	46.92	31.32	74.00	54.00	-27.08	-22.68
7442.63	H	50.06	34.90	74.00	54.00	-23.94	-19.10
9565.18	H	47.21	32.37	74.00	54.00	-26.79	-21.63

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
  - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
  - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Temperature:	24℃	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2387.60	H	46.93	74	30.10	54
2386.48	V	41.80	74	25.10	54

Temperature:	24℃	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	King Kong
Test mode:	GFSK	Frequency:	Channel 78: 2480MHz


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.731	H	40.66	74	25.10	54
2486.486	V	40.85	74	25.70	54

Temperature:	24℃	Test Date:	September 28, 2016
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Hopping


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2383.960	H	42.58	74	26.30	54
2385.200	V	45.75	74	30.50	54
2401.000	H	44.23	74	28.20	54
2400.000	V	50.19	74	35.60	54

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth DSS		
	Channel 0: 2402MHz	GFSK	H
	Test By: King Kong		




Test Model	Spurious Emission in Restricted Band 2310-2390MHz		
	Bluetooth DSS		
	Channel 0: 2402MHz	GFSK	V
	Test By: King Kong		




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth DSS		
	Channel 78: 2480MHz	GFSK	H
Test By: King Kong			




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth DSS		
	Channel 78: 2480MHz	GFSK	V
Test By: King Kong			




Test Model	Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz		
	Bluetooth DSS		
	Hopping	GFSK	H
Test By: King Kong			



Test Model	Spurious Emission in Restricted Band 2310-2390MHz and 2400-2483.5MHz		
	Bluetooth DSS		
	Hopping	GFSK	V
Test By: King Kong			



■ Spurious Emission below 1GHz (30MHz to 1GHz)



Site 3m Chamber #3

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15C

Power: AC 120V/60Hz

Humidity: 53 %


Mode:TX BT 3.0 LOW

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		72.6800	47.39	-18.44	28.95	40.00	-11.05	QP		
2		103.7200	50.29	-15.30	34.99	43.50	-8.51	QP		
3		186.1700	47.13	-16.93	30.20	43.50	-13.30	QP		
4		267.6500	42.24	-12.79	29.45	46.00	-16.55	QP		
5		288.0200	47.95	-12.11	35.84	46.00	-10.16	QP		
6	*	335.5500	50.67	-10.51	40.16	46.00	-5.84	QP		

\*:Maximum data x:Over limit !:over margin

Operator:



Site 3m Chamber #3

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15C

Power: AC 120V/60Hz

Humidity: 53 %


Mode:TX BT 3.0 LOW

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table
		MHz	Level	Factor	ment			Height	Degree
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
							Detector		Comment
1		110.5100	39.63	-15.48	24.15	43.50	-19.35	QP	
2		186.1700	45.13	-16.93	28.20	43.50	-15.30	QP	
3		288.0200	48.10	-12.11	35.99	46.00	-10.01	QP	
4		316.1500	46.01	-11.39	34.62	46.00	-11.38	QP	
5	*	335.5500	49.47	-10.51	38.96	46.00	-7.04	QP	
6		720.6400	33.34	-3.95	29.39	46.00	-16.61	QP	

\*:Maximum data x:Over limit !:over margin


Operator:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		104.6900	51.49	-15.32	36.17	43.50	-7.33	QP			
2		182.2900	48.35	-17.08	31.27	43.50	-12.23	QP			
3		288.0200	47.34	-12.11	35.23	46.00	-10.77	QP			
4	*	335.5500	49.35	-10.51	38.84	46.00	-7.16	QP			
5		528.5800	38.18	-7.00	31.18	46.00	-14.82	QP			
6		579.0200	39.29	-6.18	33.11	46.00	-12.89	QP			

\*:Maximum data    x:Over limit    !:over margin

Operator:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		186.1700	45.91	-16.93	28.98	43.50	-14.52	QP		
2		288.0200	47.96	-12.11	35.85	46.00	-10.15	QP		
3	*	335.5500	49.24	-10.51	38.73	46.00	-7.27	QP		
4		386.9600	36.48	-9.90	26.58	46.00	-19.42	QP		
5		596.4800	32.91	-5.90	27.01	46.00	-18.99	QP		
6		720.6400	33.47	-3.95	29.52	46.00	-16.48	QP		

\*:Maximum data x:Over limit !:over margin

Operator:






No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		104.6900	51.04	-15.32	35.72	43.50	-7.78	QP		
2		156.1000	49.22	-18.56	30.66	43.50	-12.84	QP		
3		288.0200	47.19	-12.11	35.08	46.00	-10.92	QP		
4	*	335.5500	50.82	-10.51	40.31	46.00	-5.69	QP		
5		444.1900	37.49	-8.71	28.78	46.00	-17.22	QP		
6		579.0200	39.17	-6.18	32.99	46.00	-13.01	QP		

\*:Maximum data x:Over limit !:over margin

Operator:



Site 3m Chamber #3 Polarization: **Horizontal** Temperature: 24 C  
 Limit: (RE)FCC PART 15C Power: AC 120V/60Hz Humidity: 53 %  
 Mode:TX BT 3.0 HIGH  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		161.9200	45.39	-18.16	27.23	43.50	-16.27	QP		
2		185.2000	45.38	-16.97	28.41	43.50	-15.09	QP		
3		230.7900	43.41	-14.19	29.22	46.00	-16.78	QP		
4		288.0200	47.98	-12.11	35.87	46.00	-10.13	QP		
5	*	335.5500	48.29	-10.51	37.78	46.00	-8.22	QP		
6		441.2800	34.97	-8.67	26.30	46.00	-19.70	QP		

\*:Maximum data x:Over limit !:over margin

Operator:

## 9.8 CONDUCTED EMISSION TEST

### 9.8.1 Applicable Standard

According to FCC Part 15.207(a)

### 9.8.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50
Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.		

### 9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

### 9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.  
 Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
 Repeat above procedures until all frequency measured were complete.

### 9.8.5 Test Results

Pass

The 120V & 240V voltage have been tested, and the worst result recorded was report as below:

## Conducted Emission Measurement


File :doking

Data :#3

Date: 16/09/22/

Time: 2/18/19

80.0 dBuV



Site Conduction #1

Phase: **L1**

Temperature: 22

Limit: (CE)FCC Part15 class B\_QP

Power: AC 120V/60Hz

Humidity: 55 %

Mode: ON

Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector	Comment
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.1800	42.44	0.00	42.44	64.49	-22.05	QP	
2	0.1800	29.15	0.00	29.15	54.49	-25.34	AVG	
3	0.2400	39.69	0.00	39.69	62.10	-22.41	QP	
4	0.2400	27.25	0.00	27.25	52.10	-24.85	AVG	
5	0.5050	47.50	0.00	47.50	56.00	-8.50	QP	
6 *	0.5050	39.45	0.00	39.45	46.00	-6.55	AVG	
7	0.8650	41.50	0.00	41.50	56.00	-14.50	QP	
8	0.8650	31.11	0.00	31.11	46.00	-14.89	AVG	
9	1.2200	37.71	0.00	37.71	56.00	-18.29	QP	
10	1.2200	25.99	0.00	25.99	46.00	-20.01	AVG	
11	1.6050	37.72	0.00	37.72	56.00	-18.28	QP	
12	1.6050	25.79	0.00	25.79	46.00	-20.21	AVG	

\*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:

### Conducted Emission Measurement


File :doking

Data :#4

Date: 16/09/22/

Time: 2/20/55

80.0 dBuV



Site Conduction #1

Phase: **N**

Temperature: 22

Limit: (CE)FCC Part15 class B\_QP

Power: AC 120V/60Hz

Humidity: 55 %

Mode: ON

Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	0.1685	42.52	0.00	42.52	65.03	-22.51	QP	
2	0.1685	25.16	0.00	25.16	55.03	-29.87	AVG	
3	0.2600	39.97	0.00	39.97	61.43	-21.46	QP	
4	0.2600	23.68	0.00	23.68	51.43	-27.75	AVG	
5 *	0.5100	47.71	0.00	47.71	56.00	-8.29	QP	
6	0.5100	34.29	0.00	34.29	46.00	-11.71	AVG	
7	0.8850	39.47	0.00	39.47	56.00	-16.53	QP	
8	0.8850	25.02	0.00	25.02	46.00	-20.98	AVG	
9	1.2650	35.96	0.00	35.96	56.00	-20.04	QP	
10	1.2650	20.19	0.00	20.19	46.00	-25.81	AVG	
11	1.6500	36.43	0.00	36.43	56.00	-19.57	QP	
12	1.6500	20.78	0.00	20.78	46.00	-25.22	AVG	

\*:Maximum data    x:Over limit    !:over margin    Comment: Factor build in receiver.    Operator:

## 9.9 ANTENNA APPLICATION

### 9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 9.9.2 Result

PASS.

The EUT has 1 antenna: a PCB antenna for BT, the gain is 1.87 dBi;

- Note:
- ☒ Antenna use a permanently attached antenna which is not replaceable.
  - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
  - ☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.