


TEST REPORT

Applicant: Lenovo (Shanghai) Electronics Technology Co., Ltd.
Address: Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA
Equipment Type: Notebook Computer
Model Name: LNV CB Duet 11M889, LNV Chrome Duet EDU G2 (refer to section 2.3)
Brand Name: Lenovo
FCC ID: O57DUET11M889
Test Standard: FCC 47 CFR Part 2.1093 (refer to section 3.1)
Maximum SAR: Body (1 g): 0.71 W/kg
Limbs (10 g): 0.31 W/kg
Sample Arrival Date: May 11, 2024
Test Date: May 15, 2024 - May 18, 2024
Date of Issue: Jun. 26, 2024

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Xiong Lining**Checked by:** Xu Rui**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Jun. 26, 2024</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
1.3	Test Environment Condition	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Ancillary Equipment	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULT	7
3.1	Test Standards	7
3.2	Device Category and SAR Limit	8
3.3	Test Result Summary	9
3.4	Test Uncertainty	11
4	MEASUREMENT SYSTEM	12
4.1	Specific Absorption Rate (SAR) Definition	12
4.2	DASY SAR System	13
5	SYSTEM VERIFICATION	20
5.1	Purpose of System Check	20
5.2	System Check Setup	20
6	TEST POSITION CONFIGURATIONS	21
6.1	Tablet Exposure Condition	21
7	MEASUREMENT PROCEDURE	22

7.1	Measurement Process Diagram.....	22
7.2	SAR Scan General Requirement	23
7.3	Measurement Procedure.....	24
7.4	Area & Zoom Scan Procedure	24
8	CONDUCTED RF OUPUT POWER.....	25
8.1	WIFI.....	25
8.2	Bluetooth	39
9	TEST EXCLUSION CONSIDERATION.....	40
9.1	Tablet Mode antenna location sketch.....	40
9.2	SAR Test Consideration Table.....	42
10	TEST RESULT	48
10.1	Bluetooth (Aux. Antenna)	49
10.2	WIFI 2.4GHz.....	50
10.3	WIFI 5GHz.....	52
11	SAR Measurement Variability.....	55
12	SIMULTANEOUS TRANSMISSION	56
12.1	Simultaneous Transmission Mode Considerations	56
12.2	Sum SAR of Simultaneous Transmission	57
13	TEST EQUIPMENTS LIST	58
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT	59
ANNEX B	SYSTEM CHECK RESULT	60
ANNEX C	TEST DATA.....	69
ANNEX D	SAR TEST SETUP PHOTOS.....	105
ANNEX E	EUT EXTERNAL PHOTOS	105
ANNEX F	CALIBRATION REPORT	105
ANNEX G	TUNE-UP PROCEDURE	105

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

1.3 Test Environment Condition

Ambient Temperature	18°C to 25°C
Ambient Relative Humidity	30% to 70%

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Lenovo (Shanghai) Electronics Technology Co., Ltd.
Address	Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA

2.2 Manufacturer Information

Manufacturer	Lenovo PC HK Limited
Address	23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, P.R. China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Notebook Computer
Model Name Under Test	LVN CB Duet 11M889
Series Model Name	LVN Chrome Duet EDU G2, LVN CB Duet 11M889*****, LVN Chrome Duet EDU G2***** (* can be 0-9, a-z, A-Z, any symbol, blank or nothing)
Description of Model name differentiation	Only differences are model names for trading purpose. (this information provided by the applicant)
Hardware Version	V3
Software Version	R126-15878.0.0(dev channel)
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

Antenna Information:

Antenna Port	Model Name	Antenna Manufacturer	Antenna Type	Antenna Gain (dBi)				
				2.4 GHz	5.15-5.25 GHz	5.25-5.35 GHz	5.47-5.725 GHz	5.725-5.85 GHz
Main Antenna	F001E4101990001	INNOWAVE	PIFA	2.53	1.95	1.45	2.86	3.00
Auxiliary Antenna	F001E4111910001		PIFA	1.77	1.72	1.72	1.94	2.04
Main Antenna	WA-F-LB-02-352	INPAQ	PIFA	2.86	2.95	2.85	2.97	2.85
Auxiliary Antenna	WA-F-LB-01-120		PIFA	1.68	1.06	1.13	1.36	1.93

2.4 Ancillary Equipment

Note: Not application.

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) and 802.11ax(HE20/40) 5G WIFI 802.11a, 802.11n(HT20/40) ,802.11ac(VHT20/40/80) and 802.11ax(HE20/40/80) U-NII-1/2A/2C/3
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	2.4G WLAN; 5G WLAN; Bluetooth	
Frequency Range	802.11b/g	2412 MHz ~ 2476 MHz
	802.11n(HT20/HT40)	2412 MHz ~ 2476 MHz
	802.11a	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11n(HT20/HT40)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11ac(VHT20/VHT40/VHT80)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	Bluetooth	2402 MHz ~ 2480 MHz
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna	
Hotspot Function	N/A	
Exposure Category	General Population/Uncontrolled exposure	
Product Type	Portable Device	
EUT Type	☒ Production unit	☐ Identical prototype

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
4	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
5	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
6	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters
7	KDB 616217 D04v01r02	SAR for laptop and tablets

3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

General Population/Uncontrolled Exposure: Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Occupational/Controlled Exposure: Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure. In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

3.3 Test Result Summary

3.3.1 Highest SAR (1 g Value)

Equipment Class	Band	Antenna	Maximum Scaled SAR (W/kg)	Maximum Report SAR (W/kg)	
			Body (0mm)	Body (0mm)	
DTS	2.4G WLAN	Main	0.12	0.71	
	2.4G WLAN	Aux.	0.71		
U-NII-2A	5.3G WLAN	Main	0.12		
	5.3G WLAN	Aux.	0.47		
U-NII-2C	5.6G WLAN	Main	0.13		
	5.6G WLAN	Aux.	0.51		
U-NII-3	5.8G WLAN	Main	0.15		
	5.8G WLAN	Aux.	0.57		
DSS	Bluetooth	Aux.	0.20		
Limit (W/kg)			1.60		
Verdict			Pass		

3.3.2 Highest SAR (10 g Value)

Equipment Class	Band	Antenna	Maximum Scaled SAR (W/kg)	Maximum Report SAR (W/kg)
			Limbs (0mm)	Limbs (0mm)
DTS	2.4G WLAN	Main	0.15	0.31
	2.4G WLAN	Aux.	0.31	
U-NII-2A	5.3G WLAN	Main	0.08	
	5.3G WLAN	Aux.	0.18	
U-NII-2C	5.6G WLAN	Main	0.08	
	5.6G WLAN	Aux.	0.19	
U-NII-3	5.8G WLAN	Main	0.08	
	5.8G WLAN	Aux.	0.21	
DSS	Bluetooth	Aux.	0.09	
Limit (W/kg)			4.00	
Verdict			Pass	

3.3.3 Highest Simultaneous Transmission SAR Values (1 g Value)

Equipment Class	Maximum Report SAR (W/kg)	SPLSR
	Body (0mm)	
DTS	0.72	/
NII	0.85	/
DSS	0.85	/
Limit (W/Kg)	1.60	0.04
Verdict	Pass	Pass

Note: The simultaneous transmission SAR detail please refer to section 12.

3.3.4 Highest Simultaneous Transmission SAR Values (10 g Value)

Equipment Class	Maximum Report SAR (W/kg)	SPLSR
	Limbs (0mm)	
DTS	0.32	/
NII	0.32	/
DSS	0.32	/
Limit (W/Kg)	4.00	0.04
Verdict	Pass	Pass

Note: The simultaneous transmission SAR detail please refer to section 12.

3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 0.71 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

The maximum 10 g SAR for the EUT in this report is 0.31 W/kg, which is lower than 3.75 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

4 MEASUREMENT SYSTEM

4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,

ρ is the mass density of the tissue and E is the RMS electrical field strength.

4.2 DASY SAR System

4.2.1 DASY SAR System Diagram




The DASY system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY measurement server.
6. The DASY measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASY software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision
(repeatability ± 0.02 mm)
- High reliability
(industrial design)
- Low maintenance costs
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements
(brush less synchron motors; no stepper motors)
- Low ELF interference
(motor control _elds shielded via the closed metallic construction shields)

4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4- SN: 7607 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	4 MHz to 10 GHz; Linearity: ± 0.2 dB
Directivity	± 0.2 dB in HSL (rotation around probe axis) ; ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)



E-Field Probe Calibration Process

Probe calibration is realized, in compliance with IEC/IEEE 62209-1528 and IEEE 1528 std, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the IEC/IEEE 62209-1528 annexe technique using reference guide at the five frequencies.

4.2.4 Data Acquisition Electronics


The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M Ω m
- The Inputs: Symmetrical and Floating
- Commom Mode Rejection: Above 80dB

4.2.5 Phantoms

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of below 10 GHz. ELI V8.0 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI V8.0 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.



· Flat phantom

Photo of Phantom SN2159



Serial Number	Shell Thickness (mm)	Major ellipse axis (mm)	Minor axis(mm)
SN 2159 ELI V8.0	2.0 ± 0.2	600	400

4.2.6 Device Holder


The DASY device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of 65° . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA's only. If necessary an additional support of polystyrene material is used. Larger DUT's (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. Incompliance with CENELEC, the tilt angle uncertainty is lower than 1° .

4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

The following table gives the recipes for tissue simulating liquid.

TSL	Manufacturer / Model	Freq Range (MHz)	Main Ingredients
Head WideBand	SPEAG HBBL600-10000V6	600-10000	Ethanediol, Sodium petroleum sulfonate, Hexylene Glycol / 2-Methyl-pentane-2.4-diol, Alkoxylated alcohol


5 SYSTEM VERIFICATION

5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



6 TEST POSITION CONFIGURATIONS

6.1 Tablet Exposure Condition

This DUT was tested in four different positions. They are front side, back side, left side and right side in these positions, the surface of DUT is touching with phantom 0mm.





Fig Illustration for Lap-touching Position

7 MEASUREMENT PROCEDURE

7.1 Measurement Process Diagram



7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: Δx Area , Δy Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx Zoom , Δy Zoom			≤ 2 GHz: ≤ 8 mm 2 –3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: Δz Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	Δz Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
				4–5 GHz: ≤ 2.5 mm
		Δz Zoom (n>1): between subsequent points	≤ 1.5·Δz Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm

Note:

1. δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.
2. * When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

8 CONDUCTED RF OUTPUT POWER

8.1 WIFI

8.1.1 2.4G WIFI (Main Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
2.4 (2.4~2.483)	802.11b	1	2412	10.57	11.00	Yes
		6	2437	10.94	11.00	Yes
		11	2462	10.85	11.00	Yes
	802.11g	1	2412	10.58	11.00	No
		6	2437	10.57	11.00	No
		11	2462	10.26	11.00	No
	802.11n(HT20)	1	2412	10.49	11.00	No
		6	2437	10.26	11.00	No
		11	2462	10.53	11.00	No
	802.11n(HT40)	3	2422	10.69	11.00	No
		6	2437	10.58	11.00	No
		9	2452	10.81	11.00	No
	802.11ax(HE20)	1	2412	10.83	11.00	No
		6	2437	10.79	11.00	No
		11	2462	10.80	11.00	No
	802.11ax(HE40)	3	2422	10.27	11.00	No
		6	2437	10.30	11.00	No
		9	2452	10.75	11.00	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Adjusted SAR = Report SAR * (max power (OFDM)/ max power (DSSS)) = 0.12 * (12.59mW/12.59mW) = 0.12 W/Kg, so the 2.4G OFDM SAR test is not required.

8.1.2 2.4G WIFI (Aux. Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
2.4 (2.4~2.483)	802.11b	1	2412	10.83	11.00	No
		6	2437	10.85	11.00	No
		11	2462	10.59	11.00	No
	802.11g	1	2412	10.79	11.00	No
		6	2437	10.33	11.00	No
		11	2462	10.59	11.00	No
	802.11n(HT20)	1	2412	10.75	11.00	No
		6	2437	10.82	11.00	No
		11	2462	10.31	11.00	No
	802.11n(HT40)	3	2422	10.36	11.00	Yes
		6	2437	10.41	11.00	Yes
		9	2452	10.60	11.00	Yes
	802.11ax(HE20)	1	2412	10.50	11.00	No
		6	2437	10.34	11.00	No
		11	2462	10.46	11.00	No
	802.11ax(HE40)	3	2422	10.85	11.00	No
		6	2437	10.59	11.00	No
		9	2452	10.45	11.00	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.

Adjusted SAR = Report SAR * (max power (OFDM)/ max power (DSSS)) = 0.71 * (12.59mW/12.59mW) = 0.71 W/Kg, so the 2.4G OFDM SAR test is not required.

8.1.3 5G WIFI (Main Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	7.56	8.00	No
		40	5200	7.79	8.00	No
		48	5240	7.70	8.00	No
	802.11n(HT20)	36	5180	7.44	8.00	No
		40	5200	7.42	8.00	No
		48	5240	7.65	8.00	No
	802.11n(HT40)	38	5190	7.44	8.00	No
		46	5230	7.36	8.00	No
	802.11ac(VHT20)	36	5180	7.82	8.00	No
		40	5200	7.80	8.00	No
		48	5240	7.62	8.00	No
	802.11ac(VHT40)	38	5190	7.64	8.00	No
		46	5230	7.83	8.00	No
	802.11ac(VHT80)	42	5210	7.81	8.00	No
	802.11ax(HE20)	36	5180	7.50	8.00	No
		40	5200	7.70	8.00	No
		48	5240	7.51	8.00	No
	802.11ax(HE40)	38	5190	7.51	8.00	No
		46	5230	7.85	8.00	No
	802.11ax(HE80)	42	5210	7.50	8.00	No
5.3 (5.25 ~5.35)	802.11a	52	5260	7.34	8.00	No
		60	5300	7.56	8.00	No
		64	5320	7.47	8.00	No
	802.11n(HT20)	52	5260	7.78	8.00	No
		60	5300	7.75	8.00	No
		64	5320	7.74	8.00	No
	802.11n(HT40)	54	5270	7.60	8.00	No
		62	5310	7.38	8.00	No
	802.11ac(VHT20)	52	5260	7.45	8.00	No
		60	5300	7.56	8.00	No
		64	5320	7.35	8.00	No
	802.11ac(VHT40)	54	5270	7.42	8.00	No
		62	5310	7.54	8.00	No
	802.11ac(VHT80)	58	5290	7.56	8.00	Yes
	802.11ax(HE20)	52	5260	7.53	8.00	No
		60	5300	7.69	8.00	No
		64	5320	7.75	8.00	No
	802.11ax(HE40)	54	5270	7.83	8.00	No
		62	5310	7.32	8.00	No

	802.11ax(HE80)	58	5290	7.75	8.00	No
5.6 (5.47~5.725)	802.11a	100	5500	7.46	8.00	No
		116	5580	7.33	8.00	No
		140	5700	7.50	8.00	No
		144	5720	7.85	8.00	No
	802.11n(HT20)	100	5500	7.80	8.00	No
		116	5580	7.82	8.00	No
		140	5700	7.85	8.00	No
		144	5720	7.57	8.00	No
	802.11n(HT40)	102	5510	7.79	8.00	No
		110	5550	7.34	8.00	No
		134	5670	7.45	8.00	No
		142	5710	7.31	8.00	No
	802.11ac(VHT20)	100	5500	7.46	8.00	No
		116	5580	7.53	8.00	No
		140	5700	7.60	8.00	No
		144	5720	7.76	8.00	No
	802.11ac(VHT40)	102	5510	7.44	8.00	No
		110	5550	7.30	8.00	No
		134	5670	7.66	8.00	No
		142	5710	7.54	8.00	No
	802.11ac(VHT80)	106	5530	7.61	8.00	Yes
		122	5610	7.73	8.00	Yes
		138	5690	7.62	8.00	Yes
	802.11ax(HE20)	100	5500	7.73	8.00	No
		116	5580	7.26	8.00	No
		140	5700	7.51	8.00	No
		144	5720	7.49	8.00	No
	802.11ax(HE40)	102	5510	7.63	8.00	No
		110	5550	7.35	8.00	No
		134	5670	7.28	8.00	No
		142	5710	7.84	8.00	No
	802.11ax(HE80)	106	5530	7.28	8.00	No
		122	5610	7.74	8.00	No
		138	5690	7.58	8.00	No
5.8 (5.725~5.875)	802.11a	149	5745	7.56	8.00	No
		157	5785	7.57	8.00	No
		165	5825	7.77	8.00	No
	802.11n(HT20)	149	5745	7.36	8.00	No
		157	5785	7.50	8.00	No
		165	5825	7.35	8.00	No
	802.11n(HT40)	151	5755	7.31	8.00	No
		159	5795	7.72	8.00	No

	802.11ac(VHT20)	149	5745	7.52	8.00	No
		157	5785	7.70	8.00	No
		165	5825	7.44	8.00	No
	802.11ac(VHT40)	151	5755	7.47	8.00	No
		159	5795	7.68	8.00	No
	802.11ac(VHT80)	155	5775	7.71	8.00	Yes
	802.11ax(HE20)	149	5745	7.30	8.00	No
		157	5785	7.36	8.00	No
		165	5825	7.33	8.00	No
	802.11ax(HE40)	151	5755	7.40	8.00	No
		159	5795	7.73	8.00	No
	802.11ax(HE80)	155	5775	7.49	8.00	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

Band (GHz)	Mode	Channel	Freq. (MHz)	RU Config	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11ax (HE20)	36	5180	26	7.52	8.00	No
				52	7.85	8.00	No
				106	7.65	8.00	No
		44	5220	26	7.75	8.00	No
				52	7.55	8.00	No
				106	7.77	8.00	No
		48	5240	26	7.43	8.00	No
				52	7.94	8.00	No
				106	7.74	8.00	No
	802.11ax (HE40)	38	5190	26	7.49	8.00	No
				52	7.67	8.00	No
				106	7.55	8.00	No
				242	7.83	8.00	No
		46	5230	26	7.17	8.00	No
				52	7.89	8.00	No
				106	7.78	8.00	No
				242	7.48	8.00	No
	802.11ax (HE80)	42	5210	26	7.58	8.00	No
				52	7.76	8.00	No
				106	7.61	8.00	No
				242	7.78	8.00	No
				484	7.71	8.00	No
5.3 (5.25~5.35)	802.11ax (HE20)	52	5260	26	7.50	8.00	No
				52	7.69	8.00	No
				106	7.50	8.00	No
		60	5300	26	7.65	8.00	No
				52	7.76	8.00	No
				106	7.64	8.00	No
		64	5320	26	7.41	8.00	No
				52	7.55	8.00	No
				106	7.42	8.00	No
	802.11ax (HE40)	54	5270	26	7.87	8.00	No
				52	7.55	8.00	No
				106	7.92	8.00	No
				242	7.64	8.00	No
		62	5310	26	7.86	8.00	No
				52	7.43	8.00	No
				106	7.83	8.00	No
				242	7.50	8.00	No

	802.11ax (HE80)	58	5290	26	7.60	8.00	No
				52	7.70	8.00	No
				106	7.53	8.00	No
				242	7.76	8.00	No
				484	7.80	8.00	No
5.6 (5.47~5.725)	802.11ax (HE20)	100	5500	26	7.65	8.00	No
				52	7.95	8.00	No
				106	7.77	8.00	No
		116	5580	26	7.50	8.00	No
				52	7.37	8.00	No
				106	7.67	8.00	No
		140	5700	26	7.83	8.00	No
				52	7.69	8.00	No
				106	7.53	8.00	No
	802.11ax (HE40)	102	5510	26	7.59	8.00	No
				52	7.82	8.00	No
				106	7.75	8.00	No
				242	7.94	8.00	No
		110	5550	26	7.84	8.00	No
				52	7.53	8.00	No
				106	7.46	8.00	No
				242	7.72	8.00	No
		134	5670	26	7.53	8.00	No
				52	7.54	8.00	No
				106	7.90	8.00	No
				242	7.53	8.00	No
	802.11ax (HE80)	106	5530	26	7.81	8.00	No
				52	7.52	8.00	No
				106	7.80	8.00	No
				242	7.54	8.00	No
				484	7.47	8.00	No
		122	5610	26	7.92	8.00	No
				52	7.52	8.00	No
				106	7.53	8.00	No
				242	7.48	8.00	No
				484	7.84	8.00	No
5.8 (5.725~5.875)	802.11ax (HE20)	149	5745	26	7.69	8.00	No
				52	7.73	8.00	No
				106	7.64	8.00	No
		157	5785	26	7.52	8.00	No
				52	7.65	8.00	No
				106	7.46	8.00	No
		165	5825	26	7.45	8.00	No

				52	7.54	8.00	No
				106	7.45	8.00	No
	802.11ax (HE40)	151	5755	26	7.64	8.00	No
				52	7.62	8.00	No
				106	7.57	8.00	No
				242	7.67	8.00	No
				26	7.71	8.00	No
		159	5795	52	7.78	8.00	No
				106	7.72	8.00	No
				242	7.86	8.00	No
	802.11ax (HE80)	155	5775	26	7.77	8.00	No
				52	7.85	8.00	No
				106	7.66	8.00	No
				242	7.56	8.00	No
				484	7.56	8.00	No
5.6~5.8 (5.47~5.875)	802.11ax (HE20)	144	5720	26	7.36	8.00	No
				52	7.82	8.00	No
				106	7.32	8.00	No
	802.11ax (HE40)	142	5710	26	7.23	8.00	No
				52	7.70	8.00	No
				106	7.28	8.00	No
				242	7.47	8.00	No
	802.11ax (HE80)	138	5690	26	7.55	8.00	No
				52	7.66	8.00	No
				106	7.66	8.00	No
				242	7.62	8.00	No
				484	7.50	8.00	No
Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.							

8.1.4 5G WIFI (Aux. Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	7.47	8.00	No
		40	5200	7.34	8.00	No
		48	5240	7.54	8.00	No
	802.11n(HT20)	36	5180	7.38	8.00	No
		40	5200	7.84	8.00	No
		48	5240	7.74	8.00	No
	802.11n(HT40)	38	5190	7.35	8.00	No
		46	5230	7.31	8.00	No
	802.11ac(VHT20)	36	5180	7.65	8.00	No
		40	5200	7.77	8.00	No
		48	5240	7.59	8.00	No
	802.11ac(VHT40)	38	5190	7.62	8.00	No
		46	5230	7.48	8.00	No
	802.11ac(VHT80)	42	5210	7.89	8.00	No
	802.11ax(HE20)	36	5180	7.54	8.00	No
		40	5200	7.44	8.00	No
		48	5240	7.82	8.00	No
	802.11ax(HE40)	38	5190	7.55	8.00	No
		46	5230	7.53	8.00	No
	802.11ax(HE80)	42	5210	7.54	8.00	No
5.3 (5.25 ~5.35)	802.11a	52	5260	7.55	8.00	No
		60	5300	7.74	8.00	No
		64	5320	7.59	8.00	No
	802.11n(HT20)	52	5260	7.71	8.00	No
		60	5300	7.53	8.00	No
		64	5320	7.83	8.00	No
	802.11n(HT40)	54	5270	7.68	8.00	No
		62	5310	7.59	8.00	No
	802.11ac(VHT20)	52	5260	7.44	8.00	No
		60	5300	7.61	8.00	No
		64	5320	7.54	8.00	No
	802.11ac(VHT40)	54	5270	7.34	8.00	No
		62	5310	7.78	8.00	No
	802.11ac(VHT80)	58	5290	7.51	8.00	Yes
	802.11ax(HE20)	52	5260	7.82	8.00	No
		60	5300	7.28	8.00	No
		64	5320	7.81	8.00	No
	802.11ax(HE40)	54	5270	7.80	8.00	No
		62	5310	7.61	8.00	No

	802.11ax(HE80)	58	5290	7.30	8.00	No
5.6 (5.47~5.725)	802.11a	100	5500	7.84	8.00	No
		116	5580	7.50	8.00	No
		140	5700	7.71	8.00	No
		144	5720	7.52	8.00	No
	802.11n(HT20)	100	5500	7.33	8.00	No
		116	5580	7.60	8.00	No
		140	5700	7.83	8.00	No
		144	5720	7.64	8.00	No
	802.11n(HT40)	102	5510	7.28	8.00	No
		110	5550	7.68	8.00	No
		134	5670	7.72	8.00	No
		142	5710	7.52	8.00	No
	802.11ac(VHT20)	100	5500	7.26	8.00	No
		116	5580	7.59	8.00	No
		140	5700	7.30	8.00	No
		144	5720	7.73	8.00	No
	802.11ac(VHT40)	102	5510	7.82	8.00	No
		110	5550	7.54	8.00	No
		134	5670	7.54	8.00	No
		142	5710	7.71	8.00	No
	802.11ac(VHT80)	106	5530	7.59	8.00	Yes
		122	5610	7.86	8.00	Yes
		138	5690	7.49	8.00	Yes
	802.11ax(HE20)	100	5500	7.73	8.00	No
		116	5580	7.52	8.00	No
		140	5700	7.85	8.00	No
		144	5720	7.27	8.00	No
	802.11ax(HE40)	102	5510	7.85	8.00	No
		110	5550	7.35	8.00	No
		134	5670	7.58	8.00	No
		142	5710	7.65	8.00	No
	802.11ax(HE80)	106	5530	7.82	8.00	No
		122	5610	7.51	8.00	No
		138	5690	7.71	8.00	No
5.8 (5.725~5.875)	802.11a	149	5745	6.94	8.00	No
		157	5785	6.68	8.00	No
		165	5825	6.90	8.00	No
	802.11n(HT20)	149	5745	6.83	8.00	No
		157	5785	7.23	8.00	No
		165	5825	6.98	8.00	No
	802.11n(HT40)	151	5755	7.16	8.00	No
		159	5795	7.10	8.00	No

	802.11ac(VHT20)	149	5745	6.88	8.00	No
		157	5785	7.24	8.00	No
		165	5825	7.03	8.00	No
	802.11ac(VHT40)	151	5755	7.19	8.00	No
		159	5795	7.76	8.00	No
	802.11ac(VHT80)	155	5775	6.67	8.00	Yes
	802.11ax(HE20)	149	5745	6.95	8.00	No
		157	5785	7.01	8.00	No
		165	5825	7.17	8.00	No
	802.11ax(HE40)	151	5755	6.83	8.00	No
		159	5795	7.19	8.00	No
	802.11ax(HE80)	155	5775	7.07	8.00	No

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

Band (GHz)	Mode	Channel	Freq. (MHz)	RU Config	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11ax (HE20)	36	5180	26	7.10	8.00	No
				52	7.72	8.00	No
				106	7.62	8.00	No
		44	5220	26	7.62	8.00	No
				52	7.90	8.00	No
				106	7.75	8.00	No
		48	5240	26	7.04	8.00	No
				52	7.56	8.00	No
				106	7.63	8.00	No
	802.11ax (HE40)	38	5190	26	7.74	8.00	No
				52	7.83	8.00	No
				106	7.78	8.00	No
				242	7.95	8.00	No
		46	5230	26	7.11	8.00	No
				52	7.94	8.00	No
				106	7.85	8.00	No
				242	7.99	8.00	No
	802.11ax (HE80)	42	5210	26	7.63	8.00	No
				52	7.67	8.00	No
				106	7.58	8.00	No
				242	7.66	8.00	No
				484	7.61	8.00	No
5.3 (5.25~5.35)	802.11ax (HE20)	52	5260	26	7.95	8.00	No
				52	7.56	8.00	No
				106	7.98	8.00	No
		60	5300	26	7.93	8.00	No
				52	7.48	8.00	No
				106	7.86	8.00	No
		64	5320	26	7.69	8.00	No
				52	7.81	8.00	No
				106	7.76	8.00	No
	802.11ax (HE40)	54	5270	26	7.76	8.00	No
				52	7.84	8.00	No
				106	7.80	8.00	No
				242	7.97	8.00	No
		62	5310	26	7.57	8.00	No
				52	7.62	8.00	No
				106	7.61	8.00	No
				242	7.78	8.00	No

	802.11ax (HE80)	58	5290	26	7.64	8.00	No
				52	7.77	8.00	No
				106	7.72	8.00	No
				242	7.86	8.00	No
				484	7.86	8.00	No
5.6 (5.47~5.725)	802.11ax (HE20)	100	5500	26	7.82	8.00	No
				52	7.97	8.00	No
				106	7.91	8.00	No
		116	5580	26	7.79	8.00	No
				52	7.44	8.00	No
				106	7.83	8.00	No
		140	5700	26	7.74	8.00	No
				52	7.89	8.00	No
				106	7.76	8.00	No
	802.11ax (HE40)	102	5510	26	7.75	8.00	No
				52	7.86	8.00	No
				106	7.86	8.00	No
				242	7.57	8.00	No
		110	5550	26	7.68	8.00	No
				52	7.73	8.00	No
				106	7.79	8.00	No
				242	7.48	8.00	No
		134	5670	26	7.89	8.00	No
				52	7.54	8.00	No
				106	7.93	8.00	No
				242	7.58	8.00	No
	802.11ax (HE80)	106	5530	26	7.50	8.00	No
				52	7.59	8.00	No
				106	7.58	8.00	No
				242	7.74	8.00	No
				484	7.69	8.00	No
		122	5610	26	7.80	8.00	No
				52	7.95	8.00	No
				106	7.76	8.00	No
				242	7.86	8.00	No
				484	7.70	8.00	No
5.8 (5.725~5.875)	802.11ax (HE20)	149	5745	26	7.86	8.00	No
				52	7.52	8.00	No
				106	7.85	8.00	No
		157	5785	26	7.60	8.00	No
				52	7.71	8.00	No
				106	7.61	8.00	No
		165	5825	26	7.79	8.00	No

				52	7.91	8.00	No
				106	7.73	8.00	No
	802.11ax (HE40)	151	5755	26	7.73	8.00	No
				52	7.85	8.00	No
				106	7.79	8.00	No
				242	7.94	8.00	No
				26	7.73	8.00	No
		159	5795	52	7.76	8.00	No
				106	7.75	8.00	No
				242	7.92	8.00	No
	802.11ax (HE80)	155	5775	26	7.53	8.00	No
				52	7.73	8.00	No
				106	7.53	8.00	No
				242	7.60	8.00	No
				484	7.47	8.00	No

5.6~5.8 (5.47~5.875)	802.11ax (HE20)	144	5720	26	7.70	8.00	No
				52	7.83	8.00	No
				106	7.35	8.00	No
	802.11ax (HE40)	142	5710	26	7.63	8.00	No
				52	7.61	8.00	No
				106	7.41	8.00	No
				242	7.76	8.00	No
	802.11ax (HE80)	138	5690	26	7.77	8.00	No
				52	7.94	8.00	No
				106	7.91	8.00	No
242				7.60	8.00	No	
484				7.90	8.00	No	

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

8.2 Bluetooth

8.2.1 Bluetooth (Aux. Antenna)


Mode	GFSK			$\pi/4$ -DQPSK		
Channel	0	39	78	0	39	78
Frequency (MHz)	2402	2441	2480	2402	2441	2480
Conducted power (dBm)	6.34	6.58	6.27	3.29	3.60	3.34
Tune-Up Limit (dBm)	7.00	7.00	7.00	4.00	4.00	4.00
SAR Test Require	Yes	Yes	Yes	No	No	No
Mode	8-DPSK			/		
Channel	0	39	78	/	/	/
Frequency (MHz)	2402	2441	2480	/	/	/
Conducted power (dBm)	3.35	3.65	3.63	/	/	/
Tune-Up Limit (dBm)	4.00	4.00	4.00	/	/	/
SAR Test Require	No	No	No	/	/	/
Mode	BLE-1Mbps			BLE-2Mbps		
Channel	0	19	39	1	19	38
Frequency (MHz)	2402	2442	2480	2404	2442	2478
Conducted power (dBm)	3.49	3.22	3.07	3.50	3.46	3.13
Tune-Up Limit (dBm)	4.00	4.00	4.00	4.00	4.00	4.00
SAR Test Require	No	No	No	No	No	No

Note: Since Bluetooth BR mode is the maximum output power mode, SAR measurements were performed with test software using DH5 modulation, and SAR measurement is not required for the EDR and LE. When the secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode.

The Bluetooth duty cycle is 57.55 % as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation.


Duty Cycle


Bluetooth-GFSK



9 TEST EXCLUSION CONSIDERATION

9.1 Tablet Mode antenna location sketch





Antenna	Support Bands
Antenna Aux.	BT、WLAN 2.4/5G
Antenna Main	WLAN 2.4/5G

9.2 SAR Test Consideration Table

According with FCC KDB 447498 D04, Appendix B, The SAR-based exemption formula applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). The following table shows the power threshold from 5mm to 50mm.

Power Thresholds (mW)					
Frequency (MHz)	At separation distance of ≤ 5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
300	39 mW	65 mW	88 mW	110 mW	129 mW
450	22 mW	44 mW	67 mW	89 mW	112 mW
835	9 mW	25 mW	44 mW	66 mW	90 mW
1900	3 mW	12 mW	26 mW	44 mW	66 mW
2450	3 mW	10 mW	22 mW	38 mW	59 mW
3600	2 mW	8 mW	18 mW	32 mW	49 mW
5800	1 mW	6 mW	14 mW	25 mW	40 mW
Frequency (MHz)	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of 50 mm
300	148 mW	166 mW	184 mW	201 mW	217 mW
450	135 mW	158 mW	180 mW	203 mW	226 mW
835	116 mW	145 mW	175 mW	207 mW	240 mW
1900	92 mW	122 mW	157 mW	195 mW	236 mW
2450	83 mW	111 mW	143 mW	179 mW	219 mW
3600	71 mW	96 mW	125 mW	158 mW	195 mW
5800	58 mW	80 mW	106 mW	136 mW	169 mW

9.2.1 Tablet mode SAR Test Consideration

This host is a tablet, under normal use the RF exposure scenarios are shown in the table below:

RF exposure Position	RF exposure scenarios
Front Side	Limbs
Back Side	Body&Limbs
Left Edge	Body&Limbs
Right Edge	Body&Limbs
Top Edge	Body&Limbs
Bottom Edge	Body&Limbs

Main Antenna Body RF exposure scenarios

Main Antenna					
Test Position Configurations	Mode	WLAN 2.4GHz	UNII-2A	UNII-2C	UNII-3
Calculated Frequency(MHz)		2462	5320	5710	5825
Back Side	Distance to User (mm)	0.8			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	0.08	0.03	0.03	0.03
	SAR Test Required	Yes	Yes	Yes	Yes
Left Edge	Distance to User (mm)	1.7			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	0.35	0.16	0.15	0.14
	SAR Test Required	Yes	Yes	Yes	Yes
Right Edge	Distance to User (mm)	230			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	3992.48	4086.94	4095.72	4098.20
	SAR Test Required	No	No	No	No
Top Edge	Distance to User (mm)	100			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	818.08	728.50	720.79	718.63
	SAR Test Required	No	No	No	No
Bottom Edge	Distance to User (mm)	16.9			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	27.75	18.35	17.67	17.48
	SAR Test Required	No	No	No	No

Main Antenna Limbs RF exposure scenarios

Main Antenna					
Test Position Configurations	Mode	WLAN 2.4GHz	UNII-2A	UNII-2C	UNII-3
Calculated Frequency(MHz)		2462	5320	5710	5825
Front Side	Distance to User (mm)	5			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	6.83	3.69	3.48	3.43
	SAR Test Required	Yes	Yes	Yes	Yes
Back Side	Distance to User (mm)	0.8			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	0.21	0.08	0.08	0.07
	SAR Test Required	Yes	Yes	Yes	Yes
Left Edge	Distance to User (mm)	1.7			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	0.88	0.39	0.37	0.36
	SAR Test Required	Yes	Yes	Yes	Yes
Right Edge	Distance to User (mm)	230			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	9981.19	10217.34	10239.30	10245.50
	SAR Test Required	No	No	No	No
Top Edge	Distance to User (mm)	100			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	2045.21	1821.26	1801.97	1796.57
	SAR Test Required	No	No	No	No
Bottom Edge	Distance to User (mm)	16.9			
	Max. Peak Power (dBm)	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	69.38	45.89	44.18	43.71
	SAR Test Required	No	No	No	No

Aux. Antenna Body RF exposure scenarios

Aux. Antenna						
Test Position Configurations	Mode	Bluetooth	WLAN 2.4GHz	UNII-2A	UNII-2C	UNII-3
Calculated Frequency(MHz)		2480	2462	5320	5710	5825
Back Side	Distance to User (mm)	2.4				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	0.67	0.68	0.32	0.30	0.30
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Left Edge	Distance to User (mm)	210				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	3358.02	3357.76	3385.28	3387.82	3388.53
	SAR Test Required	No	No	No	No	No
Right Edge	Distance to User (mm)	9.8				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	9.79	9.84	5.94	5.67	5.60
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Top Edge	Distance to User (mm)	30.5				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	85.12	85.37	62.32	60.55	60.06
	SAR Test Required	No	No	No	No	No
Bottom Edge	Distance to User (mm)	135				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	1447.37	1448.27	1356.10	1347.93	1345.64
	SAR Test Required	No	No	No	No	No

Aux. Antenna Limbs RF exposure scenarios

Aux. Antenna						
Test Position Configurations	Mode	Bluetooth	WLAN 2.4GHz	UNII-2A	UNII-2C	UNII-3
Calculated Frequency(MHz)		2480	2462	5320	5710	5825
Front Side	Distance to User (mm)	5				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	6.79	6.83	3.69	3.48	3.43
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Back Side	Distance to User (mm)	2.4				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	1.68	1.69	0.81	0.75	0.74
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Left Edge	Distance to User (mm)	210				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	8395.04	8394.39	8463.20	8469.54	8471.33
	SAR Test Required	No	No	No	No	No
Right Edge	Distance to User (mm)	9.8				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	24.48	24.59	14.85	14.18	13.99
	SAR Test Required	Yes	Yes	Yes	Yes	Yes
Top Edge	Distance to User (mm)	30.5				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	212.79	213.43	155.81	151.37	150.15
	SAR Test Required	No	No	No	No	No
Bottom Edge	Distance to User (mm)	135				
	Max. Peak Power (dBm)	7.00	11.00	8.00	8.00	8.00
	Max. Peak Power (mW)	5.01	12.59	6.31	6.31	6.31
	Exclusion Threshold (mW)	3618.43	3620.68	3390.24	3369.83	3364.10
	SAR Test Required	No	No	No	No	No

Note:

1. Maximum power is the source-based time-average power and represents the maximum RF output power including tune-up tolerance among production units
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
4. Per KDB 447498 D04, for separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive), the threshold Pth (mW) is given by Following:

$$P_{th}(mW) = \begin{cases} ERP_{20cm}(d/20cm)^x & d \leq 20cm \\ ERP_{20cm} & 20cm < d \leq 40cm \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right)$$

- a. f(GHz) is the RF channel transmit frequency in GHz
- b. d is the separation distance (cm), The result is rounded to one decimal place for comparison
- c. ERP_{20cm} are determined by:

$$ERP_{20cm}(mW) = f(x) = \begin{cases} 2040f & 0.3GHz \leq f < 1.5GHz \\ 3060 & 1.5GHz \leq f \leq 6GHz \end{cases}$$

5. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion.8. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate
6. Per KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions.
 - a. When KDB Publication 447498 D04 SAR test exclusion applies to the OFDM configuration.
 - b. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
7. Per KDB 248227 D01 SAR is not required for the following U-NII-1 and U-NII-2A bands conditions.
 - a. When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
 - b. When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.
8. For Limb SAR, SAR test exemption considered by applying a factor of 2.5 to the applicable power level thresholds.

10 TEST RESULT

1. The reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".
 - c. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Absorbed power density (APD) using a 4cm² averaging area is reported based on SAR measurements.
3. Per KDB 447498 D04, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
4. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg

10.1 Bluetooth (Aux. Antenna)

Antenna	Mode	Antenna Manufa cturer	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Report SAR (W/kg)	Meas. No.
Body															
Aux.	DH5	INPAQ	Back Side	0	39	2441	-0.05	0.092	6.58	7.0	1.102	57.55	1.738	0.176	/
			Right Edge	0	39	2441	0.17	0.008	6.58	7.0	1.102	57.55	1.738	0.015	/
			Back Side	0	0	2402	0.16	0.085	6.34	7.0	1.164	57.55	1.738	0.172	/
			Back Side	0	78	2480	0.01	0.091	6.27	7.0	1.183	57.55	1.738	0.187	/
Aux.	DH5	INNOW AVE	Back Side	0	39	2441	0.01	0.105	6.58	7.0	1.102	57.55	1.738	0.201	1#
			Right Edge	0	39	2441	-0.01	0.005	6.58	7.0	1.102	57.55	1.738	0.010	/
			Back Side	0	0	2402	-0.18	0.095	6.34	7.0	1.164	57.55	1.738	0.192	/
			Back Side	0	78	2480	-0.03	0.097	6.27	7.0	1.183	57.55	1.738	0.199	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

Antenna	Mode	Antenna Manufa cturer	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Report SAR (W/kg)	Meas. No.
Limbs															
Aux.	DH5	INPAQ	Front Side	0	39	2441	-0.03	0.011	6.58	7.0	1.102	57.55	1.738	0.021	/
			Back Side	0	39	2441	-0.05	0.039	6.58	7.0	1.102	57.55	1.738	0.075	/
			Right Edge	0	39	2441	0.17	0.004	6.58	7.0	1.102	57.55	1.738	0.008	/
			Back Side	0	0	2402	0.16	0.036	6.34	7.0	1.164	57.55	1.738	0.073	/
			Back Side	0	78	2480	0.01	0.041	6.27	7.0	1.183	57.55	1.738	0.084	/
Aux.	DH5	INNOW AVE	Front Side	0	39	2441	0.05	0.014	6.58	7.0	1.102	57.55	1.738	0.027	/
			Back Side	0	39	2441	0.01	0.045	6.58	7.0	1.102	57.55	1.738	0.086	10#
			Right Edge	0	39	2441	-0.01	0.003	6.58	7.0	1.102	57.55	1.738	0.006	/
			Back Side	0	0	2402	-0.18	0.042	6.34	7.0	1.164	57.55	1.738	0.085	/
			Back Side	0	78	2480	-0.03	0.041	6.27	7.0	1.183	57.55	1.738	0.084	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

10.2WIFI 2.4GHz

Antenna	Mode	Antenna Manufa cturer	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Report SAR (W/kg)	Meas. No.
Body															
Main	802.11b	INNOW AVE	Back Side	0	6	2437	-0.15	0.007	10.94	11.00	1.014	99.20	1.008	0.007	/
			Left Edge	0	6	2437	0.18	0.111	10.94	11.00	1.014	99.20	1.008	0.113	/
			Left Edge	0	1	2412	0.16	0.104	10.57	11.00	1.104	99.20	1.008	0.116	/
			Left Edge	0	11	2462	0.19	0.105	10.85	11.00	1.035	99.20	1.008	0.110	/
Main	802.11b	INPAQ	Back Side	0	6	2437	-0.14	0.009	10.94	11.00	1.014	99.20	1.008	0.009	/
			Left Edge	0	6	2437	0.01	0.117	10.94	11.00	1.014	99.20	1.008	0.120	2#
			Left Edge	0	1	2412	-0.18	0.105	10.57	11.00	1.104	99.20	1.008	0.117	/
			Left Edge	0	11	2462	0.10	0.096	10.85	11.00	1.035	99.20	1.008	0.100	/
Aux.	802.11b	INNOW AVE	Back Side	0	6	2437	-0.10	0.558	10.85	11.00	1.035	99.20	1.008	0.582	/
			Right Edge	0	6	2437	-0.01	0.033	10.85	11.00	1.035	99.20	1.008	0.034	/
			Back Side	0	1	2412	0.12	0.472	10.83	11.00	1.040	99.20	1.008	0.495	/
			Back Side	0	11	2462	0.02	0.641	10.59	11.00	1.099	99.20	1.008	0.710	3#
Aux.	802.11b	INPAQ	Back Side	0	6	2437	0.11	0.413	10.85	11.00	1.035	99.20	1.008	0.431	/
			Right Edge	0	6	2437	-0.11	0.028	10.85	11.00	1.035	99.20	1.008	0.029	/
			Back Side	0	1	2412	-0.10	0.483	10.83	11.00	1.040	99.20	1.008	0.506	/
			Back Side	0	11	2462	0.14	0.492	10.59	11.00	1.099	99.20	1.008	0.545	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

Antenna	Mode	Antenna Manufa cturer	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Report SAR (W/kg)	Meas. No.
Limbs															
Main	802.11b	INNOW AVE	Front Side	0	6	2437	0.16	0.119	10.94	11.00	1.014	99.20	1.008	0.122	/
			Back Side	0	6	2437	-0.15	0.003	10.94	11.00	1.014	99.20	1.008	0.003	/
			Left Edge	0	6	2437	0.18	0.048	10.94	11.00	1.014	99.20	1.008	0.049	/
			Front Side	0	1	2412	0.15	0.105	10.57	11.00	1.104	99.20	1.008	0.117	/
			Front Side	0	11	2462	-0.11	0.108	10.85	11.00	1.035	99.20	1.008	0.113	/
Main	802.11b	INPAQ	Front Side	0	6	2437	-0.01	0.144	10.94	11.00	1.014	99.20	1.008	0.147	11#
			Back Side	0	6	2437	-0.14	0.005	10.94	11.00	1.014	99.20	1.008	0.005	/
			Left Edge	0	6	2437	0.01	0.059	10.94	11.00	1.014	99.20	1.008	0.060	/
			Front Side	0	1	2412	0.06	0.113	10.57	11.00	1.104	99.20	1.008	0.126	/
			Front Side	0	11	2462	0.05	0.126	10.85	11.00	1.035	99.20	1.008	0.131	/
Aux.	802.11b	INNOW AVE	Front Side	0	6	2437	0.07	0.007	10.85	11.00	1.035	99.20	1.008	0.007	/
			Back Side	0	6	2437	-0.10	0.243	10.85	11.00	1.035	99.20	1.008	0.254	/
			Right Edge	0	6	2437	-0.01	0.014	10.85	11.00	1.035	99.20	1.008	0.015	/
			Back Side	0	1	2412	0.12	0.206	10.83	11.00	1.040	99.20	1.008	0.216	/
			Back Side	0	11	2462	0.02	0.281	10.59	11.00	1.099	99.20	1.008	0.311	12#
Aux.	802.11b	INPAQ	Front Side	0	6	2437	0.02	0.006	10.85	11.00	1.035	99.20	1.008	0.006	/
			Back Side	0	6	2437	0.11	0.180	10.85	11.00	1.035	99.20	1.008	0.188	/
			Right Edge	0	6	2437	-0.11	0.012	10.85	11.00	1.035	99.20	1.008	0.013	/
			Back Side	0	1	2412	-0.10	0.211	10.83	11.00	1.040	99.20	1.008	0.221	/
			Back Side	0	11	2462	0.14	0.215	10.59	11.00	1.099	99.20	1.008	0.238	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.															

10.3WIFI 5GHz

Fre. Band	Antenna	Mode	Antenna Manufa- cturer	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	1g Report SAR (W/kg)	Meas. No.
Body																
5.3G	Main	802.11 ac80	INNOW AVE	Back Side	0	58	5290	-0.07	0.010	7.56	8.00	1.107	95.80	1.044	0.012	/
				Left Edge	0	58	5290	0.08	0.096	7.56	8.00	1.107	95.80	1.044	0.111	/
	Main	802.11 ac80	INPAQ	Back Side	0	58	5290	-0.17	0.013	7.56	8.00	1.107	95.80	1.044	0.015	/
				Left Edge	0	58	5290	0.02	0.102	7.56	8.00	1.107	95.80	1.044	0.118	4#
	Aux.	802.11 ac80	INNOW AVE	Back Side	0	58	5290	-0.10	0.405	7.51	8.00	1.119	95.80	1.044	0.473	5#
				Right Edge	0	58	5290	0.19	0.076	7.51	8.00	1.119	95.80	1.044	0.089	/
	Aux.	802.11 ac80	INPAQ	Back Side	0	58	5290	0.02	0.320	7.51	8.00	1.119	95.80	1.044	0.374	/
				Right Edge	0	58	5290	0.10	0.072	7.51	8.00	1.119	95.80	1.044	0.084	/
5.6G	Main	802.11 ac80	INNOW AVE	Back Side	0	122	5610	0.07	0.032	7.73	8.00	1.064	95.80	1.044	0.036	/
				Left Edge	0	122	5610	-0.08	0.095	7.73	8.00	1.064	95.80	1.044	0.106	/
				Left Edge	0	106	5530	-0.04	0.100	7.61	8.00	1.094	95.80	1.044	0.114	/
				Left Edge	0	138	5690	0.06	0.073	7.62	8.00	1.091	95.80	1.044	0.083	/
	Main	802.11 ac80	INPAQ	Back Side	0	122	5610	-0.02	0.035	7.73	8.00	1.064	95.80	1.044	0.039	/
				Left Edge	0	122	5610	0.00	0.101	7.73	8.00	1.064	95.80	1.044	0.112	/
				Left Edge	0	106	5530	-0.08	0.110	7.61	8.00	1.094	95.80	1.044	0.126	/
				Left Edge	0	138	5690	0.02	0.113	7.62	8.00	1.091	95.80	1.044	0.129	6#
	Aux.	802.11 ac80	INNOW AVE	Back Side	0	122	5610	-0.01	0.471	7.86	8.00	1.033	95.80	1.044	0.508	7#
				Right Edge	0	122	5610	-0.08	0.042	7.86	8.00	1.033	95.80	1.044	0.045	/
				Back Side	0	106	5530	0.14	0.341	7.59	8.00	1.099	95.80	1.044	0.391	/
				Back Side	0	138	5690	-0.03	0.371	7.49	8.00	1.125	95.80	1.044	0.436	/
	Aux.	802.11 ac80	INPAQ	Back Side	0	122	5610	0.18	0.468	7.86	8.00	1.033	95.80	1.044	0.505	/
				Right Edge	0	122	5610	0.08	0.035	7.86	8.00	1.033	95.80	1.044	0.038	/
				Back Side	0	106	5530	0.09	0.337	7.59	8.00	1.099	95.80	1.044	0.387	/
				Back Side	0	138	5690	0.05	0.362	7.49	8.00	1.125	95.80	1.044	0.425	/
5.8G	Main	802.11 ac80	INNOW AVE	Back Side	0	155	5775	-0.10	0.077	7.71	8.00	1.069	95.80	1.044	0.086	/
				Left Edge	0	155	5775	-0.01	0.132	7.71	8.00	1.069	95.80	1.044	0.147	8#
	Main	802.11 ac80	INPAQ	Back Side	0	155	5775	-0.17	0.053	7.71	8.00	1.069	95.80	1.044	0.059	/
				Left Edge	0	155	5775	0.17	0.107	7.71	8.00	1.069	95.80	1.044	0.119	/
	Aux.	802.11 ac80	INNOW AVE	Back Side	0	155	5775	-0.12	0.399	6.67	8.00	1.358	95.80	1.044	0.566	9#
				Right Edge	0	155	5775	-0.12	0.067	6.67	8.00	1.358	95.80	1.044	0.095	/
	Aux.	802.11 ac80	INPAQ	Back Side	0	155	5775	0.09	0.359	6.67	8.00	1.358	95.80	1.044	0.509	/
				Right Edge	0	155	5775	0.17	0.047	6.67	8.00	1.358	95.80	1.044	0.067	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.																

Fre. Band	Antenna	Mode	Antenna Manufacter	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	10g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune power (dBm)	Scaling Factor	Duty cycle (%)	Duty cycle Factor	10g Report SAR (W/kg)	Meas. No.
Limbs																
5.3G	Main	802.11 ac80	INNOW AVE	Front Side	0	58	5290	0.03	0.063	7.56	8.00	1.107	95.80	1.044	0.073	/
				Back Side	0	58	5290	-0.07	0.005	7.56	8.00	1.107	95.80	1.044	0.006	/
				Left Edge	0	58	5290	0.08	0.027	7.56	8.00	1.107	95.80	1.044	0.031	/
	Main	802.11 ac80	INPAQ	Front Side	0	58	5290	-0.14	0.073	7.56	8.00	1.107	95.80	1.044	0.084	13#
				Back Side	0	58	5290	-0.17	0.005	7.56	8.00	1.107	95.80	1.044	0.006	/
				Left Edge	0	58	5290	0.02	0.051	7.56	8.00	1.107	95.80	1.044	0.059	/
	Aux.	802.11 ac80	INNOW AVE	Front Side	0	58	5290	-0.05	0.005	7.51	8.00	1.119	95.80	1.044	0.006	/
				Back Side	0	58	5290	-0.10	0.153	7.51	8.00	1.119	95.80	1.044	0.179	14#
				Right Edge	0	58	5290	0.19	0.031	7.51	8.00	1.119	95.80	1.044	0.036	/
	Aux.	802.11 ac80	INPAQ	Front Side	0	58	5290	-0.06	0.006	7.51	8.00	1.119	95.80	1.044	0.007	/
				Back Side	0	58	5290	0.02	0.119	7.51	8.00	1.119	95.80	1.044	0.139	/
				Right Edge	0	58	5290	0.10	0.028	7.51	8.00	1.119	95.80	1.044	0.033	/
5.6G	Main	802.11 ac80	INNOW AVE	Front Side	0	122	5610	-0.11	0.069	7.73	8.00	1.064	95.80	1.044	0.077	/
				Back Side	0	122	5610	0.07	0.009	7.73	8.00	1.064	95.80	1.044	0.010	/
				Left Edge	0	122	5610	-0.08	0.054	7.73	8.00	1.064	95.80	1.044	0.060	/
				Front Side	0	106	5530	-0.06	0.061	7.61	8.00	1.094	95.80	1.044	0.070	/
				Front Side	0	138	5690	0.11	0.065	7.62	8.00	1.091	95.80	1.044	0.074	/
	Main	802.11 ac80	INPAQ	Front Side	0	122	5610	-0.08	0.073	7.73	8.00	1.064	95.80	1.044	0.081	15#
				Back Side	0	122	5610	-0.02	0.009	7.73	8.00	1.064	95.80	1.044	0.010	/
				Left Edge	0	122	5610	0.00	0.057	7.73	8.00	1.064	95.80	1.044	0.063	/
				Front Side	0	106	5530	-0.03	0.065	7.61	8.00	1.094	95.80	1.044	0.074	/
				Front Side	0	138	5690	0.06	0.068	7.62	8.00	1.091	95.80	1.044	0.077	/
	Aux.	802.11 ac80	INNOW AVE	Front Side	0	122	5610	0.06	0.008	7.86	8.00	1.033	95.80	1.044	0.009	/
				Back Side	0	122	5610	-0.01	0.173	7.86	8.00	1.033	95.80	1.044	0.187	16#
				Right Edge	0	122	5610	-0.08	0.017	7.86	8.00	1.033	95.80	1.044	0.018	/
				Back Side	0	106	5530	0.14	0.128	7.59	8.00	1.099	95.80	1.044	0.147	/
				Back Side	0	138	5690	-0.03	0.117	7.49	8.00	1.125	95.80	1.044	0.137	/
	Aux.	802.11 ac80	INPAQ	Front Side	0	122	5610	-0.16	0.007	7.86	8.00	1.033	95.80	1.044	0.008	/
				Back Side	0	122	5610	0.18	0.172	7.86	8.00	1.033	95.80	1.044	0.185	/
				Right Edge	0	122	5610	0.08	0.015	7.86	8.00	1.033	95.80	1.044	0.016	/
				Back Side	0	106	5530	0.09	0.127	7.59	8.00	1.099	95.80	1.044	0.146	/
				Back Side	0	138	5690	0.05	0.135	7.49	8.00	1.125	95.80	1.044	0.159	/
5.8G	Main	802.11 ac80	INNOW AVE	Front Side	0	155	5775	-0.08	0.075	7.71	8.00	1.069	95.80	1.044	0.084	17#
				Back Side	0	155	5775	-0.10	0.021	7.71	8.00	1.069	95.80	1.044	0.023	/
				Left Edge	0	155	5775	-0.01	0.063	7.71	8.00	1.069	95.80	1.044	0.070	/
	Main	802.11 ac80	INPAQ	Front Side	0	155	5775	-0.17	0.073	7.71	8.00	1.069	95.80	1.044	0.081	/
				Back Side	0	155	5775	-0.17	0.015	7.71	8.00	1.069	95.80	1.044	0.017	/

				Left Edge	0	155	5775	0.17	0.026	7.71	8.00	1.069	95.80	1.044	0.029	/
	Aux.	802.11 ac80	INNOW AVE	Front Side	0	155	5775	0.16	0.006	6.67	8.00	1.358	95.80	1.044	0.009	/
				Back Side	0	155	5775	-0.12	0.148	6.67	8.00	1.358	95.80	1.044	0.210	18#
				Right Edge	0	155	5775	-0.12	0.025	6.67	8.00	1.358	95.80	1.044	0.035	/
	Aux.	802.11 ac80	INPAQ	Front Side	0	155	5775	-0.03	0.004	6.67	8.00	1.358	95.80	1.044	0.006	/
				Back Side	0	155	5775	0.09	0.133	6.67	8.00	1.358	95.80	1.044	0.189	/
				Right Edge	0	155	5775	0.17	0.017	6.67	8.00	1.358	95.80	1.044	0.024	/
	Note: Refer to ANNEX C for the detailed test data for each test configuration.															

11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Note: For 1g SAR, the highest measured 1g SAR is $0.641 < 0.80$ W/kg, repeated measurement is not required.

Note: For product specific 10g SAR, the highest measured 10g SAR is $0.281 < 2.0$ W/kg, repeated measurement is not required.

12 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

According KDB 447498 D04, simultaneous transmission:

- a) $SPLSR = (SAR1 + SAR2)^{1.5} / R_i$ (min. separation distance, mm), and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
SAR1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.
SAR2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition as the first.
- b) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
- c) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

12.1 Simultaneous Transmission Mode Considerations

No.	Simultaneous Tx Combination	Body	Limbs
1	Bluetooth + WLAN 2.4GHz (Antenna Main)	Yes	Yes
2	WLAN 2.4GHz (Antenna Auxiliary) + WLAN 2.4GHz (Antenna Main)	Yes	Yes
3	Bluetooth + WLAN 5GHz (Antenna Auxiliary)	Yes	Yes
4	Bluetooth + WLAN 5GHz (Antenna Main)	Yes	Yes
5	WLAN 5GHz (Antenna Auxiliary) + WLAN 5GHz (Antenna Main)	Yes	Yes
6	Bluetooth + WLAN 5GHz (Antenna Auxiliary) + WLAN 5GHz (Antenna Main)	Yes	Yes

Note:

1. The EUT supports the Antenna Auxiliary with TX/RX diversity function for WLAN and Bluetooth, the Antenna Main with TX/RX diversity function for WLAN.
2. WLAN 2.4GHz and Bluetooth will not be transmitting from the Antenna Auxiliary at same time.
3. The simultaneous transmission combinations of the more antennas contain combinations of less antennas, so only the worst simultaneous transmission combinations is shown in this report.

12.2 Sum SAR of Simultaneous Transmission

12.2.1 Body Simultaneous Transmission SAR Evaluation for WLAN Antenna with Bluetooth

State	Position	Stand alone SAR					SUM SAR		
		1	2	3	4	5			
		Bluetooth	WLAN 2.4GHz (Antenna Auxiliary)	WLAN 2.4GHz (Antenna Main)	MAX. WLAN 5GHz (Antenna Auxiliary)	MAX. WLAN 5GHz (Antenna Main)	Sum SAR (1+3)	Sum SAR (2+3)	Sum SAR (1+4+5)
Body	Back Side	0.201	0.710	0.009	0.566	0.086	0.210	0.719	0.853
Body	Left Edge	0.000	0.000	0.120	0.000	0.147	0.120	0.120	0.147
Body	Right Edge	0.015	0.034	0.000	0.095	0.000	0.015	0.034	0.110

Note:

1: The highest Summed 1g SAR is 0.853W/Kg < 1.6 W/kg, so Simultaneous Transmission SAR test is not required.

12.2.2 Limbs Simultaneous Transmission SAR Evaluation for WLAN Antenna with Bluetooth

State	Position	Stand alone SAR					SUM SAR		
		1	2	3	4	5			
		Bluetooth	WLAN 2.4GHz (Antenna Auxiliary)	WLAN 2.4GHz (Antenna Main)	MAX. WLAN 5GHz (Antenna Auxiliary)	MAX. WLAN 5GHz (Antenna Main)	Sum SAR (1+3)	Sum SAR (2+3)	Sum SAR (1+4+5)
Limbs	Front Side	0.027	0.007	0.147	0.009	0.084	0.174	0.154	0.120
Limbs	Back Side	0.086	0.311	0.005	0.210	0.023	0.091	0.316	0.319
Limbs	Left Edge	0.000	0.000	0.060	0.000	0.071	0.060	0.060	0.071
Limbs	Right Edge	0.008	0.015	0.000	0.036	0.000	0.008	0.015	0.044

Note:

1: The highest Summed 1g SAR is 0.319W/Kg < 4.0 W/kg, so Simultaneous Transmission SAR test is not required.

13 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY6	16.0.0.116	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 1062	2021/07/05	2024/07/05
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1333	2021/09/14	2024/09/14
E-Field Probe	Speag	EX3DV4	SN: 7607	2023/07/04	2024/07/04
Data Acquisition Electronicsr	Speag	DAE4	SN: 1710	2024/01/03	2025/01/03
Signal Generator	R&S	SMB100A	177746	2024/04/24	2025/04/24
Power Meter	R&S	NRVD-B2	835843/014	2023/09/05	2024/09/05
Power Sensor	R&S	NRV-Z4	100381	2023/09/05	2024/09/05
Power Sensor	R&S	NRV-Z2	100211	2023/09/05	2024/09/05
Network Analyzer	Agilent	E5071C	MY46103472	2023/11/14	2024/11/14
Thermometer	Elitech	RC-4	EF5238001628	2023/10/09	2024/10/09
Thermometer	Elitech	RC-4HC	EF7239002652	2023/11/17	2024/11/17
Power Amplifier	SATIMO	6552B	22374	N/A	N/A
Dielectric Probe Kit	Speag	DAK3.5	SN: 1312	N/A	N/A
Phantom	Speag	ELI V8.0	SN: 2159	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using a DAK3.5 Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity (σ) (S/m)	Meas. Permittivity (ϵ)	Target Conductivity (σ) (S/m)	Target Permittivity (ϵ)	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2024.05.15	Head	2450	21.6	1.80	39.42	1.80	39.20	0.00	0.56
2024.05.16	Head	5300	21.6	4.81	35.38	4.76	35.87	1.05	-1.37
2024.05.17	Head	5600	21.1	5.06	35.22	5.07	35.53	-0.20	-0.87
2024.05.18	Head	5800	21.2	5.27	34.91	5.27	35.30	0.00	-1.10
Note: The tolerance limit of Conductivity and Permittivity is $\pm 5\%$.									

ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %(for 1 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2024.05.15	Head	2450	100	5.330	53.30	54.20	-1.66
2024.05.16	Head	5300	100	7.970	79.70	81.80	-2.57
2024.05.17	Head	5600	100	8.050	80.50	83.60	-3.71
2024.05.18	Head	5800	100	8.260	82.60	82.30	0.36

Note: The tolerance limit of System validation $\pm 10\%$.

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %(for 10 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2024.05.15	Head	2450	100	2.480	24.80	25.20	-1.59
2024.05.16	Head	5300	100	2.310	23.10	23.40	-1.28
2024.05.17	Head	5600	100	2.310	23.10	23.80	-2.94
2024.05.18	Head	5800	100	2.340	23.40	23.10	1.30

Note: The tolerance limit of System validation $\pm 10\%$.

System Performance Check Data (2450MHz)

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
D2450V2, SPEAG	40.0 x 8.0 x 8.0	Dipole


Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Section, TSL	Distance [mm]		UID	Channel Number					
Flat, HSL		D2450	CW, 0--	2450.0, 2450	7.47	1.80	39.4	22.5	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-15	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	30.0 x 30.0 x 30.0	Date	2024-05-15	2024-05-15
Grid Steps [mm]	8.0 x 10.0	5.0 x 5.0 x 1.5	psSAR1g [W/kg]	5.24	5.33
Sensor	3.0	1.4	psSAR10g [W/kg]	2.47	2.48
Surface [mm]			Power Drift [dB]	-0.11	0.03
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.5	Scaling		
MAIA	N/A	N/A	Scaling		
Surface	All points	All points	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		80.6
			Dist 3dB Peak [mm]		9.0



System Performance Check Data (5300MHz)

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
D5GHZV2, SPEAG	10.0 x 10.0 x 3.0	Dipole


Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Section, TSL Flat, HSL	, Test Distance [mm]		UID	Channel Number					
		D5GHZ	CW, 0--	5300.0, 5300	5.41	4.81	35.4	22.6	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-16	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	22.0 x 22.0 x 22.0	Date	2024-05-16	2024-05-16
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/kg]	7.48	7.97
Sensor	3.0	1.4	psSAR10g [W/kg]	2.16	2.31
Surface [mm]			Power Drift [dB]	-0.04	0.05
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	N/A	N/A	Scaling		
Surface	All points	All points	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		65.1
			Dist 3dB Peak [mm]		7.4



System Performance Check Data (5600MHz)

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
D5GHzV2, SPEAG	10.0 x 10.0 x 3.0	Dipole


Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Section, TSL Flat, HSL	, Test Distance [mm]		UID	Channel Number					
		D5GHZ	CW, 0--	5600.0, 5600	4.58	5.06	35.2	22.3	21.1

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-17	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	22.0 x 22.0 x 22.0	Date	2024-05-17	2024-05-17
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/kg]	7.36	8.05
Sensor	3.0	1.4	psSAR10g [W/kg]	2.14	2.31
Surface [mm]			Power Drift [dB]	-0.05	0.02
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	N/A	N/A	Scaling		
Surface Detection	All points	All points	Factor [dB]		
Scan Method	Measured	Measured	TSL Correction	No correction	No correction
			M2/M1 [%]		62.3
			Dist 3dB Peak [mm]		7.6



System Performance Check Data (5800MHz)

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
D5GHZV2, SPEAG	10.0 x 10.0 x 3.0	Dipole


Exposure Conditions

Phantom	Position	Band	Group	Frequency [MHz]	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Section, TSL Flat, HSL	, Test Distance [mm]		UID	Channel Number					
		D5GHZ	CW, 0--	5800.0, 5800	4.78	5.27	34.9	22.2	21.2

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-18	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	22.0 x 22.0 x 22.0	Date	2024-05-18	2024-05-18
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4	psSAR1g [W/kg]	7.27	8.26
Sensor	3.0	1.4	psSAR10g [W/kg]	2.07	2.34
Surface [mm]			Power Drift [dB]	-0.11	0.07
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	N/A	N/A	Scaling		
Surface	All points	All points	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		61.4
			Dist 3dB Peak [mm]		7.9



ANNEX C TEST DATA

Meas.1 Body Plane with Back Side 0mm on 39 Channel in Bluetooth mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	ISM 2.4 GHz Band	Bluetooth, 10032-CAA	2441.0, 39	7.47	1.79	39.5	22.5	21.6


Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-15	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	30.0 x 30.0 x 30.0	Date	2024-05-15	2024-05-15
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0	psSAR1g [W/kg]	0.092	0.105
Sensor	3.0	1.4	psSAR10g [W/kg]	0.044	0.045
Surface [mm]			Power Drift [dB]	-0.14	0.01
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.5	Scaling		
MAIA	Y	Y	Scaling		
Surface Detection	VMS + 6p	VMS + 6p	Factor [dB]		
Scan Method	Measured	Measured	TSL Correction	No correction	No correction
			M2/M1 [%]		34.1

Dist 3dB Peak
[mm]

7.2



Meas.2 Body Plane with Left Edge 0mm on 6 Channel in IEEE802.11b mode with Antenna Main

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	EDGE LEFT, 0.00	WLAN 2.4GH z	WLAN, N, 10012 -CAB	2437.0, 6	7.47	1.79	39.5	22.5	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-15	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	32.0 x 32.0 x 30.0	Date	2024-05-15	2024-05-15
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0	psSAR1g [W/kg]	0.101	0.117
Sensor	3.0	1.4	psSAR10g [W/kg]	0.048	0.059
Surface [mm]			Power Drift	-0.08	0.01
Graded Grid	Yes	Yes	[dB]		
Grading Ratio	1.5	1.5	Power	Disabled	Disabled
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Scaling		
Detection			Factor [dB]		
Scan Method	Measured	Measured	TSL	No correction	No correction
			Correction		
			M2/M1 [%]		47.3
			Dist 3dB Peak [mm]		7.3



Meas.3 Body Plane with Back Side 0mm on 11 Channel in IEEE802.11b mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLAN 2.4GHz	WLAN, 10012 -CAB	2462.0, 11	7.47	1.82	39.3	22.5	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-15	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	32.0 x 32.0 x 30.0	Date	2024-05-15	2024-05-15
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0	psSAR1g [W/kg]	0.609	0.641
Sensor	3.0	1.4	psSAR10g [W/kg]	0.267	0.281
Surface [mm]			Power Drift	0.01	0.02
Graded Grid	Yes	Yes	[dB]		
Grading Ratio	1.5	1.5	Power	Disabled	Disabled
MAIA	N/A	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Scaling		
Detection			Factor [dB]		
Scan Method	Measured	Measured	TSL	No correction	No correction
			Correction		
			M2/M1 [%]		37.9
			Dist 3dB Peak [mm]		7.2



Meas.4 Body Plane with Left Edge 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Main

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	EDGE LEFT, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5290.0, 58	5.41	4.78	35.5	22.6	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-16	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-16	2024-05-16
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.085	0.102
Sensor	3.0	1.4	psSAR10g [W/kg]	0.031	0.051
Surface [mm]			Power Drift [dB]	0.17	0.02
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		58.0
			Dist 3dB Peak [mm]		6.6



Meas.5 Body Plane with Back Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5290.0, 58	5.41	4.78	35.5	22.6	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-16	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-16	2024-05-16
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.403	0.405
Sensor	3.0	1.4	psSAR10g [W/kg]	0.133	0.153
Surface [mm]			Power Drift	0.09	-0.10
Graded Grid	Yes	Yes	[dB]		
Grading Ratio	1.5	1.4	Power	Disabled	Disabled
MAIA	Y	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Scaling		
Detection			Factor [dB]		
Scan Method	Measured	Measured	TSL	No correction	No correction
			Correction		
			M2/M1 [%]		56.5
			Dist 3dB Peak [mm]		4.7



Meas.6 Body Plane with Left Edge 0mm on 138 Channel in IEEE802.11ac80 mode with Antenna Main

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	EDGE LEFT, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5690.0, 138	4.78	5.19	34.1	22.3	21.1

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-17	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-17	2024-05-17
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.099	0.113
Sensor	3.0	1.4	psSAR10g [W/kg]	0.034	0.058
Surface [mm]			Power Drift	0.19	0.02
Graded Grid	Yes	Yes	[dB]		
Grading Ratio	1.5	1.4	Power	Disabled	Disabled
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Scaling		
Detection			Factor [dB]		
Scan Method	Measured	Measured	TSL	No correction	No correction
			Correction		
			M2/M1 [%]		59.2
			Dist 3dB Peak [mm]		5.6



Meas.7 Body Plane with Back Side 0mm on 122 Channel in IEEE802.11ac80 mode with Antenna Auxiliary
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet

Exposure Conditions


Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5610.0, 122	4.58	5.07	35.1	22.3	21.1

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-17	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup
Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-17	2024-05-17
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.433	0.471
Sensor	3.0	1.4	psSAR10g [W/kg]	0.157	0.173
Surface [mm]			Power Drift [dB]	-0.09	-0.01
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		52.0
			Dist 3dB Peak [mm]		5.7



Meas.8 Body Plane with Left Edge 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Main

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	EDGE LEFT, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5775.0, 155	4.78	5.23	35.2	22.2	21.2

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-18	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-18	2024-05-18
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.109	0.132
Sensor	3.0	1.4	psSAR10g [W/kg]	0.038	0.063
Surface [mm]			Power Drift [dB]	0.04	-0.01
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		59.2
			Dist 3dB Peak [mm]		6.6



Meas.9 Body Plane with Back Side 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5775.0, 155	4.78	5.23	35.2	22.2	21.2

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-18	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-18	2024-05-18
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.383	0.399
Sensor	3.0	1.4	psSAR10g [W/kg]	0.124	0.148
Surface [mm]			Power Drift [dB]	-0.14	-0.12
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		55.5
			Dist 3dB Peak [mm]		6.4



Meas.10 Limbs Plane with Back Side 0mm on 39 Channel in Bluetooth mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	ISM 2.4 GHz Band	Bluetooth, 10032- CAA	2441.0, 39	7.47	1.79	39.5	22.5	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-15	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	30.0 x 30.0 x 30.0	Date	2024-05-15	2024-05-15
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0	psSAR1g [W/kg]	0.092	0.105
Sensor	3.0	1.4	psSAR10g [W/kg]	0.044	0.045
Surface [mm]			Power Drift [dB]	-0.14	0.01
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.5	Scaling		
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		34.1
			Dist 3dB Peak [mm]		7.2



Meas.11 Limbs Plane with Front Side 0mm on 6 Channel in IEEE802.11b mode with Antenna Main

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet

Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	SIDE FRONT , 0.00	WLAN 2.4GH z	WLAN, 10012 -CAB	2437.0, 6	7.47	1.79	39.5	22.5	21.6


Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 ,2024-05-15	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup

Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	32.0 x 32.0 x 30.0	Date	2024-05-15	2024-05-15
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0	psSAR1g [W/kg]	0.281	0.330
Sensor	3.0	1.4	psSAR10g [W/kg]	0.133	0.144
Surface [mm]			Power Drift [dB]	-0.04	-0.01
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.5	Scaling		
MAIA	N/A	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		35.9
			Dist 3dB Peak [mm]		7.0



Meas.12 Limbs Plane with Back Side 0mm on 11 Channel in IEEE802.11b mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLAN 2.4GH z	WLAN, 10012 -CAB	2462.0, 11	7.47	1.82	39.3	22.5	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-15	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	32.0 x 32.0 x 30.0	Date	2024-05-15	2024-05-15
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0	psSAR1g [W/kg]	0.609	0.641
Sensor	3.0	1.4	psSAR10g [W/kg]	0.267	0.281
Surface [mm]			Power Drift	0.01	0.02
Graded Grid	Yes	Yes	[dB]		
Grading Ratio	1.5	1.5	Power	Disabled	Disabled
MAIA	N/A	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Scaling		
Detection			Factor [dB]		
Scan Method	Measured	Measured	TSL	No correction	No correction
			Correction		
			M2/M1 [%]		37.9
			Dist 3dB Peak [mm]		7.2



Meas.13 Limbs Plane with Front Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Main
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet

Exposure Conditions


Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	SIDE FRONT , 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5290.0, 58	5.41	4.78	35.5	22.6	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 , 2024-05-16	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup
Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-16	2024-05-16
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.245	0.286
Sensor	3.0	1.4	psSAR10g [W/kg]	0.071	0.073
Surface [mm]			Power Drift [dB]	-0.14	-0.14
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		45.6
			Dist 3dB Peak [mm]		4.1



Meas.14 Limbs Plane with Back Side 0mm on 58 Channel in IEEE802.11ac80 mode with Antenna Auxiliary
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet

Exposure Conditions


Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5290.0, 58	5.41	4.78	35.5	22.6	21.6

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-16	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup
Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-16	2024-05-16
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.403	0.405
Sensor	3.0	1.4	psSAR10g [W/kg]	0.133	0.153
Surface [mm]			Power Drift	0.09	-0.10
Graded Grid	Yes	Yes	[dB]		
Grading Ratio	1.5	1.4	Power	Disabled	Disabled
MAIA	Y	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Scaling		
Detection			Factor [dB]		
Scan Method	Measured	Measured	TSL	No correction	No correction
			Correction		
			M2/M1 [%]		56.5
			Dist 3dB Peak [mm]		4.7



Meas.15 Limbs Plane with Front Side 0mm on 122 Channel in IEEE802.11ac80 mode with Antenna Main

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	SIDE FRONT , 0.00	WLA N 5GH z	WLA N, 10062 -CAD	5610.0, 122	4.58	5.07	35.1	22.3	21.1

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 , 2024-05-17	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-17	2024-05-17
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.211	0.307
Sensor	3.0	1.4	psSAR10g [W/kg]	0.069	0.073
Surface [mm]			Power Drift	0.01	-0.08
Graded Grid	Yes	Yes	[dB]		
Grading Ratio	1.5	1.4	Power	Disabled	Disabled
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Scaling		
Detection			Factor [dB]		
Scan Method	Measured	Measured	TSL	No correction	No correction
			Correction		
			M2/M1 [%]		44.3
			Dist 3dB Peak [mm]		4.0



Meas.16 Limbs Plane with Back Side 0mm on 122 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5610.0, 122	4.58	5.07	35.1	22.3	21.1

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-17	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-17	2024-05-17
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.433	0.471
Sensor	3.0	1.4	psSAR10g [W/kg]	0.157	0.173
Surface [mm]			Power Drift [dB]	-0.09	-0.01
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		52.0
			Dist 3dB Peak [mm]		5.7



Meas.17 Limbs Plane with Front Sidee 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Main
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet

Exposure Conditions


Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	SIDE FRONT , 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5775.0, 155	4.78	5.22	35.2	22.2	21.2

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 ,2024-05- 18	EX3DV4 - SN7607, 2023-07- 04	DAE4 Sn1710, 2024-01- 03

Scan Setup
Measurement Results

	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-18	2024-05-18
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.220	0.321
Sensor	3.0	1.4	psSAR10g [W/kg]	0.069	0.075
Surface [mm]			Power Drift [dB]	0.13	-0.08
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	Y	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		42.9
			Dist 3dB Peak [mm]		4.1



Meas.18 Limbs Plane with Back Side 0mm on 155 Channel in IEEE802.11ac80 mode with Antenna Auxiliary

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	DUT Type
Duet 11	255.0 x 170.0 x 10.0	Tablet


Exposure Conditions

Phantom Section , TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity	Ambient Temperature [°C]	Liquid Temperature [°C]
Flat, HSL	BACK, 0.00	WLA N 5GH z	WLA N, 10544 -AAC	5775.0, 155	4.78	5.23	35.2	22.2	21.2

Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2159	HBBL-600-10000 2024-05-18	EX3DV4 - SN7607, 2023-07-04	DAE4 Sn1710, 2024-01-03

Scan Setup			Measurement Results		
	Area Scan	Zoom Scan		Area Scan	Zoom Scan
Grid Extents [mm]	120.0 x 120.0	24.0 x 24.0 x 22.0	Date	2024-05-18	2024-05-18
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 2.0	psSAR1g [W/kg]	0.383	0.399
Sensor	3.0	1.4	psSAR10g [W/kg]	0.124	0.148
Surface [mm]			Power Drift [dB]	-0.14	-0.12
Graded Grid	Yes	Yes	Power	Disabled	Disabled
Grading Ratio	1.5	1.4	Scaling		
MAIA	Y	N/A	Scaling		
Surface	VMS + 6p	VMS + 6p	Factor [dB]		
Detection			TSL	No correction	No correction
Scan Method	Measured	Measured	Correction		
			M2/M1 [%]		55.5
			Dist 3dB Peak [mm]		6.4



ANNEX D SAR TEST SETUP PHOTOS

Please refer the document “BL-SZ2450333-AS.pdf”.

ANNEX E EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2450333-AW.pdf”.

ANNEX F CALIBRATION REPORT

Please refer the document “BL-SZ2450333-AC.pdf”.

ANNEX G TUNE-UP PROCEDURE

Please refer the document “BL-SZ2450333-AT-1.pdf”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--