

ISSUED BY  
Shenzhen BALUN Technology Co., Ltd.


FOR  
**Notebook Computer**

ISSUED TO  
Lenovo (Shanghai) Electronics Technology Co., Ltd.

Section 304-305, Building No. 4, # 222, Meiyue Road, China  
(Shanghai) Pilot Free Trade Zone, 200131, CHINA

# SAR

# TEST REPORT



Tested by: *Miao Yan*

Miao Yan

Date Feb. 17, 2022

Approved by: *Liao Jianming*

Liao Jianming

(Technical Director)

Date Feb. 17, 2022

Report No.: BL-SZ21C0792-701

EUT Name: Notebook Computer

Model Name IP Duet 3 Chrome 11Q727  
(refer section 2.3)

Brand Name: Lenovo

FCC ID: O57DUET3CB7C

Test Standard: 47 CFR Part 2.1093  
(refer section 3.1)

Maximum SAR: Body 2.4GHz(1 g): 1.096 W/kg  
Body 5GHz(1 g): 1.130 W/kg

Test Conclusion: Pass

Test Date: Jan. 05, 2022 ~ Jan. 12, 2022

Date of Issue: Feb. 17, 2022

*NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.*

**Revision History**

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Feb. 17, 2022</u>	<u>Initial Issue</u>

**TABLE OF CONTENTS**

1 GENERAL INFORMATION ..... 4

    1.1 Identification of the Testing Laboratory ..... 4

    1.2 Identification of the Responsible Testing Location ..... 4

    1.3 Test Environment Condition ..... 4

    1.4 Announce ..... 4

2 PRODUCT INFORMATION ..... 5

    2.1 Applicant Information ..... 5

    2.2 Manufacturer Information ..... 5

    2.3 General Description for Equipment under Test (EUT) ..... 5

    2.4 Ancillary Equipment ..... 6

    2.5 Technical Information ..... 6

3 SUMMARY OF TEST RESULT ..... 7

    3.1 Test Standards ..... 7

    3.2 Device Category and SAR Limit ..... 8

    3.3 Test Result Summary ..... 9

    3.4 Test Uncertainty ..... 10

4 MEASUREMENT SYSTEM ..... 11

    4.1 Specific Absorption Rate (SAR) Definition ..... 11

    4.2 DASy SAR System ..... 12

5 SYSTEM VERIFICATION ..... 20

    5.1 Purpose of System Check ..... 20

    5.2 System Check Setup ..... 20

6 TEST POSITION CONFIGURATIONS ..... 21

    6.1 Tablet Exposure Condition ..... 21

7 MEASUREMENT PROCEDURE ..... 22

    7.1 Measurement Process Diagram ..... 22

7.2	SAR Scan General Requirement .....	23
7.3	Measurement Procedure.....	24
7.4	Area & Zoom Scan Procedure .....	24
8	CONDUCTED RF OUPUT POWER.....	25
8.1	WIFI.....	25
8.2	Bluetooth (Aux. Antenna) .....	34
9	TEST EXCLUSION CONSIDERATION.....	35
9.1	Tablet Mode antenna location sketch.....	35
9.3	SAR Test Consideration Table.....	36
10	TEST RESULT .....	40
10.1	Bluetooth .....	40
10.2	WIFI 2.4GHz.....	40
10.3	WIFI 5GHz.....	41
11	SAR Measurement Variability.....	42
12	SIMULTANEOUS TRANSMISSION .....	43
12.1	Simultaneous Transmission Mode Considerations .....	43
12.2	Sum SAR of Simultaneous Transmission .....	44
13	TEST EQUIPMENTS LIST .....	47
ANNEX A	SIMULATING LIQUID VERIFICATION RESULT .....	48
ANNEX B	SYSTEM CHECK RESULT .....	49
ANNEX C	TEST DATA.....	55
ANNEX D	SAR TEST SETUP PHOTOS.....	64
ANNEX E	CALIBRATION REPORT .....	64

# 1 GENERAL INFORMATION

## 1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province,P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

## 1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co.,Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province,P. R. China
Accreditation Certificate	The laboratory is a testing organizatin accredited by FCC as a accredited testing laboratory. The designation number is CN1196.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

## 1.3 Test Environment Condition

Ambient Temperature	21°C to 23°C
Ambient Relative Humidity	32% to 49%
Ambient Pressure	100KPa to 102KPa

## 1.4 Announce

- (1) The test report reference to the report template version v2.2.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	Lenovo (Shanghai) Electronics Technology Co., Ltd.
Address	Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone, 200131, CHINA

### 2.2 Manufacturer Information

Manufacturer	Lenovo PC HK Limited
Address	23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, P.R. China

### 2.3 General Description for Equipment under Test (EUT)

EUT Name	Notebook Computer
Model Name Under Test	IP Duet 3 Chrome 11Q727
Series Model Name	IP Duet 3 Chrome 11***** (* can be 0-9, a-z, A-Z, any symbol, blank or nothing)
Description of Model name differentiation	Only differences are model names for trading purpose.
Hardware Version	V5
Software Version	R97-14324.31.0 (dev channel)
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

#### Antenna Information:

Antenna Port	Model Name	Antenna Manufacturer	Antenna Type	Antenna Gain (dBi)			
				2.4 GHz	5.15-5.35 GHz	5.47-5.725 GHz	5.725-5.85 GHz
Main Antenna	2.00005205	ZhongTianXun	PIFA	1.92	2.77	2.71	2.39
Auxiliary Antenna	2.00005206		PIFA	1.85	2.71	2.89	2.54
Main Antenna	N12-8055-R0A	South Star	PIFA	1.55	2.05	2.23	0.52
Auxiliary Antenna	N12-8056-R0A		PIFA	1.18	2.05	1.93	1.46

Note: The report only shown the antenna which matches the antenna with the highest antenna gain.

## 2.4 Ancillary Equipment

Note: not application.

## 2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) U-NII-1/2A/2C/3
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	2.4G WLAN, 5G WLAN, Bluetooth	
Frequency Range	802.11b/g	2412 MHz ~ 2476 MHz
	802.11n(HT20/HT40)	2412 MHz ~ 2476 MHz
	802.11a	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11n(HT20/HT40)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
		5470 MHz ~ 5725 MHz
		5725 MHz ~ 5850 MHz
	802.11 ac(VHT20/VHT40/VHT80)	5150 MHz ~ 5250 MHz
		5250 MHz ~ 5350 MHz
5470 MHz ~ 5725 MHz		
5725 MHz ~ 5850 MHz		
Bluetooth	2402 MHz ~ 2480 MHz	
Antenna Type	WLAN: PIFA Antenna Bluetooth: PIFA Antenna	
Hotspot Function	N/A	
Exposure Category	General Population/Uncontrolled exposure	
EUT Stage	Portable Device	
Product	Type	
	<input checked="" type="checkbox"/> Production unit	<input type="checkbox"/> Identical prototype

### 3 SUMMARY OF TEST RESULT

#### 3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices
2	ANSI C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	KDB 248227 D01 v02r02	SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters
8	KDB 616217 D04v01r02	SAR for laptop and tablets

### 3.2 Device Category and SAR Limit

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user.

Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

Table of Exposure Limits:

Body Position	SAR Value (W/Kg)	
	General Population/ Uncontrolled Exposure	Occupational/ ControlledExposure
Whole-Body SAR (averaged over the entire body)	0.08	0.4
Partial-Body SAR (averaged over any 1 gram of tissue)	1.60	8.0
SAR for hands, wrists, feet and ankles (averaged over any 10 grams of tissue)	4.0	20.0

NOTE:

**General Population/Uncontrolled Exposure:** Locations where there is the exposure of individuals who have no knowledge or control of their exposure. General population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

**Occupational/Controlled Exposure:** Locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.



### 3.3 Test Result Summary

#### 3.3.1 Highest SAR (1 g Value)

Band	Antenna	Maximum Scaled SAR (W/kg)	Maximum Report SAR (W/kg)
		Body	Body
2.4G WLAN	Aux.	1.096	<b>1.130</b>
2.4G WLAN	Main	0.556	
5.3G WLAN	Aux.	0.414	
5.3G WLAN	Main	0.531	
5.6G WLAN	Aux.	0.425	
5.6G WLAN	Main	0.284	
5.8G WLAN	Aux.	<b>1.130</b>	
5.8G WLAN	Main	0.327	
Bluetooth	Aux.	0.276	
Limit (W/kg)		1.60	
Verdict		Pass	

### 3.4 Test Uncertainty

According to KDB 865664 D01, when the highest measured 1 g SAR within a frequency band is  $< 1.5$  W/kg, the extensive SAR measurement uncertainty analysis is not required in SAR reports submitted for equipment approval.

The maximum 1 g SAR for the EUT in this report is 1.130 W/kg, which is lower than 1.5 W/kg, so the extensive SAR measurement uncertainty analysis is not required in this report.

## 4 MEASUREMENT SYSTEM

### 4.1 Specific Absorption Rate (SAR) Definition

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy ( $dW$ ) absorbed by (dissipated in) an incremental mass ( $dm$ ) contained in a volume element ( $dv$ ) of a given density ( $\rho$ ). The equation description is as below:

$$\mathbf{SAR} = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$\mathbf{SAR} = \frac{\sigma E^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,

$\rho$  is the mass density of the tissue and  $E$  is the RMS electrical field strength.

## 4.2 DASY SAR System

### 4.2.1 DASY SAR System Diagram



The DASY5 system for performing compliance tests consists of the following items:

1. A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
2. A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
3. A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
4. A unit to operate the optical surface detector which is connected to the EOC.
5. The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASYS5 measurement server.
6. The DASYS5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.
7. DASYS5 software and SEMCAD data evaluation software.
8. Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
9. The generic twin phantom enabling the testing of left-hand and right-hand usage.
10. The device holder for handheld mobile phones.
11. Tissue simulating liquid mixed according to the given recipes.
12. System validation dipoles allowing to validate the proper functioning of the system.

#### 4.2.2 Robot

The Dasy SAR system uses the high precision robots. Symmetrical design with triangular core Built-in optical fiber for surface detection system For the 6-axis controller system, Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents). The robot series have many features that are important for our application:



- High precision  
(repeatability  $\pm 0.02$  mm)
- High reliability  
(industrial design)
- Low maintenance costs  
(virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements  
(brush less synchron motors; no stepper motors)
- Low ELF interference  
(motor control \_elds shielded via the closed metallic construction shields)

### 4.2.3 E-Field Probe

The probe is specially designed and calibrated for use in liquids with high permittivities for the measurements the Specific Dosimetric E-Field Probe EX3DV4-SN:7663 with following specifications is used.

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., glycolether)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to 6 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)
Directivity	$\pm 0.2$ dB in HSL (rotation around probe axis) ; $\pm 0.4$ dB in HSL (rotation normal to probe axis)
Dynamic range	5 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB
Dimensions	Overall length: 337 mm (Tip: 9 mm) Tip diameter: 2.5 mm (Body: 10 mm) Distance from probe tip to dipole centers: 1.0 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms (EX3DV4)



#### E-Field Probe Calibration Process

Probe calibration is realized, in compliance with CENELEC EN 62209-1/-2 and IEEE 1528 std, with CALISAR, Antenna proprietary calibration system. The calibration is performed with the EN 62209-1/2 annexe technique using reference guide at the five frequencies.

#### 4.2.4 Data Acquisition Electronics

The data acquisition electronics (DAE) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converte and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.



- Input Impedance: 200M $\Omega$
- The Inputs: Symmetrical and Floating
- Commom Mode Rejection: Above 80dB

### 4.2.5 Phantoms

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.



- Left hand
- Right hand
- Flat phantom

Photo of Phantom SN1857



Serial Number	Material	Length	Height
SN 1857 SAM	Vinylester, glass fiber reinforced	1000	500



Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points.



·Flat phantom

Photo of Phantom SN1012



Serial Number	Shell Thickness (mm)	Major ellipse axis (mm)	Minor axis ( mm )
SN 1012 ELI4	2.0 ± 0.2	600	500

#### 4.2.6 Device Holder

The DASY5 device holder has two scales for device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The plane between the ear openings and the mouth tip has a rotation angle of  $65^\circ$ . The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. This device holder is used for standard mobile phones or PDA"s only. If necessary an additional support of polystyrene material is used. Larger DUT"s (e.g. notebooks) cannot be tested using this device holder. Instead a support of bigger polystyrene cubes and thin polystyrene plates is used to position the DUT in all relevant positions to find and measure spots with maximum SAR values. Therefore those devices are normally only tested at the flat part of the SAM.



The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than  $1^\circ$ .

#### 4.2.7 Simulating Liquid

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5%.



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity $\sigma$ (S/m)	Permittivity $\epsilon$
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity $\sigma$ (S/m)	Permittivity $\epsilon$
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity $\sigma$ (S/m)	Permittivity $\epsilon$
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity $\sigma$ (S/m)	Permittivity $\epsilon$
5200	78.60	21.40			/		5.54	47.86
5800	78.50	21.40			0.1		6.0	48.20


## 5 SYSTEM VERIFICATION

### 5.1 Purpose of System Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

### 5.2 System Check Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



## 6 TEST POSITION CONFIGURATIONS

### 6.1 Tablet Exposure Condition

This DUT was tested in four different positions. They are Back Side, Top Edge and Left Edge in these positions, the surface of DUT is touching with phantom 0mm.





Fig Illustration for Lap-touching Position

## 7 MEASUREMENT PROCEDURE

### 7.1 Measurement Process Diagram



## 7.2 SAR Scan General Requirement

Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1 g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013.

			≤3GHz	>3GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5±1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30°±1°	20°±1°
Maximum area scan spatial resolution: $\Delta x$ Area , $\Delta y$ Area			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3–4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x$ Zoom , $\Delta y$ Zoom			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3–4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z$ Zoom (n)		≤ 5 mm	3–4 GHz: ≤ 4 mm
				4–5 GHz: ≤ 3 mm
				5–6 GHz: ≤ 2 mm
	graded grid	$\Delta z$ Zoom (1): between 1st two points closest to phantom surface	≤ 4 mm	3–4 GHz: ≤ 3 mm
		4–5 GHz: ≤ 2.5 mm		
			5–6 GHz: ≤ 2 mm	
		$\Delta z$ Zoom (n>1): between subsequent points	≤ 1.5· $\Delta z$ Zoom (n-1)	
Minimum zoom scan volume	x, y, z		≥30 mm	3–4 GHz: ≥ 28 mm
				4–5 GHz: ≥ 25 mm
				5–6 GHz: ≥ 22 mm
<b>Note:</b> <ol style="list-style-type: none"> <li><math>\delta</math> is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.</li> <li>* When zoom scan is required and the reported SAR from the area scan based 1 g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.</li> </ol>				

### 7.3 Measurement Procedure

The following steps are used for each test position

- a. Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- b. Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- c. Measurement of the SAR distribution with a grid of 8 to 16mm \* 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- d. Around this point, a cube of 30 \* 30 \* 30 mm or 32 \* 32 \* 32 mm is assessed by measuring 5 or 8 \* 5 or 8\*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

### 7.4 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r04 quoted below.

When the 1 g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.



## 8 CONDUCTED RF OUTPUT POWER

### 8.1 WIFI

#### 8.1.1 2.4G WIFI (Aux. Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	13.39	14.00	Yes
		6	2437	<b>13.61</b>	14.00	Yes
		11	2462	13.15	14.00	Yes
	802.11g	1	2412	13.56	14.00	No
		6	2437	13.45	14.00	No
		11	2462	13.50	14.00	No
	802.11n(HT20)	1	2412	13.55	14.00	No
		6	2437	13.40	14.00	No
		11	2462	13.60	14.00	No
	802.11n(HT40)	3	2422	12.29	12.50	No
		6	2437	13.34	14.00	No
		9	2452	11.94	12.50	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

Adjusted SAR = Report SAR \* (max power (OFDM)/ max power (DSSS)) = 1.096 \* (25.12 mw)/(25.12 mw) =1.096 W/kg, so the 2.4GHz OFDM SAR test is not required.

## 8.1.2 2.4G WIFI (Main Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	<b>13.90</b>	14.00	Yes
		6	2437	13.54	14.00	Yes
		11	2462	13.34	14.00	Yes
	802.11g	1	2412	13.63	14.00	No
		6	2437	13.62	14.00	No
		11	2462	13.35	14.00	No
	802.11n(HT20)	1	2412	13.71	14.00	No
		6	2437	13.42	14.00	No
		11	2462	13.86	14.00	No
	802.11n(HT40)	3	2422	12.04	12.50	No
		6	2437	13.46	14.00	No
		9	2452	12.37	12.50	No

Note: According KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

Adjusted SAR = Report SAR \* (max power (OFDM)/ max power (DSSS)) = 1.096 \* (25.12 mw)/(25.12 mw) = 1.096 W/kg, so the 2.4GHz OFDM SAR test is not required.

## 8.1.3 2.4G WIFI (TOTAL)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
2.4 (2.4~2.4835)	802.11b	1	2412	16.66	17.00	No
		6	2437	16.59	17.00	No
		11	2462	16.26	17.00	No
	802.11g	1	2412	16.61	17.00	No
		6	2437	16.55	17.00	No
		11	2462	16.44	17.00	No
	802.11n(HT20)	1	2412	16.64	17.00	No
		6	2437	16.42	17.00	No
		11	2462	16.74	17.00	No
	802.11n(HT40)	3	2422	15.18	15.50	No
		6	2437	16.41	17.00	No
		9	2452	15.17	15.50	No

## 8.1.4 5G WIFI (Aux. Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	10.82	11.00	No
		40	5200	10.61	11.00	No
		48	5240	10.92	11.00	No
	802.11n(HT20)	36	5180	10.66	11.00	No
		40	5200	10.43	11.00	No
		48	5240	10.71	11.00	No
	802.11n(HT40)	38	5190	10.29	11.00	No
		46	5230	10.19	11.00	No
	802.11ac(VHT20)	36	5180	10.72	11.00	No
		40	5200	10.56	11.00	No
		48	5240	10.76	11.00	No
	802.11ac(VHT40)	38	5190	10.21	11.00	No
46		5230	10.07	11.00	No	
802.11ac(VHT80)	42	5210	10.81	11.00	No	
5.3 (5.25~5.35)	802.11a	52	5260	10.05	11.00	No
		60	5300	10.73	11.00	No
		64	5320	10.83	11.00	No
	802.11n(HT20)	52	5260	10.94	11.00	No
		60	5300	10.51	11.00	No
		64	5320	10.68	11.00	No
	802.11n(HT40)	54	5270	10.36	11.00	No
		62	5310	10.13	11.00	No
	802.11ac(VHT20)	52	5260	10.76	11.00	No
		60	5300	10.61	11.00	No
		64	5320	10.63	11.00	No
	802.11ac(VHT40)	54	5270	10.29	11.00	No
62		5310	10.19	11.00	No	
802.11ac(VHT80)	58	5290	<b>10.87</b>	11.00	Yes	
5.6 (5.47~5.725)	802.11a	100	5500	10.44	11.00	No
		116	5580	10.24	11.00	No
		140	5700	10.66	11.00	No
	802.11n(HT20)	100	5500	10.45	11.00	No
		116	5580	10.15	11.00	No
		140	5700	10.48	11.00	No
	802.11n(HT40)	102	5510	10.86	11.00	No
		110	5550	10.67	11.00	No
		118	5590	10.48	11.00	
		134	5670	10.65	11.00	No
	802.11ac(VHT20)	100	5500	10.74	11.00	No
		116	5580	10.42	11.00	No
140		5700	10.48	11.00	No	

	802.11ac(VHT40)	102	5510	10.72	11.00	No
		118	5590	10.57	11.00	No
		134	5670	10.61	11.00	No
	802.11ac(VHT80)	106	5530	10.77	11.00	Yes
		122	5610	10.79	11.00	Yes
		138	5690	<b>10.94</b>	11.00	Yes
5.8 (5.725~5.850)	802.11a	149	5745	10.63	11.00	No
		157	5785	10.45	11.00	No
		165	5825	10.54	11.00	No
	802.11n(HT20)	149	5745	10.78	11.00	No
		157	5785	10.89	11.00	No
		165	5825	10.79	11.00	No
	802.11n(HT40)	151	5755	10.94	11.00	No
		159	5795	10.59	11.00	No
	802.11ac(VHT20)	149	5745	10.85	11.00	No
		157	5785	10.96	11.00	No
		165	5825	10.85	11.00	No
	802.11ac(VHT40)	151	5755	10.91	11.00	No
		159	5795	10.43	11.00	No
	802.11ac(VHT80)	155	5775	<b>10.83</b>	11.00	Yes

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

## 8.1.5 5G WIFI (Main Antenna)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	10.53	11.00	No
		40	5200	10.82	11.00	No
		48	5240	10.57	11.00	No
	802.11n(HT20)	36	5180	10.83	11.00	No
		40	5200	10.74	11.00	No
		48	5240	10.93	11.00	No
	802.11n(HT40)	38	5190	10.51	11.00	No
		46	5230	10.69	11.00	No
	802.11ac(VHT20)	36	5180	10.82	11.00	No
		40	5200	10.76	11.00	No
		48	5240	10.93	11.00	No
	802.11ac(VHT40)	38	5190	10.58	11.00	No
46		5230	10.76	11.00	No	
802.11ac(VHT80)	42	5210	10.56	11.00	No	
5.3 (5.25~5.35)	802.11a	52	5260	10.76	11.00	No
		60	5300	10.54	11.00	No
		64	5320	10.62	11.00	No
	802.11n(HT20)	52	5260	10.59	11.00	No
		60	5300	10.75	11.00	No
		64	5320	10.45	11.00	No
	802.11n(HT40)	54	5270	10.86	11.00	No
		62	5310	10.76	11.00	No
	802.11ac(VHT20)	52	5260	10.51	11.00	No
		60	5300	10.79	11.00	No
		64	5320	10.85	11.00	No
	802.11ac(VHT40)	54	5270	10.86	11.00	No
62		5310	10.71	11.00	No	
802.11ac(VHT80)	58	5290	<b>10.54</b>	11.00	Yes	
5.6 (5.47~5.725)	802.11a	100	5500	10.65	11.00	No
		116	5580	10.23	11.00	No
		140	5700	10.35	11.00	No
	802.11n(HT20)	100	5500	10.61	11.00	No
		116	5580	10.93	11.00	No
		140	5700	10.32	11.00	No
	802.11n(HT40)	102	5510	10.41	11.00	No
		110	5550	10.53	11.00	No
		118	5590	10.38	11.00	
		134	5670	10.58	11.00	No
	802.11ac(VHT20)	100	5500	10.43	11.00	No
		116	5580	10.51	11.00	No
140		5700	10.93	11.00	No	

	802.11ac(VHT40)	102	5510	10.57	11.00	No
		118	5590	10.38	11.00	No
		134	5670	10.58	11.00	No
	802.11ac(VHT80)	106	5530	<b>10.65</b>	11.00	Yes
		122	5610	10.05	11.00	Yes
		138	5690	10.24	11.00	Yes
5.8 (5.725~5.850)	802.11a	149	5745	10.89	11.00	No
		157	5785	10.48	11.00	No
		165	5825	10.85	11.00	No
	802.11n(HT20)	149	5745	10.67	11.00	No
		157	5785	10.67	11.00	No
		165	5825	10.58	11.00	No
	802.11n(HT40)	151	5755	10.12	11.00	No
		159	5795	10.28	11.00	No
	802.11ac(VHT20)	149	5745	10.72	11.00	No
		157	5785	10.65	11.00	No
		165	5825	10.56	11.00	No
	802.11ac(VHT40)	151	5755	10.29	11.00	No
		159	5795	10.84	11.00	No
	802.11ac(VHT80)	155	5775	<b>10.83</b>	11.00	Yes

Note: When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.

## 8.1.6 5G WIFI (TOTAL)

Band (GHz)	Mode	Channel	Freq. (MHz)	Conducted Power (dBm)	Tune-up Power Limit (dBm)	SAR Test Require.
5.2 (5.15~5.25)	802.11a	36	5180	13.69	14.00	No
		40	5200	13.73	14.00	No
		48	5240	13.76	14.00	No
	802.11n(HT20)	36	5180	13.76	14.00	No
		40	5200	13.60	14.00	No
		48	5240	13.83	14.00	No
	802.11n(HT40)	38	5190	13.41	14.00	No
		46	5230	13.46	14.00	No
	802.11ac(VHT20)	36	5180	13.78	14.00	No
		40	5200	13.67	14.00	No
		48	5240	13.86	14.00	No
	802.11ac(VHT40)	38	5190	13.41	14.00	No
46		5230	13.44	14.00	No	
802.11ac(VHT80)	42	5210	13.70	14.00	No	
5.3 (5.25~5.35)	802.11a	52	5260	13.43	14.00	No
		60	5300	13.65	14.00	No
		64	5320	13.74	14.00	No
	802.11n(HT20)	52	5260	13.78	14.00	No
		60	5300	13.64	14.00	No
		64	5320	13.58	14.00	No
	802.11n(HT40)	54	5270	13.63	14.00	No
		62	5310	13.47	14.00	No
	802.11ac(VHT20)	52	5260	13.65	14.00	No
		60	5300	13.71	14.00	No
		64	5320	13.75	14.00	No
	802.11ac(VHT40)	54	5270	13.59	14.00	No
62		5310	13.47	14.00	No	
802.11ac(VHT80)	58	5290	13.72	14.00	No	
5.6 (5.47~5.725)	802.11a	100	5500	13.56	14.00	No
		116	5580	13.25	14.00	No
		140	5700	13.52	14.00	No
	802.11n(HT20)	100	5500	13.54	14.00	No
		116	5580	13.57	14.00	No
		140	5700	13.41	14.00	No
	802.11n(HT40)	102	5510	13.65	14.00	No
		110	5550	13.61	14.00	No
		118	5590	13.44	14.00	No
		134	5670	13.63	14.00	No
	802.11ac(VHT20)	100	5500	13.60	14.00	No
		116	5580	13.48	14.00	No
140		5700	13.72	14.00	No	



	802.11ac(VHT40)	102	5510	13.66	14.00	No
		118	5590	13.49	14.00	No
		134	5670	13.61	14.00	No
	802.11ac(VHT80)	106	5530	13.72	14.00	No
		122	5610	13.45	14.00	No
		138	5690	13.61	14.00	No
5.8 (5.725~5.850)	802.11a	149	5745	13.77	14.00	No
		157	5785	13.48	14.00	No
		165	5825	13.71	14.00	No
	802.11n(HT20)	149	5745	13.74	14.00	No
		157	5785	13.79	14.00	No
		165	5825	13.70	14.00	No
	802.11n(HT40)	151	5755	13.56	14.00	No
		159	5795	13.45	14.00	No
	802.11ac(VHT20)	149	5745	13.80	14.00	No
		157	5785	13.82	14.00	No
		165	5825	13.72	14.00	No
	802.11ac(VHT40)	151	5755	13.62	14.00	No
		159	5795	13.65	14.00	No
	802.11ac(VHT80)	155	5775	13.84	14.00	No


## 8.2 Bluetooth (Aux. Antenna)

Mode	GFSK			π/4-DQPSK		
Channel	0	39	78	0	39	78
Frequency (MHz)	2402	2441	2480	2402	2441	2480
Peak Power (dBm)	9.10	<b>10.67</b>	9.10	9.17	10.72	9.03
Tune-Up Limit (dBm)	11.00	12.00	11.00	11.00	12.00	11.00
Mode	8-DPSK			/		
Channel	0	39	78	/	/	/
Frequency (MHz)	2402	2441	2480	/	/	/
Peak Power (dBm)	9.49	11.03	9.30	/	/	/
Tune-Up Limit (dBm)	11.00	12.00	11.00	/		
Mode	BLE-1Mbps			BLE-2Mbps		
Channel	0	19	39	0	19	39
Frequency (MHz)	2402	2440	2480	2402	2440	2480
Peak Power (dBm)	0.82	2.46	1.22	1.09	2.70	1.50
Tune-Up Limit (dBm)	5.00	5.00	5.00	5.00	5.00	5.00

Note: The Bluetooth duty cycle is 76.68% as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the maximum duty cycle is 100%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation.


### Duty Cycle

#### Bluetooth-GFSK



## 9 TEST EXCLUSION CONSIDERATION

### 9.1 Tablet Mode antenna location sketch



Ant. Aux.

Position	Back Side	Left Edge	Right Edge	Top Edge	Bottom Edge
Distance(mm)	5.00	171.70	47.73	3.56	160.00

Ant. Main

Position	Back Side	Left Edge	Right Edge	Top Edge	Bottom Edge
Distance(mm)	5.00	13.45	206.10	3.56	160.00

### 9.3 SAR Test Consideration Table

According with FCC KDB 447498 D04, Appendix B, The SAR-based exemption formula applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). The following table shows the power threshold from 5mm to 50mm.

Power Thresholds (mW)					
Frequency (MHz)	At separation distance of $\leq 5$ mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
300	39 mW	65 mW	88 mW	110 mW	129 mW
450	22 mW	44 mW	67 mW	89 mW	112 mW
835	9 mW	25 mW	44 mW	66 mW	90 mW
1900	3 mW	12 mW	26 mW	44 mW	66 mW
2450	3 mW	10 mW	22 mW	38 mW	59 mW
3600	2 mW	8 mW	18 mW	32 mW	49 mW
5800	1 mW	6 mW	14 mW	25 mW	40 mW
Frequency (MHz)	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of 50 mm
300	148 mW	166 mW	184 mW	201 mW	217 mW
450	135 mW	158 mW	180 mW	203 mW	226 mW
835	116 mW	145 mW	175 mW	207 mW	240 mW
1900	92 mW	122 mW	157 mW	195 mW	236 mW
2450	83 mW	111 mW	143 mW	179 mW	219 mW
3600	71 mW	96 mW	125 mW	158 mW	195 mW
5800	58 mW	80 mW	106 mW	136 mW	169 mW

## 9.3.1 Tablet and Tent mode SAR Test Exclusion Consideration

Aux. Antenna

Band	Mode	Max. Peak Power		Test Position Configurations				
		dBm	mW	Back Side (with keyboard)	Left Edge	Right Edge	Top Edge	Bottom Edge
Distance to User (mm)				5.00	171.70	47.73	3.56	160.00
SAR Test Required								
Exclusion Threshold				3.00	2288.00	200.00	3.00	2000.00
WLAN 2.4 G	802.11b	14.00	25.12	Yes	No	No	Yes	No
	802.11g	14.00	25.12	No	No	No	No	No
	802.11n(HT20)	14.00	25.12	No	No	No	No	No
	802.11n(HT40)	14.00	25.12	No	No	No	No	No
Exclusion Threshold				1.00	2224.0	153.00	1.00	1919.00
WLAN 5.2 G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	No	No	No	No	No
Exclusion Threshold				1.00	2224.0	153.00	1.00	1919.00
WLAN 5.3G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	Yes	No	No	Yes	No
Exclusion Threshold				1.00	2224.0	153.00	1.00	1919.00
WLAN 5.6 G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	Yes	No	No	Yes	No
Exclusion Threshold				1.00	2224.0	153.00	1.00	1919.00
WLAN 5.8 G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	Yes	No	No	Yes	No
Exclusion Threshold				3.00	2288.00	200.00	3.00	2000.00
Bluetooth	BR/EDR	12.00	15.85	Yes	No	No	Yes	No
	BLE	5.00	3.16	No	No	No	No	No

## Main Antenna

Band	Mode	Max. Peak Power		Test Position Configurations				
		dBm	mW	Back Side (with keyboard)	Left Edge	Right Edge	Top Edge	Bottom Edge
Distance to User (mm)				5.00	13.45	206.10	3.56	160.00
SAR Test Required								
Exclusion Threshold				3.00	18.00	3060.00	3.00	2000.00
WLAN 2.4 G	802.11b	14.00	25.12	Yes	Yes	No	Yes	No
	802.11g	14.00	25.12	No	No	No	No	No
	802.11n(HT20)	14.00	25.12	No	No	No	No	No
	802.11n(HT40)	14.00	25.12	No	No	No	No	No
Exclusion Threshold				1.00	11.00	3060.00	1.00	1919.00
WLAN 5.2 G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	No	No	No	No	No
Exclusion Threshold				1.00	11.00	3060.00	1.00	1919.00
WLAN 5.3G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	Yes	Yes	No	Yes	No
Exclusion Threshold				1.00	11.00	3060.00	1.00	1919.00
WLAN 5.6 G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	Yes	Yes	No	Yes	No
Exclusion Threshold				1.00	11.00	3060.00	1.00	1919.00
WLAN 5.8 G	802.11a	11.00	12.59	No	No	No	No	No
	802.11n(HT20)	11.00	12.59	No	No	No	No	No
	802.11n(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT20)	11.00	12.59	No	No	No	No	No
	802.11ac(HT40)	11.00	12.59	No	No	No	No	No
	802.11ac(HT80)	11.00	12.59	Yes	Yes	No	Yes	No

## Note:

1. Maximum power is the source-based time-average power and represents the maximum RF output power including tune-up tolerance among production units
2. Per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D01, standalone SAR test exclusion threshold is applied; If the distance of the antenna to the user is < 5mm, 5mm is used to determine SAR exclusion threshold
4. Per KDB 447498 D01, for separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive), the threshold Pth (mW) is given by Following:

$$P_{th} (mW) = \begin{cases} ERP_{20cm}(d/20cm)^x & d \leq 20cm \\ ERP_{20cm} & 20cm < d \leq 40cm \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20cm}\sqrt{f}} \right)$$

- a. f(GHz) is the RF channel transmit frequency in GHz
- b. d is the separation distance (cm), The result is rounded to one decimal place for comparison
- c.  $ERP_{20cm}$  are determined by:

$$ERP_{20cm}(mW) = f(x) = \begin{cases} 2040f & 0.3GHz \leq f < 1.5GHz \\ 3060 & 1.5GHz \leq f \leq 6GHz \end{cases}$$

5. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion.8. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate
6. Per KDB 248227 D01 SAR is not required for the following 2.4 GHz OFDM conditions.
  - a. When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
  - b. When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.
7. Per KDB 248227 D01 SAR is not required for the following U-NII-1 and U-NII-2A bands conditions.
  - a. When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is  $\leq 1.2$  W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
  - b. When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is  $\leq 1.2$  W/kg, SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

# 10 TEST RESULT

## 10.1 Bluetooth

Mode	Antenna	Antenna Vendor	Test Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
<b>Body</b>																
DH5	Aux.	ZhongTian Xun	Tablet	Back Side	0	39	2441	0.16	0.156	10.67	12.00	1.358	76.68	1.304	<b>0.276</b>	1#
				Top Edge	0	39	2441	0.08	0.089	10.67	12.00	1.358	76.68	1.304	0.158	/
		South Star	Tablet	Back Side	0	39	2441	0.07	0.144	10.67	12.00	1.358	76.68	1.304	0.255	/
				Top Edge	0	39	2441	0.04	0.082	10.67	12.00	1.358	76.68	1.304	0.145	/
Note: Refer to ANNEX C for the detailed test data for each test configuration.																

## 10.2 WIFI 2.4GHz

Mode	Antenna	Antenna Vendor	Test Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.		
<b>Body</b>																		
802.11b	Aux.	ZhongTian Xun	Tablet	Back Side	0	6	2437	-0.11	0.992	13.61	14.00	1.094	99.02	1.010	<b>1.096</b>	2#		
					0	1	2412	-0.04	0.700	13.39	14.00	1.151	99.02	1.010	0.814	/		
					0	11	2462	0.16	0.745	13.15	14.00	1.216	99.02	1.010	0.915	/		
				Top Edge	0	6	2437	0.07	0.517	13.61	14.00	1.094	99.02	1.010	0.571	/		
		South Star	Tablet	Back Side	0	6	2437	0.04	0.789	13.61	14.00	1.094	99.02	1.010	0.872	/		
					0	1	2412	0.11	0.692	13.39	14.00	1.151	99.02	1.010	0.804	/		
					0	11	2462	0.18	0.658	13.15	14.00	1.216	99.02	1.010	0.808	/		
				Top Edge	0	6	2437	-0.03	0.335	13.61	14.00	1.094	99.02	1.010	0.370	/		
				ZhongTian Xun	Tablet	Back Side	0	1	2412	0.01	0.538	13.90	14.00	1.023	99.02	1.010	<b>0.556</b>	3#
						Top Edge	0	1	2412	0.08	0.442	13.90	14.00	1.023	99.02	1.010	0.457	/
Left Edge	0	1	2412			0.09	0.039	13.90	15.00	1.288	99.02	1.010	0.051	/				
South Star	Tablet	Back Side	0	1	2412	0.02	0.514	13.90	14.00	1.023	99.02	1.010	0.531	/				
		Top Edge	0	1	2412	-0.15	0.471	13.90	14.00	1.023	99.02	1.010	0.487	/				
		Left Edge	0	1	2412	0.11	0.044	13.90	14.00	1.023	99.02	1.010	0.045	/				
Note: Refer to ANNEX C for the detailed test data for each test configuration.																		



### 10.3 WIFI 5GHz

Fre. Band	Mode	Antenna	Antenna Vendor	Test Mode	Position	Dist. (mm)	Ch.	Freq. (MHz)	Power Drift (dB)	1g Meas SAR (W/kg)	Meas. Power (dBm)	Max. tune-up power (dBm)	Scaling Factor	Duty cycle	Duty Factor	1g Scaled SAR (W/kg)	Meas. No.
<b>Body</b>																	
5.3G	802.11 ac80	Aux.	ZhongTianXun	Tablet	Back Side	0	58	5290	-0.10	0.197	10.87	11.00	1.030	92.98	1.076	0.218	/
					Top Edge	0	58	5290	0.17	0.129	10.87	11.00	1.030	92.98	1.076	0.143	/
			South Star	Tablet	Back Side	0	58	5290	-0.07	0.374	10.87	11.00	1.030	92.98	1.076	<b>0.414</b>	<b>4#</b>
					Top Edge	0	58	5290	-0.13	0.353	10.87	11.00	1.030	92.98	1.076	0.391	/
5.3G	802.11 ac80	Main	ZhongTianXun	Tablet	Back Side	0	58	5290	-0.04	0.300	10.54	11.00	1.112	92.98	1.076	0.359	/
					Top Edge	0	58	5290	0.11	0.444	10.54	11.00	1.112	92.98	1.076	<b>0.531</b>	<b>5#</b>
					Left Edge	0	58	5290	-0.03	0.024	10.54	11.00	1.112	92.98	1.076	0.029	/
			South Star	Tablet	Back Side	0	58	5290	0.07	0.430	10.54	11.00	1.112	92.98	1.076	0.514	/
					Top Edge	0	58	5290	0.16	0.301	10.54	11.00	1.112	92.98	1.076	0.360	/
					Left Edge	0	58	5290	0.14	0.030	10.54	11.00	1.112	92.98	1.076	0.036	/
5.6G	802.11 ac80	Aux.	ZhongTianXun	Tablet	Back Side	0	138	5690	0.04	0.328	10.94	11.00	1.014	92.98	1.076	0.358	/
					Top Edge	0	138	5690	-0.12	0.313	10.94	11.00	1.014	92.98	1.076	0.341	/
			South Star	Tablet	Back Side	0	138	5690	-0.10	0.390	10.94	11.00	1.014	92.98	1.076	<b>0.425</b>	<b>6#</b>
					Top Edge	0	138	5690	-0.09	0.305	10.94	11.00	1.014	92.98	1.076	0.333	/
5.6G	802.11 ac80	Main	ZhongTianXun	Tablet	Back Side	0	106	5530	-0.13	0.208	10.65	11.00	1.084	92.98	1.076	0.242	/
					Top Edge	0	106	5530	-0.05	0.244	10.65	11.00	1.084	92.98	1.076	<b>0.284</b>	<b>7#</b>
					Left Edge	0	106	5530	0.02	0.022	10.05	11.00	1.245	92.98	1.076	0.029	/
			South Star	Tablet	Back Side	0	106	5530	0.09	0.238	10.65	11.00	1.084	92.98	1.076	0.277	/
					Top Edge	0	106	5530	0.07	0.229	10.65	11.00	1.084	92.98	1.076	0.267	/
					Left Edge	0	106	5530	0.00	0.018	10.05	11.00	1.245	92.98	1.076	0.024	/
5.8G	802.11 ac80	Aux.	ZhongTianXun	Tablet	Back Side	0	155	5775	0.12	0.597	10.83	11.00	1.040	92.98	1.076	0.668	/
					Top Edge	0	155	5775	0.01	0.522	10.83	11.00	1.040	92.98	1.076	0.584	/
			South Star	Tablet	Back Side	0	155	5775	0.02	1.010	10.83	11.00	1.040	92.98	1.076	<b>1.130</b>	<b>8#</b>
					Top Edge	0	155	5775	0.12	0.673	10.83	11.00	1.040	92.98	1.076	0.753	/
5.8G	802.11 ac80	Main	ZhongTianXun	Tablet	Back Side	0	155	5775	-0.02	0.208	10.83	11.00	1.040	92.98	1.076	0.233	/
					Top Edge	0	155	5775	-0.07	0.292	10.83	11.00	1.040	92.98	1.076	<b>0.327</b>	<b>9#</b>
					Left Edge	0	155	5775	0.17	0.025	10.83	11.00	1.040	92.98	1.076	0.028	/
			South Star	Tablet	Back Side	0	155	5775	-0.04	0.250	10.83	11.00	1.040	92.98	1.076	0.280	/
					Top Edge	0	155	5775	-0.18	0.202	10.83	11.00	1.040	92.98	1.076	0.226	/
					Left Edge	0	155	5775	0.15	0.023	10.83	11.00	1.040	92.98	1.076	0.026	/

Note: Refer to ANNEX C for the detailed test data for each test configuration.

## 11 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are  $\leq 1.45$  W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is  $\leq 1.10$ , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is  $< 0.80$  W/kg, repeated measurement is not required.
2. When the highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$ , or when the original or repeated measurement is  $\geq 1.45$  W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ , and the original, first or second repeated measurement is  $\geq 1.5$  W/kg, perform a third repeated measurement.

Frequency Band (MHz)	Wireless Band	Antenna	RF Exposure Conditions	Test Position	Highest Measured SAR (W/kg)	Repeated SAR (Yes/No)	Highest Measured SAR (W/kg)	Largest to Smallest SAR Ratio
2437	802.11 b	Aux.	Body	Bottom Side	0.992	Yes	0.931	1.07
5775	802.11ac (VHT80)	Aux.	Body	Bottom Side	1.010	Yes	0.984	1.03

Note: The ratio of largest to smallest SAR for the original and first repeated measurements is  $< 1.20$ , the second repeated measurement is not required.

## 12 SIMULTANEOUS TRANSMISSION

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR 1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR 1g 1.6 W/kg), SAR test exclusion is determined by the SAR to Peak Location Ratio (SPLSR).

According KDB 447498 D01v06, simultaneous transmission:

- a)  $SPLSR = (SAR1 + SAR2)^{1.5} / R_i$  (min. separation distance, mm), and the peak separation distance is determined from the square root of  $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$ , where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.  
 SAR1 is the highest reported or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.  
 SAR2 is the highest reported or estimated SAR for the second of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition as the first.
- b) If  $SPLSR \leq 0.04$ , simultaneously transmission SAR measurement is not necessary.
- c) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

### 12.1 Simultaneous Transmission Mode Considerations

NO.	Mode	Body
1	2.4 G WLAN (Main Antenna)	+ 2.4 G WLAN (Auxiliary Antenna)
2	2.4 G WLAN (Main Antenna)	+ Bluetooth (Auxiliary Antenna)
3	5 G WLAN (Main Antenna)	+ 5 G WLAN (Auxiliary Antenna)
4	5 G WLAN (Main Antenna)	+ Bluetooth (Auxiliary Antenna)
5	5 G WLAN (Main Antenna)	+ 5 G WLAN (Auxiliary Antenna) + Bluetooth (Auxiliary Antenna)

Note:

1. The EUT supports the Auxiliary antenna with TX/RX diversity function for WLAN and Bluetooth, the Main antenna with TX/RX diversity function for WLAN.
2. WLAN 2.4GHz and Bluetooth will not be transmitting from the Auxiliary antenna at same time.

## 12.2 Sum SAR of Simultaneous Transmission


### 12.2.1 Highest Bluetooth and WLAN Sum Body SAR of Simultaneous Transmission

Test Mode	Position	Mode	Max. 1g SAR (W/kg)	1g Sum SAR (W/kg)	SPLSR (Yes/No)	SPLSR Num.		
Body (Separation 0 mm)								
Tablet	Back Side	2.4 G WLAN (Main Antenna)	0.556	1.652	Yes	1#		
		2.4 G WLAN (Auxiliary Antenna)	1.096					
		2.4 G WLAN (Main Antenna)	0.556	0.832	No	/		
		Bluetooth (Auxiliary Antenna)	0.276					
		5.3G WLAN (Main Antenna)	0.514	0.928	No	/		
		5.3G WLAN (Auxiliary Antenna)	0.414					
		5.6G WLAN (Main Antenna)	0.277	0.702	No	/		
		5.6G WLAN (Auxiliary Antenna)	0.425					
		5.8G WLAN (Main Antenna)	0.280	1.410	No	/		
		5.8G WLAN (Auxiliary Antenna)	1.130					
		5.3G WLAN (Main Antenna)	0.514	0.790	No	/		
		Bluetooth (Auxiliary Antenna)	0.276					
		5.6G WLAN (Main Antenna)	0.277	0.553	No	/		
		Bluetooth (Auxiliary Antenna)	0.276					
		5.8G WLAN (Main Antenna)	0.280	0.556	No	/		
		Bluetooth (Auxiliary Antenna)	0.276					
		5.3G WLAN (Main Antenna)	0.514	1.204	No	/		
		5.3G WLAN (Auxiliary Antenna)	0.414					
		Bluetooth (Auxiliary Antenna)	0.276	0.978	No	/		
		5.6G WLAN (Main Antenna)	0.277					
		5.6G WLAN (Auxiliary Antenna)	0.425	0.922	No	/		
		Bluetooth (Auxiliary Antenna)	0.276					
		5.8G WLAN (Main Antenna)	0.280	1.686	Yes	2#		
		5.8G WLAN (Auxiliary Antenna)	1.130					
	Bluetooth (Auxiliary Antenna)	0.276	1.058	No	/			
	2.4 G WLAN (Main Antenna)	0.487						
	2.4 G WLAN (Auxiliary Antenna)	0.571						
	2.4 G WLAN (Main Antenna)	0.487				0.645	No	/
	Bluetooth (Auxiliary Antenna)	0.158						
	5.3G WLAN (Main Antenna)	0.531				0.922	No	/
	5.3G WLAN (Auxiliary Antenna)	0.391						
	5.6G WLAN (Main Antenna)	0.284				0.625	No	/
5.6G WLAN (Auxiliary Antenna)	0.341							
5.8G WLAN (Main Antenna)	0.327	1.080				No	/	
5.8G WLAN (Auxiliary Antenna)	0.753							
5.3G WLAN (Main Antenna)	0.531	0.689				No	/	
Top Edge								

		Bluetooth (Auxiliary Antenna)	0.158			
		5.6G WLAN (Main Antenna)	0.284	0.442	No	/
		Bluetooth (Auxiliary Antenna)	0.158			
		5.8G WLAN (Main Antenna)	0.327	0.485	No	/
		Bluetooth (Auxiliary Antenna)	0.158			
		5.3G WLAN (Main Antenna)	0.531	1.080	No	/
		5.3G WLAN (Auxiliary Antenna)	0.391			
		Bluetooth (Auxiliary Antenna)	0.158			
		5.6G WLAN (Main Antenna)	0.284	0.783	No	/
		5.6G WLAN (Auxiliary Antenna)	0.341			
		Bluetooth (Auxiliary Antenna)	0.158			
		5.8G WLAN (Main Antenna)	0.327	1.238	No	/
		5.8G WLAN (Auxiliary Antenna)	0.753			
		Bluetooth (Auxiliary Antenna)	0.158			
	Left Edge	2.4 G WLAN (Main Antenna)	0.051	0.051	No	/
		2.4 G WLAN (Auxiliary Antenna)	0.000			
		2.4 G WLAN (Main Antenna)	0.051	0.051	No	/
		Bluetooth (Auxiliary Antenna)	0.000			
		5.3G WLAN (Main Antenna)	0.036	0.036	No	/
		5.3G WLAN (Auxiliary Antenna)	0.000			
		5.6G WLAN (Main Antenna)	0.029	0.029	No	/
		5.6G WLAN (Auxiliary Antenna)	0.000			
		5.8G WLAN (Main Antenna)	0.028	0.028	No	/
		5.8G WLAN (Auxiliary Antenna)	0.000			
		5.3G WLAN (Main Antenna)	0.036	0.036	No	/
		Bluetooth (Auxiliary Antenna)	0.000			
		5.6G WLAN (Main Antenna)	0.029	0.029	No	/
		Bluetooth (Auxiliary Antenna)	0.000			
		5.8G WLAN (Main Antenna)	0.028	0.028	No	/
		Bluetooth (Auxiliary Antenna)	0.000			
		5.3G WLAN (Main Antenna)	0.036	0.036	No	/
		5.3G WLAN (Auxiliary Antenna)	0.000			
		Bluetooth (Auxiliary Antenna)	0.000			
		5.6G WLAN (Main Antenna)	0.029	0.029	No	/
		5.6G WLAN (Auxiliary Antenna)	0.000			
		Bluetooth (Auxiliary Antenna)	0.000			
		5.8G WLAN (Main Antenna)	0.028	0.028	No	/
		5.8G WLAN (Auxiliary Antenna)	0.000			
	Bluetooth (Auxiliary Antenna)	0.000				


**SPLSR Analysis 1#**

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Tablet	Back Side	2.4 G WLAN (Auxiliary Antenna)	1.096	-0.0238	-0.0832	-0.205	165.7	1.65	0.01	No
		2.4 G WLAN (Main Antenna)	0.556	-0.0300	0.0800	-0.177				



**SPLSR Analysis 2#**

Test Mode	Position	Antenna	Reported 1g Max. SAR (W/kg)	Coordinates (m)			1g Sum SAR (W/kg)	3D Distance (mm)	SPLSR	Simultaneous SAR Test (Yes/No)
				X	Y	Z				
Tablet	Back Side	5.8 G WLAN (Auxiliary Antenna) + Bluetooth (Auxiliary Antenna)	1.406	-0.020	-0.084	-0.205	149.1	1.69	0.01	No
		5.8 G WLAN (Main Antenna)	0.280	-0.024	0.065	-0.205				



## 13 TEST EQUIPMENTS LIST

Description	Manufacturer	Model	Serial No./Version	Cal. Date	Cal. Due
PC	Dell	N/A	N/A	N/A	N/A
Test Software	Speag	DASY5	52.8.8.1222	N/A	N/A
2450MHz Validation Dipole	Speag	D2450V2	SN: 952	2021/05/19	2024/05/18
5GHz Validation Dipole	Speag	D5GHzV2	SN: 1200	2021/05/18	2024/05/17
E-Field Probe	Speag	EX3DV4	SN: 7663	2021/07/23	2022/07/22
Data Acquisition Electronics	Speag	DAE4	SN: 878	2021/07/15	2022/07/14
Signal Generator	R&S	SMB100A	177746	2021/08/24	2022/08/23
Power Meter	R&S	NRVD-B2	7250BJ-0112/2011	2021/09/08	2022/09/07
Power Sensor	R&S	NRV-Z4	100381	2021/09/08	2022/09/07
Power Sensor	R&S	NRV-Z2	100211	2021/09/08	2022/09/07
Network Analyzer	Agilent	E5071B	MY42404001	2021/04/01	2022/03/31
Thermometer	Elitech	RC-4HC	EF720B004820	2021/12/01	2022/11/30
Power Amplifier	SATIMO	6552B	22374	N/A	N/A
Dielectric Probe Kit	SATIMO	SCLMP	SN 25/13 OCPG56	N/A	N/A
Phantom1	Speag	SAM	SN: 1857	N/A	N/A
Phantom2	Speag	ELI4	SN: 1012	N/A	N/A
Attenuator	COM-MW	ZA-S1-31	1305003187	N/A	N/A
Directional coupler	AA-MCS	AAMCS-UDC	000272	N/A	N/A

Note: For dipole antennas, BALUN has adopted 3 years as calibration intervals, and on annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole;
2. System validation with specific dipole is within 10% of calibrated value;
3. Return-loss in within 20% of calibrated measurement.
4. Impedance (real or imaginary parts) in within 5 Ohms of calibrated measurement.

## ANNEX A SIMULATING LIQUID VERIFICATION RESULT

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SCLMP Dielectric Probe Kit.

Date	Liquid Type	Fre. (MHz)	Temp. (°C)	Meas. Conductivity ( $\sigma$ ) (S/m)	Meas. Permittivity ( $\epsilon$ )	Target Conductivity ( $\sigma$ ) (S/m)	Target Permittivity ( $\epsilon$ )	Conductivity Tolerance (%)	Permittivity Tolerance (%)
2022.01.05	Head	2450	21.6	1.84	39.28	1.80	39.20	2.22	0.20
2022.01.07	Head	2450	21.8	1.77	39.18	1.80	39.20	-1.67	-0.05
2022.01.10	Head	5250	21.7	4.68	36.12	4.71	35.93	-0.64	0.53
2022.01.11	Head	5600	21.4	4.939	35.32	5.07	35.53	-2.58	-0.59
2022.01.12	Head	5750	21.5	5.12	35.33	5.22	35.36	-1.92	-0.08

Note: The tolerance limit of Conductivity and Permittivity is  $\pm 5\%$ .



## ANNEX B SYSTEM CHECK RESULT

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 % (for 1 g).

Date	Liquid Type	Freq. (MHz)	Power (mW)	Measured SAR (W/kg)	Normalized SAR (W/kg)	Dipole SAR (W/kg)	Tolerance (%)
2022.01.05	Head	2450	100	5.140	51.40	52.60	-2.28
2022.01.07	Head	2450	100	5.330	53.30	52.60	1.33
2022.01.10	Head	5250	100	7.970	79.70	77.80	2.44
2022.01.11	Head	5600	100	8.040	80.40	81.20	-0.99
2022.01.12	Head	5750	100	7.930	79.30	77.20	2.72

Note: The tolerance limit of System validation  $\pm 10\%$ .

# System Performance Check Data (2450MHz)

Date: 2022.01.05

Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.836$  S/m;  $\epsilon_r = 39.284$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.7 Liquid Temperature: 21.6

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(8.19, 8.19, 8.19); Calibrated: 2021.07.23;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**CW 2450/Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 6.04 W/kg


**CW 2450/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.12 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 10.3 W/kg

**SAR(1 g) = 5.14 W/kg; SAR(10 g) = 2.44 W/kg**

Maximum value of SAR (measured) = 6.40 W/kg



0 dB = 6.40 W/kg

# System Performance Check Data (2450MHz)

Date: 2022.01.07

Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.765$  S/m;  $\epsilon_r = 39.182$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.4 Liquid Temperature: 21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(8.19, 8.19, 8.19); Calibrated: 2021.07.23;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**CW2450/Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 5.95 W/kg


**CW2450/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 52.73 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 12.1 W/kg

**SAR(1 g) = 5.33 W/kg; SAR(10 g) = 2.43 W/kg**

Maximum value of SAR (measured) = 6.52 W/kg



0 dB = 6.52 W/kg

# System Performance Check Data (5250MHz)

Date: 2022.01.10

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5250 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.678$  S/m;  $\epsilon_r = 36.121$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.3 Liquid Temperature: 21.7

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.72, 5.72, 5.72); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**CW5250/Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 9.82 W/kg


**CW5250/Zoom Scan (7x7x21)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 55.57 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 33.8 W/kg

**SAR(1 g) = 7.97 W/kg; SAR(10 g) = 2.24 W/kg**

Maximum value of SAR (measured) = 13.9 W/kg



0 dB = 13.9 W/kg

# System Performance Check Data (5600MHz)

Date: 2022.01.11

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5600 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5600$  MHz;  $\sigma = 4.939$  S/m;  $\epsilon_r = 35.318$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.9 Liquid Temperature: 21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.1, 5.1, 5.1); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**CW5600/Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 9.04 W/kg


**CW5600/Zoom Scan (7x7x21)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 36.47 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 32.1 W/kg

**SAR(1 g) = 8.04 W/kg; SAR(10 g) = 2.18 W/kg**

Maximum value of SAR (measured) = 15.0 W/kg



0 dB = 15.0 W/kg

# System Performance Check Data (5750MHz)

Date: 2022.01.12

Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5750 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.12$  S/m;  $\epsilon_r = 35.325$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.5 Liquid Temperature: 21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.15, 5.15, 5.15); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**CW5750/Area Scan (101x101x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 8.77 W/kg


**CW5750/Zoom Scan (7x7x13)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 42.87 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 32.9 W/kg

**SAR(1 g) = 7.93 W/kg; SAR(10 g) = 2.09 W/kg**

Maximum value of SAR (measured) = 15.9 W/kg



0 dB = 15.9 W/kg

## ANNEX C TEST DATA

### Meas.1 Body Plane with Back Side 0mm on Channel 39 in Bluetooth with Antenna Auxiliary

Date: 2022.01.05

Communication System Band: Bluetooth; Frequency: 2441 MHz; Duty Cycle: 1:1.304

Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 1.826$  S/m;  $\epsilon_r = 39.481$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.7 Liquid Temperature: 21.6

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(8.19, 8.19, 8.19); Calibrated: 2021.07.23
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CD; Serial: TP1857
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.10(7331)

**Ch39/Area Scan (61x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.318 W/kg


**Ch39/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 0.7740 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 0.373 W/kg

**SAR(1 g) = 0.156 W/kg; SAR(10 g) = 0.070 W/kg**

Maximum value of SAR (measured) = 0.175 W/kg



0 dB = 0.175 W/kg

**Meas.2 Body Plane with Back Side 0mm on Channel 6 in IEEE802.11b with Antenna Auxiliary**

Date: 2022.01.07

Communication System Band: WLAN(b); Frequency: 2437 MHz; Duty Cycle: 1:1.01

Medium parameters used (interpolated):  $f = 2437$  MHz;  $\sigma = 1.747$  S/m;  $\epsilon_r = 39.657$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.4 Liquid Temperature:21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(8.19, 8.19, 8.19); Calibrated: 2021.07.23;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch6/Area Scan (61x61x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.61 W/kg


**Ch6/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.88 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 2.49 W/kg

**SAR(1 g) = 0.992 W/kg; SAR(10 g) = 0.431 W/kg**

Maximum value of SAR (measured) = 0.722 W/kg



0 dB = 0.722 W/kg



**Meas.3 Body Plane with Back Side 0mm on Channel 1 in IEEE802.11b mode with Antenna Main**

Date: 2022.01.07

Communication System Band: WLAN(b); Frequency: 2412 MHz; Duty Cycle: 1:1.01

Medium parameters used (interpolated):  $f = 2412$  MHz;  $\sigma = 1.719$  S/m;  $\epsilon_r = 39.936$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.4 Liquid Temperature:21.8

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(8.19, 8.19, 8.19); Calibrated: 2021.07.23;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch1/Area Scan (61x171x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.805 W/kg


**Ch1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.874 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.19 W/kg

**SAR(1 g) = 0.538 W/kg; SAR(10 g) = 0.242 W/kg**

Maximum value of SAR (measured) = 0.615 W/kg



0 dB = 0.615 W/kg

**Meas.4 Body Plane with Back Side 0mm on Channel 58 in IEEE802.11 ac(VHT80) with Antenna Auxiliary**

Date: 2022.01.10

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5290 MHz;Duty Cycle: 1:1.076

Medium parameters used (interpolated):  $f = 5290$  MHz;  $\sigma = 4.734$  S/m;  $\epsilon_r = 35.904$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.3 Liquid Temperature:21.7

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.61, 5.61, 5.61); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch58/Area Scan (81x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.873 W/kg


**Ch58/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 8.749 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 1.32 W/kg

**SAR(1 g) = 0.374 W/kg; SAR(10 g) = 0.105 W/kg**

Maximum value of SAR (measured) = 0.296 W/kg



**Meas.5 Body Plane with Top Edge 0mm on Channel 58 in IEEE802.11 ac(VHT80) mode with Antenna Main**

Date: 2022.01.10

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5290 MHz;Duty Cycle: 1:1.076

Medium parameters used (interpolated): f = 5290 MHz;  $\sigma$  = 4.734 S/m;  $\epsilon_r$  = 35.904;  $\rho$  = 1000 kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.3 Liquid Temperature:21.7

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.61, 5.61, 5.61); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch58/Area Scan (71x211x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.06 W/kg


**Ch58/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 1.700 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 1.64 W/kg

**SAR(1 g) = 0.444 W/kg; SAR(10 g) = 0.128 W/kg**

Maximum value of SAR (measured) = 0.565 W/kg



0 dB = 0.565 W/kg

**Meas.6 Body Plane with Back Side 0mm on Channel 138 in IEEE802.11 ac(VHT80) with Antenna Auxiliary**

Date: 2022.01.11

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5690 MHz;Duty Cycle: 1:1.076

Medium parameters used (interpolated):  $f = 5690$  MHz;  $\sigma = 5.06$  S/m;  $\epsilon_r = 34.403$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.9 Liquid Temperature:21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.1, 5.1, 5.1); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch138/Area Scan (81x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.09 W/kg


**Ch138/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 8.705 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 1.47 W/kg

**SAR(1 g) = 0.390 W/kg; SAR(10 g) = 0.114 W/kg**

Maximum value of SAR (measured) = 0.310 W/kg



0 dB = 0.310 W/kg

**Meas.7 Body Plane with Top Edge 0mm on Channel 106 in IEEE802.11 ac(VHT80) mode with Antenna Main**

Date: 2022.01.11

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5530 MHz;Duty Cycle: 1:1.076

Medium parameters used (interpolated):  $f = 5530$  MHz;  $\sigma = 4.849$  S/m;  $\epsilon_r = 36.002$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.9 Liquid Temperature:21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.3, 5.3, 5.3); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch106/Area Scan (71x211x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 0.673 W/kg


**Ch106/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.980 W/kg

**SAR(1 g) = 0.244 W/kg; SAR(10 g) = 0.063 W/kg**

Maximum value of SAR (measured) = 0.313 W/kg



0 dB = 0.313 W/kg

**Meas.8 Body Plane with Back Side 0mm on Channel 155 in IEEE802.11 ac(VHT80) with Antenna Auxiliary**

Date: 2022.01.12

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5775 MHz;Duty Cycle: 1:1.076

Medium parameters used (interpolated):  $f = 5775$  MHz;  $\sigma = 5.15$  S/m;  $\epsilon_r = 35.184$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.5 Liquid Temperature:21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.15, 5.15, 5.15); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch155/Area Scan (81x81x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 2.01 W/kg


**Ch155/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 11.59 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 4.20 W/kg

**SAR(1 g) = 1.01 W/kg; SAR(10 g) = 0.289 W/kg**

Maximum value of SAR (measured) = 0.749 W/kg



0 dB = 0.749 W/kg

**Meas.9 Body Plane with Top Side 0mm on Channel 155 in IEEE802.11ac(VHT80) mode with Antenna Main**

Date: 2022.01.12

Communication System Band: WLAN(ac) 80Mhz; Frequency: 5775 MHz;Duty Cycle: 1:1.076

Medium parameters used (interpolated):  $f = 5775$  MHz;  $\sigma = 5.213$  S/m;  $\epsilon_r = 33.952$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature:22.5 Liquid Temperature:21.5

DASY5 Configuration:

- Probe: EX3DV4 - SN7663; ConvF(5.15, 5.15, 5.15); Calibrated: 2021.07.23;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn878; Calibrated: 2021.07.15
- Phantom: SAM (20deg probe tilt) with CRP v5.0 Right 1857; Type: QD000P40CC; Serial: TP1857
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Ch58/Area Scan (81x211x1):** Interpolated grid: dx=1.000 mm, dy=1.000 mm

Maximum value of SAR (interpolated) = 1.00 W/kg


**Ch58/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 0 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.94 W/kg

**SAR(1 g) = 0.292 W/kg; SAR(10 g) = 0.073 W/kg**

Maximum value of SAR (measured) = 0.285 W/kg



## **ANNEX D SAR TEST SETUP PHOTOS**

Please refer the document "BL-SZ21C0792-AS.PDF".

## **ANNEX E CALIBRATION REPORT**

Please refer the document "CALIBRATION REPORT.pdf".

--END OF REPORT--