

FCC Test Report

(PART 27)

Report No.: RF160520W001-6

FCC ID: O57PB2650Y

Test Model: Lenovo PB2-650Y

Received Date: May 20, 2016

Test Date: May 21, 2016 ~ Jun. 13, 2016

Issued Date: Jun. 14, 2016

Applicant: Lenovo(Shanghai) Electronics Technology Co., Ltd.

Address: NO.68 BUILDING, 199 FENJU RD, China (Shanghai) Pilot
Free Trade Zone, 200131, CHINA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd.,
Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Cau Vil., Lin Kou Dist., New Taipei
City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang,
Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim
product certification, approval, or endorsement by
TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agency

TABLE OF CONTENTS

1	Certificate of Conformity.....	4
2	Summary of Test Results	5
2.1	Measurement Uncertainty	5
2.2	Test Site And Instruments	6
3	General Information.....	7
3.1	General Description of EUT	7
3.2	Configuration of System Under Test	9
3.2.1	Description Of Support Units.....	9
3.3	Test Mode Applicability and Tested Channel Detail	10
3.4	EUT Operating Conditions	11
3.5	General Description of Applied Standards	11
4	Test Types and Results	12
4.1	Output Power Measurement	12
4.1.1	Limits of Output Power Measurement	12
4.1.2	Test Procedures.....	12
4.1.3	Test Setup.....	13
4.1.4	Test Results	14
4.2	Frequency Stability Measurement.....	19
4.2.1	Limits of Frequency Stability Measurement.....	19
4.2.2	Test Procedure	19
4.2.3	Test Setup.....	19
4.2.4	Test Results	20
4.3	Occupied Bandwidth Measurement	21
4.3.1	Limits Of Occupied Bandwidth Measurement	21
4.3.2	Test Setup.....	21
4.3.3	Test Procedures.....	21
4.3.4	Test Result.....	22
4.4	Peak To Average Ratio	24
4.4.1	Limits of Peak To Average Ratio Measurement	24
4.4.2	Test Setup.....	24
4.4.3	Test Procedures.....	24
4.4.4	Test Results	25
4.5	Band Edge Measurement	27
4.5.1	Limits of Band Edge Measurement	27
4.5.2	Test Setup.....	27
4.5.3	Test Procedures.....	27
4.5.4	Test Results	28
4.6	Conducted Spurious Emissions	32
4.6.1	Limits of Conducted Spurious Emissions Measurement.....	32
4.6.2	Test Procedure	32
4.6.3	Test Setup.....	32
4.6.4	Test Results	33
4.7	Radiated Emission Measurement	34
4.7.1	Limits of Radiated Emission Measurement.....	34
4.7.2	Test Procedure	34
4.7.3	Deviation from Test Standard	34
4.7.4	Test Setup.....	35
4.7.5	Test Results	36
5	Pictures of Test Arrangements.....	46
	Appendix – Information on the Testing Laboratories	47



A D T

RELEASE CONTROL RECORD

Issue No.	Description	Date Issued
RF160520W001-6	Original release	Jun. 14, 2016

1 Certificate of Conformity

Product: Lenovo Mobile Phone

Brand: Lenovo

Test Model: Lenovo PB2-650Y

Sample Status: Identical Prototype

Applicant: Lenovo(Shanghai) Electronics Technology Co., Ltd.

Test Date: May 21, 2016 ~ Jun. 13, 2016

Standards: FCC Part 27, Subpart C, M

FCC Part 2

ANSI /TIA/EIA-603-D

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :



Date:

Jun. 14, 2016

Amyee Qian / Engineer

Approved by :



Date:

Jun. 14, 2016

William Chung / Manager

2 Summary of Test Results

Applied Standard: FCC Part 27 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 27.50(h)(2)	Equivalent Isotropically radiated power	PASS	Meet the requirement of limit.
2.1055 27.54	Frequency Stability Stay with the authorized bands of operation	PASS	Meet the requirement of limit.
2.1049 27.53(m)(6)	Occupied Bandwidth	PASS	Meet the requirement of limit.
27.50(d)(5)	Peak to average ratio	PASS	Meet the requirement of limit.
2.1051 27.53(m)(4)(6)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 27.53(m)(4)(6)	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 27.53(m)(4)(6)	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -6.50dB at 46.49MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	2.93 dB
	200MHz ~1000MHz	2.95 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.2 Test Site And Instruments

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Apr. 05,16	Apr. 04,17
Bilog Antenna 1	Teseq	CBL 6111D	30643	Jun. 25,15	Jun. 24,16
Bilog Antenna 2	Teseq	CBL 6111D	27089	Jun. 25,15	Jun. 24,16
Horn Antenna	ETS-Lindgren	3117	00062558	May 30,14	May 29,17
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Jan. 21,14	Jan. 20,17
Amplifier	Burgeon	BPA-530	100220	Apr. 05,16	Apr. 04,17
Pre-Amplifier	HP	8449B	3008A00409	Apr. 24,16	Apr. 23,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 11,15	Nov. 10,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 16
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Power Meter	Anritsu	ML2495A	1139001	Feb.19,16	Feb. 18,17
Power Sensor	Anritsu	MA2411B	1126068	Feb.19,16	Feb. 18,17
Power Sensor	Keysight	U2021XA	MY55060016	May 27,15	May 26,17
Power Sensor	Keysight	U2021XA	MY55060018	May 27,15	May 26,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct. 11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 09,15	Nov. 08,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Apr. 21, 16	Apr. 20, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Sep. 01,15	Aug. 31,16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Oct. 12, 15	Oct. 11, 16

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

3. The test was performed in HwaYa Chamber 4.

4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

5. The FCC Site Registration No. is 460141.

6. The IC Site Registration No. is IC7450F-4.

3 General Information

3.1 General Description of EUT

PRODUCT	Lenovo Mobile Phone	
BRAND	Lenovo	
MODEL NAME	Lenovo PB2-650Y	
POWER SUPPLY	5.2Vdc (adapter or host equipment) 3.8Vdc (battery)	
MODULATION TECHNOLOGY	LTE Band 7	QPSK, 16QAM
FREQUENCY RANGE	LTE Band 7 Channel Bandwidth: 5MHz	2502.5MHz ~ 2567.5MHz
	LTE Band 7 Channel Bandwidth: 10MHz	2505MHz ~ 2565MHz
	LTE Band 7 Channel Bandwidth: 15MHz	2507.5MHz ~ 2562.5MHz
	LTE Band 7 Channel Bandwidth: 20MHz	2510MHz ~ 2560MHz
EMISSION DESIGNATOR	LTE Band 7 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M48W7D
	LTE Band 7 Channel Bandwidth: 10MHz	QPSK: 8M93G7D
		16QAM: 8M93W7D
	LTE Band 7 Channel Bandwidth: 15MHz	QPSK: 13M4G7D
		16QAM: 13M4W7D
MAX. EIRP POWER	LTE Band 7 Channel Bandwidth: 5MHz	144mW
		146mW
	LTE Band 7 Channel Bandwidth: 10MHz	144mW
		130mW
ANTENNA TYPE	Fixed Internal antenna with 1.12dBi gain	
HW VERSION	LenovoPad PB2-650Y	
SW VERSION	PB2-650Y_160517	
ACCESSORY DEVICE	Refer to note as below	
DATA CABLE	USB cable: non-shielded, detachable, 1.0m	

Note:

- The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
- There were Sample A and Sample B for this project, the difference is as below:

SAMPLE	EUT CONFIGURATION INFORMATION
A	LCD panel +TP1+Front camera 1+back camera 1+eMMC 1/ eMMC 2+speaker 1+receiver 1+vibrator 1+battery 1
B	LCD panel +TP2+Front camera 2+back camera 2+eMMC 3/ eMMC 4+speaker 2+receiver 2+vibrator 2+battery 2


- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

LIST OF ACCESSORIES:


ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
AC Adapter 1	Lenovo	Acbel	C-P35	I/P:100-240Vac, 500mA O/P:5.2Vdc, 2000mA
AC Adapter 2	Lenovo	Huntkey	C-P35	I/P:100-240Vac, 500mA O/P:5.2Vdc, 2000mA
Battery 1	Lenovo	SCUD	L16D1P31	Rating: 3.8Vdc, 4050mAh
Battery 2	Lenovo	SUNWODA	L16D1P32	Rating: 3.8Vdc, 4050mAh
USB Cable 1	LIQI	--	LQ-025254	1.0m non-shielded cable w/o core
USB Cable 2	STARW	--	XJ-007046-1	1.0m non-shielded cable w/o core
LCD Panel+TP1	Tianma	--	TM065JVSP03-00IPS gold MIPI	--
LCD Panel+TP2	GIS	--	TC064GFL01 IPS Black MIPI	--
Front Camera 1	O-Film	--	L5693F20	--
Front Camera 2	Q Technology Limited	--	F5693AQ	--
Back Camera 1	Q Technology Limited	--	F3M2YBX	--
Back Camera 2	Sunny Opotech	--	F13S05Y	--
eMMC 1	SAMSUNG	--	KMRX1000BM-B614	32G
eMMC2	Samsung	--	KMQE10013M-B318	16G
eMMC 3	Hynix	--	H9TQ26ADFTACUR-KUM	32G
eMMC 4	Hynix	--	H9TQ17ABJTACUR-KUM	16G
Speaker 1	Haosheng	--	P9898_SPK_BOX_ASM	--
Speaker 2	Midi	--	P9898_SPK_BOX_ASM_MD	--
receiver 1	Xichun	--	KFR1506G2.8-32-HV	--
receiver 2	Midi	--	MIDRC1506M2.8	--
vibrator 1	Hongzhifa	--	HZF1027A-P02L9	--
vibrator 2	AWA SEIMITSU	--	LC-B68L	--

3.2 Configuration of System Under Test

FOR RADIATION EMISSION TEST



FOR E.R.P./E.I.R.P TEST



3.2.1 Description Of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X-plane. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable with LTE link
B	EUT + Battery + USB Cable with LTE link

LTE BAND 7

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM	1 RB / 0RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	20775 to 21425	21100	5MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	21100	10MHz	QPSK	1 RB / 0RB Offset
		20825 to 21375	21100	15MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	21100	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20MHz	QPSK, 16QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	20775 to 21425	20775, 21100, 21425	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20800 to 21400	20800, 21100, 21400	10MHz	QPSK, 16QAM	1 RB / 0RB Offset
		20825 to 21375	20825, 21100, 21375	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		20850 to 21350	20850, 21100 21350	20MHz	QPSK, 16QAM	1 RB / 0 RB Offset
B	BAND EDGE	20775 to 21425	20775, 21425	5MHz	QPSK	1 RB / 12 RB Offset
						25 RB / 0 RB Offset
		20800 to 21400	20800, 21400	10MHz	QPSK	1 RB / 24 RB Offset
						50 RB / 0 RB Offset
		20825 to 21375	20825, 21375	15MHz	QPSK	1 RB / 37 RB Offset
						75 RB / 0 RB Offset
B	BAND EDGE	20850 to 21350	20850, 21350	20MHz	QPSK	1 RB / 50 RB Offset
						100 RB / 0 RB Offset
B	CONDCUDED EMISSION	20775 to 21425	21100	5MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	21100	10MHz	QPSK	1 RB / 0RB Offset
		20825 to 21375	21100	15MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	21100	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	20775 to 21425	21100	5MHz	QPSK	1 RB / 0 RB Offset
		20800 to 21400	21100	10MHz	QPSK	1 RB / 0RB Offset
		20825 to 21375	21100	15MHz	QPSK	1 RB / 0 RB Offset
		20850 to 21350	21100	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
ERP	21deg. C, 71%RH 22deg. C, 71%RH	DC 3.8V from battery	Yuqiang Yin
Frequency Stability	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Occupied Bandwidth	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Band Edge	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Conducuted Emission	24deg. C, 64%RH	DC 3.8V from battery	Yuqiang Yin
Radiated Emission	21deg. C, 71%RH	5Vdc from adapter	Alex Chen

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB Publication 971168 D02

ANSI/TIA/EIA-603-D

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.r.p.

4.1.2 Test Procedures


EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 10MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$

Conducted Power Measurement:

- a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.
- b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 Test Setup EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

AVERAGE CONDUCTED OUTPUT POWER (dBm)

LTE Band 7							
BW	Modulation	RB Size	RB Offset	Low CH 20775	Mid CH 21100	High CH 21425	MPR
				Frequency 2502.5 MHz	Frequency 2535 MHz	Frequency 2567.5 MHz	
5 MHz	QPSK	1	0	22.56	22.76	22.78	0
		1	12	22.49	22.50	22.52	0
		1	24	22.55	22.43	22.33	0
		12	0	21.73	21.66	21.60	1
		12	6	21.70	21.76	21.74	1
		12	13	21.74	21.84	21.85	1
		25	0	21.76	21.82	21.83	1
	16QAM	1	0	21.84	21.77	21.86	1
		1	12	21.85	21.76	21.83	1
		1	24	21.79	21.75	21.83	1
		12	0	20.72	20.82	20.75	2
		12	6	20.74	20.80	20.86	2
		12	13	20.80	20.85	20.82	2
		25	0	20.77	20.77	20.85	2

LTE Band 7							
BW	Modulation	RB Size	RB Offset	Low CH 20800	Mid CH 21100	High CH 21400	MPR
				Frequency 2505 MHz	Frequency 2535 MHz	Frequency 2565 MHz	
10 MHz	QPSK	1	0	22.60	22.80	22.82	0
		1	24	22.53	22.54	22.56	0
		1	49	22.59	22.47	22.37	0
		25	0	21.77	21.70	21.64	1
		25	12	21.74	21.80	21.78	1
		25	25	21.78	21.88	21.89	1
		50	0	21.80	21.86	21.87	1
	16QAM	1	0	21.88	21.81	21.90	1
		1	24	21.89	21.80	21.87	1
		1	49	21.83	21.79	21.87	1
		25	0	20.76	20.86	20.79	2
		25	12	20.78	20.84	20.90	2
		25	25	20.84	20.89	20.86	2
		50	0	20.81	20.81	20.89	2

BW	Modulation	RB Size	RB Offset	Low CH 20825	Mid CH 21100	High CH 21375	MPR
				Frequency 2507.5 MHz	Frequency 2535 MHz	Frequency 2562.5 MHz	
15 MHz	QPSK	1	0	22.66	22.86	22.88	0
		1	37	22.59	22.60	22.62	0
		1	74	22.65	22.53	22.43	0
		36	0	21.83	21.76	21.70	1
		36	19	21.80	21.86	21.84	1
		36	39	21.84	21.94	21.95	1
		75	0	21.86	21.92	21.93	1
	16QAM	1	0	21.94	21.87	21.96	1
		1	37	21.95	21.86	21.93	1
		1	74	21.89	21.85	21.93	1
		36	0	20.82	20.92	20.85	2
		36	19	20.84	20.90	20.96	2
		36	39	20.90	20.95	20.92	2
		75	0	20.87	20.87	20.95	2

LTE Band 7							
BW	Modulation	RB Size	RB Offset	Low CH 20850	Mid CH 21100	High CH 21350	MPR
				Frequency 2510 MHz	Frequency 2535 MHz	Frequency 2560 MHz	
20 MHz	QPSK	1	0	22.69	22.89	22.91	0
		1	50	22.62	22.63	22.65	0
		1	99	22.68	22.56	22.46	0
		50	0	21.86	21.79	21.73	1
		50	25	21.83	21.89	21.87	1
		50	50	21.87	21.97	21.98	1
		100	0	21.89	21.95	21.96	1
	16QAM	1	0	21.97	21.90	21.99	1
		1	50	21.98	21.89	21.96	1
		1	99	21.92	21.88	21.96	1
		50	0	20.85	20.95	20.88	2
		50	25	20.87	20.93	20.99	2
		50	50	20.93	20.98	20.95	2
		100	0	20.90	20.90	20.98	2

EIRP

LTE BAND 7

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20775	2502.5	-24.79	45.65	20.86	121.84	H	2
21100	2535.0	-24.45	46.04	21.59	144.05	H	2
21425	2567.5	-25.08	45.87	20.79	119.84	H	2
20775	2502.5	-26.30	47.03	20.73	118.25	V	2
21100	2535.0	-26.83	46.57	19.74	94.19	V	2
21425	2567.5	-26.97	46.98	20.01	100.23	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20775	2502.5	-25.62	45.65	20.03	100.65	H	2
21100	2535.0	-25.47	46.04	20.57	113.89	H	2
21425	2567.5	-26.18	45.87	19.69	93.03	H	2
20775	2502.5	-27.13	47.03	19.90	97.68	V	2
21100	2535.0	-27.85	46.57	18.72	74.47	V	2
21425	2567.5	-28.07	46.98	18.91	77.80	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20800	2505.0	-24.60	45.65	21.05	127.32	H	2
21100	2535.0	-24.39	46.04	21.65	146.05	H	2
21400	2565.0	-24.95	46.07	21.12	129.27	H	2
20800	2505.0	-26.11	47.18	21.07	127.82	V	2
21100	2535.0	-26.77	46.57	19.80	95.50	V	2
21400	2565.0	-26.84	47.06	20.22	105.29	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20800	2505.0	-25.75	45.65	19.90	97.70	H	2
21100	2535.0	-25.49	46.04	20.55	113.37	H	2
21400	2565.0	-26.11	46.07	19.96	98.97	H	2
20800	2505.0	-27.26	47.18	19.92	98.08	V	2
21100	2535.0	-27.87	46.57	18.70	74.13	V	2
21400	2565.0	-28.00	47.06	19.06	80.61	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20825	2507.5	-24.61	45.63	21.02	126.56	H	2
21100	2535.0	-24.46	46.04	21.58	143.71	H	2
21375	2562.5	-25.02	45.94	20.92	123.54	H	2
20825	2507.5	-26.12	47.39	21.27	133.94	V	2
21100	2535.0	-26.84	46.57	19.73	93.97	V	2
21375	2562.5	-26.91	47.00	20.09	102.07	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20825	2507.5	-25.47	45.63	20.16	103.82	H	2
21100	2535.0	-25.33	46.04	20.71	117.63	H	2
21375	2562.5	-25.87	45.94	20.07	101.58	H	2
20825	2507.5	-26.98	47.39	20.41	109.88	V	2
21100	2535.0	-27.71	46.57	18.86	76.91	V	2
21375	2562.5	-27.76	47.00	19.24	83.93	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20850	2510.0	-25.19	45.80	20.61	115.05	H	2
21100	2535.0	-24.91	46.04	21.13	129.57	H	2
21350	2560.0	-25.60	45.83	20.23	105.51	H	2
20850	2510.0	-26.70	47.21	20.51	112.46	V	2
21100	2535.0	-27.29	46.57	19.28	84.64	V	2
21350	2560.0	-27.49	47.07	19.58	90.76	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	Limit (W)
20850	2510.0	-26.12	45.80	19.68	92.88	H	2
21100	2535.0	-25.98	46.04	20.06	101.27	H	2
21350	2560.0	-26.43	45.83	19.40	87.16	H	2
20850	2510.0	-27.63	47.21	19.58	90.78	V	2
21100	2535.0	-28.36	46.57	18.21	66.16	V	2
21350	2560.0	-28.32	47.07	18.75	74.97	V	2

NOTE: EIRP (dBm) = LVL (dBm) + Correction Factor (dB)

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

FREQUENCY ERROR vs. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)				LIMIT (ppm)
	LTE BAND 7				
	5MHz	10MHz	15MHz	20MHz	
3.8	0.0009	0.0010	0.0012	0.0009	2.5
3.5	-0.0013	-0.0012	-0.0015	-0.0012	2.5
4.4	-0.0011	-0.0011	-0.0013	-0.0012	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.4Vdc.

FREQUENCY ERROR vs. TEMPERATURE


TEMP. (°C)	FREQUENCY ERROR (ppm)				LIMIT (ppm)
	LTE BAND 7				
	5MHz	10MHz	15MHz	20MHz	
-30	-0.0043	-0.0044	-0.0043	-0.0044	2.5
-20	-0.0038	-0.0039	-0.0039	-0.0039	2.5
-10	-0.0033	-0.0034	-0.0034	-0.0033	2.5
0	-0.0029	-0.0028	-0.0030	-0.0028	2.5
+10	-0.0024	-0.0023	-0.0024	-0.0023	2.5
+20	-0.0019	-0.0018	-0.0018	-0.0018	2.5
+30	-0.0014	-0.0013	-0.0013	-0.0013	2.5
+40	-0.0008	-0.0008	-0.0008	-0.0008	2.5
+50	-0.0003	-0.0003	-0.0003	-0.0003	2.5
+60	0.0002	0.0001	0.0002	0.0001	2.5

4.3 Occupied Bandwidth Measurement

4.3.1 Limits Of Occupied Bandwidth Measurement

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.3.2 Test Setup




4.3.3 Test Procedures


- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.4 Test Result

LTE BAND 7							
CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20775	2502.5	4.49	4.47	20800	2505	8.93	8.91
21100	2535	4.48	4.47	21100	2535	8.93	8.93
21425	2567.5	4.48	4.48	21400	2565	8.93	8.93



LTE BAND 7							
CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		QPSK	16QAM			QPSK	16QAM
20825	2507.5	13.44	13.41	20850	2510	17.91	17.86
21100	2535	13.42	13.41	21100	2535	17.90	17.83
21375	2562.5	13.42	13.42	21350	2560	17.91	17.85




4.4 Peak To Average Ratio

4.4.1 Limits of Peak To Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

4.4.2 Test Setup




4.4.3 Test Procedures

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

4.4.4 Test Results

LTE BAND 7


CHANNEL BANDWIDTH: 5MHz				CHANNEL BANDWIDTH: 10MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20775	2502.5	5.44	6.05	20800	2505	5.24	5.88
21100	2535	5.69	6.35	21100	2535	5.63	6.29
21425	2567.5	5.40	6.07	21400	2565	5.27	5.99




CHANNEL BANDWIDTH: 15MHz				CHANNEL BANDWIDTH: 20MHz			
CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)		CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)	
		QPSK	16QAM			QPSK	16QAM
20825	2507.5	5.35	6.03	20850	2510	5.47	6.16
21100	2535	5.68	6.35	21100	2535	5.69	6.38
21375	2562.5	5.45	6.17	21350	2560	5.54	6.26

SPECTRUM PLOT OF WORST VALUE


15MHz / QPSK




15MHz / 16QAM



20MHz / QPSK



20MHz / 16QAM




4.5 Band Edge Measurement

4.5.1 Limits of Band Edge Measurement

According to FCC 27.53(m)(4) specified that For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. For mobile digital stations, in the 1 megahertz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least two percent may be employed.


4.5.2 Test Setup




4.5.3 Test Procedures

- The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).
- The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- The center frequency of spectrum is the band edge frequency and span is 35MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (Channel bandwidth 5MHz).
- The center frequency of spectrum is the band edge frequency and span is 50MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz (Channel bandwidth 10MHz).
- The center frequency of spectrum is the band edge frequency and span is 60MHz. RBW of the spectrum is 300kHz and VBW of the spectrum is 1MHz (Channel bandwidth 15MHz).
- The center frequency of spectrum is the band edge frequency and span is 80MHz. RBW of the spectrum is 500kHz and VBW of the spectrum is 2MHz (Channel bandwidth 20MHz).
- Record the max trace plot into the test report.



4.5.4 Test Results





LTE BAND 7

Channel Bandwidth: 15MHz / QPSK





Note: Limit has been adjusted by $10 \cdot \log(\text{RBW})$ to reflect a 1MHz measurement bandwidth.

Note: Limit has been adjusted by $10 \cdot \log(\text{RBW})$ to reflect a 1MHz measurement bandwidth.

LTE BAND 7

Channel Bandwidth: 20MHz / QPSK



Note: Limit has been adjusted by $10 \cdot \log(\text{RBW})$ to reflect a 1MHz measurement bandwidth.

Note: Limit has been adjusted by $10 \cdot \log(\text{RBW})$ to reflect a 1MHz measurement bandwidth.

4.6 Conducted Spurious Emissions


4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $55 + 10 \log_{10}(P)$ dB. The limit of emission is equal to -25dBm.

4.6.2 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 30MHz to 27GHz for LTE Band 7. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

4.6.3 Test Setup




4.6.4 Test Results

LTE BAND 7

CHANNEL 21100

5MHz / QPSK


FREQUENCY RANGE : 30MHz~27GHz



CHANNEL 21100

10MHz / QPSK


FREQUENCY RANGE : 30MHz~27GHz



CHANNEL 21100

15MHz / QPSK /


FREQUENCY RANGE : 30MHz~27GHz



CHANNEL 21100

20MHz / QPSK /

FREQUENCY RANGE : 30MHz~27GHz



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

In the FCC 27.53(m) (4), On any frequency outside a licensee's frequency block, The power of any emission shall be attenuated below the transmitter power (P) by at least $55 + 10 \log (P)$ dB. The emission limit equal to -25dBm .

4.7.2 Test Procedure


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step a. Record the power level of S.G.
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$.

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup




For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results

BELOW 1GHz WORST-CASE DATA

LTE Band 7:



Condition: FCC Part 27(B7-41) 3m Horizontal

EUT : Lenovo PB2-650Y


Mode : LTE Band7

Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	46.490	-31.50	-37.84	-25.00	-6.50	6.34	Peak	Horizontal
2	86.260	-55.84	-47.32	-25.00	-30.84	-8.52	Peak	Horizontal
3	194.900	-64.12	-46.75	-25.00	-39.12	-17.37	Peak	Horizontal
4	373.380	-77.28	-65.93	-25.00	-52.28	-11.35	Peak	Horizontal
5	627.520	-73.11	-65.33	-25.00	-48.11	-7.78	Peak	Horizontal
6	787.570	-68.31	-64.13	-25.00	-43.31	-4.18	Peak	Horizontal



Condition: FCC Part 27(B7-41) 3m Vertical

EUT : Lenovo PB2-650Y

Mode : LTE Band7

Plan : X-Plan

Remark : IMEI 869985020015014/022


Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	47.460	-42.77	-38.83	-25.00	-17.77	-3.94	Peak	Vertical
2	88.200	-59.99	-49.50	-25.00	-34.99	-10.49	Peak	Vertical
3	193.930	-57.56	-46.16	-25.00	-32.56	-11.40	Peak	Vertical
4	352.040	-77.87	-66.76	-25.00	-52.87	-11.11	Peak	Vertical
5	589.690	-72.97	-65.64	-25.00	-47.97	-7.33	Peak	Vertical
6	746.830	-70.78	-65.01	-25.00	-45.78	-5.77	Peak	Vertical

ABOVE 1GHz

LTE Band 7

CHANNEL BANDWIDTH: 5MHz / QPSK



Condition: FCC Part 27(B7-41) 3m Horizontal

EUT : Lenovo PB2-650Y


Mode : LTE Band7(5M)

Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-48.30	-56.77	-25.00	-23.30	8.47	Peak	Horizontal
2 PP	7605.000	-43.55	-57.03	-25.00	-18.55	13.48	Peak	Horizontal



Condition: FCC Part 27(B7-41) 3m Vertical

EUT : Lenovo PB2-650Y

Mode : LTE Band7(5M)


Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

			Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-48.10	-56.09	-25.00	-23.10	7.99	Peak	Vertical
2 PP	7605.000	-45.11	-58.10	-25.00	-20.11	12.99	Peak	Vertical

CHANNEL BANDWIDTH: 10MHz / QPSK



Condition: FCC Part 27(B7-41) 3m Horizontal

EUT : Lenovo PB2-650Y


Mode : LTE Band7(10M)

Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

			Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-47.53	-56.00	-25.00	-22.53	8.47	Peak	Horizontal
2 PP	7605.000	-43.98	-57.46	-25.00	-18.98	13.48	Peak	Horizontal



Condition: FCC Part 27(B7-41) 3m Vertical

EUT : Lenovo PB2-650Y

Mode : LTE Band7(10M)


Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-47.64	-55.63	-25.00	-22.64	7.99	Peak	Vertical
2 PP	7605.000	-42.86	-55.85	-25.00	-17.86	12.99	Peak	Vertical

CHANNEL BANDWIDTH: 15MHz / QPSK



Condition: FCC Part 27(B7-41) 3m Horizontal

EUT : Lenovo PB2-650Y


Mode : LTE Band7(15M)

Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-47.20	-55.67	-25.00	-22.20	8.47	Peak	Horizontal
2 PP	7605.000	-43.81	-57.29	-25.00	-18.81	13.48	Peak	Horizontal



Condition: FCC Part 27(B7-41) 3m Vertical

EUT : Lenovo PB2-650Y

Mode : LTE Band7(15M)


Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-48.72	-56.71	-25.00	-23.72	7.99	Peak	Vertical
2	PP 7605.000	-44.81	-57.80	-25.00	-19.81	12.99	Peak	Vertical

CHANNEL BANDWIDTH: 20MHz / QPSK



Condition: FCC Part 27(B7-41) 3m Horizontal

EUT : Lenovo PB2-650Y


Mode : LTE Band7(20M)

Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-47.80	-56.27	-25.00	-22.80	8.47	Peak	Horizontal
2 PP	7605.000	-44.62	-58.10	-25.00	-19.62	13.48	Peak	Horizontal



Condition: FCC Part 27(B7-41) 3m Vertical

EUT : Lenovo PB2-650Y

Mode : LTE Band7(20M)

Plan : X-Plan

Remark : IMEI 869985020015014/022

Test By : Alex Chen

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5082.000	-48.63	-56.62	-25.00	-23.63	7.99	Peak	Vertical
2 PP	7605.000	-43.88	-56.87	-25.00	-18.88	12.99	Peak	Vertical

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF Lab/Telecom Lab

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---