

FCC SAR TEST REPORT

APPLICANT : Lenovo(Shanghai) Electronics Technology Co., Ltd.
EQUIPMENT : Portable Tablet Computer
BRAND NAME : Lenovo
Model Name : TB310FU
FCC ID : O57TB310FU
STANDARD : FCC 47 CFR Part 2 (2.1093)

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



Table of Contents

1. Statement of Compliance 4
2. Administration Data 5
3. Guidance Applied..... 5
4. Equipment Under Test (EUT) Information..... 6
4.1 General Information 6
5. Proximity Sensor Triggering Test..... 7
6. RF Exposure Limits.....13
6.1 Uncontrolled Environment.....13
6.2 Controlled Environment.....13
7. Specific Absorption Rate (SAR).....14
7.1 Introduction14
7.2 SAR Definition.....14
8. System Description and Setup15
8.1 E-Field Probe16
8.2 Data Acquisition Electronics (DAE)16
8.3 Phantom.....17
8.4 Device Holder.....18
9. Measurement Procedures19
9.1 Spatial Peak SAR Evaluation.....19
9.2 Power Reference Measurement.....20
9.3 Area Scan20
9.4 Zoom Scan.....21
9.5 Volume Scan Procedures.....21
9.6 Power Drift Monitoring.....21
10. Test Equipment List.....22
11. System Verification23
11.1 Tissue Simulating Liquids.....23
11.2 Tissue Verification24
11.3 System Performance Check Results.....25
12. RF Exposure Positions26
12.1 SAR Testing for Tablet.....26
13. Conducted RF Output Power (Unit: dBm).....27
14. Antenna Location29
15. SAR Test Results30
15.1 Body SAR31
16. Simultaneous Transmission Analysis32
17. Uncertainty Assessment33
18. References34
Appendix A. Plots of System Performance Check
Appendix B. Plots of High SAR Measurement
Appendix C. DASy Calibration Certificate
Appendix D. Test Setup Photos
Appendix E. Conducted RF Output Power Table



History of this test report

Report No.	Version	Description	Issued Date
FA291508	01	Initial issue of report	Oct. 31, 2022

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Lenovo(Shanghai) Electronics Technology Co., Ltd., Portable Tablet Computer, TB310FU**, are as follows.

Equipment Class	Frequency Band		Highest SAR Summary
			Body (Separation 0mm)
			1g SAR (W/kg)
DTS	WLAN	2.4GHz WLAN	1.10
NII		5GHz WLAN	1.19
DSS	2.4GHz Band	Bluetooth	1.02
Date of Testing:			2022/9/30 ~ 2022/10/21

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications



2. Administration Data

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR05-KS	CN1257	314309

Applicant	
Company Name	Lenovo(Shanghai) Electronics Technology Co., Ltd.
Address	Section 304-305, Building No. 4, # 222, Meiyue Road, China (Shanghai) Pilot Free Trade Zone

Manufacturer	
Company Name	Lenovo PC HK Limited
Address	23/F, Lincoln House, Taikoo Place 979 King's Road, Quarry Bay, Hong Kong, China

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02



4. Equipment Under Test (EUT) Information


4.1 General Information

Product Feature & Specification	
Equipment Name	Portable Tablet Computer
Brand Name	Lenovo
Model Name	TB310FU
FCC ID	O57TB310FU
SN Code	Sample 1 : 8SSP69A6PNDTHA1129G00JC Sample 2 : 8SSP69A6PNDUHA1029H0050
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	Lenovo Tablet TB310FU
SW Version	TB310FU_RF01_220917
EUT Stage	Identical Prototype
Remark:	
<ol style="list-style-type: none"> 1. This device has no voice function. 2. 802.11n-HT40 is not supported in 2.4GHz WLAN. 3. The device employs proximity sensors that detect the presence of the user's body also a finger or hand near the bottom face, edge 1, edge 2 of the device, reduced power will be active for all WLAN bands. (P-sensor can't work at detecting presence of the user's body at other edges of the device.) 4. There are five samples, the different between them refer to the TB310FU_Operational Description of Product Equality Declaration which is exhibit separately. According to the difference, we choose sample 1 to perform full test and sample 2 to verify the worst case of sample 1. For Sample 1 and sample 4 were only different in memory and capacity, sample 2 and sample 3/5 were only different in memory and capacity, so the differences do not affect the test, so sample 3/4/5 are not tested. 	

5. Proximity Sensor Triggering Test

<Proximity Sensor Triggering Distance (KDB 616217 D04 section 6.2)>:

1. Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency 5850MHz and lowest 2450MHz frequency was used for proximity sensor triggering testing.
2. Capacitive proximity sensor placed coincident with antenna elements at the Bottom Face, Edge 1 and Edge 2 of the device are utilized to determine when the device comes in proximity of the user's body at the Bottom Face or Edge 1 and Edge 2 side of the device. There is no need to do sensor coverage testing for the proximity sensor is designed to support sufficient detection range and sensitivity to cover regions of the sensors in all applicable directions since the proximity sensor entirely covers the antenna.
3. When the sensor is active, WLAN 2.4GHz / WLAN 5.2GHz / WLAN 5.3GHz / WLAN 5.5GHz / WLAN 5.8GHz reduced power will be active.
4. The sensors used to detect the proximity of the user's body at the Bottom Face, Edge 1 and Edge 2 side of the device use a detection threshold distance. The data shown in the sections below shows the distance(s).



Proximity Sensor Triggering Distance (mm)						
Position	Bottom Face		Edge 1		Edge 2	
	Moving away	Moving towards	Moving away	Moving towards	Moving away	Moving towards
Minimum	17	18	21	22	9	10

<Proximity Sensor Triggering Coverage (KDB 616217 D04 section 6.3)>:

If a sensor is spatially offset from the antenna(s), it is necessary to verify sensor triggering for conditions where the antenna is next to the user but the sensor is laterally further away to ensure sensor coverage is sufficient for reducing the power to maintain compliance. For p-sensor coverage testing, the device is moved and “along the direction of maximum antenna and sensor offset”.


Illustrated in the internal photo exhibit, although the sensor is spatially offset, there is no trigger condition where the antenna is next to the user but the sensor is laterally further away, therefore proximity sensor coverage testing is not required.

This procedure is not required because antenna and sensor are collocated and the peak SAR location is overlapping with the sensor.

<Tablet Tilt angle influences to proximity sensor triggering (KDB 616217 D04 section 6.4)>:

The influence of table tilt angles to proximity sensor triggering was determined by positioning each tablet edge that contains a transmitting antenna, perpendicular to the flat phantom, at 21mm for Edge 1 and 9mm for Edge 2 separation for WLAN bands.

Rotating the tablet around the edge next to the phantom in $\leq 10^\circ$ increments until the tablet is $\pm 45^\circ$ from the vertical position at 0° , and the maximum output power remains in the reduced mode.



The Sensor Trigger Distance (mm)		
Position	Edge 1	Edge 2
Minimum	21	9

Proximity sensor power reduction



Exposure Position / wireless mode	Bottom Face ⁽¹⁾	Edge 1 ⁽¹⁾	Edge 2 ⁽¹⁾	Edge 3	Edge 4
WLAN 2.4GHz	9.00 dB	9.00 dB	9.00 dB	0dB	0dB
WLAN 5.2GHz	6.00 dB	6.00 dB	6.00 dB	0dB	0dB
WLAN 5.3GHz	6.50 dB	6.50 dB	6.50 dB	0dB	0dB
WLAN 5.5GHz	7.50 dB	7.50 dB	7.50 dB	0dB	0dB
WLAN 5.8GHz	7.00 dB	7.00 dB	7.00 dB	0dB	0dB



Remark:



1. ⁽¹⁾: Reduced maximum limit applied by activation of proximity sensor.
2. Tests were performed in accordance with KDB 616217 D04 section 6.1, 6.2, 6.3, 6.4 and 6.5 and compliant results are shown and described in exhibit "P-Sensor operational description"
3. For verification of compliance of power reduction scheme, additional SAR testing with EUT transmitting at full RF power at a conservative trigger distance was performed:
 - Bottom Face: 16 mm
 - Edge 1: 20 mm
 - Edge 2: 8 mm

Power Measurement during Sensor Trigger distance testing

Band/Mode	Measured power reduction (dBm)		Reduction Levels (dB)
	w/o power back-off	w/ power back-off	
WLAN 2.4GHz	20.00	11.00	9.0
WLAN 5.2GHz	19.00	13.00	6.0
WLAN 5.3GHz	19.00	12.50	6.5
WLAN 5.5GHz	19.00	11.50	7.5
WLAN 5.8GHz	19.00	12.00	7.0







6. RF Exposure Limits

6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

7. Specific Absorption Rate (SAR)

7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:




- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG).The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ±0.2 dB (30 MHz – 6 GHz)	
Directivity	±0.3 dB in TSL (rotation around probe axis) ±0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 µW/g – >100 mW/g Linearity: ±0.2 dB (noise: typically <1 µW/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

8.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.


The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Photo of DAE


8.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices. ELI4 is fully compatible with standard and all known tissue simulating liquids.


8.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (b) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0 is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{Area}, \Delta y_{Area}$	≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan

Zoom scans are used assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube shoes base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

		≤ 3 GHz	> 3 GHz	
Maximum zoom scan spatial resolution: $\Delta x_{Zoom}, \Delta y_{Zoom}$		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*	
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details. * When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.5 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	2450MHz System Validation Kit	D2450V2	1040	May. 06, 2020	May. 04, 2023
SPEAG	5000MHz System Validation Kit	D5GHzV2	1341	Dec. 13, 2021	Dec. 12, 2022
SPEAG	Data Acquisition Electronics	DAE4	1437	Oct. 26, 2021	Oct. 25, 2022
SPEAG	Dosimetric E-Field Probe	EX3DV4	7577	Nov. 23, 2021	Nov. 22, 2022
SPEAG	ELI Phantom	QD OVA 004 AA	2131	NCR	NCR
TES	Hygrometer	1310	200505600	Jul. 12, 2022	Jul. 11, 2023
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Keysight	Network Analyzer	E5071C	MY46523671	Oct. 25, 2021	Oct. 24, 2022
Speag	Dielectric Assessment KIT	DAK-3.5	1071	Jan. 24, 2022	Jan. 23, 2023
Agilent	Signal Generator	N5181A	MY50145381	Dec. 28, 2021	Dec. 27, 2022
Anritsu	Power Sensor	MA2411B	1542004	Dec. 28, 2021	Dec. 27, 2022
Anritsu	Power Meter	ML2495A	1339473	Dec. 28, 2021	Dec. 27, 2022
R&S	Power Sensor	NRP50S	101254	Apr. 07, 2022	Apr. 06, 2023
R&S	CBT BLUETOOTH TESTER	CBT	100963	Dec. 28, 2021	Dec. 27, 2022
R&S	Spectrum Analyzer	FSP7	100818	Jul. 07, 2022	Jul. 06, 2023
Anymetre	Thermo-Hygrometer	JR593	2018100802	Oct. 29, 2021	Oct. 28, 2022
SPEAG	Device Holder	N/A	N/A	Note 1	
AR	Amplifier	5S1G4	0333096	Note 1	
Mini-Circuits	Amplifier	ZVE-3W-83+	599201528	Note 1	
ET Industries	Dual Directional Coupler	C-058-10	N/A	Note 1	
ARRA	Power Divider	A3200-2	N/A	Note 1	
Weinschel	Attenuator 1	3M-10	N/A	Note 1	
Weinschel	Attenuator 2	3M-20	N/A	Note 1	

Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

11. System Verification

11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1.



Fig 11.1 Photo of Liquid Height for Body SAR



11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
2450	55.0	0	0	0	0	45.0	1.80	39.2

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
2450	Head	22.2	1.861	39.575	1.80	39.20	3.39	0.96	±5	2022/9/30
2450	Head	22.5	1.789	39.418	1.80	39.20	-0.61	0.56	±5	2022/10/19
5250	Head	22.4	4.764	36.965	4.71	35.95	1.15	2.82	±5	2022/10/1
5250	Head	22.6	4.502	36.248	4.71	35.95	-4.42	0.83	±5	2022/10/21
5600	Head	22.3	5.207	36.212	5.07	35.50	2.70	2.01	±5	2022/10/2
5600	Head	22.6	5.080	35.374	5.07	35.50	0.20	-0.35	±5	2022/10/20
5750	Head	22.6	5.382	35.934	5.22	35.35	3.10	1.65	±5	2022/10/3
5750	Head	22.5	5.119	34.477	5.22	35.35	-1.93	-2.47	±5	2022/10/20

11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2022/9/30	2450	Head	250	1040	7577	1437	13.600	51.800	54.4	5.02
2022/10/19	2450	Head	250	1040	7577	1437	14.100	51.800	56.4	8.88
2022/10/1	5250	Head	100	1341	7577	1437	8.500	80.700	85	5.33
2022/10/21	5250	Head	100	1341	7577	1437	8.470	80.700	84.7	4.96
2022/10/2	5600	Head	100	1341	7577	1437	8.480	84.500	84.8	0.36
2022/10/20	5600	Head	100	1341	7577	1437	8.300	84.500	83	-1.78
2022/10/3	5750	Head	100	1341	7577	1437	8.300	80.600	83	2.98
2022/10/20	5750	Head	100	1341	7577	1437	8.150	80.600	81.5	1.12




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo



12. RF Exposure Positions

12.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

<EUT Setup Photos>

Please refer to Appendix D for the test setup photos.



13. Conducted RF Output Power (Unit: dBm)

<WLAN Conducted Power>

General Note:


1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.



<2.4GHz Bluetooth>

General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 76.72% as following figure, according to 2016 Oct. TCB workshop for Bluetooth SAR scaling need further consideration and the duty cycle is 100%, therefore the actual duty cycle will be scaled up to the value of Bluetooth reported SAR calculation





14. Antenna Location

The detailed antenna location information can refer to SAR Test Setup Photos.

<SAR test exclusion table>

General Note:

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
3. Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
4. Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
5. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:
 - $[(max. \text{ power of channel, including tune-up tolerance, mW}) / (min. \text{ test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
6. Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)·10] mW at > 1500 MHz and ≤ 6 GHz

Exposure Position	Wireless Interface	BT ANT 3	2.4GHz WLAN ANT 3	5GHz WLAN ANT 4
	Calculated Frequency (MHz)	2480	2462	5825
	Maximum power (dBm)	12.0	20.0	19.0
	Maximum rated power(mW)	15.85	100.00	79.43
Bottom Face	Separation distance(mm)	5.0	5.0	5.0
	exclusion threshold	5.0	31.4	38.3
	Testing required	Yes	Yes	Yes
Edge 1	Separation distance(mm)	5.0	5.0	5.0
	exclusion threshold	5.0	31.4	38.3
	Testing required	Yes	Yes	Yes
Edge 2	Separation distance(mm)	10.0	10.0	8.0
	exclusion threshold	2.5	15.7	24.0
	Testing required	No	Yes	Yes
Edge 3	Separation distance(mm)	209.0	209.0	209.0
	exclusion threshold	1685.0	1686.0	1652.0
	Testing required	No	No	No
Edge 4	Separation distance(mm)	92.0	92.0	116.0
	exclusion threshold	515.0	516.0	722.0
	Testing required	No	No	No



15. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN/BT signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. The device employs proximity sensors that detect the presence of the user's body also a finger or hand near the bottom face, edge 1 and edge 2 of the device, reduced power will be active for all WLAN bands. (P-sensor can't work at detecting presence of the user's body at other edges of the device.)
5. There are five samples, the different between them refer to the TB310FU_Operational Description of Product Equality Declaration which is exhibit separately. According to the difference, we choose sample 1 to perform full test and sample 2 to verify the worst case of sample 1. For Sample 1 and sample 4 were only different in memory and capacity, sample 2 and sample 3/5 were only different in memory and capacity, so the differences do not affect the test, so sample 3/4/5 are not tested.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
3. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
4. During SAR testing the WLAN transmission was verified using a spectrum analyzer.



15.1 Body SAR

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
2450 MHz																	
	Bluetooth	DH5 1Mbps	Bottom Face	0mm	Ant 3	Full Power	39	2441	1	10.31	12.00	1.476	76.72	1.303	0.02	0.329	0.633
	Bluetooth	DH5 1Mbps	Edge 1	0mm	Ant 3	Full Power	39	2441	1	10.31	12.00	1.476	76.72	1.303	0.12	0.068	0.131
	Bluetooth	DH5 1Mbps	Edge 2	0mm	Ant 3	Full Power	39	2441	1	10.31	12.00	1.476	76.72	1.303	0.06	0.120	0.231
	Bluetooth	DH5 1Mbps	Bottom Face	0mm	Ant 3	Full Power	0	2402	1	10.24	12.00	1.500	76.72	1.303	0.09	0.417	0.815
01	Bluetooth	DH5 1Mbps	Bottom Face	0mm	Ant 3	Full Power	0	2402	2	10.24	12.00	1.500	76.72	1.303	0.01	0.523	1.022
	Bluetooth	DH5 1Mbps	Bottom Face	0mm	Ant 3	Full Power	78	2480	1	10.20	12.00	1.514	76.72	1.303	0.07	0.224	0.442
02	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Ant 3	Sensor on	1	2412	1	9.45	11.00	1.429	100	1.000	-0.06	0.770	1.100
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Ant 3	Sensor on	1	2412	2	9.45	11.00	1.429	100	1.000	0.07	0.743	1.062
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	Ant 3	Sensor on	1	2412	1	9.45	11.00	1.429	100	1.000	0.11	0.192	0.274
	WLAN2.4GHz	802.11b 1Mbps	Edge 2	0mm	Ant 3	Sensor on	1	2412	1	9.45	11.00	1.429	100	1.000	-0.02	0.171	0.244
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Ant 3	Sensor on	6	2437	1	9.31	11.00	1.476	100	1.000	0.05	0.701	1.034
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Ant 3	Sensor on	11	2462	1	9.16	11.00	1.528	100	1.000	0.01	0.472	0.721
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	16mm	Ant 3	Full Power	1	2412	1	18.43	20.00	1.435	100	1.000	0.16	0.270	0.388
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	20mm	Ant 3	Full Power	1	2412	1	18.43	20.00	1.435	100	1.000	0.1	0.275	0.395
	WLAN2.4GHz	802.11b 1Mbps	Edge 2	8mm	Ant 3	Full Power	1	2412	1	18.43	20.00	1.435	100	1.000	0.05	0.320	0.459
5000 MHz																	
03	WLAN5.2GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	42	5210	1	11.20	13.00	1.514	88.19	1.134	0.01	0.660	1.133
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	42	5210	2	11.20	13.00	1.514	88.19	1.134	0.06	0.495	0.850
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	Ant 4	Sensor on	42	5210	1	11.20	13.00	1.514	88.19	1.134	0.1	0.512	0.879
	WLAN5.2GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	Ant 4	Sensor on	42	5210	1	11.20	13.00	1.514	88.19	1.134	0.05	0.376	0.645
	WLAN5.2GHz	802.11a 6Mbps	Bottom Face	16mm	Ant 4	Full Power	36	5180	1	17.31	19.00	1.476	96.97	1.031	-0.06	0.104	0.158
	WLAN5.2GHz	802.11a 6Mbps	Edge 1	20mm	Ant 4	Full Power	36	5180	1	17.31	19.00	1.476	96.97	1.031	-0.12	0.143	0.218
	WLAN5.2GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	36	5180	1	17.31	19.00	1.476	96.97	1.031	0.07	0.379	0.577
04	WLAN5.3GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	58	5290	1	10.84	12.50	1.466	88.19	1.134	-0.08	0.653	1.085
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	58	5290	2	10.84	12.50	1.466	88.19	1.134	0.01	0.497	0.826
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	Ant 4	Sensor on	58	5290	1	10.84	12.50	1.466	88.19	1.134	0.02	0.643	1.069
	WLAN5.3GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	Ant 4	Sensor on	58	5290	1	10.84	12.50	1.466	88.19	1.134	0.08	0.473	0.786
	WLAN5.3GHz	802.11a 6Mbps	Bottom Face	16mm	Ant 4	Full Power	64	5320	1	17.46	19.00	1.426	96.97	1.031	-0.11	0.101	0.148
	WLAN5.3GHz	802.11a 6Mbps	Edge 1	20mm	Ant 4	Full Power	64	5320	1	17.46	19.00	1.426	96.97	1.031	0.03	0.173	0.254
	WLAN5.3GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	64	5320	1	17.46	19.00	1.426	96.97	1.031	0.09	0.399	0.586
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	138	5690	1	9.73	11.50	1.503	88.19	1.134	0.06	0.618	1.053
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	Ant 4	Sensor on	138	5690	1	9.73	11.50	1.503	88.19	1.134	0.09	0.443	0.755
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	Ant 4	Sensor on	138	5690	1	9.73	11.50	1.503	88.19	1.134	-0.1	0.373	0.636
05	WLAN5.5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	122	5610	1	9.69	11.50	1.517	88.19	1.134	0.13	0.693	1.192
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	122	5610	2	9.69	11.50	1.517	88.19	1.134	0.05	0.483	0.831
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	106	5530	1	9.56	11.50	1.565	88.19	1.134	0.02	0.629	1.116
	WLAN5.5GHz	802.11a 6Mbps	Bottom Face	16mm	Ant 4	Full Power	100	5500	1	17.49	19.00	1.416	96.97	1.031	-0.06	0.179	0.261
	WLAN5.5GHz	802.11a 6Mbps	Edge 1	20mm	Ant 4	Full Power	100	5500	1	17.49	19.00	1.416	96.97	1.031	-0.04	0.195	0.285
	WLAN5.5GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	100	5500	1	17.49	19.00	1.416	96.97	1.031	0.09	0.554	0.809
	WLAN5.5GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	116	5580	1	17.38	19.00	1.452	96.97	1.031	-0.05	0.465	0.696
	WLAN5.5GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	124	5620	1	17.44	19.00	1.432	96.97	1.031	-0.14	0.418	0.617
	WLAN5.5GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	132	5660	1	17.33	19.00	1.469	96.97	1.031	0.01	0.455	0.689
	WLAN5.5GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	140	5700	1	16.25	18.00	1.496	96.97	1.031	-0.07	0.427	0.659
	WLAN5.5GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	144	5720	1	17.39	19.00	1.449	96.97	1.031	0.15	0.538	0.804
06	WLAN5.8GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	155	5775	1	10.23	12.00	1.503	88.19	1.134	-0.09	0.699	1.191
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Ant 4	Sensor on	155	5775	2	10.23	12.00	1.503	88.19	1.134	0.01	0.482	0.822
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	Ant 4	Sensor on	155	5775	1	10.23	12.00	1.503	88.19	1.134	0.04	0.594	1.013
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	Ant 4	Sensor on	155	5775	1	10.23	12.00	1.503	88.19	1.134	0.08	0.431	0.735
	WLAN5.8GHz	802.11a 6Mbps	Bottom Face	16mm	Ant 4	Full Power	149	5745	1	17.41	19.00	1.442	96.97	1.031	-0.12	0.109	0.162
	WLAN5.8GHz	802.11a 6Mbps	Edge 1	20mm	Ant 4	Full Power	149	5745	1	17.41	19.00	1.442	96.97	1.031	0.13	0.171	0.254



WLAN5.8GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	149	5745	1	17.41	19.00	1.442	96.97	1.031	0.01	0.770	1.145
WLAN5.8GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	157	5785	1	17.32	19.00	1.472	96.97	1.031	-0.06	0.545	0.827
WLAN5.8GHz	802.11a 6Mbps	Edge 2	8mm	Ant 4	Full Power	165	5825	1	17.18	19.00	1.521	96.97	1.031	0.13	0.566	0.887

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations
1.	None

General Note:

1. The EUT has no voice function means data only.
2. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
3. According to the EUT character, WLAN 5GHz and Bluetooth can't transmit simultaneously.
4. According to the EUT character, WLAN 2.4GHz and Bluetooth can't transmit simultaneously.

Test Engineer : Light Wang, Martin Li, Ricky Gu



17. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.



18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [6] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.
- [7] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [8] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [9] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015

-----THE END-----