

Fig.A.6.1.67 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 1 GHz-2.5 GHz)




Fig.A.6.1.68 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 2.5 GHz-7.5 GHz)




Fig.A.6.1.69 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 7.5 GHz-10 GHz)




Fig.A.6.1.70 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 10 GHz-15 GHz)




Fig.A.6.1.71 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 15 GHz-20 GHz)




Fig.A.6.1.72 Transmitter Spurious Emission - Conducted (802.11n-HT20, Ch11, 20 GHz-26 GHz)

A.6.2 Transmitter Spurious Emission - Radiated

Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band:

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Frequency (MHz)	Field strength(µV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Test Condition

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/1MHz	15
4000-18000	1MHz/1MHz	40
18000-26500	1MHz/1MHz	20

EUT ID: EUT1



Measurement Results:

802.11b mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11b	Power	2.38GHz ~2.45GHz	Fig.A.6.2.1	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.2	P

802.11g mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11g	Power	2.38GHz ~2.43GHz	Fig.A.6.2.3	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.4	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	Power	2.38GHz ~2.45GHz	Fig.A.6.2.5	P
	Power	2.45GHz ~2.5GHz	Fig.A.6.2.6	P

Conclusion: Pass

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$



Average

802.11b

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2390.000	43.8	-38.8	27.7	54.900	H
17997.000	41.4	-17.7	45.6	13.500	H
17994.000	41.4	-17.7	45.6	13.500	V
18000.000	41.3	-45.6	44.5	42.366	H
17989.500	41.3	-17.7	45.6	13.400	V
17974.500	41.2	-17.7	45.6	13.300	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17995.500	41.4	-17.7	45.6	13.500	V
17997.000	41.3	-17.7	45.6	13.400	V
17994.000	41.2	-17.7	45.6	13.300	H
17974.500	41.2	-17.7	45.6	13.300	H
17998.500	41.1	-17.7	45.6	13.200	V
17988.000	41.1	-17.7	45.6	13.200	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2483.500	44.5	-38.9	27.7	55.700	H
17998.500	41.6	-17.7	45.6	13.700	H
17991.000	41.5	-17.7	45.6	13.600	V
17997.000	41.4	-17.7	45.6	13.500	H
17994.000	41.4	-17.7	45.6	13.500	V
17989.500	41.2	-17.7	45.6	13.300	H

802.11g

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2390.000	45.8	-38.8	27.7	56.900	H
17997.000	41.6	-17.7	45.6	13.700	V
18000.000	41.5	-45.6	44.5	42.566	H
17998.500	41.4	-17.7	45.6	13.500	H
17995.500	41.4	-17.7	45.6	13.500	H
17983.500	41.2	-17.7	45.6	13.300	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17997.000	41.4	-17.7	45.6	13.500	V
17991.000	41.4	-17.7	45.6	13.500	V
17995.500	41.3	-17.7	45.6	13.400	H
17998.500	41.3	-17.7	45.6	13.400	H
17994.000	41.3	-17.7	45.6	13.400	V
17988.000	41.2	-17.7	45.6	13.300	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2484.105	42.4	-38.9	27.7	53.600	H
17998.500	41.3	-17.7	45.6	13.400	V
17991.000	41.3	-17.7	45.6	13.400	H
17997.000	41.3	-17.7	45.6	13.400	V
17994.000	41.3	-17.7	45.6	13.400	H
17995.500	41.2	-17.7	45.6	13.300	H

802.11n-HT20

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2390.000	46.6	-38.8	27.7	57.700	H
17998.500	41.4	-17.7	45.6	13.500	V
17995.500	41.4	-17.7	45.6	13.500	V
17991.000	41.3	-17.7	45.6	13.400	H
17989.500	41.3	-17.7	45.6	13.400	V
18000.000	41.3	-45.6	44.5	42.366	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
18000.000	41.6	-45.6	44.5	42.666	H
17997.000	41.5	-17.7	45.6	13.600	V
17989.500	41.3	-17.7	45.6	13.400	H
17998.500	41.3	-17.7	45.6	13.400	V
17991.000	41.3	-17.7	45.6	13.400	H
17995.500	41.1	-17.7	45.6	13.200	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2484.265	42.5	-38.9	27.7	53.700	V
17998.500	41.4	-17.7	45.6	13.500	V
17995.500	41.4	-17.7	45.6	13.500	V
17997.000	41.3	-17.7	45.6	13.400	H
18000.000	41.3	-45.6	44.5	42.366	H
17980.500	41.2	-17.7	45.6	13.300	H

Peak

802.11b

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2389.605	54.8	-38.8	27.7	65.900	H
17829.000	54.0	-18.5	45.6	26.900	H
17920.500	53.3	-17.7	45.6	25.400	V
17997.000	52.6	-17.7	45.6	24.700	V
17926.500	52.6	-17.7	45.6	24.700	H
17971.500	52.6	-17.7	45.6	24.700	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17892.000	53.4	-18.5	45.6	26.300	H
17914.500	52.5	-17.7	45.6	24.600	V
17835.000	52.4	-18.5	45.6	25.300	H
17902.500	52.4	-18.5	45.6	25.300	H
17875.500	52.3	-18.5	45.6	25.200	V
17994.000	52.3	-17.7	45.6	24.400	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2483.520	57.1	-38.9	27.7	68.300	H
17913.000	53.0	-18.5	45.6	25.900	H
17947.500	52.8	-17.7	45.6	24.900	V
17992.500	52.7	-17.7	45.6	24.800	V
17803.500	52.6	-18.5	45.6	25.500	H
17998.500	52.5	-17.7	45.6	24.600	H

802.11g

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2389.980	60.7	-38.8	27.7	71.800	V
17998.500	53.2	-17.7	45.6	25.300	H
18000.000	53.0	-45.6	44.5	54.066	V
17827.500	52.9	-18.5	45.6	25.800	H
17932.500	52.7	-17.7	45.6	24.800	H
17926.500	52.4	-17.7	45.6	24.500	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17991	53.4	-17.7	45.6	25.500	H
17992.5	53.2	-17.7	45.6	25.300	H
17902.5	53.1	-18.5	45.6	26.000	H
17995.5	53.1	-17.7	45.6	25.200	V
18000	53.1	-45.6	44.5	54.200	H
17919	53.0	-17.7	45.6	25.100	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2484.135	54.8	-38.9	27.7	66.000	H
17935.500	52.9	-17.7	45.6	25.000	V
17919.000	52.7	-17.7	45.6	24.800	V
17850.000	52.7	-18.5	45.6	25.600	H
17941.500	52.7	-17.7	45.6	24.800	V
17920.500	52.6	-17.7	45.6	24.700	H

802.11n-HT20

Ch1

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2389.990	63.4	-38.8	27.7	74.500	H
17928.000	52.7	-17.7	45.6	24.800	H
17959.500	52.6	-17.7	45.6	24.700	V
17986.500	52.5	-17.7	45.6	24.600	H
17880.000	52.5	-18.5	45.6	25.400	V
17977.500	52.4	-17.7	45.6	24.500	H

Ch6

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
17911.500	53.3	-18.5	45.6	26.200	H
17983.500	52.8	-17.7	45.6	24.900	V
17931.000	52.7	-17.7	45.6	24.800	V
17992.500	52.5	-17.7	45.6	24.600	H
17916.000	52.4	-17.7	45.6	24.500	H
17998.500	52.4	-17.7	45.6	24.500	H

Ch11

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P _{Mea} (dBuV/m)	Polarization
2484.265	54.5	-38.9	27.7	65.700	V
17959.500	53.7	-17.7	45.6	25.800	H
17869.500	53.3	-18.5	45.6	26.200	H
17986.500	52.9	-17.7	45.6	25.000	H
17998.500	52.6	-17.7	45.6	24.700	H
17982.000	52.5	-17.7	45.6	24.600	V

Test graphs as below:




Fig.A.6.2.1 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch1, 2.38 GHz - 2.45GHz




Fig.A.6.2.2 Transmitter Spurious Emission - Radiated (Power): 802.11b, ch11, 2.45 GHz - 2.50GHz




Fig.A.6.2.3 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch1, 2.38 GHz - 2.45GHz




Fig.A.6.2.4 Transmitter Spurious Emission - Radiated (Power): 802.11g, ch11, 2.45 GHz - 2.50GHz




Fig.A.6.2.5 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch1, 2.38 GHz - 2.45GHz

Full Spectrum




Fig.A.6.2.6 Transmitter Spurious Emission - Radiated (Power): 802.11n-HT20, ch11, 2.45 GHz - 2.50GHz



A.7. AC Power-line Conducted Emission

Method of Measurement: See ANSI C63.10-2013-clause 6.2

- 1 The one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT.
- 2 If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed.
- 3 The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation.
- 4 If the EUT is comprised of equipment units that have their own separate ac power connections, e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network, each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be separately measured. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.
- 5 If the EUT uses a detachable antenna, these measurements shall be made with a suitable dummy load connected to the antenna output terminals; otherwise, the tests shall be made with the antenna connected and, if adjustable, fully extended. When measuring the ac conducted emissions from a device that operates between 150 kHz and 30 MHz a non-detachable antenna may be replaced with a dummy load for the measurements within the fundamental emission band of the transmitter, but only for those measurements.³⁶ Record the six highest EUT emissions relative to the limit of each of the current-carrying conductors of the power cords of the equipment that comprises the EUT over the frequency range specified by the procuring or regulatory agency. Diagram or photograph the test setup that was used. See Clause 8 for full reporting requirements.

Test Condition:

Voltage (V)	Frequency (Hz)
120	60

Measurement Result and limit:

WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	66 to 56	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dB μ V)	Result (dB μ V)		Conclusion
		With charger		
		802.11b	Idle	
0.15 to 0.5	56 to 46	Fig.A.7.1	Fig.A.7.2	P
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Conclusion: Pass

Test graphs as below:




Fig.A.7.1 AC Powerline Conducted Emission-802.11b

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.708000	34.2	GND	L1	19.8	21.8	56.0
2.013000	32.3	GND	L1	19.7	23.7	56.0
3.012000	35.7	GND	L1	19.7	20.3	56.0
3.660000	38.1	GND	L1	19.6	17.9	56.0
17.628000	43.3	GND	N	19.9	16.7	60.0
19.356000	42.4	GND	N	20.0	17.6	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.712500	26.8	GND	N	19.9	19.2	46.0
0.775500	22.6	GND	N	19.8	23.4	46.0
3.075000	21.9	GND	L1	19.7	24.1	46.0
4.609500	24.4	GND	N	19.7	21.6	46.0
17.106000	35.7	GND	N	19.8	14.3	50.0
17.817000	37.6	GND	N	19.9	12.4	50.0




Fig.A.7.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.717000	32.2	GND	N	19.9	23.8	56.0
2.053500	32.4	GND	L1	19.7	23.6	56.0
2.953500	37.6	GND	L1	19.7	18.4	56.0
3.718500	37.4	GND	L1	19.6	18.6	56.0
16.597500	39.8	GND	N	19.8	20.2	60.0
18.474000	39.7	GND	N	19.9	20.3	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.712500	27.0	GND	N	19.9	19.0	46.0
0.775500	25.7	GND	N	19.8	20.3	46.0
3.016500	25.0	GND	L1	19.7	21.0	46.0
3.723000	26.1	GND	N	19.7	19.9	46.0
17.038500	32.9	GND	N	19.8	17.1	50.0
17.821500	35.7	GND	L1	20.0	14.3	50.0