



TEST REPORT

No. I17Z61109-WMD03

for

Lenovo(Shanghai) Electronics Technology Co., Ltd.

Portable Tablet Computer

Model Name: Lenovo TB-7304X

FCC ID: O57TB7304X

with

Hardware Version: Lenovo Tablet TB-7304X

Software Version: TB-7304X_RF01_170728_ROW

Issued Date: 2017-08-15



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I17Z61109-WMD03	Rev.0	1 st edition	2017-08-15



CONTENTS

1. TEST LABORATORY	4
1.1. TESTING LOCATION	4
1.2. TESTING ENVIRONMENT	4
1.3. PROJECT DATA	4
1.4. SIGNATURE.....	4
2. CLIENT INFORMATION	5
2.1. APPLICANT INFORMATION.....	5
2.2. MANUFACTURER INFORMATION.....	5
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	6
3.1. ABOUT EUT.....	6
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	6
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	6
3.4. GENERAL DESCRIPTION	7
4. REFERENCE DOCUMENTS.....	8
4.1. REFERENCE DOCUMENTS FOR TESTING.....	8
5. LABORATORY ENVIRONMENT.....	9
6. SUMMARY OF TEST RESULTS.....	10
6.1. SUMMARY OF TEST RESULTS	10
6.2. STATEMENTS.....	10
7. TEST EQUIPMENTS UTILIZED.....	11
ANNEX A: MEASUREMENT RESULTS	12
A.1 OUTPUT POWER	12
A.2 EMISSION LIMIT	18
A.3 FREQUENCY STABILITY	22
A.4 OCCUPIED BANDWIDTH.....	24
A.5 EMISSION BANDWIDTH	29
A.6 BAND EDGE COMPLIANCE.....	34
A.7 CONDUCTED SPURIOUS EMISSION	38
A.8 PEAK-TO-AVERAGE POWER RATIO	40
ANNEX B: ACCREDITATION CERTIFICATE	41

1. Test Laboratory

1.1. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,
Haidian District, Beijing, P. R. China 100191

1.2. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: 2017-07-28

Testing End Date: 2017-08-03

1.4. Signature



Shen Yi

(Prepared this test report)



Zhou Yu

(Reviewed this test report)



Zhao Hui Lin

Deputy Director of the laboratory

(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: Lenovo(Shanghai) Electronics Technology Co., Ltd.
Address /Post: NO.68 BUILDING, 199 FENJU RD, Pilot Free Trade Zone, 200131,
China
Contact: Spring Zhou
Email: zhoub1@lenovo.com
Telephone: +86-21-50504500-8281
Fax: +86-21-50504500-8281

2.2. Manufacturer Information

Company Name: Lenovo PC HK Limited
Address /Post: 23/F, Lincoln Ho23/F, Lincoln House, Taikoo Place
979 King's Road, Quarry Bay, Hong Konguse, Taikoo Place
Contact: Jason Wang
Email: wangjun28@lenovo.com
Telephone: +86-10-57877542
Fax: +86-10-58863425

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Portable Tablet Computer
Model Name	Lenovo TB-7304X
FCC ID	O57TB7304X
Antenna	Integrated
Output power	16.78dBm maximum EIRP measured for Band 7
Extreme vol. Limits	3.45VDC to 4.35VDC (nominal: 3.8VDC)
Extreme temp. Tolerance	5°C to +45°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, Academy of Telecommunication Research, MIIT

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version	Date of receipt
UT45a	HGCEJPZR(24)	Lenovo Tablet TB-7304X	TB-7304X_RF01_170728_ROW	2017-07-17
UT11a	HGCEJQ1M(24)	Lenovo Tablet TB-7304X	TB-7304X_RF01_170728_ROW	2017-07-17

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Battery
AE3	Travel charger
AE4	Travel charger
AE1	
Model	L13D1P31
Manufacturer	Sunwoda
Capacitance	3450mAh
AE2	
Model	L13D1P31
Manufacturer	SCUD
Capacitance	3450mAh
AE3	
Model	C-P56/C-P57/C-P58/C-P59/C-P60/ C-P61
Manufacturer	Huntkey
AE4	
Model	C-P56/ C-P57/ C-P58/ C-P45
Manufacturer	Acbel

*AE ID: is used to identify the test sample in the lab internally.



3.4. General Description

The Equipment Under Test (EUT) is a model of Portable Tablet Computer with integrated antenna. Manual and specifications of the EUT were provided to fulfil the test.



4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	10-1-16 Edition
ANSI/TIA-603-D	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2010
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS	v02r02

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m/10m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Fully-anechoic chamber FAC-3 (9 meters×6.5 meters×4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

6.1. Summary of test results

Abbreviations used in this clause:		
Verdict Column	P	Pass
	F	Fail
	NA	Not applicable
	NM	Not measured
Location Column	A/B/C/D	The test is performed in test location A, B, C or D which are described in section 1.1 of this report

LTE Band 7

Items	Test Name	Clause in FCC rules	Section in this report	Verdict
1	Output Power	27.50(h)(2)	A.1	P
2	Emission Limit	27.53(m), 2.1051	A.2	P
3	Frequency Stability	27.54, 2.1055	A.3	P
4	Occupied Bandwidth	2.1049(h)(i)	A.4	P
5	Emission Bandwidth	27.53(m)	A.5	P
6	Band Edge Compliance	27.53(m)	A.6	P
7	Conducted Spurious Emission	27.53(m), 2.1057	A.7	P
8	Peak to Average Power Ratio	27.50(a)	A.8	P

6.2. Statements

The test cases listed in section 6.1 of this report for the EUT specified in section 3 were performed by CTTL according to the standards or reference documents in section 4.1

The EUT met all applicable requirements of the standards or reference documents in section 4.1.

This report only deals with the LTE functions among the features described in section 3.

7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Test Receiver	ESU26	100235	R&S	2018-03-01	1 year
2	Test Receiver	ESU26	100376	R&S	2017-10-26	1 year
3	EMI Antenna	3117	00058889	ETS-Lindgren	2017-12-15	3 year
4	Universal Radio Communication Tester	CMW500	149646	R&S	2017-11-02	1 year
5	Spectrum Analyzer	FSU26	200030	R&S	2018-06-10	1 year
6	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2017-10-29	3 year
7	Signal Generator	SMF100A	101295	R&S	2017-11-07	1 year
8	Climate chamber	SH-241	92007454	ESPEC	2017-12-14	2 year
9	Loop Antenna	HFH2-Z2	829324/007	R&S	2017-12-10	3 year

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation. These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

A.1.2.2 Measurement result

LTE band 7

Bandwidth	RB size/offset	Frequency (MHz)	Power(dBm)	
			QPSK	16QAM
5MHz	1 RB high	2567.5	22.23	21.09
		2535	22.35	21.21
		2502.5	22.47	21.32
	1 RB low	2567.5	22.37	21.21
		2535	22.39	21.25
		2502.5	22.60	21.42
	50% RB mid	2567.5	21.35	20.36
		2535	21.45	20.44
		2502.5	21.71	20.70
	100% RB	2567.5	21.27	20.23
		2535	21.38	20.31
		2502.5	21.64	20.54
10MHz	1 RB high	2565	22.38	21.66
		2535	22.48	21.36
		2505	22.58	21.98
	1 RB low	2565	22.51	21.92
		2535	22.44	21.36
		2505	22.78	22.12
	50% RB mid	2565	21.36	20.49
		2535	21.39	20.46
		2505	21.65	20.67
	100% RB	2565	21.25	20.40



		2535	21.38	20.38
		2505	21.63	20.61
15MHz	1 RB high	2562.5	22.47	21.71
		2535	22.55	21.75
		2507.5	22.34	21.87
	1 RB low	2562.5	22.64	22.04
		2535	22.50	21.76
		2507.5	22.78	22.11
	50% RB mid	2562.5	21.59	20.53
		2535	21.63	20.50
		2507.5	21.75	20.61
	100% RB	2562.5	21.60	20.55
		2535	21.62	20.52
		2507.5	21.74	20.62
20MHz	1 RB high	2560	22.50	21.62
		2535	22.57	21.93
		2510	22.45	21.67
	1 RB low	2560	22.69	21.88
		2535	22.46	21.92
		2510	22.74	21.91
	50% RB mid	2560	21.48	20.50
		2535	21.46	20.41
		2510	21.50	20.44
	100% RB	2560	21.51	20.52
		2535	21.48	20.45
		2510	21.53	20.48

A.1.3 Radiated

A.1.3.1 Description


This is the test for the maximum radiated power from the EUT.

Rule Part 27.50(h)(2) specifies “Mobile stations are limited to 2.0 watts EIRP.”.


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603D-2010 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (P_r).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna

polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.

The cable loss (P_{cl}), the substitution antenna Gain (G_a) and the amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{\text{Mea}} - P_{\text{Ag}} - P_{\text{cl}} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15$.

A.1.3.3 Measurement result

LTE Band 7

LTE Band 7_5MHz_QPSK

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2502.50	-31.95	3.58	-45.68	-6.10	16.25	33.00	16.75	H
2535.00	-30.60	3.63	-44.82	-6.16	16.75	33.00	16.25	H
2567.50	-32.22	3.65	-44.92	-6.22	15.27	33.00	17.73	H

LTE Band 7_10MHz_QPSK

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2505.00	-31.88	3.59	-45.64	-6.11	16.28	33.00	16.72	H
2535.00	-30.62	3.63	-44.82	-6.16	16.73	33.00	16.27	H
2565.00	-32.24	3.65	-44.97	-6.22	15.30	33.00	17.70	H

LTE Band 7_15MHz_QPSK

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2507.50	-31.21	3.59	-44.92	-6.11	16.23	33.00	16.77	H
2535.00	-30.58	3.63	-44.82	-6.16	16.77	33.00	16.23	H
2562.50	-32.77	3.65	-45.67	-6.21	15.46	33.00	17.54	H

LTE Band 7_20MHz_QPSK

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2510.00	-31.64	3.58	-45.36	-6.12	16.26	33.00	16.74	H
2535.00	-30.57	3.63	-44.82	-6.16	16.78	33.00	16.22	H
2560.00	-32.87	3.64	-45.98	-6.21	15.68	33.00	17.32	H



LTE Band 7_5MHz_16QAM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2502.50	-32.81	3.58	-45.68	-6.10	15.39	33.00	17.61	H
2535.00	-31.56	3.63	-44.82	-6.16	15.79	33.00	17.21	H
2567.50	-33.09	3.65	-44.92	-6.22	14.40	33.00	18.60	H

LTE Band 7_10MHz_16QAM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2505.00	-32.94	3.59	-45.64	-6.11	15.22	33.00	17.78	H
2535.00	-31.58	3.63	-44.82	-6.16	15.77	33.00	17.23	H
2565.00	-33.09	3.65	-44.97	-6.22	14.45	33.00	18.55	H

LTE Band 7_15MHz_16QAM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2507.50	-32.09	3.59	-44.92	-6.11	15.35	33.00	17.65	H
2535.00	-31.47	3.63	-44.82	-6.16	15.88	33.00	17.12	H
2562.50	-33.72	3.65	-45.67	-6.21	14.51	33.00	18.49	H

LTE Band 7_20MHz_16QAM

Frequency(MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a Antenna Gain(dB)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2510.00	-32.60	3.58	-45.36	-6.12	15.30	33.00	17.70	H
2535.00	-31.62	3.63	-44.82	-6.16	15.73	33.00	17.27	H
2560.00	-33.68	3.64	-45.98	-6.21	14.87	33.00	18.13	H

Peak EIRP(dBm) = P_{Mea}(-30.57dBm) - G_a -(-6.16dBi) - P_{Ag} (-44.82dB) - P_{cl} (3.63dB) =16.78dBm

ANALYZER SETTINGS:

RBW = VBW = 8MHz for occupied bandwidths equal to or less than 5MHz.

RBW = VBW = 20MHz for occupied bandwidths equal to or greater than 10MHz.

Note: Expanded measurement uncertainty is $U = 0.96$ dB, $k = 2$.

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurements procedures in TIA-603D-2010 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Band 7.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dB}$.

A.2.2 Measurement Limit

Part 27.53(m) specifies that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Band 7. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Band 7 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this. The evaluated frequency range is from 30MHz to 26GHz.



LTE Band 7, 5 MHz, QPSK, Channel 20775

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
5625.02	-55.66	7.26	10.57	-52.35	-13.00	39.35	H
7503.01	-46.29	8.38	12.20	-42.47	-13.00	29.47	V
10645.01	-52.24	9.29	13.13	-48.40	-13.00	35.40	H
13106.01	-46.68	10.91	13.65	-43.94	-13.00	30.94	H
15547.00	-43.40	11.51	13.70	-41.21	-13.00	28.21	V
17898.00	-41.35	12.87	15.46	-38.76	-13.00	25.76	H

LTE Band 7, 5 MHz, QPSK, Channel 21100

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
5657.02	-55.70	7.27	10.57	-52.40	-13.00	39.40	H
7611.01	-49.81	8.02	12.29	-45.54	-13.00	32.54	H
10156.01	-51.37	9.37	12.96	-47.78	-13.00	34.78	H
13032.01	-47.27	10.62	13.54	-44.35	-13.00	31.35	H
15699.00	-43.83	11.61	13.70	-41.74	-13.00	28.74	H
17973.00	-42.51	12.89	15.56	-39.84	-13.00	26.84	H

LTE Band 7, 5 MHz, QPSK, Channel 21425

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
5637.02	-55.95	7.27	10.57	-52.65	-13.00	39.65	H
7702.01	-50.31	8.42	12.36	-46.37	-13.00	33.37	V
10277.01	-52.00	9.56	13.01	-48.55	-13.00	35.55	H
13067.01	-47.38	10.78	13.59	-44.57	-13.00	31.57	V
15535.00	-43.99	11.52	13.70	-41.81	-13.00	28.81	H
17965.00	-41.56	12.89	15.55	-38.90	-13.00	25.90	H

LTE Band 7, 5 MHz, 16QAM, Channel 20775

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
5577.02	-56.04	7.21	10.58	-52.67	-13.00	39.67	V
7505.01	-45.40	8.37	12.20	-41.57	-13.00	28.57	V
10225.01	-52.08	9.39	12.99	-48.48	-13.00	35.48	H
13131.01	-46.95	10.80	13.68	-44.07	-13.00	31.07	H
15785.00	-43.37	11.65	13.70	-41.32	-13.00	28.32	H
17979.00	-42.42	12.90	15.57	-39.75	-13.00	26.75	H

LTE Band 7, 5 MHz, 16QAM, Channel 21100

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
5321.02	-56.06	6.99	10.35	-52.70	-13.00	39.70	V
7609.01	-49.65	8.01	12.29	-45.37	-13.00	32.37	H
10715.01	-52.39	9.34	13.14	-48.59	-13.00	35.59	H
13141.01	-47.57	10.76	13.70	-44.63	-13.00	31.63	H
15669.00	-43.87	11.57	13.70	-41.74	-13.00	28.74	H
17971.00	-42.55	12.89	15.56	-39.88	-13.00	26.88	H

LTE Band 7, 5 MHz, 16QAM, Channel 21425

Frequency(MHz)	P _{Mea} (dBm)	Path Loss	Antenna Gain	Peak EIRP(dBm)	Limit (dBm)	Margin(dB)	Polarization
5138.02	-54.94	6.86	10.09	-51.71	-13.00	38.71	V
7709.01	-49.05	8.41	12.37	-45.09	-13.00	32.09	H
10281.01	-51.68	9.58	13.01	-48.25	-13.00	35.25	V
13125.01	-46.71	10.83	13.68	-43.86	-13.00	30.86	H
15195.00	-44.00	11.40	13.88	-41.52	-13.00	28.52	V
17971.00	-42.60	12.89	15.56	-39.93	-13.00	26.93	H

Note: The maximum value of expanded measurement uncertainty for this test item is $U = 4.2$ dB, $k = 2$.

A.3 FREQUENCY STABILITY

A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a “call mode”. This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at 10°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 7, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from 10°C to +40°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from 10°C to +40°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.3.2 Measurement Limit

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d) (2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.45VDC and 4.35VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance from -5.4% to 10.8%. For the purposes of measuring frequency stability these voltage limits are to be used.

A.3.3 Measurement results

LTE Band 7, 10MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

Voltage (V)	Frequency error (Hz)		Frequency error (ppm)	
	QPSK	16QAM	QPSK	16QAM
3.45	2.80	6.69	0.001	0.003
3.8	7.74	9.76	0.003	0.004
4.35	2.69	15.88	0.001	0.006

Frequency Error vs Temperature

Temperature (°C)	Frequency error (Hz)		Frequency error (ppm)	
	QPSK	16QAM	QPSK	16QAM
40°	3.42	13.02	0.001	0.005
30°	10.40	14.13	0.004	0.006
20°	3.20	10.79	0.001	0.004
10°	2.79	9.90	0.001	0.004

A.4 OCCUPIED BANDWIDTH

A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.


The measurement method is from KDB 971168 4.2:

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (i.e., two to five times the OBW).
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- Set the reference level of the instrument as required to keep the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope must be at least $10\log(\text{OBW} / \text{RBW})$ below the reference level.
- Set the detection mode to peak, and the trace mode to max hold.
- Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

LTE band 7, 5MHz (99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)	
2535.0	QPSK	16QAM
	4519.23	4519.23


LTE band 7, 5MHz Bandwidth, QPSK (99% BW)



Date: 31.JUL.2017 09:57:33



LTE band 7, 5MHz Bandwidth,16QAM (99% BW)




Date: 31.JUL.2017 09:57:48

LTE band 7, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)(kHz)	
2535.0	QPSK	16QAM
	8990.38	9038.46

LTE band 7, 10MHz Bandwidth, QPSK (99% BW)



Date: 31.JUL.2017 10:04:24

LTE band 7, 10MHz Bandwidth, 16QAM (99% BW)




Date: 31.JUL.2017 10:04:39

LTE band 7, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)(kHz)	
2535.0	QPSK	16QAM
	13485.58	13485.58

LTE band 7, 15MHz Bandwidth, QPSK (99% BW)



Date: 31.JUL.2017 10:11:20

LTE band 7, 15MHz Bandwidth, 16QAM (99% BW)




Date: 31.JUL.2017 10:11:35

LTE band 7, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)(kHz)	
2535.0	QPSK	16QAM
	17980.77	17980.77

LTE band 7, 20MHz Bandwidth, QPSK (99% BW)



Date: 31.JUL.2017 10:18:20

LTE band 7, 20MHz Bandwidth, 16QAM (99% BW)



Date: 31.JUL.2017 10:18:35

A.5 EMISSION BANDWIDTH


A.5.1 Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.

LTE band 7, 5MHz (-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc)(kHz)	
2535.0	QPSK	16QAM
	4927.88	4927.88


LTE band 7, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 31.JUL.2017 09:58:41



LTE band 7, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 31.JUL.2017 09:58:58

LTE band 7, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)(kHz)	
	2535.0	QPSK
9711.54		9807.69

LTE band 7, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 31.JUL.2017 10:05:32

LTE band 7, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 31.JUL.2017 10:05:49

LTE band 7, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)(kHz)	
	2535.0	QPSK
14927.88		14855.77

LTE band 7, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 31.JUL.2017 10:12:29

LTE band 7, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 31.JUL.2017 10:12:46

LTE band 7, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)(kHz)	
	2535.0	QPSK
19326.92		19519.23

LTE band 7, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 31.JUL.2017 10:19:28

LTE band 7, 20MHz Bandwidth, 16QAM (-26dBc BW)



Date: 31.JUL.2017 10:19:45

A.6 BAND EDGE COMPLIANCE

A.6.1 Measurement limit


Part 27.53(m) states that for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

A.6.2 Measurement result

Only worst case result is given below

LTE band 7


OBW: 1RB-low_offset



Date: 31.JUL.2017 11:05:13




LOW BAND EDGE BLOCK-1RB-low_offset




Date: 31.JUL.2017 11:05:56

OBW: 1RB-high_offset




Date: 31.JUL.2017 11:08:07

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 31.JUL.2017 11:08:50

LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 31.JUL.2017 10:59:56

HIGH BAND EDGE BLOCK-20MHz-100%RB



Date: 31.JUL.2017 16:48:14

A.7 CONDUCTED SPURIOUS EMISSION

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.

A. 7.2 Measurement Limit


Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

A. 7.3 Measurement result

Only worst case result is given below

LTE band 7: 30MHz – 26GHz

Spurious emission limit –13dBm.



Date: 31.JUL.2017 11:06:50

A.8 PEAK-TO-AVERAGE POWER RATIO

Reference

FCC: CFR 27.50(a)

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

According to KDB 971168 5.7.1:

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth \geq signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

A.8.1 Measurement limit


not exceed 13 dB

A.8.2 Measurement results

LTE band 7, 20MHz

Frequency(MHz)	PAPR(dB)	
	QPSK	16QAM
2510.0	7.18	7.72

ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p>  <hr/> <p>Certificate of Accreditation to ISO/IEC 17025:2005</p> <hr/> <p>NVLAP LAB CODE: 600118-0</p> <p>Telecommunication Technology Labs, CAICT Beijing China</p> <p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p> <p>Electromagnetic Compatibility & Telecommunications</p> <p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p> <table border="0" style="width: 100%;"><tr><td style="width: 40%;"><hr/><p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p></td><td style="width: 20%; text-align: center;"></td><td style="width: 40%;"><hr/><p><i>[Signature]</i> For the National Voluntary Laboratory Accreditation Program</p></td></tr></table>		<hr/> <p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p>		<hr/> <p><i>[Signature]</i> For the National Voluntary Laboratory Accreditation Program</p>
<hr/> <p>2016-09-29 through 2017-09-30 <i>Effective Dates</i></p>		<hr/> <p><i>[Signature]</i> For the National Voluntary Laboratory Accreditation Program</p>		

END OF REPORT